



State of Ohio Environmental Protection Agency

RE: DRAFT PERMIT TO INSTALL  
PIKE COUNTY

CERTIFIED MAIL

Street Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center

Application No: 06-06474

DATE: 7/31/2001

Mills Pride Limited Partnership  
Debra Hannah  
423 Hopewell Rd  
Waverly, OH 456909700

You are hereby notified that the Ohio Environmental Protection Agency has made a draft action recommending that the Director issue a Permit to Install for the air contaminant source(s) [emissions unit(s)] shown on the enclosed draft permit. This draft action is not an authorization to begin construction or modification of your emissions unit(s). The purpose of this draft is to solicit public comments on the proposed installation. A public notice concerning the draft permit will appear in the Ohio EPA Weekly Review and the newspaper in the county where the facility will be located. Public comments will be accepted by the field office within 30 days of the date of publication in the newspaper. Any comments you have on the draft permit should be directed to the appropriate field office within the comment period. A copy of your comments should also be mailed to Robert Hodanbosi, Division of Air Pollution Control, Ohio EPA, P.O. Box 1049, Columbus, OH, 43266-0149.

A Permit to Install may be issued in proposed or final form based on the draft action, any written public comments received within 30 days of the public notice, or record of a public meeting if one is held. You will be notified in writing of a scheduled public meeting. Upon issuance of a final Permit to Install a fee of \$1000 will be due. Please do not submit any payment now.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469. If you have any questions about this draft permit, please contact the field office where you submitted your application, or Mike Ahern, Field Operations & Permit Section at (614) 644-3631.

Very truly yours,

Thomas G. Rigo  
Field Operations and Permit Section  
Division of Air Pollution Control

CC: USEPA

SEDO

KY

WV



STATE OF OHIO ENVIRONMENTAL PROTECTION AGENCY

Permit To Install  
Terms and Conditions

Issue Date: To be entered upon final issuance  
Effective Date: To be entered upon final issuance

**DRAFT PERMIT TO INSTALL 06-06474**

Application Number: 06-06474  
APS Premise Number: 0666010033  
Permit Fee: **To be entered upon final issuance**  
Name of Facility: Mills Pride Limited Partnership  
Person to Contact: Debra Hannah  
Address: 423 Hopewell Rd  
Waverly, OH 456909700

Location of proposed air contaminant source(s) [emissions unit(s)]:

**423 Hopewell Rd  
Waverly, Ohio**

Description of proposed emissions unit(s):

**Specialty Booth and Spray Booth.**

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Mills Pride Limited Partnership

Facility ID: 0666010033

PTI Application: 06-06474

Issued: To be entered upon final issuance

Part I - GENERAL TERMS AND CONDITIONS

**A. State and Federally Enforceable Permit To Install General Terms and Conditions**

**1. Monitoring and Related Recordkeeping and Reporting Requirements**

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
  - i. The date, place (as defined in the permit), and time of sampling or measurements.
  - ii. The date(s) analyses were performed.
  - iii. The company or entity that performed the analyses.
  - iv. The analytical techniques or methods used.
  - v. The results of such analyses.
  - vi. The operating conditions existing at the time of sampling or measurement.
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
  - i. Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
  - ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to the appropriate Ohio EPA District Office or local air agency. The written reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. See B.10 below if no deviations occurred during the quarter.

**Mills Pride Limited Partnership**

**Facility ID: 0666010033**

**PTI Application: 06-06474**

**Issued: To be entered upon final issuance**

- iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted to the appropriate Ohio EPA District Office or local air agency every six months, i.e., by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.
- iv. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

## **2. Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

## **3. Risk Management Plans**

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

## **4. Title IV Provisions**

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

## **5. Severability Clause**

**Mills Pride Limited Partnership**

**Facility ID: 0666010033**

**PTI Application: 06-06474**

**Issued: To be entered upon final issuance**

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition declared invalid.

## **6. General Requirements**

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

## **7. Fees**

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit To Install fees within 30 days after the issuance of this Permit To Install.

## **8. Federal and State Enforceability**

Only those terms and conditions designated in this permit as federally enforceable, that are required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit

**Mills Pride Limited Partnership**

**Facility ID: 0666010033**

**PTI Application: 06-06474**

**Issued: To be entered upon final issuance**

shall not be federally enforceable and shall be enforceable under State law only.

## **9. Compliance Requirements**

- a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
  - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
  - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.
  - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
  - iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
  - i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
  - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

**Mills Pride Limited Partnership**

**Facility ID: 0666010033**

**PTI Application: 06-06474**

**Issued: To be entered upon final issuance**

#### **10. Permit To Operate Application**

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).
- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the source(s) covered by this permit.

#### **11. Best Available Technology**

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

**Mills Pride Limited Partnership**

**Facility ID: 0666010033**

**PTI Application: 06-06474**

**Issued: To be entered upon final issuance**

**B. State Only Enforceable Permit To Install General Terms and Conditions**

**1. Compliance Requirements**

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

**2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements**

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

**3. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

**4. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

**5. Termination of Permit To Install**

**Mills Pride Limited Partnership**

**Facility ID: 0666010033**

**PTI Application: 06-06474**

**Issued: To be entered upon final issuance**

This permit to install shall terminate within eighteen months of the effective date of the permit to install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

**6. Construction of New Sources(s)**

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

**7. Public Disclosure**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

**8. Applicability**

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

**Mills Pride Limited Partnership**

**Facility ID: 0666010033**

**PTI Application: 06-06474**

**Issued: To be entered upon final issuance**

**9. Construction Compliance Certification**

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit To Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

Mills 1

PTI A

Emissions Unit ID: K001

**Issued: To be entered upon final issuance**

**10. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)**

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

**C. Permit To Install Summary of Allowable Emissions**

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)  
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
VOC	130.91 (decrease of 2.01 tons based on previous PTI allowable emission limits)

12

**Mills Pride Limited Partnership**

**PTI Application: 06-06474**

**Issued: To be entered upon final issuance**

**Facility ID: 0666010033**

**Mills 1****PTI A**

Emissions Unit ID: K001

**Issued: To be entered upon final issuance****Part II - FACILITY SPECIFIC TERMS AND CONDITIONS****A. State and Federally Enforceable Permit To Install Facility Specific Terms and Conditions**

The total facility Hazardous Air Pollution (HAP) emissions shall be less than 10 tons per year of a individual HAP, and 25 tons per year of a total of HAPs. The tons per year limits, shall be based upon a rolling twelve month period. The total facility limits are required to be federally enforceable in order to be exempt this facility from 40 CFR 63, Subpart JJ.

**B. State Only Enforceable Permit To Install Facility Specific Terms and Conditions**

None

Mills 1

PTI A

Emissions Unit ID: K001

Issued: To be entered upon final issuance

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>
K001 - Flatline Finishing System (system includes 3 spray booths, 1 dryer, and 2 curing ovens controlled by a Regenerative Thermal Oxidizer )	OAC rule 3745-21-07(G)(1)  OAC rule 3745-31-05(D) (Synthetic Minor to avoid MACT)  OAC rule 3745-21-07(G)(6)(a)  OAC rule 3745-17-07(A)  OAC rule 3745-21-07(G)(2)  OAC rule 3745-17-11(B) (Table 1)  OAC rule 3745-31-05(A)(3)

**Mills 1**

**PTI A**

Emissions Unit ID: K001

**Issued: To be entered upon final issuance**

Applicable Emissions  
Limitations/Control  
Measures

Compliance with this rule also includes compliance with OAC rules 3745-17-07(A) and 3745-17-11(B)

The emission reduction requirement specified in this rule (85% overall control efficiency) is less stringent than the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

The total facility Hazardous Air Pollution (HAP) emissions shall be less than 10 tons per year of a individual HAP, and 25 tons per year of a total of HAPs.

Visible particulate emissions from any stack shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.

The emission reduction requirement specified in this rule (90% or more of the carbon in the organic material being incinerated) is less stringent to the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

Particulate emissions shall not exceed 0.551 lb/hr.

The emission reduction requirement specified in this rule (85% overall control efficiency) is less stringent than the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

Volatile organic compound (VOC) emissions shall not exceed 40.94 lbs/hr and 74.08 tons/yr. See section A.I.2.a.

**Issued: To be entered upon final issuance****2. Additional Terms and Conditions**

- 2.a** The facility shall maintain an overall VOC control efficiency which is at least 90%, by weight, and a Regenerative Thermal Oxidizer (RTO) control efficiency (i.e., destruction or removal efficiency) which is at least 90%, by weight, for this emissions unit.

**II. Operational Restrictions**

1. The average combustion temperature within the RTO, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
2. The total facility Hazardous Air Pollution (HAP) emissions shall be less than 10 tons per year of a individual HAP, and 25 tons per year of a total of HAPs. The tons per year limits, shall be based upon a rolling twelve month period. The total facility limits are required to be federally enforceable in order to be exempt this facility from 40 CFR 63, Subpart JJ.
3. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the RTO when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day for the control equipment:

- a. All 3-hour blocks of time during which the average combustion temperature within the RTO, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.
  - b. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
2. The permittee shall collect and record the following information each day for materials used in the

Emissions Unit ID: K001

emission unit.

- a. The company identification for each coating and cleanup material employed.
  - b. The number of gallons of each coating and cleanup material employed.
  - c. The VOC content of each coating and cleanup material, in pounds per gallon, excluding water.
  - d. The total uncontrolled VOC emission rate in pounds (the sum of (b)x(c) for all coatings employed).
  - e. The total controlled VOC emission rate for all coatings and cleanup materials, in pounds (i.e., calculated using the overall control efficiency from the most recent performance test that demonstrated that the emissions unit was in compliance).
  - f. The hours of operation of the emissions unit.
  - g. The calculated average hourly emission rate in pounds per hour, based upon the total daily coatings employed and the actual hours of operation of the emission unit.
  - h. The total controlled VOC emissions from all coatings and cleanup materials employed year to date, in tons (i.e., calculated using the overall control efficiency from the most recent performance test that demonstrated that the emissions unit was in compliance.).
3. The permittee shall collect and record the following information each month for materials used at the facility.
- a. The company identification for each coating and cleanup material employed.
  - b. The number of gallons of each coating and cleanup material employed.
  - c. The total HAP content of each coating, thinner, and cleanup material in pounds per gallon.
  - d. The total uncontrolled HAP emission rate in tons (the sum of (b)x(c)x(0.0005 ton/lb).
  - e. The total controlled HAP emission rate for all coatings and cleanup materials, in tons (i.e., calculated using the overall control efficiency from the most recent performance test).
  - f. The individual HAP content of each coating, thinner, and cleanup material in pounds per gallon.
  - g. The total uncontrolled individual HAP emission rate in tons (the sum of (b)x(g)x(0.0005 ton/lb).
  - h. The total controlled HAP emission rate for all coatings and cleanup materials, in tons (i.e.,

Mills 1

PTI A

Emissions Unit ID: K001

**Issued: To be entered upon final issuance**

calculated using the overall control efficiency from the most recent performance test).

- i. The rolling, 12-month summation of the data required in sections A.III.3.f. and A.III.3.i. above(i.e., the 12-month summations for individual HAP and total HAPs shall be calculated each month by adding the emission rate for the month to the emission rate for the previous 11 calendar months).

**IV. Reporting Requirements**

1. The permittee shall submit deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the RTO, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent performance test that demonstrated the emissions unit was in compliance.
2. The permittee shall submit quarterly summaries which include a log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
3. The quarterly summaries shall be submitted, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.
4. The permittee shall notify the Director (the Ohio EPA Southeast District Office) of any monthly record showing emissions in excess of the rolling, 12-month limitation specified in A.II. A copy of such record shall be sent to the Director within 30 days following the end of the calendar month.

**V. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
  - a. Emission Limitation

20% opacity

Applicable Compliance Method

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

**Mills Pride Limited Partnership**

PTI Application: 06-06474

**Issued****Facility ID: 0666010033**

Emissions Unit ID: K001

b. Emission Limitation

40.94 lb/hr VOC (based on a daily average)

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.2. above.

c. Emission Limitation

74.08 TPY of VOC

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.2

d. Emission Limitation

90% destruction efficiency / 90% overall reduction of emissions

Applicable Compliance Method

Compliance shall be determined in accordance with 40 CFR 60 Appendix A, Method 25 or 25A, the procedures specified in OAC rule 3745-21-10 and the requirements found in Sections A.III and A.IV.

The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:

2. The emission testing shall be conducted as specified by the permittee's Title V permit.
3. The emission testing shall be conducted to demonstrate compliance with the allowable mass emission rate(s) for VOC and the capture efficiency and control efficiency limitations for VOC.
4. The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s): for VOC, Method 25 or 25A of 40 CFR Part 60, Appendix A. The test method(s) which must be employed to demonstrate compliance with the capture efficiency and control efficiency limitations for VOC are specified below. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.
5. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency.

**Issued: To be entered upon final issuance**

6. The capture efficiency shall be determined using Methods 204 through 204F, as specified in 40 CFR Part 51, Appendix M, or the permittee may request to use an alternative method or procedure for the determination of capture efficiency in accordance with the USEPA's "Guidelines for Determining Capture Efficiency," dated January 9, 1995. The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in OAC rule 3745-21-10. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

- a. Emission Limitation

Total facility individual HAP emission less than 10 TPY.

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.3. above.

- b. Emission Limitation

Emissions Unit ID: K001

Total facility HAP's emissions less than 25 TPY.

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.3

c. Emission Limitation

0.551 lb/hr of Particulate Matter

Applicable Compliance Method

Compliance with the particulate matter emission limitation in Section A.I. of these terms and conditions shall be determined in accordance with the following method:

To determine the actual worst case emission rate for particulate matter, the following equation shall be used:

$$E = \text{maximum coating solids usage rate (in pounds per hour)} * (1-TE) * (1-CE)$$

$$E = \text{particulate emissions rate (lb/hr)}$$

$$TE = \text{transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used.}$$

$$CE = \text{control efficiency of the control equipment (ie. booth filters)}$$

d. Emission Limitation

2.4 TPY of PM

Applicable Compliance Method

Compliance shall be based upon a one time calculation of potential as follows:

$$E = MHER * 8760 \text{ hr/yr} * 0.0005 \text{ Ton/lb} = \text{TPY}$$

Where

MHER is the maximum controlled hourly emission rate determined in section A.V

## VI. Miscellaneous Requirements

None

Mills 1

PTI A

Emissions Unit ID: K001

**Issued: To be entered upon final issuance**

**B. State Only Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
K001 - Flatline Finishing System (system includes 3 spray booths, 1 dryer, and 2 curing ovens controlled by a Regenerative Thermal Oxidizer )	OAC rule 3745-31-05	LIMIT(s)

**2. Additional Terms and Conditions**

- 2.a None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

23

**Mills 1**

**PTI A**

**Issued: To be entered upon final issuance**

Emissions Unit ID: K001

None

Mills 1

PTI A

Emissions Unit ID: R001

Issued: To be entered upon final issuance

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
R001- Specialty booth finishing system (1 spray booth controlled by a Regenerative Thermal Oxidizer)	OAC rule 3745-21-07(G)(1)	
	OAC rule 3745-21-07(G)(6)(a)	OAC 3745-31-05(D) (Synthetic Minor to avoid MACT)
	OAC rule 3745-21-07(G)(2)	OAC rule 3745-17-07(A)
		OAC rule 3745-17-11(B) (Table 1)
	OAC rule 3745-31-05(A)(3)	

**Mills Pride Limited Partnership**

PTI Application: 06-06474

**Issued****Facility ID: 0666010033**

Emissions Unit ID: R001

Applicable Emissions  
Limitations/Control  
Measures

The emission reduction requirement specified in this rule (85% overall control efficiency) is less stringent than the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

The emission reduction requirement specified in this rule (90% or more of the carbon in the organic material being incinerated) is less stringent to the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

The emission reduction requirement specified in this rule (85% overall control efficiency) is less stringent than the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

Volatile organic compound (VOC) emissions shall not exceed 4.10 lbs/hr and 2.01 tons/yr.  
See section A.I.2.a.

Compliance with this rule also includes compliance with OAC rules 3745-17-07(A) and 3745-17-11(B)

The total facility Hazardous Air Pollution (HAP) emissions shall be less than 10 tons per year of a individual HAP, and 25 tons per year of a total of HAPs.

Visible particulate emissions from any stack shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.

Particulate emissions shall not exceed 0.551 lb/hr.

**Issued: To be entered upon final issuance****2. Additional Terms and Conditions**

- 2.a** The facility shall maintain an overall VOC control efficiency which is at least 90%, by weight, and a Regenerative Thermal Oxidizer (RTO) control efficiency (i.e., destruction or removal efficiency) which is at least 90%, by weight, for this emissions unit.

**II. Operational Restrictions**

1. The average combustion temperature within the RTO, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
2. The total facility Hazardous Air Pollution (HAP) emissions shall be less than 10 tons per year of a individual HAP, and 25 tons per year of a total of HAPs. The tons per year limits, shall be based upon a rolling twelve month period. The total facility limits are required to be federally enforceable in order to be exempt this facility from 40 CFR 63, Subpart JJ.
3. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the RTO when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day for the control equipment:

- a. All 3-hour blocks of time during which the average combustion temperature within the RTO, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.
  - b. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
2. The permittee shall collect and record the following information each day for materials used in the

emission unit.

- a. The company identification for each coating and cleanup material employed.
  - b. The number of gallons of each coating and cleanup material employed.
  - c. The VOC content of each coating and cleanup material, in pounds per gallon, excluding water.
  - d. The total uncontrolled VOC emission rate in pounds (the sum of (b)x(c) for all coatings employed).
  - e. The total controlled VOC emission rate for all coatings and cleanup materials, in pounds (i.e., calculated using the overall control efficiency from the most recent performance test that demonstrated that the emissions unit was in compliance).
  - f. The hours of operation of the emissions unit.
  - g. The calculated average hourly emission rate in pounds per hour, based upon the total daily coatings employed and the actual hours of operation of the emission unit.
  - h. The total controlled VOC emissions from all coatings and cleanup materials employed year to date, in tons (i.e., calculated using the overall control efficiency from the most recent performance test that demonstrated that the emissions unit was in compliance.).
3. The permittee shall collect and record the following information each month for materials used at the facility.
- a. The company identification for each coating and cleanup material employed.
  - b. The number of gallons of each coating and cleanup material employed.
  - c. The total HAP content of each coating, thinner, and cleanup material in pounds per gallon.
  - d. The total uncontrolled HAP emission rate in tons (the sum of (b)x(c)x(0.0005 ton/lb).
  - e. The total controlled HAP emission rate for all coatings and cleanup materials, in tons (i.e., calculated using the overall control efficiency from the most recent performance test).
  - f. The individual HAP content of each coating, thinner, and cleanup material in pounds per gallon.
  - g. The total uncontrolled individual HAP emission rate in tons (the sum of (b)x(g)x(0.0005 ton/lb).
  - h. The total controlled HAP emission rate for all coatings and cleanup materials, in tons (i.e.,

**Issued: To be entered upon final issuance**

calculated using the overall control efficiency from the most recent performance test).

- i. The rolling, 12-month summation of the data required in sections A.III.3.f. and A.III.3.i. above(i.e., the 12-month summations for individual HAP and total HAPs shall be calculated each month by adding the emission rate for the month to the emission rate for the previous 11 calendar months).

**IV. Reporting Requirements**

1. The permittee shall submit deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the RTO, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent performance test that demonstrated the emissions unit was in compliance.
2. The permittee shall submit quarterly summaries which include a log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
3. The quarterly summaries shall be submitted, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.
4. The permittee shall notify the Director (the Ohio EPA Southeast District Office) of any monthly record showing emissions in excess of the rolling, 12-month limitation specified in A.II. A copy of such record shall be sent to the Director within 30 days following the end of the calendar month.

Mills 1

PTI A

Emissions Unit ID: R001

**Issued: To be entered upon final issuance****V. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation

20% opacity

Applicable Compliance Method

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

- b. Emission Limitation

4.10 lb/hr VOC (based on a daily average)

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.2. above.

- c. Emission Limitation

2.01 TPY of VOC

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.2

- d. Emission Limitation

90% destruction efficiency / 90% overall reduction of emissions

Applicable Compliance Method

Compliance shall be determined in accordance with 40 CFR 60 Appendix A, Method 25 or 25A, the procedures specified in OAC rule 3745-21-10 and the requirements found in

Sections A.III and A.IV.

The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:

2. The emission testing shall be conducted as specified by the permittee's Title V permit.
3. The emission testing shall be conducted to demonstrate compliance with the allowable mass emission rate(s) for VOC and the capture efficiency and control efficiency limitations for VOC.
4. The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s): for VOC, Method 25 or 25A of 40 CFR Part 60, Appendix A. The test method(s) which must be employed to demonstrate compliance with the capture efficiency and control efficiency limitations for VOC are specified below. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.
5. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency.
6. The capture efficiency shall be determined using Methods 204 through 204F, as specified in 40 CFR Part 51, Appendix M, or the permittee may request to use an alternative method or procedure for the determination of capture efficiency in accordance with the USEPA's "Guidelines for Determining Capture Efficiency," dated January 9, 1995. The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in OAC rule 3745-21-10. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District

**Mills 1**

**PTI A**

Emissions Unit ID: R001

**Issued: To be entered upon final issuance**

Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

**Issued: To be entered upon final issuance**a. Emission Limitation

Total facility individual HAP emission less than 10 TPY.

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.3. above.

b. Emission Limitation

Total facility HAP's emissions less than 25 TPY.

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.3

c. Emission Limitation

0.551 lb/hr of Particulate Matter

Applicable Compliance Method

Compliance with the particulate matter emission limitation in Section A.I. of these terms and conditions shall be determined in accordance with the following method:

To determine the actual worst case emission rate for particulate matter, the following equation shall be used:

$$E = \text{maximum coating solids usage rate (in pounds per hour)} * (1-TE) * (1-CE)$$

$$E = \text{particulate emissions rate (lb/hr)}$$

$$TE = \text{transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used.}$$

$$CE = \text{control efficiency of the control equipment (ie. booth filters)}$$

d. Emission Limitation

**Mills Pride Limited Partnership**

**PTI Application: 06-06474**

**Issued**

**Facility ID: 0666010033**

Emissions Unit ID: R001

2.4 TPY of PM

Applicable Compliance Method

Compliance shall be based upon a one time calculation of potential as follows:

$$E = \text{MHER} * 8760 \text{ hr/yr} * 0.0005 \text{ Ton/lb} = \text{TPY}$$

Where

MHER is the maximum controlled hourly emission rate determined in section A.V

**VI. Miscellaneous Requirements**

None

Mills 1

PTI A

Emissions Unit ID: R001

**Issued: To be entered upon final issuance****B. State Only Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R001- Specialty booth finishing system (1 spray booth controlled by a Regenerative Thermal Oxidizer)	OAC rule 3745-31-05	LIMIT(s)

**2. Additional Terms and Conditions**

2.a None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

35

**Mills 1**

**PTI A**

**Issued: To be entered upon final issuance**

None

Emissions Unit ID: R001

Mills 1

PTI A

Emissions Unit ID: R002

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
R002 - Cefla line stain roll coater /oven (1 rollcoater and curing oven controlled by a Regenerative Thermal Oxidizer)	OAC rule 3745-21-07(G)(1)	
	OAC rule 3745-21-07(G)(6)(a)	OAC 3745-31-05(D) (Synthetic Minor to avoid MACT)
		OAC rule 3745-17-07(A)
	OAC rule 3745-21-07(G)(2)	
		OAC rule 3745-17-11(B) (Table 1)
	OAC rule 3745-31-05(A)(3)	

**Mills 1****PTI A**

Emissions Unit ID: R002

**Issued: To be entered upon final issuance**

Applicable Emissions  
Limitations/Control  
Measures

The emission reduction requirement specified in this rule (85% overall control efficiency) is less stringent than the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

The emission reduction requirement specified in this rule (90% or more of the carbon in the organic material being incinerated) is less stringent to the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

The emission reduction requirement specified in this rule (85% overall control efficiency) is less stringent than the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

Total combined volatile organic compound (VOC) emissions from emission units R002, R003, and R004 shall not exceed 2.05 lbs/hr

and 7.47 tons/yr.  
 See section A.I.2.a.

Compliance with this rule also includes compliance with OAC rules 3745-17-07(A) and 3745-17-11(B)

The total facility Hazardous Air Pollution (HAP) emissions shall be less than 10 tons per year of a individual HAP, and 25 tons per year of a total of HAPs.

Visible particulate emissions from any stack shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.

Particulate emissions shall not exceed 0.551 lb/hr.

**2. Additional Terms and Conditions**

- 2.a** The facility shall maintain an overall VOC control efficiency which is at least 90%, by weight, and a Regenerative Thermal Oxidizer (RTO) control efficiency (i.e., destruction or removal efficiency) which is at least 90%, by weight, for this emissions unit.

**II. Operational Restrictions**

1. The average combustion temperature within the RTO, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
2. The total facility Hazardous Air Pollution (HAP) emissions shall be less than 10 tons per year of a individual HAP, and 25 tons per year of a total of HAPs. The tons per year limits, shall be based upon a rolling twelve month period. The total facility limits are required to be federally enforceable in order to be exempt this facility from 40 CFR 63, Subpart JJ.
3. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the RTO when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day for the control equipment:

- a. All 3-hour blocks of time during which the average combustion temperature within the RTO, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.
  - b. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
2. The permittee shall collect and record the following information each day for materials used in the emission unit.
    - a. The company identification for each coating and cleanup material employed.
    - b. The number of gallons of each coating and cleanup material employed.

**Issued: To be entered upon final issuance**

- c. The VOC content of each coating and cleanup material, in pounds per gallon, excluding water.
  - d. The total uncontrolled VOC emission rate in pounds (the sum of (b)x(c) for all coatings employed).
  - e. The total controlled VOC emission rate for all coatings and cleanup materials, in pounds (i.e., calculated using the overall control efficiency from the most recent performance test that demonstrated that the emissions unit was in compliance).
  - f. The hours of operation of the emissions unit.
  - g. The calculated average hourly emission rate in pounds per hour, based upon the total daily coatings employed and the actual hours of operation of the emission unit.
  - h. The total controlled VOC emissions from all coatings and cleanup materials employed year to date, in tons (i.e., calculated using the overall control efficiency from the most recent performance test that demonstrated that the emissions unit was in compliance.).
3. The permittee shall collect and record the following information each month for materials used at the facility.
- a. The company identification for each coating and cleanup material employed.
  - b. The number of gallons of each coating and cleanup material employed.
  - c. The total HAP content of each coating, thinner, and cleanup material in pounds per gallon.
  - d. The total uncontrolled HAP emission rate in tons (the sum of (b)x(c)x(0.0005 ton/lb).
  - e. The total controlled HAP emission rate for all coatings and cleanup materials, in tons (i.e., calculated using the overall control efficiency from the most recent performance test).
  - f. The individual HAP content of each coating, thinner, and cleanup material in pounds per gallon.
  - g. The total uncontrolled individual HAP emission rate in tons (the sum of (b)x(g)x(0.0005 ton/lb).
  - h. The total controlled HAP emission rate for all coatings and cleanup materials, in tons (i.e.,

**Mills Pride Limited Partnership****PTI Application: 06-06474****Issued****Facility ID: 0666010033**

Emissions Unit ID: R002

calculated using the overall control efficiency from the most recent performance test).

- i. The rolling, 12-month summation of the data required in sections A.III.3.f. and A.III.3.i. above (i.e., the 12-month summations for individual HAP and total HAPs shall be calculated each month by adding the emission rate for the month to the emission rate for the previous 11 calendar months).

#### **IV. Reporting Requirements**

1. The permittee shall submit deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the RTO, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent performance test that demonstrated the emissions unit was in compliance.
2. The permittee shall submit quarterly summaries which include a log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
3. The quarterly summaries shall be submitted, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.
4. The permittee shall notify the Director (the Ohio EPA Southeast District Office) of any monthly record showing emissions in excess of the rolling, 12-month limitation specified in A.II. A copy of such record shall be sent to the Director within 30 days following the end of the calendar month.

Issued: To be entered upon final issuance

## V. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation

20% opacity

Applicable Compliance Method

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

- b. Emission Limitation

Total combined volatile organic compound (VOC) emissions from emission units R002, R003, and R004 shall not exceed 2.05 lbs/hr (based on a daily average)

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.2. above.

- c. Emission Limitation

Total combined volatile organic compound (VOC) emissions from emission units R002, R003, and R004 shall not exceed 7.47 tons/yr.

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.2

- d. Emission Limitation

90% destruction efficiency / 90% overall reduction of emissions

Applicable Compliance Method

**Issued: To be entered upon final issuance**

Compliance shall be determined in accordance with 40 CFR 60 Appendix A, Method 25 or 25A, the procedures specified in OAC rule 3745-21-10 and the requirements found in Sections A.III and A.IV.

The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:

2. The emission testing shall be conducted as specified by the permittee's Title V permit.
3. The emission testing shall be conducted to demonstrate compliance with the allowable mass emission rate(s) for VOC and the capture efficiency and control efficiency limitations for VOC.
4. The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s): for VOC, Method 25 or 25A of 40 CFR Part 60, Appendix A. The test method(s) which must be employed to demonstrate compliance with the capture efficiency and control efficiency limitations for VOC are specified below. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.
5. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency.
6. The capture efficiency shall be determined using Methods 204 through 204F, as specified in 40 CFR Part 51, Appendix M, or the permittee may request to use an alternative method or procedure for the determination of capture efficiency in accordance with the USEPA's "Guidelines for Determining Capture Efficiency," dated January 9, 1995. The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in OAC rule 3745-21-10. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).

Emissions Unit ID: R002

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

a. Emission Limitation

Total facility individual HAP emission less than 10 TPY.

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.3. above.

b. Emission Limitation

Total facility HAP's emissions less than 25 TPY.

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.3

c. Emission Limitation

0.551 lb/hr of Particulate Matter

Applicable Compliance Method

Compliance with the particulate matter emission limitation in Section A.I. of these terms and conditions shall be determined in accordance with the following method:

To determine the actual worst case emission rate for particulate matter, the following equation shall be used:

$$E = \text{maximum coating solids usage rate (in pounds per hour)} * (1-TE) * (1-CE)$$

$$E = \text{particulate emissions rate (lb/hr)}$$

$$TE = \text{transfer efficiency, which is the ratio of the amount of coating solids deposited on}$$

Mills 1

PTI A

Emissions Unit ID: R002

Issued: To be entered upon final issuance

the coated part to the amount of coating solids used.

CE = control efficiency of the control equipment (ie. booth filters)

d. Emission Limitation

2.4 TPY of PM

**Mills 1****PTI A**

Emissions Unit ID: R002

**Issued: To be entered upon final issuance**Applicable Compliance Method

Compliance shall be based upon a one time calculation of potential as follows:

$$E = \text{MHER} * 8760 \text{ hr/yr} * 0.0005 \text{ Ton/lb} = \text{TPY}$$

Where

MHER is the maximum controlled hourly emission rate determined in section A.V

**VI. Miscellaneous Requirements**

None

Mills Pride Limited Partnership

PTI Application: 06-06474

Issued

Facility ID: 0666010033

Emissions Unit ID: R002

**B. State Only Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R002 - Cefla line stain roll coater /oven (1 rollcoater and curing oven controlled by a Regenerative Thermal Oxidizer)	OAC rule 3745-31-05	LIMIT(s)

**2. Additional Terms and Conditions**

2.a None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

Mills 1

PTI A

Emissions Unit ID: R003

Issued: To be entered upon final issuance

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
R003 - Cefla line roll coater #1/UV lamp (1 roll coater and ultraviolet curing oven controlled by a Regenerative Thermal Oxidizer)	OAC rule 3745-21-07(G)(1)	
	OAC rule 3745-21-07(G)(6)(a)	OAC 3745-31-05(D)
	OAC rule 3745-21-07(G)(2)	OAC rule 3745-17-07(A)
		OAC rule 3745-17-11(B) (Table 1)
	OAC rule 3745-31-05(A)(3)	

**Mills 1****PTI A**

Emissions Unit ID: R003

**Issued: To be entered upon final issuance**

Applicable Emissions  
Limitations/Control  
Measures

The emission reduction requirement specified in this rule (85% overall control efficiency) is less stringent than the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

The emission reduction requirement specified in this rule (90% or more of the carbon in the organic material being incinerated) is less stringent to the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

The emission reduction requirement specified in this rule (85% overall control efficiency) is less stringent than the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

Total combined volatile organic compound (VOC) emissions from emission units R002, R003, and R004 shall not exceed 2.05 lbs/hr

and 7.47 tons/yr.  
 See section A.I.2.a.

Compliance with this rule also includes compliance with OAC rules 3745-17-07(A) and 3745-17-11(B)

The total facility Hazardous Air Pollution (HAP) emissions shall be less than 10 tons per year of a individual HAP, and 25 tons per year of a total of HAPs.

Visible particulate emissions from any stack shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.

Particulate emissions shall not exceed 0.551 lb/hr.

**Issued: To be entered upon final issuance****2. Additional Terms and Conditions**

- 2.a** The facility shall maintain an overall VOC control efficiency which is at least 90%, by weight, and a Regenerative Thermal Oxidizer (RTO) control efficiency (i.e., destruction or removal efficiency) which is at least 90%, by weight, for this emissions unit.

**II. Operational Restrictions**

1. The average combustion temperature within the RTO, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
2. The total facility Hazardous Air Pollution (HAP) emissions shall be less than 10 tons per year of a individual HAP, and 25 tons per year of a total of HAPs. The tons per year limits, shall be based upon a rolling twelve month period. The total facility limits are required to be federally enforceable in order to be exempt this facility from 40 CFR 63, Subpart JJ.
3. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the RTO when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day for the control equipment:

- a. All 3-hour blocks of time during which the average combustion temperature within the RTO, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.
  - b. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
2. The permittee shall collect and record the following information each day for materials used in the

emission unit.

- a. The company identification for each coating and cleanup material employed.
  - b. The number of gallons of each coating and cleanup material employed.
  - c. The VOC content of each coating and cleanup material, in pounds per gallon, excluding water.
  - d. The total uncontrolled VOC emission rate in pounds (the sum of (b)x(c) for all coatings employed).
  - e. The total controlled VOC emission rate for all coatings and cleanup materials, in pounds (i.e., calculated using the overall control efficiency from the most recent performance test that demonstrated that the emissions unit was in compliance).
  - f. The hours of operation of the emissions unit.
  - g. The calculated average hourly emission rate in pounds per hour, based upon the total daily coatings employed and the actual hours of operation of the emission unit.
  - h. The total controlled VOC emissions from all coatings and cleanup materials employed year to date, in tons (i.e., calculated using the overall control efficiency from the most recent performance test that demonstrated that the emissions unit was in compliance.).
3. The permittee shall collect and record the following information each month for materials used at the facility.
- a. The company identification for each coating and cleanup material employed.
  - b. The number of gallons of each coating and cleanup material employed.
  - c. The total HAP content of each coating, thinner, and cleanup material in pounds per gallon.
  - d. The total uncontrolled HAP emission rate in tons (the sum of (b)x(c)x(0.0005 ton/lb).
  - e. The total controlled HAP emission rate for all coatings and cleanup materials, in tons (i.e., calculated using the overall control efficiency from the most recent performance test).
  - f. The individual HAP content of each coating, thinner, and cleanup material in pounds per gallon.
  - g. The total uncontrolled individual HAP emission rate in tons (the sum of (b)x(g)x(0.0005 ton/lb).
  - h. The total controlled HAP emission rate for all coatings and cleanup materials, in tons (i.e.,

**Issued: To be entered upon final issuance**

calculated using the overall control efficiency from the most recent performance test).

- i. The rolling, 12-month summation of the data required in sections A.III.3.f. and A.III.3.i. above(i.e., the 12-month summations for individual HAP and total HAPs shall be calculated each month by adding the emission rate for the month to the emission rate for the previous 11 calendar months).

**IV. Reporting Requirements**

1. The permittee shall submit deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the RTO, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent performance test that demonstrated the emissions unit was in compliance.
2. The permittee shall submit quarterly summaries which include a log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
3. The quarterly summaries shall be submitted, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.
4. The permittee shall notify the Director (the Ohio EPA Southeast District Office) of any monthly record showing emissions in excess of the rolling, 12-month limitation specified in A.II. A copy of such record shall be sent to the Director within 30 days following the end of the calendar month.

**V. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation

20% opacity

Applicable Compliance Method

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

- b. Emission Limitation

Total combined volatile organic compound (VOC) emissions from emission units R002, R003, and R004 shall not exceed 2.05 lbs/hr.(based on a daily average)

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.2. above.

- c. Emission Limitation

Total combined volatile organic compound (VOC) emissions from emission units R002, R003, and R004 shall not exceed 7.47 tons/yr.

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.2

- d. Emission Limitation

90% destruction efficiency / 90% overall reduction of emissions

Applicable Compliance Method

Compliance shall be determined in accordance with 40 CFR 60 Appendix A, Method 25 or 25A, the procedures specified in OAC rule 3745-21-10 and the requirements found in Sections A.III and A.IV.

The permittee shall conduct, or have conducted, emission testing for this emissions unit in

**Issued: To be entered upon final issuance**

accordance with the following requirements:

2. The emission testing shall be conducted as specified by the permittee's Title V permit.
3. The emission testing shall be conducted to demonstrate compliance with the allowable mass emission rate(s) for VOC and the capture efficiency and control efficiency limitations for VOC.
4. The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s): for VOC, Method 25 or 25A of 40 CFR Part 60, Appendix A. The test method(s) which must be employed to demonstrate compliance with the capture efficiency and control efficiency limitations for VOC are specified below. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.
5. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency.
6. The capture efficiency shall be determined using Methods 204 through 204F, as specified in 40 CFR Part 51, Appendix M, or the permittee may request to use an alternative method or procedure for the determination of capture efficiency in accordance with the USEPA's "Guidelines for Determining Capture Efficiency," dated January 9, 1995. The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in OAC rule 3745-21-10. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

Emissions Unit ID: R003

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

a. Emission Limitation

Total facility individual HAP emission less than 10 TPY.

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.3. above.

b. Emission Limitation

Total facility HAP's emissions less than 25 TPY.

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.3

c. Emission Limitation

0.551 lb/hr of Particulate Matter

Applicable Compliance Method

Compliance with the particulate matter emission limitation in Section A.I. of these terms and conditions shall be determined in accordance with the following method:

To determine the actual worst case emission rate for particulate matter, the following equation shall be used:

$$E = \text{maximum coating solids usage rate (in pounds per hour)} * (1-TE) * (1-CE)$$

$$E = \text{particulate emissions rate (lb/hr)}$$

$$TE = \text{transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used.}$$

$$CE = \text{control efficiency of the control equipment (ie. booth filters)}$$

d. Emission Limitation

55

**Mills 1**

**PTI A**

**Issued: To be entered upon final issuance**

Emissions Unit ID: R003

2.4 TPY of PM

**Mills 1****PTI A**

Emissions Unit ID: R003

**Issued: To be entered upon final issuance**Applicable Compliance Method

Compliance shall be based upon a one time calculation of potential as follows:

$$E = \text{MHER} * 8760 \text{ hr/yr} * 0.0005 \text{ Ton/lb} = \text{TPY}$$

Where

MHER is the maximum controlled hourly emission rate determined in section A.V

**VI. Miscellaneous Requirements**

None

Mills 1

PTI A

Emissions Unit ID: R003

**Issued: To be entered upon final issuance**

**B. State Only Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R003 - Cefla line roll coater #1/UV lamp (1 roll coater and ultraviolet curing oven controlled by a Regenerative Thermal Oxidizer)	OAC rule 3745-31-05	LIMIT(s)

**2. Additional Terms and Conditions**

**2.a** None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

58

**Mills 1**

**PTI A**

**Issued: To be entered upon final issuance**

Emissions Unit ID: R003

None

Mills 1

PTI A

Emissions Unit ID: R004

Issued: To be entered upon final issuance

Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. State and Federally Enforceable Section

I. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
R004 - Cefla line roll coater #2/UV lamp (1 roll coater and ultraviolet curing oven controlled by a Regenerative Thermal Oxidizer)	OAC rule 3745-21-07(G)(1)	
	OAC rule 3745-21-07(G)(6)(a)	OAC 3745-31-05(D) (Synthetic Minor to avoid MACT)
	OAC rule 3745-21-07(G)(2)	OAC rule 3745-17-07(A)
		OAC rule 3745-17-11(B) (Table 1)
	OAC rule 3745-31-05(A)(3)	

**Mills Pride Limited Partnership**

PTI Application: 06-06474

**Issued****Facility ID: 0666010033**

Emissions Unit ID: R004

Applicable Emissions  
Limitations/Control  
Measures

The emission reduction requirement specified in this rule (85% overall control efficiency) is less stringent than the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

The emission reduction requirement specified in this rule (90% or more of the carbon in the organic material being incinerated) is less stringent to the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

The emission reduction requirement specified in this rule (85% overall control efficiency) is less stringent than the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

Total combined volatile organic compound (VOC) emissions from emission units R002, R003, and R004 shall not exceed 2.05 lbs/hr and 7.47 tons/yr. See section A.I.2.a.

Compliance with this rule also includes compliance

with OAC rules 3745-17-07(A) and 3745-17-11(B)

The total facility Hazardous Air Pollution (HAP) emissions shall be less than 10 tons per year of a individual HAP, and 25 tons per year of a total of HAPs.

Visible particulate emissions from any stack shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.

Particulate emissions shall not exceed 0.551 lb/hr.

**Issued: To be entered upon final issuance****2. Additional Terms and Conditions**

- 2.a** The facility shall maintain an overall VOC control efficiency which is at least 90%, by weight, and a Regenerative Thermal Oxidizer (RTO) control efficiency (i.e., destruction or removal efficiency) which is at least 90%, by weight, for this emissions unit.

**II. Operational Restrictions**

1. The average combustion temperature within the RTO, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
2. The total facility Hazardous Air Pollution (HAP) emissions shall be less than 10 tons per year of a individual HAP, and 25 tons per year of a total of HAPs. The tons per year limits, shall be based upon a rolling twelve month period. The total facility limits are required to be federally enforceable in order to be exempt this facility from 40 CFR 63, Subpart JJ.
3. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the RTO when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be

**Issued: To be entered upon final issuance**

capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day for the control equipment:

- a. All 3-hour blocks of time during which the average combustion temperature within the RTO, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.
  - b. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
2. The permittee shall collect and record the following information each day for materials used in the emission unit.
- a. The company identification for each coating and cleanup material employed.
  - b. The number of gallons of each coating and cleanup material employed.
  - c. The VOC content of each coating and cleanup material, in pounds per gallon, excluding water.
  - d. The total uncontrolled VOC emission rate in pounds (the sum of (b)x(c) for all coatings employed).
  - e. The total controlled VOC emission rate for all coatings and cleanup materials, in pounds (i.e., calculated using the overall control efficiency from the most recent performance test that demonstrated that the emissions unit was in compliance).
  - f. The hours of operation of the emissions unit.
  - g. The calculated average hourly emission rate in pounds per hour, based upon the total daily coatings employed and the actual hours of operation of the emission unit.
  - h. The total controlled VOC emissions from all coatings and cleanup materials employed year to date, in tons (i.e., calculated using the overall control efficiency from the most recent performance test that demonstrated that the emissions unit was in compliance.).

Emissions Unit ID: R004

3. The permittee shall collect and record the following information each month for materials used at the facility.
  - a. The company identification for each coating and cleanup material employed.
  - b. The number of gallons of each coating and cleanup material employed.
  - c. The total HAP content of each coating, thinner, and cleanup material in pounds per gallon.
  - d. The total uncontrolled HAP emission rate in tons (the sum of (b)x(c)x(0.0005 ton/lb).
  - e. The total controlled HAP emission rate for all coatings and cleanup materials, in tons (i.e., calculated using the overall control efficiency from the most recent performance test).
  - f. The individual HAP content of each coating, thinner, and cleanup material in pounds per gallon.
  - g. The total uncontrolled individual HAP emission rate in tons (the sum of (b)x(g)x(0.0005 ton/lb).
  - h. The total controlled HAP emission rate for all coatings and cleanup materials, in tons (i.e., calculated using the overall control efficiency from the most recent performance test).
  - i. The rolling, 12-month summation of the data required in sections A.III.3.f. and A.III.3.i. above(i.e., the 12-month summations for individual HAP and total HAPs shall be calculated each month by adding the emission rate for the month to the emission rate for the previous 11 calendar months).

#### **IV. Reporting Requirements**

1. The permittee shall submit deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the RTO, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent performance test that demonstrated the emissions unit was in compliance.
2. The permittee shall submit quarterly summaries which include a log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
3. The quarterly summaries shall be submitted, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.
4. The permittee shall notify the Director (the Ohio EPA Southeast District Office) of any monthly record showing emissions in excess of the rolling, 12-month limitation specified in A.II. A copy of such record shall be sent to the Director within 30 days following the end of the calendar month.

**Issued: To be entered upon final issuance****V. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

- a. Emission Limitation

20% opacity

Applicable Compliance Method

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

- b. Emission Limitation

Total combined volatile organic compound (VOC) emissions from emission units R002, R003, and R004 shall not exceed 2.05 lbs/hr. (based on a daily average)

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.2. above.

- c. Emission Limitation

Total combined volatile organic compound (VOC) emissions from emission units R002, R003, and R004 shall not exceed 7.47 tons/yr.

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.2

- d. Emission Limitation

90% destruction efficiency / 90% overall reduction of emissions

Applicable Compliance Method

**Mills Pride Limited Partnership****PTI Application: 06-06474****Issued****Facility ID: 0666010033**

Emissions Unit ID: R004

Compliance shall be determined in accordance with 40 CFR 60 Appendix A, Method 25 or 25A, the procedures specified in OAC rule 3745-21-10 and the requirements found in Sections A.III and A.IV.

The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:

2. The emission testing shall be conducted as specified by the permittee's Title V permit.
3. The emission testing shall be conducted to demonstrate compliance with the allowable mass emission rate(s) for VOC and the capture efficiency and control efficiency limitations for VOC.
4. The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s): for VOC, Method 25 or 25A of 40 CFR Part 60, Appendix A. The test method(s) which must be employed to demonstrate compliance with the capture efficiency and control efficiency limitations for VOC are specified below. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.
5. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency.
6. The capture efficiency shall be determined using Methods 204 through 204F, as specified in 40 CFR Part 51, Appendix M, or the permittee may request to use an alternative method or procedure for the determination of capture efficiency in accordance with the USEPA's "Guidelines for Determining Capture Efficiency," dated January 9, 1995. The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in OAC rule 3745-21-10. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

**Issued: To be entered upon final issuance**

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

a. Emission Limitation

Total facility individual HAP emission less than 10 TPY.

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.3. above.

b. Emission Limitation

Total facility HAP's emissions less than 25 TPY.

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.3

c. Emission Limitation

0.551 lb/hr of Particulate Matter

Applicable Compliance Method

Compliance with the particulate matter emission limitation in Section A.I. of these terms and conditions shall be determined in accordance with the following method:

To determine the actual worst case emission rate for particulate matter, the following equation shall be used:

$$E = \text{maximum coating solids usage rate (in pounds per hour)} * (1-TE) * (1-CE)$$

$$E = \text{particulate emissions rate (lb/hr)}$$

$$TE = \text{transfer efficiency, which is the ratio of the amount of coating solids deposited on}$$

**Mills Pride Limited Partnership**

**PTI Application: 06-06474**

**Issued**

**Facility ID: 0666010033**

Emissions Unit ID: R004

the coated part to the amount of coating solids used.

CE = control efficiency of the control equipment (ie. booth filters)

d. Emission Limitation

2.4 TPY of PM

**Mills 1****PTI A**

Emissions Unit ID: R004

**Issued: To be entered upon final issuance**Applicable Compliance Method

Compliance shall be based upon a one time calculation of potential as follows:

$$E = \text{MHER} * 8760 \text{ hr/yr} * 0.0005 \text{ Ton/lb} = \text{TPY}$$

Where

MHER is the maximum controlled hourly emission rate determined in section A.V

**VI. Miscellaneous Requirements**

None

Mills 1

PTI A

Emissions Unit ID: R004

**Issued: To be entered upon final issuance****B. State Only Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R004 - Cefla line roll coater #2/UV lamp (1 roll coater and ultraviolet curing oven controlled by a Regenerative Thermal Oxidizer)	OAC rule 3745-31-05	LIMIT(s)

**2. Additional Terms and Conditions**

2.a None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

70

**Mills 1**

**PTI A**

**Issued: To be entered upon final issuance**

Emissions Unit ID: R004

None

Mills 1

PTI A

Emissions Unit ID: R011

**Issued: To be entered upon final issuance****Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)****A. State and Federally Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
R011 - Backline Finishing System ( 2 spray booths, and 2 IR drying ovens controlled by a Regenerative Thermal Oxidizer)	OAC rule 3745-21-07(G)(1)	OAC 3745-31-05(D) (Synthetic Minor to avoid MACT)
	OAC rule 3745-21-07(G)(6)(a)	OAC rule 3745-17-07(A)
	OAC rule 3745-21-07(G)(2)	OAC rule 3745-17-11(B) (Table 1)
	OAC rule 3745-31-05(A)(3)	

**Mills 1****PTI A**

Emissions Unit ID: R011

**Issued: To be entered upon final issuance**

Applicable Emissions  
Limitations/Control  
Measures

The emission reduction requirement specified in this rule (85% overall control efficiency) is less stringent than the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

The emission reduction requirement specified in this rule (90% or more of the carbon in the organic material being incinerated) is less stringent to the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

The emission reduction requirement specified in this rule (85% overall control efficiency) is less stringent than the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

Volatile organic compound (VOC) emissions shall not exceed 10.85 lbs/hr and 45.34 tons/yr. See section A.I.2.a.

Compliance with this rule also includes compliance with OAC rules 3745-17-07(A) and 3745-17-11(B)

The total facility Hazardous Air Pollution (HAP) emissions shall be less than 10 tons per year of a individual HAP, and 25 tons per year of a total of HAPs.

Visible particulate emissions from any stack shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.

Particulate emissions shall not exceed 0.551 lb/hr.

**2. Additional Terms and Conditions**

- 2.a** The facility shall maintain an overall VOC control efficiency which is at least 90%, by weight, and a Regenerative Thermal Oxidizer (RTO) control efficiency (i.e., destruction or removal efficiency) which is at least 90%, by weight, for this emissions unit.

**II. Operational Restrictions**

1. The average combustion temperature within the RTO, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
2. The total facility Hazardous Air Pollution (HAP) emissions shall be less than 10 tons per year of a individual HAP, and 25 tons per year of a total of HAPs. The tons per year limits, shall be based upon a rolling twelve month period. The total facility limits are required to be federally enforceable in order to be exempt this facility from 40 CFR 63, Subpart JJ.
3. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the RTO when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day for the control equipment:

- a. All 3-hour blocks of time during which the average combustion temperature within the RTO, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.
  - b. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
2. The permittee shall collect and record the following information each day for materials used in the emission unit.
    - a. The company identification for each coating and cleanup material employed.
    - b. The number of gallons of each coating and cleanup material employed.

**Issued: To be entered upon final issuance**

- c. The VOC content of each coating and cleanup material, in pounds per gallon, excluding water.
  - d. The total uncontrolled VOC emission rate in pounds (the sum of (b)x(c) for all coatings employed).
  - e. The total controlled VOC emission rate for all coatings and cleanup materials, in pounds (i.e., calculated using the overall control efficiency from the most recent performance test that demonstrated that the emissions unit was in compliance).
  - f. The hours of operation of the emissions unit.
  - g. The calculated average hourly emission rate in pounds per hour, based upon the total daily coatings employed and the actual hours of operation of the emission unit.
  - h. The total controlled VOC emissions from all coatings and cleanup materials employed year to date, in tons (i.e., calculated using the overall control efficiency from the most recent performance test that demonstrated that the emissions unit was in compliance.).
3. The permittee shall collect and record the following information each month for materials used at the facility.
- a. The company identification for each coating and cleanup material employed.
  - b. The number of gallons of each coating and cleanup material employed.
  - c. The total HAP content of each coating, thinner, and cleanup material in pounds per gallon.
  - d. The total uncontrolled HAP emission rate in tons (the sum of (b)x(c)x(0.0005 ton/lb).
  - e. The total controlled HAP emission rate for all coatings and cleanup materials, in tons (i.e., calculated using the overall control efficiency from the most recent performance test).
  - f. The individual HAP content of each coating, thinner, and cleanup material in pounds per gallon.
  - g. The total uncontrolled individual HAP emission rate in tons (the sum of (b)x(g)x(0.0005 ton/lb).
  - h. The total controlled HAP emission rate for all coatings and cleanup materials, in tons (i.e.,

calculated using the overall control efficiency from the most recent performance test).

- i. The rolling, 12-month summation of the data required in sections A.III.3.f. and A.III.3.i. above(i.e., the 12-month summations for individual HAP and total HAPs shall be calculated each month by adding the emission rate for the month to the emission rate for the previous 11 calendar months).

#### **IV. Reporting Requirements**

1. The permittee shall submit deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the RTO, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent performance test that demonstrated the emissions unit was in compliance.
2. The permittee shall submit quarterly summaries which include a log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
3. The quarterly summaries shall be submitted, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.
4. The permittee shall notify the Director (the Ohio EPA Southeast District Office) of any monthly record showing emissions in excess of the rolling, 12-month limitation specified in A.II. A copy of such record shall be sent to the Director within 30 days following the end of the calendar month.

#### **V. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

**Issued: To be entered upon final issuance**a. Emission Limitation

20% opacity

Applicable Compliance Method

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

b. Emission Limitation

10.85 lb/hr VOC (based on a daily average)

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.2. above.

c. Emission Limitation

45.34 TPY of VOC

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.2

d. Emission Limitation

90% destruction efficiency / 90% overall reduction of emissions

Applicable Compliance Method

Compliance shall be determined in accordance with 40 CFR 60 Appendix A, Method 25 or 25A, the procedures specified in OAC rule 3745-21-10 and the requirements found in Sections A.III and A.IV.

The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:

**Issued: To be entered upon final issuance**

2. The emission testing shall be conducted as specified by the permittee's Title V permit.
3. The emission testing shall be conducted to demonstrate compliance with the allowable mass emission rate(s) for VOC and the capture efficiency and control efficiency limitations for VOC.
4. The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s): for VOC, Method 25 or 25A of 40 CFR Part 60, Appendix A. The test method(s) which must be employed to demonstrate compliance with the capture efficiency and control efficiency limitations for VOC are specified below. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.
5. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency.
6. The capture efficiency shall be determined using Methods 204 through 204F, as specified in 40 CFR Part 51, Appendix M, or the permittee may request to use an alternative method or procedure for the determination of capture efficiency in accordance with the USEPA's "Guidelines for Determining Capture Efficiency," dated January 9, 1995. The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in OAC rule 3745-21-10. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District

**Mills Pride Limited Partnership****PTI Application: 06-06474****Issued****Facility ID: 0666010033**

Emissions Unit ID: R011

Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

a. Emission Limitation

Total facility individual HAP emission less than 10 TPY.

**Issued: To be entered upon final issuance**Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.3. above.

b. Emission Limitation

Total facility HAP's emissions less than 25 TPY.

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.3

c. Emission Limitation

0.551 lb/hr of Particulate Matter

Applicable Compliance Method

Compliance with the particulate matter emission limitation in Section A.I. of these terms and conditions shall be determined in accordance with the following method:

To determine the actual worst case emission rate for particulate matter, the following equation shall be used:

$$E = \text{maximum coating solids usage rate (in pounds per hour)} * (1-TE) * (1-CE)$$

$$E = \text{particulate emissions rate (lb/hr)}$$

$$TE = \text{transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used.}$$

$$CE = \text{control efficiency of the control equipment (ie. booth filters)}$$

d. Emission Limitation

2.4 TPY of PM

Applicable Compliance Method

80

**Mills 1**

**PTI A**

Emissions Unit ID: R011

**Issued: To be entered upon final issuance**

Compliance shall be based upon a one time calculation of potential as follows:

$$E = \text{MHER} * 8760 \text{ hr/yr} * 0.0005 \text{ Ton/lb} = \text{TPY}$$

81

**Mills 1**

**PTI A**

Emissions Unit ID: R011

**Issued: To be entered upon final issuance**

Where

MHER is the maximum controlled hourly emission rate determined in section A.V

**VI. Miscellaneous Requirements**

None

Mills 1

PTI A

Emissions Unit ID: R011

**Issued: To be entered upon final issuance****B. State Only Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R011 - Backline Finishing System ( 2 spray booths, and 2 IR drying ovens controlled by a Regenerative Thermal Oxidizer)	OAC rule 3745-31-05	LIMIT(s)

**2. Additional Terms and Conditions**

2.a None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

83

**Mills Pride Limited Partnership**

**PTI Application: 06-06474**

**Issued**

**Facility ID: 0666010033**

Emissions Unit ID: R011

None

Mills 1

PTI A

Emissions Unit ID: R013

Issued: To be entered upon final issuance

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
R013 - Backline Finishing System ( 1 spray booth controlled by a Regenerative Thermal Oxidizer)	OAC rule 3745-21-07(G)(1)	OAC 3745-31-05(D) (Synthetic Minor to avoid MACT)
	OAC rule 3745-21-07(G)(6)(a)	OAC rule 3745-17-07(A)
	OAC rule 3745-21-07(G)(2)	OAC rule 3745-17-11(B) (Table 1)
	OAC rule 3745-31-05(A)(3)	

**Mills 1****PTI A**

Emissions Unit ID: R013

**Issued: To be entered upon final issuance**Applicable Emissions  
Limitations/Control  
Measures

The emission reduction requirement specified in this rule (85% overall control efficiency) is less stringent than the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

The emission reduction requirement specified in this rule (90% or more of the carbon in the organic material being incinerated) is less stringent to the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

The emission reduction requirement specified in this rule (85% overall control efficiency) is less stringent than the emission reduction requirement established pursuant OAC rule 3745-31-05(A)(3). See section A.I.2.a.

Volatile organic compound (VOC) emissions shall not exceed 4.10 lbs/hr and 2.01 tons/yr.  
See section A.I.2.a.

Compliance with this rule also includes compliance with OAC rules 3745-17-07(A) and 3745-17-11(B)

The total facility Hazardous Air Pollution (HAP) emissions shall be less than 10 tons per year of a individual HAP, and 25 tons per year of a total of HAPs.

Visible particulate emissions from any stack shall not exceed 20% opacity as a 6-minute average, except as provided by the rule.

Particulate emissions shall not exceed 0.551 lb/hr.

**Issued: To be entered upon final issuance****2. Additional Terms and Conditions**

- 2.a** The facility shall maintain an overall VOC control efficiency which is at least 90%, by weight, and a Regenerative Thermal Oxidizer (RTO) control efficiency (i.e., destruction or removal efficiency) which is at least 90%, by weight, for this emissions unit.

**II. Operational Restrictions**

1. The average combustion temperature within the RTO, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
2. The total facility Hazardous Air Pollution (HAP) emissions shall be less than 10 tons per year of a individual HAP, and 25 tons per year of a total of HAPs. The tons per year limits, shall be based upon a rolling twelve month period. The total facility limits are required to be federally enforceable in order to be exempt this facility from 40 CFR 63, Subpart JJ.
3. The permittee shall operate the dry filtration system whenever this emissions unit is in operation.

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the RTO when the emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day for the control equipment:

- a. All 3-hour blocks of time during which the average combustion temperature within the RTO, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated that the emissions unit was in compliance.
  - b. A log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
2. The permittee shall collect and record the following information each day for materials used in the

emission unit.

- a. The company identification for each coating and cleanup material employed.
  - b. The number of gallons of each coating and cleanup material employed.
  - c. The VOC content of each coating and cleanup material, in pounds per gallon, excluding water.
  - d. The total uncontrolled VOC emission rate in pounds (the sum of (b)x(c) for all coatings employed).
  - e. The total controlled VOC emission rate for all coatings and cleanup materials, in pounds (i.e., calculated using the overall control efficiency from the most recent performance test).
  - f. The hours of operation of the emissions unit.
  - g. The calculated average hourly emission rate in pounds per hour, based upon the total daily coatings employed and the actual hours of operation of the emission unit.
  - h. The total controlled VOC emissions from all coatings and cleanup materials employed year to date, in tons (i.e., calculated using the overall control efficiency from the most recent performance test).
3. The permittee shall collect and record the following information each month for materials used at the facility.
- a. The company identification for each coating and cleanup material employed.
  - b. The number of gallons of each coating and cleanup material employed.
  - c. The total HAP content of each coating, thinner, and cleanup material in pounds per gallon.
  - d. The total uncontrolled HAP emission rate in tons (the sum of (b)x(c)x(0.0005 ton/lb).
  - e. The total controlled HAP emission rate for all coatings and cleanup materials, in tons (i.e., calculated using the overall control efficiency from the most recent performance test that demonstrated that the emissions unit was in compliance).
  - f. The individual HAP content of each coating, thinner, and cleanup material in pounds per gallon.
  - g. The total uncontrolled individual HAP emission rate in tons (the sum of (b)x(g)x(0.0005 ton/lb).

**Mills 1****PTI A**

Emissions Unit ID: R013

**Issued: To be entered upon final issuance**

- h. The total controlled HAP emission rate for all coatings and cleanup materials, in tons (i.e., calculated using the overall control efficiency from the most recent performance test that demonstrated that the emissions unit was in compliance).
- i. The rolling, 12-month summation of the data required in sections A.III.3.f. and A.III.3.i. above (i.e., the 12-month summations for individual HAP and total HAPs shall be calculated each month by adding the emission rate for the month to the emission rate for the previous 11 calendar months).

**IV. Reporting Requirements**

1. The permittee shall submit deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the RTO, when the emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent performance test that demonstrated the emissions unit was in compliance.
2. The permittee shall submit quarterly summaries which include a log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
3. The quarterly summaries shall be submitted, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.
4. The permittee shall notify the Director (the Ohio EPA Southeast District Office) of any monthly record showing emissions in excess of the rolling, 12-month limitation specified in A.II. A copy of such record shall be sent to the Director within 30 days following the end of the calendar month.

**V. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

a. Emission Limitation

20% opacity

Applicable Compliance Method

If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(c) of OAC rule 3745-17-03.

b. Emission Limitation

4.10 lb/hr VOC (based on a daily average)

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.2. above.

c. Emission Limitation

2.01 TPY of VOC

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.2

d. Emission Limitation

90% destruction efficiency / 90% overall reduction of emissions

Applicable Compliance Method

Compliance shall be determined in accordance with 40 CFR 60 Appendix A, Method 25 or 25A, the procedures specified in OAC rule 3745-21-10 and the requirements found in Sections A.III and A.IV.

The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:

2. The emission testing shall be conducted as specified by the permittee's Title V permit.
3. The emission testing shall be conducted to demonstrate compliance with the allowable mass emission rate(s) for VOC and the capture efficiency and control efficiency limitations for VOC.

**Issued: To be entered upon final issuance**

4. The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s): for VOC, Method 25 or 25A of 40 CFR Part 60, Appendix A. The test method(s) which must be employed to demonstrate compliance with the capture efficiency and control efficiency limitations for VOC are specified below. Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.
5. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency.
6. The capture efficiency shall be determined using Methods 204 through 204F, as specified in 40 CFR Part 51, Appendix M, or the permittee may request to use an alternative method or procedure for the determination of capture efficiency in accordance with the USEPA's "Guidelines for Determining Capture Efficiency," dated January 9, 1995. The control efficiency (i.e., the percent reduction in mass emissions between the inlet and outlet of the control system) shall be determined in accordance with the test methods and procedures specified in OAC rule 3745-21-10. The test methods and procedures selected shall be based on a consideration of the diversity of the organic species present and their total concentration, and on a consideration of the potential presence of interfering gases.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

- a. Emission Limitation

91

**Mills Pride Limited Partnership**

**PTI Application: 06-06474**

**Issued**

**Facility ID: 0666010033**

Emissions Unit ID: R013

Total facility individual HAP emission less than 10 TPY.

**Issued: To be entered upon final issuance**Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.3. above.

b. Emission Limitation

Total facility HAP's emissions less than 25 TPY.

Applicable Compliance Method

Compliance shall be based upon the monitoring and recordkeeping in Section A.III.3

c. Emission Limitation

0.551 lb/hr of Particulate Matter

Applicable Compliance Method

Compliance with the particulate matter emission limitation in Section A.I. of these terms and conditions shall be determined in accordance with the following method:

To determine the actual worst case emission rate for particulate matter, the following equation shall be used:

$$E = \text{maximum coating solids usage rate (in pounds per hour)} * (1-TE) * (1-CE)$$

$$E = \text{particulate emissions rate (lb/hr)}$$

$$TE = \text{transfer efficiency, which is the ratio of the amount of coating solids deposited on the coated part to the amount of coating solids used.}$$

$$CE = \text{control efficiency of the control equipment (ie. booth filters)}$$

d. Emission Limitation

2.4 TPY of PM

Applicable Compliance Method

93

**Mills 1**

**PTI A**

Emissions Unit ID: R013

**Issued: To be entered upon final issuance**

Compliance shall be based upon a one time calculation of potential as follows:

$$E = \text{MHER} * 8760 \text{ hr/yr} * 0.0005 \text{ Ton/lb} = \text{TPY}$$

**Mills 1**

**PTI A**

Emissions Unit ID: R013

**Issued: To be entered upon final issuance**

Where

MHER is the maximum controlled hourly emission rate determined in section A.V

**VI. Miscellaneous Requirements**

None

Mills 1

PTI A

Emissions Unit ID: R013

**Issued: To be entered upon final issuance**

**B. State Only Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
R013 - Backline Finishing System ( 1 spray booth controlled by a Regenerative Thermal Oxidizer)	OAC rule 3745-31-05	LIMIT(s)

**2. Additional Terms and Conditions**

2.a None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

96

**Mills 1**

**PTI A**

**Issued: To be entered upon final issuance**

None

Emissions Unit ID: R013

**NEW SOURCE REVIEW FORM B**

PTI Number: 06-06474 Facility ID: 0666010033

FACILITY NAME Mills Pride Limited Partnership

FACILITY DESCRIPTION Finished Wooden Cabinet Components CITY/TWP Waverly

SIC CODE 2434 SCC CODE 4-02-021-32 EMISSIONS UNIT ID K001

EMISSIONS UNIT DESCRIPTION Flatline Finishing System- ( 3 spray booths, 1 drying, and 2 curing ovens)

DATE INSTALLED 01/89

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter		0.551 lb/hr	2.4	0.551 lb/hr	2.4
PM <sub>10</sub>					
Sulfur Dioxide					
Organic Compounds		40.94 lb/hr	74.08	40.94 lb/hr	74.08
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination** - PTI results in decrease of allowable emission, from previously issued PTI's. *In order to avoid being a MACT Facility the following federally enforceable emission limits have been established.* The facility shall maintain an overall VOC control efficiency which is at least 90%, by weight, and a Regenerative Thermal Oxidizer (RTO) control efficiency (i.e., destruction or removal efficiency) which is at least 90%, by weight, for this emissions unit. *This emission limitation has also been established as BAT.*

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

No (PTI results in decrease of allowable by 2.01 tpy VOC. therefore toxic policy does not apply.)

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

\$

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*?

YES X NO

IDENTIFY THE AIR CONTAMINANTS:

**NEW SOURCE REVIEW FORM B**

PTI Number: 06-06474 Facility ID: 0666010033

FACILITY NAME Mills Pride Limited Partnership

FACILITY DESCRIPTION Finished Wooden Cabinet Components CITY/TWP Waverlv

Emissions Unit ID: R013

SIC CODE 2434 SCC CODE 4-02-021-32 EMISSIONS UNIT ID R001

EMISSIONS UNIT DESCRIPTION Specialty Booth Finishing System (1 spray booth)

DATE INSTALLED 01/89

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment	0551 lb/hr	2.4	0.551 lb/hr	2.4
PM <sub>10</sub>	Attainment				
Sulfur Dioxide	Attainment				
Organic Compounds	Attainment	4.10 lb/hr	2.01	4.10 lb/hr	2.01
Nitrogen Oxides	Attainment				
Carbon Monoxide	Attainment				
Lead	Attainment				
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination** - PTI results in decrease of allowable emission, from previously issued PTI's. *In order to avoid being a MACT Facility the following federally enforceable emission limits have been established.* The facility shall maintain an overall VOC control efficiency which is at least 90%, by weight, and a Regenerative Thermal Oxidizer (RTO) control efficiency (i.e., destruction or removal efficiency) which is at least 90%, by weight, for this emissions unit. *This emission limitation has also been established as BAT.*

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? No (PTI results in decrease of allowable by 2.01 tpy VOC. therefore toxic policy does not apply.)

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? YES X NO

IDENTIFY THE AIR CONTAMINANTS:

**NEW SOURCE REVIEW FORM B**

PTI Number: 06-06474 Facility ID: 0666010033

FACILITY NAME Mills Pride Limited Partnership

FACILITY DESCRIPTION Finished Wooden Cabinet Components CITY/TWP Waverlv

Emissions Unit ID: R013

SIC CODE 2434 SCC CODE 4-02-021-01 EMISSIONS UNIT ID R002

EMISSIONS UNIT DESCRIPTION Celfa line stain rollcoater/oven - (1 rollcoater and curing oven)

DATE INSTALLED 07/94

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment	0.551 lb/hr	2.4	0.551 lb/hr	2.4
PM <sub>10</sub>	Attainment				
Sulfur Dioxide	Attainment				
Organic Compounds	Attainment	2.05 lb./hr (R002,R003, and R004 combine emission limit)	7.47 (R002,R003, and R004 combine emission limit)	2.05 lb/hr (R002,R003, and R004 combine emission limit)	7.47 (R002,R003, and R004 combine emission limit)
Nitrogen Oxides	Attainment				
Carbon Monoxide	Attainment				
Lead	Attainment				
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination** - PTI results in decrease of allowable emission, from previously issued PTI's. *In order to avoid being a MACT Facility the following federally enforceable emission limits have been established.* The facility shall maintain an overall VOC control efficiency which is at least 90%, by weight, and a Regenerative Thermal Oxidizer (RTO) control efficiency (i.e., destruction or removal efficiency) which is at least 90%, by weight, for this emissions unit. *This emission limitation has also been established as BAT.*

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? No (PTI results in decrease of allowable by 2.01 tpy VOC. therefore toxic policy does not apply.)

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? \_\_\_\_\_ YES \_\_\_\_\_ NO

IDENTIFY THE AIR CONTAMINANTS: \_\_\_\_\_

**NEW SOURCE REVIEW FORM B**

PTI Number: 06-06474 Facility ID: 0666010033

FACILITY NAME Mills Pride Limited Partnership

FACILITY DESCRIPTION Finished Wooden Cabinet Components CITY/TWP Waverlv

Emissions Unit ID: R013

SIC CODE 2434 SCC CODE 4-02-021-33 EMISSIONS UNIT ID R003

EMISSIONS UNIT DESCRIPTION Celfa line rollcoater #1/UV lamp - (1 rollcoater and ultraviolet curing oven)

DATE INSTALLED 07/94

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment	0.551 lb/hr	2.4	0.551 lb/hr	2.4
PM <sub>10</sub>	Attainment				
Sulfur Dioxide	Attainment				
Organic Compounds	Attainment	2.05 lb./hr (R002,R003, and R004 combine emission limit)	7.47 (R002,R003, and R004 combine emission limit)	2.05 lb/hr (R002,R003, and R004 combine emission limit)	7.47 (R002,R003, and R004 combine emission limit)
Nitrogen Oxides	Attainment				
Carbon Monoxide	Attainment				
Lead	Attainment				
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination** - PTI results in decrease of allowable emission, from previously issued PTI's. *In order to avoid being a MACT Facility the following federally enforceable emission limits have been established.* The facility shall maintain an overall VOC control efficiency which is at least 90%, by weight, and a Regenerative Thermal Oxidizer (RTO) control efficiency (i.e., destruction or removal efficiency) which is at least 90%, by weight, for this emissions unit. *This emission limitation has also been established as BAT.*

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? No (PTI results in decrease of allowable by 2.01 tpy VOC. therefore toxic policy does not apply.)

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? \_\_\_\_\_ YES X NO

IDENTIFY THE AIR CONTAMINANTS: \_\_\_\_\_

**NEW SOURCE REVIEW FORM B**

PTI Number: 06-06474 Facility ID: 0666010033

FACILITY NAME Mills Pride Limited Partnership

FACILITY DESCRIPTION Finished Wooden Cabinet Components CITY/TWP Waverlv

Emissions Unit ID: R013

SIC CODE 2434 SCC CODE 4-02-021-33 EMISSIONS UNIT ID R004

EMISSIONS UNIT DESCRIPTION Cefla Line Rollcoater #2/UV lamp - (1 rollcoater and ultraviolet oven)

DATE INSTALLED

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment	0.551 lb/hr	2.4	0.551 lb/hr	2.4
PM <sub>10</sub>	Attainment				
Sulfur Dioxide	Attainment				
Organic Compounds	Attainment	2.05 lb./hr (R002,R003, and R004 combine emission limit)	7.47 (R002,R003, and R004 combine emission limit)	2.05 lb/hr (R002,R003, and R004 combine emission limit)	7.47 (R002,R003, and R004 combine emission limit)
Nitrogen Oxides	Attainment				
Carbon Monoxide	Attainment				
Lead	Attainment				
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination** - PTI results in decrease of allowable emission, from previously issued PTI's. *In order to avoid being a MACT Facility the following federally enforceable emission limits have been established.* The facility shall maintain an overall VOC control efficiency which is at least 90%, by weight, and a Regenerative Thermal Oxidizer (RTO) control efficiency (i.e., destruction or removal efficiency) which is at least 90%, by weight, for this emissions unit. *This emission limitation has also been established as BAT.*

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? No (PTI results in decrease of allowable by 2.01 tpy VOC. therefore toxic policy does not apply.)

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? \_\_\_\_\_ YES X NO

IDENTIFY THE AIR CONTAMINANTS: \_\_\_\_\_

**NEW SOURCE REVIEW FORM B**

PTI Number: 06-06474

Facility ID: 0666010033

FACILITY NAME Mills Pride Limited Partnership

FACILITY DESCRIPTION Finished Wooden Cabinet Components CITY/TWP Waverlv

Emissions Unit ID: R013

SIC CODE 2434 SCC CODE 4-02-021-06 EMISSIONS UNIT ID R011

EMISSIONS UNIT DESCRIPTION Backline Finishing System - (2 spray booths, and 2 Infrared drying ovens)

DATE INSTALLED 05/94

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment	0.551 lb/hr	2.4	0.551 lb/hr	2.4
PM <sub>10</sub>	Attainment				
Sulfur Dioxide	Attainment				
Organic Compounds	Attainment	10.85 lb/hr	45.34	10.85 lb/hr	45.34
Nitrogen Oxides	Attainment				
Carbon Monoxide	Attainment				
Lead	Attainment				
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS?

NESHAP?

PSD?

OFFSET POLICY?

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination** - PTI results in decrease of allowable emission, from previously issued PTI's. *In order to avoid being a MACT Facility the following federally enforceable emission limits have been established.* The facility shall maintain an overall VOC control efficiency which is at least 90%, by weight, and a Regenerative Thermal Oxidizer (RTO) control efficiency (i.e., destruction or removal efficiency) which is at least 90%, by weight, for this emissions unit. *This emission limitation has also been established as BAT.*

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

No (PTI results in decrease of allowable by 2.01 tpy VOC. therefore toxic policy does not apply.)

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

\$

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to containinants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? \_\_\_\_\_ YES X NO

IDENTIFY THE AIR CONTAMINANTS: \_\_\_\_\_

**NEW SOURCE REVIEW FORM B**

PTI Number: 06-06474 Facility ID: 0666010033  
 FACILITY NAME Mills Pride Limited Partnership  
 FACILITY DESCRIPTION Finished Wooden Cabinet Components CITY/TWP Waverly

Emissions Unit ID: R013

SIC CODE 2434 SCC CODE 4-02-021-32 EMISSIONS UNIT ID R013  
 EMISSIONS UNIT DESCRIPTION Specialty Booth No 2 Finishing System (1 spray booth)  
 DATE INSTALLED upon receipt of permit

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment	0.551 lb/hr	2.4	0.551 lb/hr	2.4
PM <sub>10</sub>	Attainment				
Sulfur Dioxide	Attainment				
Organic Compounds	Attainment	4.10 lb/hr	2.01	4.10 lb/hr	2.01
Nitrogen Oxides	Attainment				
Carbon Monoxide	Attainment				
Lead	Attainment				
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? NESHAP? PSD? OFFSET POLICY?

**WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?**

**Enter Determination** - PTI results in decrease of allowable emission, from previously issued PTI's. *In order to avoid being a MACT Facility the following federally enforceable emission limits have been established.* The facility shall maintain an overall VOC control efficiency which is at least 90%, by weight, and a Regenerative Thermal Oxidizer (RTO) control efficiency (i.e., destruction or removal efficiency) which is at least 90%, by weight, for this emissions unit. *This emission limitation has also been established as BAT.*

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? No (PTI results in decrease of allowable by 2.01 tpy VOC. therefore toxic policy does not apply.)

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$

**TOXIC AIR CONTAMINANTS**

Ohio EPA's air toxics policy applies to containinants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED\*? \_\_\_\_\_ YES X NO

IDENTIFY THE AIR CONTAMINANTS: \_\_\_\_\_