



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL MODIFICATION  
WASHINGTON COUNTY**

**CERTIFIED MAIL**

Street Address:

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov.  
Center

**Application No: 06-06770**

**DATE: 5/27/2004**

Degussa Engineered Carbons LP  
Donald Loubiere  
Box 369  
Belpre, OH 45714

Enclosed Please find a modification to the Ohio EPA Permit To Install referenced above which will modify the terms and conditions.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission  
309 South Fourth Street, Room 222  
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern, Supervisor  
Field Operations and Permit Section  
Division of Air Pollution Control

CC: USEPA

SEDO



**Permit To Install  
Terms and Conditions**

**Issue Date: 5/27/2004  
Effective Date: 5/27/2004**

## FINAL ADMINISTRATIVE MODIFICATION OF PERMIT TO INSTALL 06-06770

Application Number: 06-06770  
APS Premise Number: 0684010049  
Permit Fee: **\$2375**  
Name of Facility: Degussa Engineered Carbons LP  
Person to Contact: Donald Loubiere  
Address: Box 369  
Belpre, OH 45714

Location of proposed air contaminant source(s) [emissions unit(s)]:  
**Rte 7 N, 1 mile N of Belpre  
Belpre, Ohio**

Description of proposed emissions unit(s):  
**Administrative modification to PTI 06-06770 to revise emission factors based on stack testing of the sources.**

The above named entity is hereby granted a modification to the permit to install described above pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this modification does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans included in the application, the above described source(s) of pollutants will be granted the necessary operating permits.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

## **Part I - GENERAL TERMS AND CONDITIONS**

### **A. State and Federally Enforceable Permit To Install General Terms and Conditions**

#### **1. Monitoring and Related Recordkeeping and Reporting Requirements**

- a. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall maintain records that include the following, where applicable, for any required monitoring under this permit:
  - i. The date, place (as defined in the permit), and time of sampling or measurements.
  - ii. The date(s) analyses were performed.
  - iii. The company or entity that performed the analyses.
  - iv. The analytical techniques or methods used.
  - v. The results of such analyses.
  - vi. The operating conditions existing at the time of sampling or measurement.
- b. Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.
- c. Except as may otherwise be provided in the terms and conditions for a specific emissions unit, the permittee shall submit required reports in the following manner:
  - i. Reports of any required monitoring and/or recordkeeping of federally enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
  - ii. Quarterly written reports of (i) any deviations from federally enforceable emission limitations, operational restrictions, and control device operating parameter limitations, excluding deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06, that have been detected by the testing, monitoring and recordkeeping requirements specified in this permit, (ii) the probable cause of such deviations, and (iii) any corrective actions or preventive measures taken, shall be made to the appropriate Ohio EPA District Office or local air agency. The written reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous

calendar quarters. See B.9 below if no deviations occurred during the quarter.

- iii. Written reports, which identify any deviations from the federally enforceable monitoring, recordkeeping, and reporting requirements contained in this permit shall be submitted to the appropriate Ohio EPA District Office or local air agency every six months, i.e., by January 31 and July 31 of each year for the previous six calendar months. If no deviations occurred during a six-month period, the permittee shall submit a semi-annual report, which states that no deviations occurred during that period.
- iv. Each written report shall be signed by a responsible official certifying that, based on information and belief formed after reasonable inquiry, the statements and information in the report are true, accurate, and complete.

## **2. Scheduled Maintenance/Malfunction Reporting**

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction, i.e., upset, of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. (The definition of an upset condition shall be the same as that used in OAC rule 3745-15-06(B)(1) for a malfunction.) The verbal and written reports shall be submitted pursuant to OAC rule 3745-15-06.

Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emission unit(s) that is (are) served by such control system(s).

## **3. Risk Management Plans**

If the permittee is required to develop and register a risk management plan pursuant to section 112(r) of the Clean Air Act, as amended, 42 U.S.C. 7401 et seq. ("Act"), the permittee shall comply with the requirement to register such a plan.

## **4. Title IV Provisions**

If the permittee is subject to the requirements of 40 CFR Part 72 concerning acid rain, the permittee shall ensure that any affected emissions unit complies with those requirements. Emissions exceeding any allowances that are lawfully held under Title IV of the Act, or any regulations adopted thereunder, are prohibited.

## **5. Severability Clause**

A determination that any term or condition of this permit is invalid shall not invalidate the force or effect of any other term or condition thereof, except to the extent that any other term or condition depends in whole or in part for its operation or implementation upon the term or condition

declared invalid.

## **6. General Requirements**

- a. The permittee must comply with all terms and conditions of this permit. Any noncompliance with the federally enforceable terms and conditions of this permit constitutes a violation of the Act, and is grounds for enforcement action or for permit revocation, revocation and reissuance, or modification, or for denial of a permit renewal application.
- b. It shall not be a defense for the permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the federally enforceable terms and conditions of this permit.
- c. This permit may be modified, reopened, revoked, or revoked and reissued, for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or revocation, or of a notification of planned changes or anticipated noncompliance does not stay any term and condition of this permit.
- d. This permit does not convey any property rights of any sort, or any exclusive privilege.
- e. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon request, the permittee shall also furnish to the Director or an authorized representative of the Director, copies of records required to be kept by this permit. For information claimed to be confidential in the submittal to the Director, if the Administrator of the U.S. EPA requests such information, the permittee may furnish such records directly to the Administrator along with a claim of confidentiality.

## **7. Fees**

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit To Install fees within 30 days after the issuance of this Permit To Install.

## **8. Federal and State Enforceability**

Only those terms and conditions designated in this permit as federally enforceable, that are

required under the Act, or any of its applicable requirements, including relevant provisions designed to limit the potential to emit of a source, are enforceable by the Administrator of the U.S. EPA, the State, and citizens under the Act. All other terms and conditions of this permit shall not be federally enforceable and shall be enforceable under State law only.

## **9. Compliance Requirements**

- a. Any document (including reports) required to be submitted and required by a federally applicable requirement in this permit shall include a certification by a responsible official that, based on information and belief formed after reasonable inquiry, the statements in the document are true, accurate, and complete.
- b. Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Director of the Ohio EPA or an authorized representative of the Director to:
  - i. At reasonable times, enter upon the permittee's premises where a source is located or the emissions-related activity is conducted, or where records must be kept under the conditions of this permit.
  - ii. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit, subject to the protection from disclosure to the public of confidential information consistent with ORC section 3704.08.
  - iii. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit.
  - iv. As authorized by the Act, sample or monitor at reasonable times substances or parameters for the purpose of assuring compliance with the permit and applicable requirements.
- c. The permittee shall submit progress reports to the appropriate Ohio EPA District Office or local air agency concerning any schedule of compliance for meeting an applicable requirement. Progress reports shall be submitted semiannually, or more frequently if specified in the applicable requirement or by the Director of the Ohio EPA. Progress reports shall contain the following:
  - i. Dates for achieving the activities, milestones, or compliance required in any schedule of compliance, and dates when such activities, milestones, or compliance were achieved.
  - ii. An explanation of why any dates in any schedule of compliance were not or will not be met, and any preventive or corrective measures adopted.

## **10. Permit To Operate Application**

- a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).
- b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the source(s) covered by this permit.

## **11. Best Available Technology**

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

## **12. Air Pollution Nuisance**

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

## **B. State Only Enforceable Permit To Install General Terms and Conditions**

### **1. Compliance Requirements**

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

### **2. Reporting Requirements**

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping of state-only enforceable information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from state-only required emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

### **3. Permit Transfers**

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

### **4. Termination of Permit To Install**

This permit to install shall terminate within eighteen months of the effective date of the permit to install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete

within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

#### **5. Construction of New Sources(s)**

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

#### **6. Public Disclosure**

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

#### **7. Applicability**

Degussa Engineered Carbons LP

Facility ID: **0684010049**

PTI Application: **06-06770**

**Modification Issued: 5/27/2004**

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

**8. Construction Compliance Certification**

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit To Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

Emissions Unit ID: P001

**9. Additional Reporting Requirements When There Are No Deviations of Federally Enforceable Emission Limitations, Operational Restrictions, or Control Device Operating Parameter Limitations (See Section A of This Permit)**

If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters.

**C. Permit To Install Summary of Allowable Emissions**

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)**

<u>Pollutant</u>	<u>Tons Per Year</u>
SO2	4547.0
VOC	151.0
CO	2556.0
NOx	508.0
PM/PM10 (total)	84.9
H2S	17.3
COS	3.4
CS2	7.8
HCN	4.2

12

Degussa Engineered Carbons LP  
PTI Application: **06-06770**  
**Modification Issued: 5/27/2004**

Facility ID: **0684010049**

13

Degus:

PTI A<sub>1</sub>

**Modification Issued: 5/27/2004**

Emissions Unit ID: P001

**Part II - FACILITY SPECIFIC TERMS AND CONDITIONS**

**A. State and Federally Enforceable Permit To Install Facility Specific Terms and Conditions**

None

**B. State Only Enforceable Permit To Install Facility Specific Terms and Conditions**

None

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	OAC rule 3745-31-05(C)
P001 - Carbon Black Unit Number 1 (Administrative modification to PTI#06-06770, issued August 21, 2003) to correct emission factors	OAC rule 3745-31-05(A)(3)	
	OAC rule 3745-31-10 through 20	
		OAC rule 3745-17-07(A)
		OAC rule 3745-17-11(B)(1)
		OAC rule 3745-18-06(E)(2)

**Modification Issued: 5/27/2004**

Applicable Emissions Limitations/Control Measures	12-month summation.	3745-31-05(A)(3).
The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07 and 40 CFR 52.21.	See section A.I.2.c	
See sections A.I.2.a and A.I.2.b below	Total emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following based upon a rolling, 12-month summation:  4547.0 tons of SO <sub>2</sub> 508.0 tons of NO <sub>x</sub> 84.9 tons of PE	
Total emissions from emissions units P001 and P002 combined shall be limited to the following during normal operation from the flare:	Total emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following based upon a rolling, 365 day summation:	
3% Sulfur content, 544.3 lbs/hr, and 2,384 tons of SO <sub>2</sub> based upon a rolling, 365-day summation.	2556.0 tons of CO 151.0 tons of VOC  See Section A.I.2.b	
43.7 lbs/hr and 191.4 tons/yr of NO <sub>x</sub> based upon a rolling, 12-month summation.	Visible particulate emissions shall not exceed twenty percent opacity, as a six-minute average except as provided by rule.	
9.4 lbs/hr and 41.2 tons/yr of VOC based upon a rolling, 12-month summation.	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).	
354.6 lbs/hr and 1,553.1 tons/yr of CO based upon a rolling, 12-month summation.	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule	
5.7 lbs/hr and 24.9 tons/yr of PE based upon a rolling,		

**Modification Issued: 5/27/2004****2. Additional Terms and Conditions**

**2.a** This emissions unit shall be limited to the following emissions during start-up and shutdown (vent emissions):

6.8 lbs/hr and 0.3 tons/yr SO<sub>2</sub>  
380 lbs/hr and 15 tons/yr VOC  
14,254 lbs/hr and 577 tons/yr CO  
8.4 lbs/hr and 0.3 tons/yr of NO<sub>x</sub>  
7.8 lbs/hr and 0.3 tons/yr of PM/PM<sub>10</sub>  
154 lbs/hr and 6.2 tons/yr of H<sub>2</sub>S  
30 lbs/hr and 1.2 tons/yr of COS  
70 lbs/hr and 2.8 tons/yr of CS<sub>2</sub>  
37 lbs/hr and 1.5 tons/yr of HCN

**2.b** Maximum annual production of carbon black for emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed 223,000,000 pounds on a rolling 12-month summation. This emissions unit is currently permitted and operating, and as such, has existing records of production and emissions, therefore eliminating the need to establish the first year's cumulative rolling 12-month summation of carbon black production. The existing, previous 12-month record of 223,000,000 lb/yr of carbon black shall be maintained as the rolling daily record, upon the issuance of this permit.

**2.c** The permittee shall employ good combustion practices to minimize emissions to the extent possible.

**II. Operational Restrictions**

1. This emissions unit shall:
  - a. utilize feedstock oil which contains no more than 3% sulfur;
  - b. be equipped with a product exhaust bag filter with a design efficiency not less than 99.7%; and
  - c. employ a flare with a design destruction efficiency of 95 percent for particulate emissions and 98 percent for CO and VOC.
2. This emissions unit shall be limited to 81 hours per year for all start-up and shutdown operations.

**Modif**

Emissions Unit ID: P001

3. A pilot flame shall be maintained at all times in the flare's pilot light burner.
4. If the mass flow rate meter employed to continuously monitor the feedstock oil feed rate is not in operation, the production of carbon black shall be automatically terminated.

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall perform daily checks, while the equipment is in operation and when the weather conditions allow, for any visible particulate emissions from the stack of this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log.
  - a. the location and color of the emissions;
  - b. whether the emissions are representative of normal operations;
  - c. if the emissions are not representative of normal operations, the cause of the visible emissions;
  - d. the total duration of any visible emission incident; and
  - e. any corrective actions taken to eliminate the visible emissions.
2. The permittee shall keep daily records for all start-up and shutdown periods that contain the following information:
  - a. The date of each start-up and/or shut down;
  - b. The time period during which the start-up or shut down occurred;
  - c. The year-to-date, total hours of all start-up and shutdown periods; and
  - d. At the end of each year, the permittee shall add and maintain a record of the total hours and total emissions from start-up/shutdown events, from the records maintained as required above.
3. The permittee shall maintain records of the feedstock oil for this emissions unit in accordance with either Alternative 1 or Alternative 2 described below.
  - a. Alternative 1:

For each shipment of feedstock oil received for this emissions unit, the permittee shall collect or require the oil supplier to collect a representative grab sample of the feedstock oil and maintain records of the total quantity of feedstock oil received, and the permittee's or oil supplier's analyses for sulfur content and density.

**Modification Issued: 5/27/2004**

## b. Alternative 2:

The permittee shall collect a representative grab sample of the feedstock oil for this emissions unit for each day when the emissions unit is in operation. If additional feedstock oil is added to the tank serving this emissions unit on a day when the emissions unit is in operation, the permittee shall collect a sufficient number of grab samples to create a composite sample that is representative of the average quality of feedstock oil used in this emissions unit. The permittee shall maintain records of the total quantity of feedstock oil used each day, and the permittee's analyses for sulfur content and density.

4. The permittee shall measure the sulfur content (in weight %) of the feedstock oil in accordance with the procedures specified in ASTM standard D4294, "Standard Test Method for Sulfur in Petroleum and Petroleum Products by Energy-Dispersive X-ray Fluorescence Spectrometry". In addition, the permittee shall measure the density (in pounds per gallon) of the feedstock oil in accordance with the procedures specified in ASTM standard D287, "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)".
5. For each day of operation of this emissions unit, the permittee shall collect a sufficient number of grab samples of carbon black product to create a composite sample that is representative of the average quality of the carbon black produced in this emissions unit. The permittee shall measure and maintain a record of the sulfur content (in weight %) of each composite sample of carbon black product in accordance with the procedures specified in ASTM standard D1619, "Standard Test Method for Carbon Black- Sulfur Content".
6. The permittee shall properly install, operate, and maintain a device to continuously monitor the pilot flame when the emissions unit is in operation. The monitoring device and any recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions and operating manuals.

The permittee shall record the following information each day:

- a. all periods during which there was no pilot flame.
  - b. the corrective action taken to reestablish the flame; and
  - c. the downtimes for the flare, monitoring equipment, and the associated emissions unit.
7. The permittee shall properly operate and maintain a Micro Motion mass flow rate meter, model number D100, or equivalent monitor, to continuously monitor the feedstock oil feed rate when

Emissions Unit ID: P001

the emissions unit is in operation and producing carbon black. The monitoring device and any recorder shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manuals.

The permittee shall record the following information each day:

- a. all periods during which the Micro Motion mass flow rate meter, model number D100, or equivalent monitor, was not in operation while the emissions unit is in operation;
  - b. all downtimes for the monitoring equipment and the associated emissions unit, while the emissions unit is in operation; and
  - c. the corrective actions taken to reestablish correct operation of the mass flow rate meter.
8. The permittee shall maintain monthly records of the following information:
- a. the carbon black production rate, in pounds per month for this emissions unit;
  - b. the production rate for emission units P001, P002, P005, P006, P011 and P012 (tons carbon black/month);
  - c. the rolling, 12-month summation of the production rates for emission units P001, P002, P005, P006, P011, and P012, combined (tons carbon black/rolling 12 months);
  - d. the total hours of operation of this emissions unit; and
  - e. the total emission of SO<sub>2</sub>, NO<sub>x</sub>, PE and VOC, calculated as required in the appropriate sections in "Testing Requirements", Section V. Emissions factors submitted by the permittee in their permit application shall be applied, until better factors are developed from the most recent stack testing results for emission units P001, P002, and/or P011 and P012 prior to their thermal incinerator, in pounds of pollutant per 1,000 gallons of oil burned or per 1,000 pounds of carbon black produced.
- \* a permanent, rather than monthly record may be maintained for 8.a above
9. The permittee shall maintain daily records of the following information for this emissions unit:
- a. the OEPA identification number of this emissions unit;
  - b. the current day, month, and year;
  - c. the grade of each feedstock oil processed (% sulfur);
  - d. the yield of each feedstock oil, defined as the average amount of carbon black produced, per gallon of feedstock oil used during the day (lbs carbon black/gal);

**Modification Issued: 5/27/2004**

- e. the sulfur content of each feedstock oil, in weight percent;
- f. the sulfur content of the carbon black product, in weight percent;
- g. the feedstock oil feed rate, in gallons per hour for each hour of operation continuously monitored using a Micro Motion mass flow rate meter, model number D100 or an equivalent monitor;
- h. the carbon black production rate, in pounds per hour for each hour of operation, determined by multiplying the feedstock oil feed rate (gal/hr) by the yield of the feedstock oil (lbs/gal);
- i. the average hourly SO<sub>2</sub> emission rate for each feedstock oil, in pounds per hour, calculated as specified in Section A.III.10;
- j. the total hours of operation for each feedstock oil;
- k. the daily sulfur dioxide emission rate for all feedstock oils, in pounds (i.e., the summation of (i) x (j) for all of the feedstock oils);
- l. the rolling, 365-day SO<sub>2</sub> emission rate for all feedstock oils, in tons;
- m. the daily and year-to-date SO<sub>2</sub> emission rates for all carbon black products produced in this emissions unit, in pounds, i.e., the value from A.III.9.k above for all feedstock oils employed, multiplied by 66%\*;;
- n. the rolling, 365-day SO<sub>2</sub> emission rate for all feedstock oils, for emission units P001 and P002 combined, in tons, calculated from the records maintained for emission units P001 and P002, Section A.III.9.l above, multiplied by the factor of 66%\* for the carbon black unit/dryer split;
- o. the average hourly CO and VOC emission rate for each feedstock oil used in P001, P002, P005, P006, P011 and P012, in pounds per hour, calculated as specified in Section A.V.1.c & e; and
- p. the rolling, 365-day CO and VOC emission rate for P001, P002, P005, P006, P011 and P012, in tons.

\* The factor applied above may change with future testing on the capture efficiency of the

Emissions Unit ID: P001

dryer and/or the emission's split between this emissions unit and/or P002 and its dryer.

10. The average hourly sulfur dioxide emission rate for each feedstock oil shall be calculated each day using the following equations:

$$E = ((SFS) - (SCB)) \times (1 - TG) \times (64/32)$$

where:

E = sulfur dioxide emission rate, in pounds per hour;

SFS = feedstock oil sulfur weight rate, in pounds per hour;

SCB = carbon black sulfur weight rate, in pounds per hour;

TG = fraction of stream to tailgas (constant at .34); and

64/32 = constant to convert molecular weight rate of sulfur to molecular weight of sulfur dioxide.

NOTE: The permittee conservatively assumes all of the sulfur emissions are emitted as sulfur dioxide emissions.

The feedstock oil sulfur weight rate utilized in the equation above is computed in the following manner:

$$SFS = FSR \times SFSP$$

where:

SFS = feedstock oil sulfur weight rate, in pounds per hour;

FSR = maximum daily recorded feedstock oil feed rate, in gallons per hour (from A.III.7); and

SFSP = feedstock oil sulfur content, in weight percent (from A.III.4).

The carbon black sulfur weight rate utilized in the equation above is computed in the following manner:

$$SCB = CBPR \times SCBP$$

where:

SCB = carbon black sulfur weight rate, in pounds per hour;

CBPR = maximum recorded carbon black production rate, in pounds per hour (from A.III.8.a); and

SCBP = carbon black sulfur content, in weight percent (from A.III.5).

#### IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all periods of time during which the pilot flame was not functioning properly. The reports shall include the date,

**Modification Issued: 5/27/2004**

time, and duration of each such period.

2. The permittee shall submit quarterly deviation (excursion) reports that identify all periods of time during which the Micro Motion mass flow rate meter or equivalent flow meter, model number D100 or equivalent flow meter, was not functioning properly. The reports shall include the date, time, and duration of each such period, and the corrective action(s) to ensure correct operation.
3. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month production rate limitation of 223,000,000 lb/yr carbon black for emission units P001, P002, P005, P006, P001, and P002 combined.
4. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the sulfur content limitation. The reports shall include the date, time, and duration of each such period of time when the sulfur content of the oil used in this emissions unit is greater than 3.0 percent, and the corrective action to bring the sulfur content below 3.0 percent.
5. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the average hourly SO<sub>2</sub> emission rate from emission units P001 and P002 combined exceeded 544.3 lbs/hr, and the actual average hourly SO<sub>2</sub> emissions for each such day.
6. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the 365-day SO<sub>2</sub> emission rate from emission units P001 and P002 combined exceeded 2,384 tons, and the actual SO<sub>2</sub> emissions for each such day.
7. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the stack of this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (Ohio EPA Southeast District Office) by January 31 and July 31 of each year and shall cover the previous 6-month period.
8. The permittee shall submit annual reports that include the following information:
  - a. the total hours of start-up and shutdown operations for this emissions unit for the previous calendar year, and the emissions calculated from start-up and shutdown events, calculated and recorded as required in Section A.III.2;
  - b. the total hours of operation of this emissions unit;
  - c. the total production from emissions units P001, P002, P005, P006, P011, and P012 for each 12-month period ending during the calendar year; and

- d. the total SO<sub>2</sub> emissions (including all calculations), in tons, from emission units P001, P002, P005, P006, P011 and P012 for the previous calendar year using the monthly emission records required in Sections A.III.3, A.III.8 and A.III.9.

These reports shall be submitted to the Director (Ohio EPA Southeast District Office) by January 31 of each year.

9. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the rolling 12-month emission rates for emission units P001, P002, P005, P006, P011 and P012, combined, exceeded the rolling 12-month ton per year limit listed in A.I.1.
10. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the rolling 365-day CO and VOC emission rates from emission units P001, P002, P005, P006, P011 and P012 combined exceeded 2,983 tons and 80.4 tons respectively. The report shall also include the actual SO<sub>2</sub> emissions for each day the deviation occurs.

Quarterly deviation reports shall be submitted as required in the General Terms & Conditions of this permit.

## V. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

The emission factors used in the compliance calculations below, as pounds of pollutant per 1,000 pounds of product or per 1,000 gallons of oil burned, shall be adjusted, as derived from the most recent stack testing results. It shall be assumed that the emissions per gallon of process oil or per pound of carbon black produced are similar on all carbon black units, prior to control. The pounds of each pollutant per 1,000 pounds of product or per 1,000 gallons of oil shall be determined from the testing results obtained from emission units P001 and P002, prior to their flare, and/or P011 and P012 prior to the thermal incinerator, as required in Sections V.4 for emission units P011 and P012. The designed destruction efficiency of 95% for PE and 98% for CO and VOC for the flare shall be used in the calculations that will demonstrate compliance with the limits for these pollutants below, since stack testing after the flare is not possible.

a. **Emission Limitation**

Total emissions from emissions units P001 and P002 combined shall be limited to 544.3 lb/hr of SO<sub>2</sub> during normal operations.

**Applicable Compliance Method**

Compliance shall be demonstrated based upon the monitoring and recordkeeping specified

**Modification Issued: 5/27/2004**

in sections A.III. and A.IV.

If required, compliance shall also be demonstrated based upon the procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 4 and Method 6 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996.

b. **Emissions Limitation**

Total emissions from emissions units P001 and P002 combined shall be limited to 2,384 TPY of SO<sub>2</sub> based upon a rolling, 365-day summation during normal operations.

**Applicable Compliance Method**

Compliance shall be demonstrated based upon the sum of the daily SO<sub>2</sub> emissions on the last day of each year, maintained and recorded as required in Section A.III.9.1, and divided by 2000 lbs/ton. Any exceedance shall be reported as required in Section IV.6.

c. **Emissions Limitation**

Total emissions from emissions units P001 and P002 combined shall be limited to 9.4 lb/hr of VOC during normal operations.

**Applicable Compliance Method**

Compliance shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E = [(VEF * (GOB)) - ((VEF * (GOB)) * (1 - 0.34))] * (1 - 0.98)$$

Where

E = VOC emission rate from P001 and P002 combined, in pounds per hour

VEF is the VOC emission factor per 1,000 gallons of oil burned (200lbs VOC/1,000 gal oil burned, submitted by the permittee and based upon their best engineering judgement and knowledge of the process).

GOB is the total gallons of oil burned per hour from emission units P001 and P002 combined.

(1-0.34) 34 percent of the raw tailgas is captured and burned by the dryer as fuel.

Emissions Unit ID: P001

(1-0.98) 98 percent is the designed destruction efficiency of the flare.

d. **Emissions Limitation**

Total emissions from emissions units P001 and P002 combined shall be limited to 41.2 TPY of VOC based upon a rolling, 12-month summation during normal operations.

**Applicable Compliance Method**

Compliance with the annual limit shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E(\text{tpy}) = \text{AHEF} * \text{actual hours of normal operation} * 0.0005 \text{ ton/lb}$$

where

E(tpy) = the ton per year emissions of VOC from P001 and P002 combined

AHEF is the hourly emission factor for P001 and P002 combined, as determined in A.V.1.c, the value of E (lbs VOC/hr).

e. **Emissions Limitation**

Total emissions from emissions units P001 and P002 combined shall be limited to 354.6 lbs/hr of CO during normal operations.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the following equation:

$$E = [(CEF * (GOB)) - ((CEF * (GOB)) * (1 - 0.34))] * (1 - 0.98)$$

Where

E = CO emission rate from P001 and P002 combined, in pounds per hour

CEF is the CO emission factor per 1,000 gallons of oil burned or per 1,000 pounds of carbon black produced, derived from the most recent stack testing results for P001, P002, and/or P011 and P012 prior to their thermal incinerator. Until testing is complete "7,500 lb CO/1,000 gallons of oil burned", shall be used to calculate emissions, submitted by the permittee and based upon their best engineering judgement and knowledge of the process.

GOB is the total gallons of oil burned per hour from emission units P001 and P002 combined (or if the permittee develops a factor per 1,000 pounds of product, pounds of carbon black per hour from P001 and P002).

(1-0.34) 34 percent of the raw tailgas is captured and burned by the dryer as fuel.

**Modification Issued: 5/27/2004**

(1-0.98) 98 percent is the designed destruction efficiency of the flare.

f. **Emissions Limitation**

Total emissions from emissions units P001 and P002 combined shall be limited to 1,553.1 TPY of CO based upon a rolling, 12-month summation during normal operations.

**Applicable Compliance Method:**

Compliance with the annual limit shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E(\text{tpy}) = \text{AHEF} * \text{actual hours of normal operation} * 0.0005 \text{ ton/lb}$$

Where

E(tpy) = the ton per year emissions of CO from P001 and P002 combined  
AHEF is the hourly emission factor for P001 and P002 combined, as determined in A.V.1.e, the value of E (lbs CO/hr).

g. **Emission Limitation:**

Total emissions from emissions units P001 and P002 combined shall be limited to 43.7 lbs/hr of NO<sub>x</sub> during normal operations.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the following equation:

$$E = \text{NEF} * \text{PPPH}$$

Where

E = NO<sub>x</sub> emission rate from P001 and P002 combined, in pounds per hour

NEF is the NO<sub>x</sub> emission factor per 1,000 pounds of carbon black produced or per 1,000 pounds of carbon black produced, derived from the most recent stack testing results for P001, P002, and/or P011 and P012 prior to their thermal incinerator. Until testing is complete "2.14 lbs NO<sub>x</sub>/1,000 gallons of oil burned", shall be used to calculate emissions, submitted by the permittee and based upon their best engineering judgement and knowledge of the process.

**Modification Issued: 5/27/2004**

PPPH is the pounds of product produced per hour from emission units P001 and P002 combined (or if the permittee develops a factor per gallons of oil burned, the gallons of oil burned per hour).

h. **Emission Limitation:**

Total emissions from emissions units P001 and P002 combined shall be limited to 191.4 TPY of NO<sub>x</sub> based upon a rolling, 12-month summation during normal operations.

**Applicable Compliance Method:**

Compliance with the annual limit shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E = NEF * PPPY * 0.0005 \text{ ton/lb}$$

Where

E(tpy) = the ton per year emissions of NO<sub>x</sub> from P001 and P002 combined

NEF is the NO<sub>x</sub> emissions in pounds per 1,000 pounds of product (or per 1,000 gallons of oil burned); and

PPPY is the pounds of product produced per year on P001 and P002 combined (or gallons of oil burned).

i. **Emission Limitation:**

Total emissions from emissions units P001 and P002 combined shall be limited to 5.7 lbs/hr of particulate emissions during normal operations.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the following equation:

$$E = PEM * PPPH * (1 - 0.95)$$

where

Emissions Unit ID: P001

E = PE emission rate from P001 and P002 combined, in pounds per hour

PEM is the PM emission factor per 1,000 pounds of carbon black produced or per 1,000 gallons of oil burned, derived from the most recent stack testing results from P001, P002, and/or P011 and P012, prior to their thermal incinerator. Until testing is completed, "0.278 lb PM/1,000 lb of product" shall be used to calculate emissions, submitted by the permittee based upon their best engineering judgement and knowledge of the process; and

PPPH is the pounds of product produced per hour from emission units P001 and P002 combined (or if the permittee develops a factor per gallons of oil burned, the gallons of oil burned per hour).

(1 - 0.95) 95% is the control efficiency of the flare for PE.

j. **Emission Limitation:**

Total emissions from emissions units P001 and P002 combined shall be limited to 24.9 TPY of particulate emissions based upon a rolling, 12-month summation during normal operations.

**Applicable Compliance Method:**

Compliance with the annual limit shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E(\text{tpy}) = \text{AHER} * \text{actual hours of normal operation} * 0.0005 \text{ ton/lb}$$

where

E(tpy) = the ton per year emissions of PE from P001 and P002 combined, determined in A.V.1.i, the value of E (lbs PE/hr).

AHER is the actual hourly emission rate from P001 and P002 combined, determined in A.V.1.i.

k. **Emission Limitation:**

Visible particulate emissions shall not exceed twenty percent opacity, as a six-minute average except as provided by rule.

**Applicable Compliance Method:**

If required, compliance shall be demonstrated in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Method 9 and the methods and procedures specified in OAC rule 3745-17-03(B)(1).

**Modification Issued: 5/27/2004**

2. Compliance with the operational restrictions in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

a. **Operational Restriction:**

Maximum annual production of carbon black for emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed 223,000,000 pounds as a rolling 12-month average.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in Section A.III.8.

b. **Operational Restriction:**

This emissions unit shall utilize feedstock oil which contains no more than 3% sulfur.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in Sections A.III.3 and A.III.4.

c. **Operational Restriction:**

This emissions unit shall be limited to 81 hours per year for all start-up and shutdown operations.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in Section A.III.2.

d. **Operational Restriction:**

Annual emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following as a rolling 12-month average:

4547.0 tons of SO<sub>2</sub>

30

Degus:

PTI A<sub>1</sub>

**Modification Issued: 5/27/2004**

Emissions Unit ID: P001

508.0 tons of NO<sub>x</sub>

84.9 tons of PE

**Modification Issued: 5/27/2004****Applicable Compliance Method:**

Compliance shall be demonstrated based upon the monitoring, recordkeeping, reporting and testing requirements specified in Sections A.III, A.IV, and A.V.

e. **Operational Restriction:**

Annual emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following as a rolling 365-day average:

151.0 tons of VOC  
2556.0 tons of CO

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the monitoring, recordkeeping, reporting and testing requirements specified in Sections A.III, A.IV, and A.V.

3. The hourly limitations for start-up and shutdown operations in Section A.I.2.a are the uncontrolled emission rates determined by the known chemical reaction of the process and represent the potentials to emit for this emissions unit; therefore, compliance with the hourly emission limitations is assumed. Compliance with the annual start-up and shutdown emission limitation(s) in Section A.I.2.a. of these terms and conditions shall be determined in accordance with the following method(s):

a. **Emission Limitation:**

0.3 TPY of SO<sub>2</sub> during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 6.8 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

b. **Emission Limitation:**

15 TPY of VOC during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 380 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

c. **Emission Limitation:**

577 TPY of CO during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 14,254 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

d. **Emission Limitation:**

0.3 TPY of NO<sub>x</sub> during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 8.4 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

e. **Emission Limitation:**

0.3 TPY of particulate emissions during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 7.8 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

f. **Emission Limitation:**

6.2 TPY of H<sub>2</sub>S during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 154 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

33

Degus:

PTI A<sub>1</sub>

**Modification Issued: 5/27/2004**

Emissions Unit ID: P001

g. **Emission Limitation:**

1.2 TPY of COS during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 30 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

h. **Emission Limitation:**

2.8 TPY of CS<sub>2</sub> during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 70 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

i. **Emission Limitation:**

1.5 TPY of HCN during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 37 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

**VI. Miscellaneous Requirements**

1. For purposes of this permit to install, normal operations is any time except during startup or shutdown of the emissions unit.

**Modification Issued: 5/27/2004**

**B. State Only Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P001 - Carbon Black Unit Number 1	OAC rule 3745-31-05	None

**2. Additional Terms and Conditions**

**2.a** None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

- 1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
P002 - Carbon Black Unit Number 2 (Administrative modification to PTI#06-06770, issued August 21, 2003) to correct emission factors	OAC rule 3745-31-05(A)(3)	OAC rule 3745-31-05(C)
	OAC rule 3745-31-10 through 20	
		OAC rule 3745-17-07(A)
		OAC rule 3745-17-11(B)(1)

**Modification Issued: 5/27/2004**

	<u>Applicable Emissions Limitations/Control Measures</u>	
OAC rule 3745-18-06(E)(2)	The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07 and 40 CFR 52.21.	P012 combined shall not exceed the following based upon a rolling, 12-month summation:  4547.0 tons of SO <sub>2</sub> 508.0 tons of NO <sub>x</sub> 84.9 tons of PE
	See sections A.I.2.a and A.I.2.b below	
	Total emissions from emissions units P001 and P002 combined shall be limited to the following during normal operation from the flare:	Total emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following based upon a rolling, 365 day summation:  2556.0 tons of CO 151.0 tons of VOC
	3% Sulfur content, 544.3 lbs/hr, and 2,384 tons of SO <sub>2</sub> based upon a rolling, 365-day summation.	See Section A.I.2.b
	43.7 lbs/hr and 191.4 tons/yr of NO <sub>x</sub> based upon a rolling, 12-month summation.	Visible particulate emissions shall not exceed twenty percent opacity, as a six-minute average except as provided by rule.
	9.4 lbs/hr and 41.2 tons/yr of VOC based upon a rolling, 12-month summation.	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	354.6 lbs/hr and 1,553.1 tons/yr of CO based upon a rolling, 12-month summation.	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	5.7 lbs/hr and 24.9 tons/yr of PE based upon a rolling, 12-month summation.	
	See section A.I.2.c	
	Total emissions from emission units P001, P002, P005, P006, P011 and	

**Modification Issued: 5/27/2004****2. Additional Terms and Conditions**

**2.a** This emissions unit shall be limited to the following emissions during start-up and shutdown (vent emissions):

6.8 lbs/hr and 0.3 tons/yr SO<sub>2</sub>  
380 lbs/hr and 15 tons/yr VOC  
14,254 lbs/hr and 577 tons/yr CO  
8.4 lbs/hr and 0.3 tons/yr of NO<sub>x</sub>  
7.8 lbs/hr and 0.3 tons/yr of PM/PM<sub>10</sub>  
154 lbs/hr and 6.2 tons/yr of H<sub>2</sub>S  
30 lbs/hr and 1.2 tons/yr of COS  
70 lbs/hr and 2.8 tons/yr of CS<sub>2</sub>  
37 lbs/hr and 1.5 tons/yr of HCN

**2.b** Maximum annual production of carbon black for emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed 223,000,000 pounds on a rolling 12-month summation. This emissions unit is currently permitted and operating, and as such, has existing records of production and emissions, therefore eliminating the need to establish the first year's cumulative rolling 12-month summation of carbon black production. The existing, previous 12-month record of 223,000,000 lb/yr of carbon black shall be maintained as the rolling daily record, upon the issuance of this permit.

**2.c** The permittee shall employ good combustion practices to minimize emissions to the extent possible.

**II. Operational Restrictions**

1. This emissions unit shall:
  - a. utilize feedstock oil which contains no more than 3% sulfur;
  - b. be equipped with a product exhaust bag filter with a design efficiency not less than 99.7%; and
  - c. employ a flare with a design destruction efficiency of 95 percent for particulate emissions and 98 percent for CO and VOC.
2. This emissions unit shall be limited to 81 hours per year for all start-up and shutdown operations.

**Modif**

Emissions Unit ID: P002

3. A pilot flame shall be maintained at all times in the flare's pilot light burner.
4. If the mass flow rate meter employed to continuously monitor the feedstock oil feed rate is not in operation, the production of carbon black shall be automatically terminated.

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall perform daily checks, while the equipment is in operation and when the weather conditions allow, for any visible particulate emissions from the stack of this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log.
  - a. the location and color of the emissions;
  - b. whether the emissions are representative of normal operations;
  - c. if the emissions are not representative of normal operations, the cause of the visible emissions;
  - d. the total duration of any visible emission incident; and
  - e. any corrective actions taken to eliminate the visible emissions.
2. The permittee shall keep daily records for all start-up and shutdown periods that contain the following information:
  - a. The date of each start-up and/or shut down;
  - b. The time period during which the start-up or shut down occurred;
  - c. The year-to-date, total hours of all start-up and shutdown periods; and
  - d. At the end of each year, the permittee shall add and maintain a record of the total hours and total emissions from start-up/shutdown events, from the records maintained as required above.
3. The permittee shall maintain records of the feedstock oil for this emissions unit in accordance with either Alternative 1 or Alternative 2 described below.
  - a. Alternative 1:

For each shipment of feedstock oil received for this emissions unit, the permittee shall collect or require the oil supplier to collect a representative grab sample of the feedstock oil and maintain records of the total quantity of feedstock oil received, and the permittee's or oil supplier's analyses for sulfur content and density.

**Modification Issued: 5/27/2004**

## b. Alternative 2:

The permittee shall collect a representative grab sample of the feedstock oil for this emissions unit for each day when the emissions unit is in operation. If additional feedstock oil is added to the tank serving this emissions unit on a day when the emissions unit is in operation, the permittee shall collect a sufficient number of grab samples to create a composite sample that is representative of the average quality of feedstock oil used in this emissions unit. The permittee shall maintain records of the total quantity of feedstock oil used each day, and the permittee's analyses for sulfur content and density.

4. The permittee shall measure the sulfur content (in weight %) of the feedstock oil in accordance with the procedures specified in ASTM standard D4294, "Standard Test Method for Sulfur in Petroleum and Petroleum Products by Energy-Dispersive X-ray Fluorescence Spectrometry". In addition, the permittee shall measure the density (in pounds per gallon) of the feedstock oil in accordance with the procedures specified in ASTM standard D287, "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)".
5. For each day of operation of this emissions unit, the permittee shall collect a sufficient number of grab samples of carbon black product to create a composite sample that is representative of the average quality of the carbon black produced in this emissions unit. The permittee shall measure and maintain a record of the sulfur content (in weight %) of each composite sample of carbon black product in accordance with the procedures specified in ASTM standard D1619, "Standard Test Method for Carbon Black- Sulfur Content".
6. The permittee shall properly install, operate, and maintain a device to continuously monitor the pilot flame when the emissions unit is in operation. The monitoring device and any recorder shall be installed, calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions and operating manuals.

The permittee shall record the following information each day:

- a. all periods during which there was no pilot flame.
  - b. the corrective action taken to reestablish the flame; and
  - c. the downtimes for the flare, monitoring equipment, and the associated emissions unit.
7. The permittee shall properly operate and maintain a Micro Motion mass flow rate meter, model number D100, or equivalent monitor, to continuously monitor the feedstock oil feed rate when

Emissions Unit ID: P002

the emissions unit is in operation and producing carbon black. The monitoring device and any recorder shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manuals.

The permittee shall record the following information each day:

- a. all periods during which the Micro Motion mass flow rate meter, model number D100, or equivalent monitor, was not in operation while the emissions unit is in operation;
- b. all downtimes for the monitoring equipment and the associated emissions unit, while the emissions unit is in operation; and
- c. the corrective actions taken to reestablish correct operation of the mass flow rate meter.

**Modification Issued: 5/27/2004**

8. The permittee shall maintain monthly records of the following information:
  - a. the carbon black production rate, in pounds per month for this emissions unit;
  - b. the production rate for emission units P001, P002, P005, P006, P011 and P012 (tons carbon black/month);
  - c. the rolling, 12-month summation of the production rates for emission units P001, P002, P005, P006, P011, and P012, combined (tons carbon black/rolling 12 months);
  - d. the total hours of operation of this emissions unit; and
  - e. the total emission of SO<sub>2</sub>, NO<sub>x</sub>, PE and VOC, calculated as required in the appropriate sections in "Testing Requirements", Section V. Emissions factors submitted by the permittee in their permit application shall be applied, until better factors are developed from the most recent stack testing results for emission units P001, P002, and/or P011 and P012 prior to their thermal incinerator, in pounds of pollutant per 1,000 gallons of oil burned or per 1,000 pounds of carbon black produced.  
  
\* a permanent, rather than monthly record may be maintained for 8.a above
  
9. The permittee shall maintain daily records of the following information for this emissions unit:
  - a. the OEPA identification number of this emissions unit;
  - b. the current day, month, and year;
  - c. the grade of each feedstock oil processed (% sulfur);
  - d. the yield of each feedstock oil, defined as the average amount of carbon black produced, per gallon of feedstock oil used during the day (lbs carbon black/gal);
  - e. the sulfur content of each feedstock oil, in weight percent;
  - f. the sulfur content of the carbon black product, in weight percent;
  - g. the feedstock oil feed rate, in gallons per hour for each hour of operation continuously monitored using a Micro Motion mass flow rate meter, model number D100 or an equivalent monitor;

**Modification Issued: 5/27/2004**

- h. the carbon black production rate, in pounds per hour for each hour of operation, determined by multiplying the feedstock oil feed rate (gal/hr) by the yield of the feedstock oil (lbs/gal);
  - i. the average hourly SO<sub>2</sub> emission rate for each feedstock oil, in pounds per hour, calculated as specified in Section A.III.10;
  - j. the total hours of operation for each feedstock oil;
  - k. the daily sulfur dioxide emission rate for all feedstock oils, in pounds (i.e., the summation of (i) x (j) for all of the feedstock oils);
  - l. the rolling, 365-day SO<sub>2</sub> emission rate for all feedstock oils, in tons;
  - m. the daily and year-to-date SO<sub>2</sub> emission rates for all carbon black products produced in this emissions unit, in pounds, i.e., the value from A.III.9.k above for all feedstock oils employed, multiplied by 66%\*;;
  - n. the rolling, 365-day SO<sub>2</sub> emission rate for all feedstock oils, for emission units P001 and P002 combined, in tons, calculated from the records maintained for emission units P001 and P002, Section A.III.9.l above, multiplied by the factor of 66%\* for the carbon black unit/dryer split;
  - o. the average hourly CO and VOC emission rate for each feedstock oil used in P001, P002, P005, P006, P011 and P012, in pounds per hour, calculated as specified in Section A.V.1.c & e; and
  - p. the rolling, 365-day CO and VOC emission rate for P001, P002, P005, P006, P011 and P012, in tons.
- \* The factor applied above may change with future testing on the capture efficiency of the dryer and/or the emission's split between this emissions unit and/or P002 and its dryer.
10. The average hourly sulfur dioxide emission rate for each feedstock oil shall be calculated each day using the following equations:

$$E = ((SFS) - (SCB)) \times (1 - TG) \times (64/32)$$

where:

$E$  = sulfur dioxide emission rate, in pounds per hour;  
 $SFS$  = feedstock oil sulfur weight rate, in pounds per hour;  
 $SCB$  = carbon black sulfur weight rate, in pounds per hour;  
 $TG$  = fraction of stream to tailgas (constant at .34); and  
 $64/32$  = constant to convert molecular weight rate of sulfur to molecular weight of sulfur dioxide.

NOTE: The permittee conservatively assumes all of the sulfur emissions are emitted as sulfur dioxide emissions.

The feedstock oil sulfur weight rate utilized in the equation above is computed in the following manner:

$$SFS = FSR \times SFSP$$

where:

$SFS$  = feedstock oil sulfur weight rate, in pounds per hour;  
 $FSR$  = maximum daily recorded feedstock oil feed rate, in gallons per hour (from A.III.7); and  
 $SFSP$  = feedstock oil sulfur content, in weight percent (from A.III.4).

The carbon black sulfur weight rate utilized in the equation above is computed in the following manner:

$$SCB = CBPR \times SCBP$$

where:

$SCB$  = carbon black sulfur weight rate, in pounds per hour;  
 $CBPR$  = maximum recorded carbon black production rate, in pounds per hour (from A.III.8.a);  
 and  
 $SCBP$  = carbon black sulfur content, in weight percent (from A.III.5).

#### IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that identify all periods of time during which the pilot flame was not functioning properly. The reports shall include the date, time, and duration of each such period.
2. The permittee shall submit quarterly deviation (excursion) reports that identify all periods of time during which the Micro Motion mass flow rate meter or equivalent flow meter, model number D100 or equivalent flow meter, was not functioning properly. The reports shall include the date, time, and duration of each such period, and the corrective action(s) to ensure correct operation.
3. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month production rate limitation of 223,000,000 lb/yr carbon black for emission

**Modification Issued: 5/27/2004**

units P001, P002, P005, P006, P001, and P002 combined.

4. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the sulfur content limitation. The reports shall include the date, time, and duration of each such period of time when the sulfur content of the oil used in this emissions unit is greater than 3.0 percent, and the corrective action to bring the sulfur content below 3.0 percent.
5. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the average hourly SO<sub>2</sub> emission rate from emission units P001 and P002 combined exceeded 544.3 lbs/hr, and the actual average hourly SO<sub>2</sub> emissions for each such day.
6. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the 365-day SO<sub>2</sub> emission rate from emission units P001 and P002 combined exceeded 2,384 tons, and the actual SO<sub>2</sub> emissions for each such day.
7. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from the stack of this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (Ohio EPA Southeast District Office) by January 31 and July 31 of each year and shall cover the previous 6-month period.
8. The permittee shall submit annual reports that include the following information:
  - a. the total hours of start-up and shutdown operations for this emissions unit for the previous calendar year, and the emissions calculated from start-up and shutdown events, calculated and recorded as required in Section A.III.2;
  - b. the total hours of operation of this emissions unit;
  - c. the total production from emissions units P001, P002, P005, P006, P011, and P012 for each 12-month period ending during the calendar year; and
  - d. the total SO<sub>2</sub> emissions (including all calculations), in tons, from emission units P001, P002, P005, P006, P011 and P012 for the previous calendar year using the monthly emission records required in Sections A.III.3, A.III.8 and A.III.9.

These reports shall be submitted to the Director (Ohio EPA Southeast District Office) by January 31 of each year.

9. The permittee shall submit quarterly deviation (excursion) reports that identify each day during

**Modif**

Emissions Unit ID: P002

which the rolling 12-month emission rates for emission units P001, P002, P005, P006, P011 and P012, combined, exceeded the rolling 12-month ton per year limit listed in A.I.1.

10. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the rolling 365-day CO and VOC emission rates from emission units P001, P002, P005, P006, P011 and P012 combined exceeded 2,983 tons and 80.4 tons respectively. The report shall also include the actual SO<sub>2</sub> emissions for each day the deviation occurs.

Quarterly deviation reports shall be submitted as required in the General Terms & Conditions of this permit.

**V. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

The emission factors used in the compliance calculations below, as pounds of pollutant per 1,000 pounds of product or per 1,000 gallons of oil burned, shall be adjusted, as derived from the most recent stack testing results. It shall be assumed that the emissions per gallon of process oil or per pound of carbon black produced are similar on all carbon black units, prior to control. The pounds of each pollutant per 1,000 pounds of product or per 1,000 gallons of oil shall be determined from the testing results obtained from emission units P001 and P002, prior to their flare, and/or P011 and P012 prior to the thermal incinerator, as required in Sections V.4 for emission units P011 and P012. The designed destruction efficiency of 95% for PE and 98% for CO and VOC for the flare shall be used in the calculations that will demonstrate compliance with the limits for these pollutants below, since stack testing after the flare is not possible.

- a. **Emission Limitation**

Total emissions from emissions units P001 and P002 combined shall be limited to 544.3 lb/hr of SO<sub>2</sub> during normal operations.

**Applicable Compliance Method**

Compliance shall be demonstrated based upon the monitoring and recordkeeping specified in sections A.III. and A.IV.

If required, compliance shall also be demonstrated based upon the procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 4 and Method 6 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996.

- b. **Emissions Limitation**

Total emissions from emissions units P001 and P002 combined shall be limited to 2,384 TPY of SO<sub>2</sub> based upon a rolling, 365-day summation during normal operations.

**Applicable Compliance Method**

Compliance shall be demonstrated based upon the sum of the daily SO<sub>2</sub> emissions on the

48

Degus:

PTI A<sub>1</sub>

**Modification Issued: 5/27/2004**

Emissions Unit ID: P002

last day of each year, maintained and recorded as required in Section A.III.9.1, and divided by 2000 lbs/ton. Any exceedance shall be reported as required in Section IV.6.

**Modification Issued: 5/27/2004**c. **Emissions Limitation**

Total emissions from emissions units P001 and P002 combined shall be limited to 9.4 lb/hr of VOC during normal operations.

**Applicable Compliance Method**

Compliance shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E = [(VEF * (GOB)) - ((VEF * (GOB)) * (1 - 0.34))] * (1 - 0.98)$$

Where

E = VOC emission rate from P001 and P002 combined, in pounds per hour

VEF is the VOC emission factor per 1,000 gallons of oil burned (200lbs VOC/1,000 gal oil burned, submitted by the permittee and based upon their best engineering judgement and knowledge of the process).

GOB is the total gallons of oil burned per hour from emission units P001 and P002 combined.

(1-0.34) 34 percent of the raw tailgas is captured and burned by the dryer as fuel.

(1-0.98) 98 percent is the designed destruction efficiency of the flare.

d. **Emissions Limitation**

Total emissions from emissions units P001 and P002 combined shall be limited to 41.2 TPY of VOC based upon a rolling, 12-month summation during normal operations.

**Applicable Compliance Method**

Compliance with the annual limit shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E(\text{tpy}) = \text{AHEF} * \text{actual hours of normal operation} * 0.0005 \text{ ton/lb}$$

where

E(tpy) = the ton per year emissions of VOC from P011 and P002 combined

AHEF is the hourly emission factor for P001 and P002 combined, as determined in A.V.1.c, the value of E (lbs VOC/hr).

e. **Emissions Limitation**

Total emissions from emissions units P001 and P002 combined shall be limited to 354.6 lbs/hr of CO during normal operations.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the following equation:

$$E = [(CEF * (GOB)) - ((CEF * (GOB))*(1 - 0.34))] * (1-0.98)$$

Where

E = CO emission rate from P001 and P002 combined, in pounds per hour

CEF is the CO emission factor per 1,000 gallons of oil burned or per 1,000 pounds of carbon black produced, derived from the most recent stack testing results for P001, P002, and/or P011 and P012 prior to their thermal incinerator. Until testing is complete "7,500 lb CO/1,000 gallons of oil burned", shall be used to calculate emissions, submitted by the permittee and based upon their best engineering judgement and knowledge of the process.

GOB is the total gallons of oil burned per hour from emission units P001 and P002 combined (or if the permittee develops a factor per 1,000 pounds of product, pounds of carbon black per hour from P001 and P002).

(1-0.34) 34 percent of the raw tailgas is captured and burned by the dryer as fuel.

(1-0.98) 98 percent is the designed destruction efficiency of the flare.

f. **Emissions Limitation**

Total emissions from emissions units P001 and P002 combined shall be limited to 1,553.1 TPY of CO based upon a rolling, 12-month summation during normal operations.

**Applicable Compliance Method:**

Compliance with the annual limit shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E(\text{tpy}) = \text{AHEF} * \text{actual hours of normal operation} * 0.0005 \text{ ton/lb}$$

Where

E(tpy) = the ton per year emissions of CO from P001 and P002 combined

AHEF is the hourly emission factor for P001 and P002 combined, as determined in A.V.1.e, the value of E (lbs CO/hr).

**Modification Issued: 5/27/2004**

g. **Emission Limitation:**

Total emissions from emissions units P001 and P002 combined shall be limited to 43.7 lbs/hr of NO<sub>x</sub> during normal operations.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the following equation:

$$E = NEF * PPPH$$

Where

E = NO<sub>x</sub> emission rate from P001 and P002 combined, in pounds per hour

NEF is the NO<sub>x</sub> emission factor per 1,000 pounds of carbon black produced or per 1,000 gallons of carbon black produced, derived from the most recent stack testing results for P001, P002, and/or P011 and P012 prior to their thermal incinerator. Until testing is complete "2.14 lbs NO<sub>x</sub>/1,000 gallons of oil burned", shall be used to calculate emissions, submitted by the permittee and based upon their best engineering judgement and knowledge of the process.

PPPH is the pounds of product produced per hour from emission units P001 and P002 combined (or if the permittee develops a factor per gallons of oil burned, the gallons of oil burned per hour).

h. **Emission Limitation:**

Total emissions from emissions units P001 and P002 combined shall be limited to 191.4 TPY of NO<sub>x</sub> based upon a rolling, 12-month summation during normal operations.

**Applicable Compliance Method:**

Compliance with the annual limit shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E = NEF * PPPY * 0.0005 \text{ ton/lb}$$

Where

E(tpy) = the ton per year emissions of NO<sub>x</sub> from P001 and P002 combined

NEF is the NO<sub>x</sub> emissions in pounds per 1,000 pounds of product (or per 1,000 gallons of oil burned); and

PPPY is the pounds of product produced per year on P001 and P002 combined (or gallons of oil burned).

**Modification Issued: 5/27/2004**i. **Emission Limitation:**

Total emissions from emissions units P001 and P002 combined shall be limited to 5.7 lbs/hr of particulate emissions during normal operations.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the following equation:

$$E = PEM * PPPH * (1 - 0.95)$$

where

E = PE emission rate from P001 and P002 combined, in pounds per hour

PEM is the PM emission factor per 1,000 pounds of carbon black produced or per 1,000 gallons of oil burned, derived from the most recent stack testing results from P001, P002, and/or P011 and P012, prior to their thermal incinerator. Until testing is completed, "0.278 lb PM/1,000 lb of product" shall be used to calculate emissions, submitted by the permittee based upon their best engineering judgement and knowledge of the process; and

PPPH is the pounds of product produced per hour from emission units P001 and P002 combined (or if the permittee develops a factor per gallons of oil burned, the gallons of oil burned per hour).

(1 - 0.95) 95% is the control efficiency of the flare for PE.

j. **Emission Limitation:**

Total emissions from emissions units P001 and P002 combined shall be limited to 24.9 TPY of particulate emissions based upon a rolling, 12-month summation during normal operations.

**Applicable Compliance Method:**

Compliance with the annual limit shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E(\text{tpy}) = \text{AHER} * \text{actual hours of normal operation} * 0.0005 \text{ ton/lb}$$

**Modification Issued: 5/27/2004**

where

E(tpy) = the ton per year emissions of PE from P001 and P002 combined, determined in A.V.1.i, the value of E (lbs PE/hr).

AHER is the actual hourly emission rate from P001 and P002 combined, determined in A.V.1.i.

k. **Emission Limitation:**

Visible particulate emissions shall not exceed twenty percent opacity, as a six-minute average except as provided by rule.

**Applicable Compliance Method:**

If required, compliance shall be demonstrated in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Method 9 and the methods and procedures specified in OAC rule 3745-17-03(B)(1).

2. Compliance with the operational restrictions in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

a. **Operational Restriction:**

Maximum annual production of carbon black for emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed 223,000,000 pounds as a rolling 12-month average.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in Section A.III.8.

b. **Operational Restriction:**

This emissions unit shall utilize feedstock oil which contains no more than 3% sulfur.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in

Sections A.III.3 and A.III.4.

c. **Operational Restriction:**

This emissions unit shall be limited to 81 hours per year for all start-up and shutdown operations.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in Section A.III.2.

d. **Operational Restriction:**

Annual emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following as a rolling 12-month average:

4547.0 tons of SO<sub>2</sub>  
508.0 tons of NO<sub>x</sub>  
84.9 tons of PE

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the monitoring, recordkeeping, reporting and testing requirements specified in Sections A.III, A.IV, and A.V.

e. **Operational Restriction:**

Annual emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following as a rolling 365-day average:

151.0 tons of VOC  
2556.0 tons of CO

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the monitoring, recordkeeping, reporting and testing requirements specified in Sections A.III, A.IV, and A.V.

3. The hourly limitations for start-up and shutdown operations in section A.I.2.a are the uncontrolled emission rates determined by the known chemical reaction of the process and represent the potentials to emit for this emissions unit; therefore, compliance with the hourly emission limitations is assumed. Compliance with the annual start-up and shutdown emission limitation(s) in Section A.I.2.a. of these terms and conditions shall be determined in accordance with the following method(s):

a. **Emission Limitation:**

57

Degussa Engineered Carbons LP

PTI Application: 06 06770

**Modif**

Facility ID: 0684010049

Emissions Unit ID: P002

0.3 TPY of SO2 during start-up/shutdown

**Modification Issued: 5/27/2004****Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 6.8 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

b. **Emission Limitation:**

15 TPY of VOC during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 380 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

c. **Emission Limitation:**

577 TPY of CO during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 14,254 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

d. **Emission Limitation:**0.3 TPY of NO<sub>x</sub> during start-up/shutdown**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 8.4 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

e. **Emission Limitation:**

0.3 TPY of particulate emissions during start-up/shutdown

**Modification Issued: 5/27/2004****Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 7.8 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

f. **Emission Limitation:**6.2 TPY of H<sub>2</sub>S during start-up/shutdown**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 154 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

g. **Emission Limitation:**

1.2 TPY of COS during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 30 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

h. **Emission Limitation:**2.8 TPY of CS<sub>2</sub> during start-up/shutdown**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 70 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

i. **Emission Limitation:**

1.5 TPY of HCN during start-up/shutdown

60

Degus:

PTI A<sub>1</sub>

**Modification Issued: 5/27/2004**

Emissions Unit ID: P002

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{TPY}) = 37 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

**VI. Miscellaneous Requirements**

1. For purposes of this permit to install, normal operations is any time except during startup or shutdown of the emissions unit.

**Modification Issued: 5/27/2004**

**B. State Only Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P002 - Carbon Black Unit Number 2	OAC rule 3745-31-05	None

**2. Additional Terms and Conditions**

**2.a** None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
P005 - Unit Number 1 Dryer (Administrative modification to PTI#06-06770, issued August 21, 2003) to correct emission factors	OAC rule 3745-31-05(A)(3)	OAC rule 3745-31-05(C)
	OAC rule 3745-31-10 through 20	
		OAC rule 3745-17-07(A)
		OAC rule 3745-17-11(B)(1)
		OAC rule 3745-18-06(E)(2)

Degus:

PTI A<sub>1</sub>**Modification Issued: 5/27/2004**

Emissions Unit ID: P005

Applicable Emissions <u>Limitations/Control</u> <u>Measures</u>	See section A.I.2.b
The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07, OAC rule 3745-31-05(C), and 40 CFR 52.21.	Total emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following, based upon a rolling 12-month summation:
See A.I.2.a	4547.0 tons of SO <sub>2</sub> 508.0 tons of NO <sub>x</sub> 84.9 tons of PE
Total emissions from emissions units P005 and P006 combined shall be limited to the following from the central stack.	Total emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following, based upon a rolling 365-day summation.
3% sulfur content, 290.4 lbs/hr, and 1,272 tons/yr of SO <sub>2</sub> , based upon a 365-day rolling basis.	151.0 tons of VOC 2556.0 tons of CO
19.5 lb/hr and 85.4 tons/yr of VOC based upon a rolling 12-month summation.	Visible particulate emissions shall not exceed twenty percent opacity, as a six-minute average except as provided by rule.
56.0 lbs/hr and 219.0 tons/yr of NO <sub>x</sub> based upon a rolling 12-month summation.	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
299.8 lb/hr and 1313.7 tons/yr of CO based upon a rolling 12-month summation.	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
6.8 lbs/hr and 29.8 tons/yr of PM/PM <sub>10</sub> based upon a rolling 12-month summation.	

**Modification Issued: 5/27/2004****2. Additional Terms and Conditions**

- 2.a** Maximum annual production of carbon black for emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed 223,000,000 pounds on a rolling 12-month summation. This emissions unit is currently permitted and operating, and, as such, has existing records of production and emissions, therefore eliminating the need to establish the first year's cumulative rolling 12-month summation carbon black production. The existing, previous 12-month record of the 223,000,000 lb/yr of carbon black shall be maintained as the rolling monthly record, upon the issuance of this permit.
- 2.b** The permittee shall employ good combustion practices to minimize emissions to the extent possible.

**II. Operational Restrictions**

1. The pressure drop across the baghouse shall be maintained within the range of 2 to 7 inches of water, while the emissions unit is in operation.

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall properly operate and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a daily basis.
2. The permittee shall maintain monthly records of the following information:
  - a. the production rate for emission units P001, P002, P005, P006, P011 and P012 (tons carbon black/month);
  - b. the rolling, 12-month summation of the production rates for emissions units P001, P002, P005, P006, P011, and P012, combined (tons carbon black/rolling 12-months);
  - c. the total hours of operation of this emissions unit; and
  - d. the total emission of SO<sub>2</sub>, NO<sub>x</sub>, CO, VOC and PE calculated by multiplying the hours of operation during the month (c) for both emission units P005 and P006, times the pound per hour emissions for each pollutant, as determined in the most recent stack test. The pound per hour emission limits shall be used until better factors are developed from the

stack testing requirements found in Section A.V.3.

3. The permittee shall maintain daily records of the following information:
  - a. the average hourly SO<sub>2</sub> emission rate for each carbon black product dried in this emissions unit, in pounds per hour, i.e., the value from Section A.III.9.i for emissions unit P001 for each feedstock oil employed, multiplied by 34% for the carbon black unit-to-dryer split;
  - b. the daily and year-to-date SO<sub>2</sub> emission rates for all carbon black products dried in this emissions unit, in pounds, i.e., the value from Section A.III.9.k for emissions unit P001 for all feedstock oils employed, multiplied by 34% for the carbon black unit-to-dryer split;
  - c. the annual SO<sub>2</sub> emission rate for all feedstock oils, for emission units P005 and P006 combined, in tons, calculated from the records maintained for emission units P001 and P002, and multiplying the factor of 34% for the carbon black unit-to-dryer split;
  - d. the average hourly CO and VOC emission rate for each feedstock oil used in P001, P002, P005, P006, P011 and P012, in pounds per hour, calculated using the feed oil recordkeeping and the equations as specified in P001; and
  - e. the rolling, 365-day CO and VOC emission rate for P001, P002, P005, P006, P011 and P012, in tons.

The factor applied above may change with future testing on the capture efficiency of the dryer and/or the emission's split between P001 and this dryer.

#### IV. Reporting Requirements

1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above.
2. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month production rate limitation for emission units P001, P002, P005, P006, P011 and P012.
3. The permittee shall submit annual reports that include the following information:
  - a. the total hours of operation of this emissions unit;
  - b. the total production from emissions units P001, P002, P005, P006, P011, and P012; and
  - c. the emissions (including all calculations), in tons, from this emissions unit for the previous calendar year for each pollutant with an annual limit in Section A.I.1.

**Modification Issued: 5/27/2004**

These reports shall be submitted to the Director (Ohio EPA Southeast District Office) by January 31 of each year.

4. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the average hourly SO<sub>2</sub> emission rate from emission units P005 and P006 combined exceeded 290.4 lbs/hr, and the actual average hourly SO<sub>2</sub> emissions for each such day.
5. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the 365-day SO<sub>2</sub> emission rate from emission units P005 and P006 combined exceeded 1,271 tons, and the actual SO<sub>2</sub> emissions for each such 365 day period.
6. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the rolling, 365-day SO<sub>2</sub> emissions rate for emission units P001, P002, P005, P006, P011 and P012 combined, exceeded 4,545 tons, and the actual SO<sub>2</sub> emissions for each such 365 day period.
7. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the rolling 365-day CO and VOC emission rates from emission units P001, P002, P005, P006, P011 and P012 combined exceeded 2,983 tons and 80.4 tons respectively. The report shall also include the actual 365-day SO<sub>2</sub> emissions for each day the deviation occurs.

Quarterly deviation reports shall be submitted as required in the General Terms & Conditions of this permit.

**V. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

- a. **Emission Limitation:**

Total emissions from emissions units P005 and P006 combined shall not exceed 6.8 lbs/hr of particulate emissions.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in Section A.III.2 and the emission testing procedures specified in section A.V.3.

- b. **Emission Limitation:**

Emissions Unit ID: P005

Total emissions from emissions units P005 and P006 combined shall not exceed 299.8 lb/hr of CO.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in Section A.III.2 and the emission testing procedures specified in section A.V.3.

c. **Emission Limitation:**

Total emissions from emissions units P005 and P006 combined shall not exceed 56.0 lbs/hr of NO<sub>x</sub>.

**Modification Issued: 5/27/2004****Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in Section A.III.2 and the emission testing procedures specified in section A.V.3.

**d. Emission Limitation:**

Total emissions from emissions units P005 and P006 combined shall not exceed 290.4 lbs/hr of SO<sub>2</sub>.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in Section A.III.3 and the emission testing procedures specified in section A.V.3.

**e. Emission Limitation:**

Total emissions from emissions units P005 and P006 combined shall not exceed 19.5 lb/hr of VOC.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in Section A.III.3 and the emission testing procedures specified in section A.V.3.

**f. Emission Limitation:**

Visible particulate emissions shall not exceed twenty percent opacity, as a six-minute average except as provided by rule.

**Applicable Compliance Method:**

Compliance shall be demonstrated in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Method 9 and the methods and procedures specified in OAC rule 3745-17-03(B)(1).

**g. Emission Limitation:**

Total emissions from emissions units P005 and P006 combined shall not exceed 1,272 tpy of SO<sub>2</sub> per year based upon a rolling, 365-day summation.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in section A.III.3.

h. **Emission Limitation:**

Total emissions from emissions units P005 and P006 combined shall not exceed 29.8 tpy of particulate emissions based upon a rolling, 12-month summation.

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = \text{HER} * \text{AHO} * 0.0005 \text{ ton/lb}$$

where

$E(\text{tpy})$  = the ton per year emissions of PE from emission units P005 and P006 combined

HER is the hourly emission rate in pounds of particulate emissions from emission units P005 and P006 combined, as determined during the most recent performance test, and

AHO is the actual hours of operation during which emissions are being vented through the central stack.

i. **Emission Limitation:**

Total emissions from emissions units P005 and P006 combined shall not exceed 1313.7 tons/yr of CO based upon a rolling, 12-month summation.

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = \text{HER} * \text{AHO} * 0.0005 \text{ ton/lb}$$

where

**Modification Issued: 5/27/2004**

$E(\text{tpy})$  = the ton per year emissions of CO from emission units P005 and P006 combined

HER is the hourly emission rate in pounds of CO from emission units P005 and P006 combined, as determined during the most recent performance test, and

AHO is the actual hours of operation during which emissions are being vented through the central stack.

j. **Emission Limitation:**

Total emissions from emissions units P005 and P006 combined shall not exceed 219.0 tons/yr of NO<sub>x</sub> based upon a rolling, 12-month summation.

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = \text{HER} * \text{AHO} * 0.0005 \text{ ton/lb}$$

where

$E(\text{tpy})$  = the ton per year emissions of NO<sub>x</sub> from emission units P005 and P006 combined

HER is the hourly emission rate in pounds of NO<sub>x</sub> from emission units P005 and P006 combined, as determined during the most recent performance test, and

AHO is the actual hours of operation during which emissions are being vented through the central stack.

k. **Emission Limitation:**

Total emissions from emissions unit P005 and P006 combined shall not exceed 85.4 tons/yr of VOC based upon a rolling 12-month summation.

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = \text{HER} * \text{AHO} * 0.0005 \text{ ton/lb}$$

where

$E(\text{tpy})$  = the ton per year emissions of VOC from emission units P005 and P006 combined

HER is the hourly emission rate in pounds of VOC from emission units P005 and P006 combined, as determined during the most recent performance test, and

AHO is the actual hours of operation during which emissions are being vented through the central stack.

2. Compliance with the operational restrictions in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

a. **Operational Restriction:**

Maximum annual production of carbon black for emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed 223,000,000 pounds on a rolling 12-month summation.

**Applicable Compliance Method**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in Section A.III.8.

b. **Operational Restriction**

Annual emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following as a rolling 12-month summation:

4547.0 tons of SO<sub>2</sub>

508.0 tons of NO<sub>x</sub>

84.9 tons of PE

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the monitoring, recordkeeping and testing requirements specified in Sections A.III, A.IV, and A.V.

c. **Operational Restriction**

Annual emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following as a rolling 365-day summation:

151.0 tons of VOC

2556.0 tons of CO

**Applicable Compliance Method:**

**Modification Issued: 5/27/2004**

Compliance shall be demonstrated based upon the monitoring, recordkeeping and testing requirements specified in Sections A.III, A.IV, and A.V.

3. The permittee shall conduct, or have conducted, emission testing for emission units P005 and P006 combined in accordance with the following requirements:
  - a. The emission testing shall be conducted within 60 days after the issuance of this permit and while using a feedstock oil with 3% sulfur.
  - b. The emission testing shall be conducted for emission units P005 and P006 to demonstrate compliance with the combined allowable mass emission rates for CO, VOC, particulates, SO<sub>2</sub>, and NO<sub>x</sub>.
  - c. The following test methods shall be employed to demonstrate compliance with the allowable mass emission rates:

for particulates, Methods 1 through 5 of 40 CFR Part 60, Appendix A;  
for SO<sub>2</sub>, Methods 1 through 4 and Method 6 of 40 CFR Part 60, Appendix A;  
for VOC, Methods 1 through 4 and Method 25 of 40 CFR Part 60, Appendix A;  
for NO<sub>x</sub>, Methods 1 through 4 and Method 7 of 40 CFR Part 60, Appendix A; and  
for CO, Methods 1 through 4 and Method 10 of 40 CFR Part 60, Appendix A.

Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.

- d. The test(s) shall be conducted while emission units P005 and P006 and emission units P001 and P002 are all operating at or near their maximum capacities, unless otherwise specified or approved by the Ohio EPA Southeast District Office.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA Southeast District Office. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA Southeast District Office's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA Southeast District Office shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the

**Modif**

Emissions Unit ID: P005

emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA Southeast District Office within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA Southeast District Office.

**VI. Miscellaneous Requirements**

None

**Modification Issued: 5/27/2004**

**B. State Only Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P005 - Unit Number 1 Dryer	OAC rule 3745-31-05	None

**2. Additional Terms and Conditions**

**2.a** None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

**Modification Issued: 5/27/2004**

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>
P006 - Unit Number 2 Dryer (Administrative modification to PTI#06-06770, issued August 21, 2003) to correct emission factors	OAC rule 3745-31-05(A)(3)
	OAC rule 3745-31-05(C)
	OAC rule 3745-31-10 through 20
	OAC rule 3745-17-07(A)

**Modification Issued: 5/27/2004**

	<u>Applicable Emissions Limitations/Control Measures</u>	
OAC rule 3745-17-11(B)(1)	The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07, OAC rule 3745-31-05(C), and 40 CFR 52.21.	P012 combined shall not exceed the following, based upon a rolling 12-month summation:  4547.0 tons of SO <sub>2</sub> 508.0 tons of NO <sub>x</sub> 84.9 tons of PE
OAC rule 3745-18-06(E)(2)	See A.I.2.a  Total emissions from emissions units P005 and P006 combined shall be limited to the following from the central stack.	Total emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following, based upon a rolling 365-day summation.  151.0 tons of VOC 2556.0 tons of CO
	3% sulfur content, 290.4 lbs/hr, and 1,272 tons/yr of SO <sub>2</sub> , based upon a 365-day rolling basis.	Visible particulate emissions shall not exceed twenty percent opacity, as a six-minute average except as provided by rule.
	19.5 lb/hr and 85.4 tons/yr of VOC based upon a rolling 12-month summation.	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	56.0 lbs/hr and 219.0 tons/yr of NO <sub>x</sub> based upon a rolling 12-month summation.	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).
	299.8 lb/hr and 1313.7 tons/yr of CO based upon a rolling 12-month summation.	
	6.8 lbs/hr and 29.8 tons/yr of PM/PM <sub>10</sub> based upon a rolling 12-month summation.	
	See section A.I.2.b	
	Total emissions from emission units P001, P002, P005, P006, P011 and	

**2. Additional Terms and Conditions**

- 2.a** Maximum annual production of carbon black for emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed 223,000,000 pounds on a rolling 12-month summation. This emissions unit is currently permitted and operating, and, as such, has existing records of production and emissions, therefore eliminating the need to establish the first year's cumulative rolling 12-month summation carbon black production. The existing, previous 12-month record of the 223,000,000 lb/yr of carbon black shall be maintained as the rolling monthly record, upon the issuance of this permit.
- 2.b** The permittee shall employ good combustion practices to minimize emissions to the extent possible.

**II. Operational Restrictions**

1. The pressure drop across the baghouse shall be maintained within the range of 2 to 7 inches of water, while the emissions unit is in operation.

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall properly operate and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a daily basis.
2. The permittee shall maintain monthly records of the following information:
  - a. the production rate for emission units P001, P002, P005, P006, P011 and P012 (tons carbon black/month);
  - b. the rolling, 12-month summation of the production rates for emissions units P001, P002, P005, P006, P011, and P012, combined (tons carbon black/rolling 12-months);
  - c. the total hours of operation of this emissions unit; and
  - d. the total emission of SO<sub>2</sub>, NO<sub>x</sub>, CO, VOC and PE calculated by multiplying the hours of operation during the month (c) for both emission units P005 and P006, times the pound per hour emissions for each pollutant, as determined in the most recent stack test. The pound per hour emission limits shall be used until better factors are developed from the stack testing requirements found in Section A.V.3.
3. The permittee shall maintain daily records of the following information:
  - a. the average hourly SO<sub>2</sub> emission rate for each carbon black product dried in this emissions

**Modification Issued: 5/27/2004**

- unit, in pounds per hour, i.e., the value from Section A.III.9.i for emissions unit P001 for each feedstock oil employed, multiplied by 34% for the carbon black unit-to-dryer split;
- b. the daily and year-to-date SO<sub>2</sub> emission rates for all carbon black products dried in this emissions unit, in pounds, i.e., the value from Section A.III.9.k for emissions unit P001 for all feedstock oils employed, multiplied by 34% for the carbon black unit-to-dryer split;
  - c. the annual SO<sub>2</sub> emission rate for all feedstock oils, for emission units P005 and P006 combined, in tons, calculated from the records maintained for emission units P001 and P002, and multiplying the factor of 34% for the carbon black unit-to-dryer split;
  - d. the average hourly CO and VOC emission rate for each feedstock oil used in P001, P002, P005, P006, P011 and P012, in pounds per hour, calculated using the feed oil recordkeeping and the equations as specified in P001; and
  - e. the rolling, 365-day CO and VOC emission rate for P001, P002, P005, P006, P011 and P012, in tons.

The factor applied above may change with future testing on the capture efficiency of the dryer and/or the emission's split between P001 and this dryer.

**IV. Reporting Requirements**

1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above.
2. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month production rate limitation for emission units P001, P002, P005, P006, P011 and P012.
3. The permittee shall submit annual reports that include the following information:
  - a. the total hours of operation of this emissions unit;
  - b. the total production from emissions units P001, P002, P005, P006, P011, and P012; and
  - c. the emissions (including all calculations), in tons, from this emissions unit for the previous calendar year for each pollutant with an annual limit in Section A.I.1.

**Modif**

Emissions Unit ID: P006

These reports shall be submitted to the Director (Ohio EPA Southeast District Office) by January 31 of each year.

4. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the average hourly SO<sub>2</sub> emission rate from emission units P005 and P006 combined exceeded 290.4 lbs/hr, and the actual average hourly SO<sub>2</sub> emissions for each such day.
5. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the 365-day SO<sub>2</sub> emission rate from emission units P005 and P006 combined exceeded 1,271 tons, and the actual SO<sub>2</sub> emissions for each such 365 day period.
6. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the rolling, 365-day SO<sub>2</sub> emissions rate for emission units P001, P002, P005, P006, P011 and P012 combined, exceeded 4,545 tons, and the actual SO<sub>2</sub> emissions for each such 365 day period.
7. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the rolling 365-day CO and VOC emission rates from emission units P001, P002, P005, P006, P011 and P012 combined exceeded 2,983 tons and 80.4 tons respectively. The report shall also include the actual 365-day SO<sub>2</sub> emissions for each day the deviation occurs.

Quarterly deviation reports shall be submitted as required in the General Terms & Conditions of this permit.

**V. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

- a. **Emission Limitation:**

Total emissions from emissions units P005 and P006 combined shall not exceed 6.8 lbs/hr of particulate emissions.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in Section A.III.2 and the emission testing procedures specified in section A.V.3.

- b. **Emission Limitation:**

Total emissions from emissions units P005 and P006 combined shall not exceed 299.8 lb/hr of CO.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in Section A.III.2 and the emission testing procedures specified in section A.V.3.

c. **Emission Limitation:**

Total emissions from emissions units P005 and P006 combined shall not exceed 56.0 lbs/hr of NO<sub>x</sub>.

**Modification Issued: 5/27/2004****Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in Section A.III.2 and the emission testing procedures specified in section A.V.3.

**d. Emission Limitation:**

Total emissions from emissions units P005 and P006 combined shall not exceed 290.4 lbs/hr of SO<sub>2</sub>.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in Section A.III.3 and the emission testing procedures specified in section A.V.3.

**e. Emission Limitation:**

Total emissions from emissions units P005 and P006 combined shall not exceed 19.5 lb/hr of VOC.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in Section A.III.3 and the emission testing procedures specified in section A.V.3.

**f. Emission Limitation:**

Visible particulate emissions shall not exceed twenty percent opacity, as a six-minute average except as provided by rule.

**Applicable Compliance Method:**

Compliance shall be demonstrated in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Method 9 and the methods and procedures specified in OAC rule 3745-17-03(B)(1).

**g. Emission Limitation:**

Total emissions from emissions units P005 and P006 combined shall not exceed 1,272 tpy of SO<sub>2</sub> per year based upon a rolling, 365-day summation.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in section A.III.3.

h. **Emission Limitation:**

Total emissions from emissions units P005 and P006 combined shall not exceed 29.8 tpy of particulate emissions based upon a rolling, 12-month summation.

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = \text{HER} * \text{AHO} * 0.0005 \text{ ton/lb}$$

where

$E(\text{tpy})$  = the ton per year emissions of PE from emission units P005 and P006 combined

HER is the hourly emission rate in pounds of particulate emissions from emission units P005 and P006 combined, as determined during the most recent performance test, and

AHO is the actual hours of operation during which emissions are being vented through the central stack.

i. **Emission Limitation:**

Total emissions from emissions units P005 and P006 combined shall not exceed 1313.7 tons/yr of CO based upon a rolling, 12-month summation.

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = \text{HER} * \text{AHO} * 0.0005 \text{ ton/lb}$$

where

$E(\text{tpy})$  = the ton per year emissions of CO from emission units P005 and P006 combined

HER is the hourly emission rate in pounds of CO from emission units P005 and P006 combined, as determined during the most recent performance test, and

AHO is the actual hours of operation during which emissions are being vented through the

central stack.

j. **Emission Limitation:**

Total emissions from emissions units P005 and P006 combined shall not exceed 219.0 tons/yr of NO<sub>x</sub> based upon a rolling, 12-month summation.

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = \text{HER} * \text{AHO} * 0.0005 \text{ ton/lb}$$

where

E(tpy) = the ton per year emissions of NO<sub>x</sub> from emission units P005 and P006 combined

HER is the hourly emission rate in pounds of NO<sub>x</sub> from emission units P005 and P006 combined, as determined during the most recent performance test, and

AHO is the actual hours of operation during which emissions are being vented through the central stack.

k. **Emission Limitation:**

Total emissions from emissions unit P005 and P006 combined shall not exceed 85.4 tons/yr of VOC based upon a rolling 12-month summation.

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = \text{HER} * \text{AHO} * 0.0005 \text{ ton/lb}$$

where

E(tpy) = the ton per year emissions of VOC from emission units P005 and P006 combined

HER is the hourly emission rate in pounds of VOC from emission units P005 and P006 combined, as determined during the most recent performance test, and

AHO is the actual hours of operation during which emissions are being vented through the central stack.

2. Compliance with the operational restrictions in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

a. **Operational Restriction:**

Maximum annual production of carbon black for emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed 223,000,000 pounds on a rolling 12-month summation.

**Applicable Compliance Method**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in Section A.III.8.

b. **Operational Restriction**

Annual emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following as a rolling 12-month summation:

4547.0 tons of SO<sub>2</sub>  
508.0 tons of NO<sub>x</sub>  
84.9 tons of PE

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the monitoring, recordkeeping and testing requirements specified in Sections A.III, A.IV, and A.V.

c. **Operational Restriction**

Annual emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following as a rolling 365-day summation:

151.0 tons of VOC  
2556.0 tons of CO

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the monitoring, recordkeeping and testing requirements specified in Sections A.III, A.IV, and A.V.

3. The permittee shall conduct, or have conducted, emission testing for emission units P005 and

P006 combined in accordance with the following requirements:

- a. The emission testing shall be conducted within 60 days after the issuance of this permit and while using a feedstock oil with 3% sulfur.
- b. The emission testing shall be conducted for emission units P005 and P006 to demonstrate compliance with the combined allowable mass emission rates for CO, VOC, particulates, SO<sub>2</sub>, and NO<sub>x</sub>.

- c. The following test methods shall be employed to demonstrate compliance with the allowable mass emission rates:

for particulates, Methods 1 through 5 of 40 CFR Part 60, Appendix A;  
for SO<sub>2</sub>, Methods 1 through 4 and Method 6 of 40 CFR Part 60, Appendix A;  
for VOC, Methods 1 through 4 and Method 25 of 40 CFR Part 60, Appendix A;  
for NO<sub>x</sub>, Methods 1 through 4 and Method 7 of 40 CFR Part 60, Appendix A; and  
for CO, Methods 1 through 4 and Method 10 of 40 CFR Part 60, Appendix A.

Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.

- d. The test(s) shall be conducted while emission units P005 and P006 and emission units P001 and P002 are all operating at or near their maximum capacities, unless otherwise specified or approved by the Ohio EPA Southeast District Office.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA Southeast District Office. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA Southeast District Office's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA Southeast District Office shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA Southeast District Office within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA Southeast District Office.

## VI. Miscellaneous Requirements

None

Degus:

PTI A<sub>1</sub>

Modification Issued: 5/27/2004

Emissions Unit ID: P006

**B. State Only Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P006 - Unit Number 2 Dryer	OAC rule 3745-31-05	None

**2. Additional Terms and Conditions**

2.a None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

**Modification Issued: 5/27/2004**

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
P011 - Carbon Black Unit Number 3 (Administrative modification to PTI#06-06770, issued August 21, 2003) to correct emission factors	OAC rule 3745-31-05(A)(3)	OAC rule 3745-31-05(C)
	OAC rule 3745-31-10 through 20	
		OAC rule 3745-17-07(A)

**Modif**

	Applicable Emissions <u>Limitations/Control Measures</u>	Emissions Unit ID: P011
OAC rule 3745-17-11(B)(1)		508.0 tons of NOx 84.9 tons of PE
OAC rule 3745-18-06(E)(2)	<p>The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07, OAC rule 3745-31-05(C), and 40 CFR 52.21.</p> <p>See A.I.2.a and A.I.2.b below</p> <p>Total emissions from emissions units P011 and P012 combined shall be limited to the following during normal operation from the thermal oxidizer:</p> <p>337.3 lbs/hr and 1,477.4 tons/yr of SO<sub>2</sub> on rolling 365-day basis</p> <p>37.0 lb/hr and 162.1 tons/yr of NO<sub>x</sub> based upon a rolling 12-month summation.</p> <p>10.0 lb/hr and 43.8 tons/yr of VOC based upon a rolling 12-month summation.</p> <p>10.0 lbs/hr and 43.8 tons/yr of CO based upon a rolling 12-month summation.</p> <p>9.17 lbs/hr and 36.3 tons/yr of PM/PM<sub>10</sub> based upon a rolling 12-month summation.</p> <p>See Section A.I.2.c</p> <p>Total emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following based upon a rolling, 12-month summation</p> <p>4547.0 tons of SO<sub>2</sub></p>	<p>Total emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following based upon a rolling, 365-day summation:</p> <p>151.0 tons of VOC 2556.0 tons of CO</p> <p>Visible particulate emissions shall not exceed twenty percent opacity, as a six-minute average except as provided by rule.</p> <p>The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).</p> <p>The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).</p>

**Modification Issued: 5/27/2004****2. Additional Terms and Conditions**

**2.a** This emissions unit shall be limited to the following emissions during start-up and shutdown (vent emissions):

2.0 lbs/hr and 0.1 tons/yr of SO<sub>2</sub>  
110 lbs/hr and 4.6 tons/yr of VOC  
4,112 lbs/hr and 172 tons/yr of CO  
2.4 lbs/hr and 0.1 tons/yr of NO<sub>x</sub>  
2.3 lbs/hr and 0.1 tons/yr of PM/PM<sub>10</sub>  
44.5 lbs/hr and 1.9 tons/yr of H<sub>2</sub>S  
8.7 lbs/hr and 0.4 tons/yr of COS  
20.1 lbs/hr and 0.9 tons/yr of CS<sub>2</sub>  
10.7 lbs/hr and 0.5 tons/yr of HCN

**2.b** Maximum annual production of carbon black for emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed 223,000,000 pounds on a rolling 12-month summation. This emissions unit is currently permitted and operating, and, as such, has existing records of production and emissions, therefore eliminating the need to establish the first year's cumulative rolling 12-month summation carbon black production. The existing, previous 12-month record of the 223,000,000 lb/yr of carbon black shall be maintained as the rolling monthly record, upon the issuance of this permit.

**2.c** The permittee shall employ good combustion practices to minimize emissions to the extent possible.

**II. Operational Restrictions**

1. This emissions unit shall
  - a. utilize feedstock oil which contains no more than 3% sulfur;
  - b. be equipped with a product exhaust bag filter with a design efficiency not less than 99.7%; and
  - c. employ a thermal incinerator with a destruction efficiency of 95% for particulate emissions and 98% for VOC and CO.
2. This emissions unit shall be limited to 84 hours per year for all start-up and shutdown operations.

**Modification Issued: 5/27/2004**

3. The average combustion temperature within the thermal incinerator, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
4. If the mass flow rate meter employed to continuously monitor the feedstock oil feed rate is not in operation, the production of carbon black shall be automatically terminated.

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall perform daily checks, while the equipment is in operation and when the weather conditions allow, for any visible particulate emissions from the stack of this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log.
  - a. the location and color of the emissions;
  - b. whether the emissions are representative of normal operations;
  - c. if the emissions are not representative of normal operations, the cause of the visible emissions;
  - d. the total duration of any visible emission incident; and
  - e. any corrective actions taken to eliminate the visible emissions.
2. The permittee shall keep daily records for all start-up and shutdown periods that contain the following information:
  - a. the date of each start-up and/or shutdown;
  - b. the time period during which each start-up or shutdown occurred;
  - c. the year-to-date, total hours of all start-up and shutdown periods.; and
  - d. At the end of each year, the permittee shall add and maintain a record of the total hours and total emissions from start-up/shutdown events, from the records maintained as required above.
3. The permittee shall maintain records of the feedstock oil for this emissions unit in accordance with

either Alternative 1 or Alternative 2 described below.

a. Alternative 1:

For each shipment of feedstock oil received for this emissions unit, the permittee shall collect or require the oil supplier to collect a representative grab sample of the feedstock oil and maintain records of the total quantity of feedstock oil received, and the permittee's or oil supplier's analyses for sulfur content and density.

b. Alternative 2:

The permittee shall collect a representative grab sample of the feedstock oil for this emissions unit for each day when the emissions unit is in operation. If additional feedstock oil is added to the tank serving this emissions unit on a day when the emissions unit is in operation, the permittee shall collect a sufficient number of grab samples to create a composite sample that is representative of the average quality of feedstock oil used in this emissions unit. The permittee shall maintain records of the total quantity of feedstock oil used each day, and the permittee's analyses for sulfur content and density.

4. The permittee shall measure the sulfur content (in weight %) of the feedstock oil in accordance with the procedures specified in ASTM standard D4294, "Standard Test Method for Sulfur in Petroleum and Petroleum Products by Energy-Dispersive X-ray Fluorescence Spectrometry". In addition, the permittee shall measure the density (in pounds per gallon) of the feedstock oil in accordance with the procedures specified in ASTM standard D287, "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)".
5. For each day of operation of this emissions unit, the permittee shall collect a sufficient number of grab samples of carbon black product to create a composite sample that is representative of the average quality of the carbon black produced in this emissions unit. The permittee shall measure and maintain a record of the sulfur content (in weight %) of each composite sample of carbon black product in accordance with the procedures specified in ASTM standard D1619, "Standard Test Method for Carbon Black- Sulfur Content".
6. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal incinerator when this emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day:

- a. all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when this emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that

Emissions Unit ID: P011

demonstrated the emissions unit was in compliance; and

- b. a log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
7. The permittee shall properly operate and maintain a Micro Motion mass flow rate meter, model number D100, or equivalent monitor, to continuously monitor the feedstock oil feed rate when the emissions unit is in operation and producing carbon black. The monitoring device and any recorder shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manuals.

The permittee shall record the following information each day:

- a. all periods during which the Micro Motion mass flow rate meter, model number D100, or equivalent monitor, was not in operation while the emissions unit is in operation;
- b. all downtimes for the monitoring equipment and the associated emissions unit; and
- c. the corrective actions taken to reestablish correct operation of the mass flow rate meter.

**Modification Issued: 5/27/2004**

8. The permittee shall maintain monthly records of the following information:
  - a. the carbon black production rate\*, in pounds per month, for this emissions unit;
  - b. the production rate for emission units P001, P002, P005, P006, P011 and P012 (tons carbon black/month);
  - c. the rolling, 12-month summation of the production rates for emissions units P001, P002, P005, P006, P011, and P012, combined (tons carbon black/rolling 12-months); and
  - d. the total hours of operation of this emissions unit.

\* a permanent, rather than monthly record may be maintained for 8.a above
9. The permittee shall maintain daily records of the following information for this emissions unit:
  - a. the OEPA identification number of this emissions unit;
  - b. the current day, month, and year;
  - c. the grade of each feedstock oil processed (% sulfur);
  - d. the yield of each feedstock oil, (defined as the average amount of carbon black produced in pounds, per gallon of feedstock oil used during the day (lbs carbon black/gal);
  - e. the sulfur content of each feedstock oil, in weight percent;
  - f. the sulfur content of the carbon black product, in weight percent;
  - g. the feedstock oil feed rate, in gallons per hour for each hour of operation, continuously monitored using a Micro Motion mass flow rate meter, model number D100 or an equivalent monitor;
  - h. the carbon black production rate, in pounds per hour for each hour of operation, determined by multiplying the feedstock oil feed rate (gal/hr) by the yield of the feedstock oil (lbs/gal);
  - i. the average hourly sulfur dioxide emission rate for each feedstock oil, in pounds per hour, calculated as specified in Section A.III.10;

**Modification Issued: 5/27/2004**

- j. the total hours of operation for each feedstock oil;
  - k. the daily sulfur dioxide emission rate for all feedstock oils, in pounds (i.e., the summation of (i) x (j) for all of the feedstock oils);
  - l. the rolling, 365-day SO<sub>2</sub> emission rate for all feedstock oils, in tons;
  - m. the average hourly CO and VOC emission rate for each feedstock oil used in P001, P002, P005, P006, P011 and P012, in pounds per hour, calculated as specified in Section A.V.1.b & d; and
  - n. the rolling, 365-day CO and VOC emission rate for P001, P002, P005, P006, P011 and P012, in tons.
10. The average hourly sulfur dioxide emission rate for each feedstock oil shall be calculated each day using the following equations:

$$E = [(SFS) - (SCB)] \times (64/32)$$

where:

E = sulfur dioxide emission rate, in pounds per hour;  
 SFS = feedstock oil sulfur weight rate, in pounds per hour;  
 SCB = carbon black sulfur weight rate, in pounds per hour; and  
 64/32 = constant to convert molecular weight rate of sulfur to molecular weight of sulfur dioxide.

NOTE: The permittee conservatively assumes all of the sulfur emissions are emitted as sulfur dioxide emissions.

The feedstock oil sulfur weight rate utilized in the equation above is computed in the following manner:

$$SFS = FSR \times SFSP$$

where:

SFS = feedstock oil sulfur weight rate, in pounds per hour;  
 FSR = maximum recorded feedstock oil feed rate, in pounds per hour (from A.III.7); and  
 SFSP = feedstock oil sulfur content, in weight percent (from A.III.4).

**Modif**

Emissions Unit ID: P011

The carbon black sulfur weight rate utilized in the equation above is computed in the following manner:

$$\text{SCB} = \text{CBPR} \times \text{SCBP}$$

where:

**Modification Issued: 5/27/2004**

SCB = carbon black sulfur weight rate, in pounds per hour;

CBPR = maximum recorded carbon black production rate, in pounds per hour (from A.III.8.a);  
and

SCBP = carbon black sulfur content, in weight percent (from A.III.5).

**IV. Reporting Requirements**

1. The permittee shall submit quarterly deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator does not comply with the temperature limitation specified above.
2. The permittee shall submit quarterly deviation (excursion) reports that identify all periods of time during which the Micro Motion mass flow rate meter, model number D100 or equivalent flow meter, was not functioning properly. The reports shall include the date, time, and duration of each such period, and the corrective action(s) to ensure correct operation.
3. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month production rate limitation of 223,000,000 lb/yr carbon black, for emission units P001, P002, P005, P006, P011 and P012.
4. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the sulfur content limitation. The reports shall include the date, time, and duration of each such period when the sulfur content of the oil used in this emissions unit is greater than 3.0 percent, and the corrective action to bring the sulfur content below 3.0 percent.
5. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the average hourly SO<sub>2</sub> emission rate from emissions units P011 and P012, combined exceeded 337.3 lbs/hr, and the actual average hourly SO<sub>2</sub> emissions for each such day.
6. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the SO<sub>2</sub> emission rate from emission units P011 and P012 combined exceeded 1,477.4 tons, and the actual SO<sub>2</sub> emissions for each such day.
7. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be submitted to the Director (Ohio EPA Southeast District Office) by January 31 and July 31 of each year and shall cover the previous 6-month period.

**Modification Issued: 5/27/2004**

8. The permittee shall submit annual reports that include the following information:
  - a. the total hours of start-up and shutdown operations for this emissions unit for the previous calendar year, and the emissions calculated from start-up and shutdown events, calculated and recorded as required in Section A.III.2;
  - b. the total hours of operation of this emissions unit;
  - c. the total production from emissions units P001, P002, P005, P006, P011, and P012; and
  - d. the total SO<sub>2</sub> emissions (including all calculations), in tons, from emission units P001, P002, P005, P006, P011 and P012 for the previous calendar year.

These reports shall be submitted to the Director (Ohio EPA Southeast District Office) by January 31 of each year.

9. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the rolling, 12-month emission rates for emissions units P001, P002, P005, P006, P011, and P012, combined, exceeded the rolling 12-month ton per year limits listed in A.I.1.
10. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the rolling 365-day CO and VOC emission rates from emission units P001, P002, P005, P006, P011 and P012 combined exceeded 2,983 tons and 80.4 tons respectively. The report shall also include the actual SO<sub>2</sub> emissions for each day the deviation occurs.

**V. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
  - a. **Emission Limitation**

Emissions units P011 and P012 combined shall be limited to 9.17 lb/hr of PM/PM<sub>10</sub> during normal operation from the thermal oxidizer:

**Applicable Compliance Method:**

Compliance shall be demonstrated by testing as specified in Section A.V.3 based upon the procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 5 as set forth in "Appendix of Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New

Emissions Unit ID: P011

Stationary Sources"), as such Appendix existed on July 1, 1996.

b. **Emission Limitation:**

Emissions units P011 and P012 combined shall be limited to 10.0 lb/hr of VOC during normal operation from the thermal oxidizer:

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following:

$$E = (VEF * GOB) * (1 - 0.98)$$

Where

E = VOC emission rate from emission units P011 and P012 combined, in pounds per hour.

VEF is the VOC emission factor per 1,000 gallons of oil burned, 200 lbs VOC/1,000 gal oil burned, submitted by the permittee and based upon their best engineering judgement and knowledge of the process.

GOB is the total gallons of oil burned per hour from emission units P011 and P012 combined.

(1 - 0.98) 98% is the required minimum destruction efficiency of the thermal incinerator for VOCs, which may be adjusted for emission records and reporting, if testing demonstrates a more accurate control efficiency.

If required, compliance shall be demonstrated based upon the procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 5 and Method 25 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996.

c. **Emission Limitation:**

Emissions units P011 and P012 combined shall be limited to 37.0 lb/hr of NO<sub>x</sub> during normal operation from the thermal oxidizer:

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E = NEF * PPPH$$

where

E = NO<sub>x</sub> emission rate from emission units P011 and P012 combined, in pounds per hour.

NEF is the NO<sub>x</sub> emission factor per 1,000 gallons of oil burned, 2.14 lbs NO<sub>x</sub>/1,000 lbs product, submitted by the permittee based upon their best engineering judgement and knowledge of the process.

PPPH is the pounds of product produced per hour from emission units P011 and P012 combined.

d. **Emission Limitation:**

Emissions units P011 and P012 combined shall be limited to 10.0 lb/hr of CO during normal operation from the thermal oxidizer:

**Applicable Compliance Method:**

Compliance shall be demonstrated by testing as specified in Section A.V.3 based upon the procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 5 and Method 10 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996.

e. **Emission Limitation:**

Emissions units P011 and P012 combined shall be limited to 337.3 lb/hr of SO<sub>2</sub> during normal operation from the thermal oxidizer:

**Applicable Compliance Method:**

Compliance shall be demonstrated by testing as specified in Section A.V.3 based upon the monitoring and recordkeeping requirements specified in sections A.III.3, A.III.4, A.III.5 and A.III.9; the emission calculation as specified in Section A.III.10; reporting requirement as specified in Section A.IV.5; and testing required in Section A.V.4 below.

f. **Emission Limitation:**

Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.

**Applicable Compliance Method:**

If required, compliance shall be demonstrated in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Method 9 and the methods and procedures specified in OAC rule 3745-17-03(B)(1).

g. **Emission Limitation:**

Emissions units P011 and P012 combined shall be limited to 1,477.4 tpy based upon a rolling, 365-day summation of SO<sub>2</sub> during normal operations.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the sum of the daily SO<sub>2</sub> emissions on the last day of each year, maintained and recorded as required in Section A.III.9.1, and divided by 2000 lbs/ton. Any exceedance shall be reported as required in Section A.IV.6.

h. **Emission Limitation:**

Emissions units P011 and P012 combined shall be limited to 43.8 tons of CO per year based upon a rolling, 12-month summation during normal operation from the thermal oxidizer:

**Applicable Compliance Method:**

Compliance with the annual limit shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E(\text{tpy}) = \text{AHEF} * \text{actual hours of normal operations} * 0.0005 \text{ ton/lb}$$

where

$E(\text{tpy})$  = the ton per year emissions of CO from emission units P011 and P012 combined.

AHEF is the hourly emission factor for emission units P011 and P012 combined, as determined in A.V.1.d, the value of E (lbs CO/hr); until testing is completed as required in Section A.V.4, an emission rate of "4.13 lbs CO/hr" shall be used.

i. **Emission Limitation:**

Emissions units P011 and P012 combined shall be limited to 162.1 tons/yr of NO<sub>x</sub> based upon a rolling, 12-month summation during normal operation from the thermal oxidizer:

**Applicable Compliance Method:**

Compliance with the annual limit shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E(\text{tpy}) = \text{AHEF} * \text{actual hours of normal operations} * 0.0005 \text{ ton/lb}$$

where

$E(\text{tpy})$  = the ton per year emissions of NO<sub>x</sub> from emission units P011 and P012 combined.

**Modification Issued: 5/27/2004**

AHEF is the hourly emission factor for emission units P011 and P012 combined, as determined in A.V.1.e, the value of E (lbs NO<sub>x</sub>/hr); until testing is completed as required in Section A.V.4, an emission rate of "0.5 lbs NO<sub>x</sub>/hr" shall be used.

j. **Emission Limitation:**

Emissions units P011 and P012 combined shall be limited to 36.3 tpy of particulate emissions based upon a rolling, 12-month summation during normal operations.

**Applicable Compliance Method:**

Compliance with the annual limit shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E(\text{tpy}) = \text{AHEF} * \text{actual hours of normal operations} * 0.0005 \text{ ton/lb}$$

where

E(tpy) = the ton per year emissions of PE from emission units P011 and P012 combined.

AHEF is the hourly emission factor for emission units P011 and P012 combined, as determined in A.V.1.e, the value of E (lbs PE<sub>10</sub>/hr); until testing is completed as required in Section A.V.4, an emission rate of "9.17 lbs PE/hr" shall be used.

k. **Emission Limitation:**

This emissions unit Emissions units P011 and P012 combined shall be limited to 43.8 tons of VOC per year based upon a rolling, 12-month summation during normal operation from the thermal oxidizer:

**Applicable Compliance Method:**

Compliance with the annual limit shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E(\text{tpy}) = \text{AHEF} * \text{actual hours of normal operations} * 0.0005 \text{ ton/lb}$$

where

**Modification Issued: 5/27/2004**

E(tpy) = the ton per year emissions of VOC from emission units P011 and P012 combined.

AHEF is the hourly emission factor for emission units P011 and P012 combined, as determined in A.V.1.b, the value of E (lbs VOC/hr).

2. Compliance with the operational restrictions in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

a. **Operational Restriction:**

Maximum annual production of carbon black for emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed 223,000,000 pounds on a rolling 12-month summation.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in section A.III.8.

b. **Operational Restriction:**

3.0% sulfur content in the feedstock oil

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in sections A.III.3 and A.III.4.

c. **Operational Restriction:**

84 hrs/yr of start-up and shutdown operations

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in section A.III.2.

d. **Operational Restriction:**

Emissions Unit ID: P011

Annual emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following as a rolling 12-month average:

4547.0 tons of SO<sub>2</sub>

508.0 tons of NO<sub>x</sub>

84.9 tons of PE

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the monitoring, recordkeeping and testing requirements specified in Sections A.III, A.IV, and A.V.

e. **Operational Restriction:**

Annual emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following as a rolling 365-day average:

151.0 tons of VOC

2556.0 tons of CO

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the monitoring, recordkeeping and testing requirements specified in Sections A.III, A.IV, and A.V.

3. The hourly limitations for start-up and shutdown operations in section A.I.2.a are the uncontrolled emission rates determined by the known chemical reaction of the process and represent the potentials to emit for this emissions unit; therefore, compliance with the hourly emission limitations is assumed. Compliance with the annual start-up and shutdown emission limitation(s) in Section A.I.2.a. of these terms and conditions shall be determined in accordance with the following method(s):

a. **Emission Limitation:**

0.1 tpy of SO<sub>2</sub> during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 2.0 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

b. **Emission Limitation:**

4.6 tpy of VOC during start-up/shutdown

106

Degus:

PTI A<sub>1</sub>

**Modification Issued: 5/27/2004**

Emissions Unit ID: P011

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 110 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

c. **Emission Limitation:**

172 tpy of CO during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 4,112 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

d. **Emission Limitation:**

0.1 tpy of NO<sub>x</sub> during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 2.4 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

e. **Emission Limitation:**

0.1 tpy of particulate emissions during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 2.3 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

f. **Emission Limitation:**

1.9 tpy of H<sub>2</sub>S during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 44.5 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

g. **Emission Limitation:**

0.4 tpy of COS during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 8.7 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

**h. Emission Limitation:**

0.9 tpy of CS<sub>2</sub> during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 20.1 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

**i. Emission Limitation:**

0.5 tpy of HCN during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 10.7 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

4. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
- a. The emission testing shall be conducted within 3 months after issuance of the original permit.
  - b. The emission testing shall be conducted to demonstrate compliance with the allowable mass emission rates for particulates, SO<sub>2</sub>, and CO.
  - c. The following test methods shall be employed to demonstrate compliance with the allowable mass emission rates:  
  
for particulates, Methods 1 through 5 of 40 CFR Part 60, Appendix A;  
for SO<sub>2</sub>, Methods 1 through 4 and Method 6 of 40 CFR Part 60, Appendix A; and

**Modif**

Emissions Unit ID: P011

for CO, Methods 1 through 4 and Method 10 of 40 CFR Part 60, Appendix A.

Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.

- d. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency.

**Modification Issued: 5/27/2004**

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

**VI. Miscellaneous Requirements**

1. For purposes of this permit to install, normal operations is any time except during startup or shutdown of the emissions unit.

**B. State Only Enforceable Section****I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P011 - Carbon Black Unit Number 3	OAC rule 3745-31-05	None

**2. Additional Terms and Conditions**

- 2.a None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None

**Part III - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**

**A. State and Federally Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	
P012 - Carbon Black Unit Number 4(Administrative modification to PTI#06-06770, issued August 21, 2003) to correct emission factors	OAC rule 3745-31-05(A)(3)	OAC rule 3745-31-05(C)
	OAC rule 3745-31-10 through 20	
		OAC rule 3745-17-07(A)

Emissions Unit ID: P012

<p>OAC rule 3745-17-11(B)(1)</p>	<p style="text-align: center;">Applicable Emissions <u>Limitations/Control Measures</u></p>	<p>508.0 tons of NOx 84.9 tons of PE</p>
<p>OAC rule 3745-18-06(E)(2)</p>	<p>The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07, OAC rule 3745-31-05(C), and 40 CFR 52.21.</p>	<p>Total emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following based upon a rolling, 365-day summation:</p>
	<p>See A.I.2.a and A.I.2.b below</p>	<p>151.0 tons of VOC 2556.0 tons of CO</p>
	<p>Total emissions from emissions units P011 and P012 combined shall be limited to the following during normal operation from the thermal oxidizer:</p>	<p>Visible particulate emissions shall not exceed twenty percent opacity, as a six-minute average except as provided by rule.</p>
	<p>337.3 lbs/hr and 1,477.4 tons/yr of SO<sub>2</sub> on rolling 365-day basis</p>	<p>The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).</p>
	<p>37.0 lb/hr and 162.1 tons/yr of NO<sub>x</sub> based upon a rolling 12-month summation.</p>	<p>The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).</p>
	<p>10.0 lb/hr and 43.8 tons/yr of VOC based upon a rolling 12-month summation.</p>	
	<p>10.0 lbs/hr and 43.8 tons/yr of CO based upon a rolling 12-month summation.</p>	
	<p>9.17 lbs/hr and 36.3 tons/yr of PM/PM<sub>10</sub> based upon a rolling 12-month summation.</p>	
	<p>See Section A.I.2.c</p>	
	<p>Total emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following based upon a rolling, 12-month summation</p>	
	<p>4547.0 tons of SO<sub>2</sub></p>	

**2. Additional Terms and Conditions**

**2.a** This emissions unit shall be limited to the following emissions during start-up and shutdown (vent emissions):

- 2.0 lbs/hr and 0.1 tons/yr of SO<sub>2</sub>
- 110 lbs/hr and 4.6 tons/yr of VOC
- 4,112 lbs/hr and 172 tons/yr of CO
- 2.4 lbs/hr and 0.1 tons/yr of NO<sub>x</sub>

**Modification Issued: 5/27/2004**

2.3 lbs/hr and 0.1 tons/yr of PM/PM<sub>10</sub>

44.5 lbs/hr and 1.9 tons/yr of H<sub>2</sub>S

8.7 lbs/hr and 0.4 tons/yr of COS

20.1 lbs/hr and 0.9 tons/yr of CS<sub>2</sub>

10.7 lbs/hr and 0.5 tons/yr of HCN

- 2.b** Maximum annual production of carbon black for emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed 223,000,000 pounds on a rolling 12-month summation. This emissions unit is currently permitted and operating, and, as such, has existing records of production and emissions, therefore eliminating the need to establish the first year's cumulative rolling 12-month summation carbon black production. The existing, previous 12-month record of the 223,000,000 lb/yr of carbon black shall be maintained as the rolling monthly record, upon the issuance of this permit.
- 2.c** The permittee shall employ good combustion practices to minimize emissions to the extent possible.

**II. Operational Restrictions**

1. This emissions unit shall
  - a. utilize feedstock oil which contains no more than 3% sulfur;
  - b. be equipped with a product exhaust bag filter with a design efficiency not less than 99.7%; and
  - c. employ a thermal incinerator with a destruction efficiency of 95% for particulate emissions and 98% for VOC and CO.
2. This emissions unit shall be limited to 84 hours per year for all start-up and shutdown operations.
3. The average combustion temperature within the thermal incinerator, for any 3-hour block of time when the emissions unit is in operation, shall not be more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance.
4. If the mass flow rate meter employed to continuously monitor the feedstock oil feed rate is not in operation, the production of carbon black shall be automatically terminated.

**III. Monitoring and/or Recordkeeping Requirements**

1. The permittee shall perform daily checks, while the equipment is in operation and when the weather conditions allow, for any visible particulate emissions from the stack of this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log.
  - a. the location and color of the emissions;
  - b. whether the emissions are representative of normal operations;
  - c. if the emissions are not representative of normal operations, the cause of the visible emissions;
  - d. the total duration of any visible emission incident; and
  - e. any corrective actions taken to eliminate the visible emissions.
2. The permittee shall keep daily records for all start-up and shutdown periods that contain the following information:
  - a. the date of each start-up and/or shutdown;
  - b. the time period during which each start-up or shutdown occurred;
  - c. the year-to-date, total hours of all start-up and shutdown periods.; and
  - d. At the end of each year, the permittee shall add and maintain a record of the total hours and total emissions from start-up/shutdown events, from the records maintained as required above.
3. The permittee shall maintain records of the feedstock oil for this emissions unit in accordance with either Alternative 1 or Alternative 2 described below.
  - a. Alternative 1:

For each shipment of feedstock oil received for this emissions unit, the permittee shall collect or require the oil supplier to collect a representative grab sample of the feedstock oil and maintain records of the total quantity of feedstock oil received, and the permittee's or oil supplier's analyses for sulfur content and density.

- b. Alternative 2:

The permittee shall collect a representative grab sample of the feedstock oil for this emissions unit for each day when the emissions unit is in operation. If additional feedstock oil is added to the tank serving this emissions unit on a day when the emissions unit is in operation, the permittee

Emissions Unit ID: P012

shall collect a sufficient number of grab samples to create a composite sample that is representative of the average quality of feedstock oil used in this emissions unit. The permittee shall maintain records of the total quantity of feedstock oil used each day, and the permittee's analyses for sulfur content and density.

4. The permittee shall measure the sulfur content (in weight %) of the feedstock oil in accordance with the procedures specified in ASTM standard D4294, "Standard Test Method for Sulfur in Petroleum and Petroleum Products by Energy-Dispersive X-ray Fluorescence Spectrometry". In addition, the permittee shall measure the density (in pounds per gallon) of the feedstock oil in accordance with the procedures specified in ASTM standard D287, "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)".
5. For each day of operation of this emissions unit, the permittee shall collect a sufficient number of grab samples of carbon black product to create a composite sample that is representative of the average quality of the carbon black produced in this emissions unit. The permittee shall measure and maintain a record of the sulfur content (in weight %) of each composite sample of carbon black product in accordance with the procedures specified in ASTM standard D1619, "Standard Test Method for Carbon Black- Sulfur Content".
6. The permittee shall operate and maintain a continuous temperature monitor and recorder which measures and records the combustion temperature within the thermal incinerator when this emissions unit is in operation. Units shall be in degrees Fahrenheit. The monitoring and recording devices shall be capable of accurately measuring the desired parameter. The temperature monitor and recorder shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, with any modifications deemed necessary by the permittee.

The permittee shall collect and record the following information for each day:

- a. all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator, when this emissions unit was in operation, was more than 50 degrees Fahrenheit below the average temperature during the most recent emission test that demonstrated the emissions unit was in compliance; and
  - b. a log of the downtime for the capture (collection) system, control device, and monitoring equipment, when the associated emissions unit was in operation.
7. The permittee shall properly operate and maintain a Micro Motion mass flow rate meter, model number D100, or equivalent monitor, to continuously monitor the feedstock oil feed rate when the emissions unit is in operation and producing carbon black. The monitoring device and any recorder shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manuals.

The permittee shall record the following information each day:

- a. all periods during which the Micro Motion mass flow rate meter, model number D100, or

Emissions Unit ID: P012

- equivalent monitor, was not in operation while the emissions unit is in operation;
- b. all downtimes for the monitoring equipment and the associated emissions unit; and
  - c. the corrective actions taken to reestablish correct operation of the mass flow rate meter.
8. The permittee shall maintain monthly records of the following information:
- a. the carbon black production rate\*, in pounds per month, for this emissions unit;
  - b. the production rate for emission units P001, P002, P005, P006, P011 and P012 (tons carbon black/month);
  - c. the rolling, 12-month summation of the production rates for emissions units P001, P002, P005, P006, P011, and P012, combined (tons carbon black/rolling 12-months); and
  - d. the total hours of operation of this emissions unit.
- \* a permanent, rather than monthly record may be maintained for 8.a above
9. The permittee shall maintain daily records of the following information for this emissions unit:
- a. the OEPA identification number of this emissions unit;
  - b. the current day, month, and year;
  - c. the grade of each feedstock oil processed (% sulfur);
  - d. the yield of each feedstock oil, (defined as the average amount of carbon black produced in pounds, per gallon of feedstock oil used during the day (lbs carbon black/gal);
  - e. the sulfur content of each feedstock oil, in weight percent;
  - f. the sulfur content of the carbon black product, in weight percent;
  - g. the feedstock oil feed rate, in gallons per hour for each hour of operation, continuously monitored using a Micro Motion mass flow rate meter, model number D100 or an equivalent monitor;
  - h. the carbon black production rate, in pounds per hour for each hour of operation, determined by multiplying the feedstock oil feed rate (gal/hr) by the yield of the feedstock oil (lbs/gal);
  - i. the average hourly sulfur dioxide emission rate for each feedstock oil, in pounds per hour, calculated as specified in Section A.III.10;

**Modification Issued: 5/27/2004**

- j. the total hours of operation for each feedstock oil;
  - k. the daily sulfur dioxide emission rate for all feedstock oils, in pounds (i.e., the summation of (i) x (j) for all of the feedstock oils);
  - l. the rolling, 365-day SO<sub>2</sub> emission rate for all feedstock oils, in tons;
  - m. the average hourly CO and VOC emission rate for each feedstock oil used in P001, P002, P005, P006, P011 and P012, in pounds per hour, calculated as specified in Section A.V.1.b & d; and
  - n. the rolling, 365-day CO and VOC emission rate for P001, P002, P005, P006, P011 and P012, in tons.
10. The average hourly sulfur dioxide emission rate for each feedstock oil shall be calculated each day using the following equations:

$$E = [(SFS) - (SCB)] \times (64/32)$$

where:

E = sulfur dioxide emission rate, in pounds per hour;  
 SFS = feedstock oil sulfur weight rate, in pounds per hour;  
 SCB = carbon black sulfur weight rate, in pounds per hour; and  
 64/32 = constant to convert molecular weight rate of sulfur to molecular weight of sulfur dioxide.

NOTE: The permittee conservatively assumes all of the sulfur emissions are emitted as sulfur dioxide emissions.

The feedstock oil sulfur weight rate utilized in the equation above is computed in the following manner:

$$SFS = FSR \times SFSP$$

where:

SFS = feedstock oil sulfur weight rate, in pounds per hour;  
 FSR = maximum recorded feedstock oil feed rate, in pounds per hour (from A.III.7); and  
 SFSP = feedstock oil sulfur content, in weight percent (from A.III.4).

The carbon black sulfur weight rate utilized in the equation above is computed in the following manner:

$$SCB = CBPR \times SCBP$$

where:

SCB = carbon black sulfur weight rate, in pounds per hour;

CBPR = maximum recorded carbon black production rate, in pounds per hour (from A.III.8.a);  
and

SCBP = carbon black sulfur content, in weight percent (from A.III.5).

#### IV. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports which identify all 3-hour blocks of time during which the average combustion temperature within the thermal incinerator does not comply with the temperature limitation specified above.
2. The permittee shall submit quarterly deviation (excursion) reports that identify all periods of time during which the Micro Motion mass flow rate meter, model number D100 or equivalent flow meter, was not functioning properly. The reports shall include the date, time, and duration of each such period, and the corrective action(s) to ensure correct operation.
3. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the rolling, 12-month production rate limitation of 223,000,000 lb/yr carbon black, for emission units P001, P002, P005, P006, P011 and P012.
4. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the sulfur content limitation. The reports shall include the date, time, and duration of each such period when the sulfur content of the oil used in this emissions unit is greater than 3.0 percent, and the corrective action to bring the sulfur content below 3.0 percent.
5. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the average hourly SO<sub>2</sub> emission rate from emissions units P011 and P012, combined exceeded 337.3 lbs/hr, and the actual average hourly SO<sub>2</sub> emissions for each such day.
6. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the SO<sub>2</sub> emission rate from emission units P011 and P012 combined exceeded 1,477.4 tons, and the actual SO<sub>2</sub> emissions for each such day.
7. The permittee shall submit semiannual written reports that (a) identify all days during which any visible particulate emissions were observed from this emissions unit and (b) describe any corrective actions taken to eliminate the visible particulate emissions. These reports shall be

**Modification Issued: 5/27/2004**

submitted to the Director (Ohio EPA Southeast District Office) by January 31 and July 31 of each year and shall cover the previous 6-month period.

8. The permittee shall submit annual reports that include the following information:
  - a. the total hours of start-up and shutdown operations for this emissions unit for the previous calendar year, and the emissions calculated from start-up and shutdown events, calculated and recorded as required in Section A.III.2;
  - b. the total hours of operation of this emissions unit;
  - c. the total production from emissions units P001, P002, P005, P006, P011, and P012; and
  - d. the total SO<sub>2</sub> emissions (including all calculations), in tons, from emission units P001, P002, P005, P006, P011 and P012 for the previous calendar year.

These reports shall be submitted to the Director (Ohio EPA Southeast District Office) by January 31 of each year.

9. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the rolling, 12-month emission rates for emissions units P001, P002, P005, P006, P011, and P012, combined, exceeded the rolling 12-month ton per year limits listed in A.I.1.
10. The permittee shall submit quarterly deviation (excursion) reports that identify each day during which the rolling 365-day CO and VOC emission rates from emission units P001, P002, P005, P006, P011 and P012 combined exceeded 2,983 tons and 80.4 tons respectively. The report shall also include the actual SO<sub>2</sub> emissions for each day the deviation occurs.

**V. Testing Requirements**

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):
  - a. **Emission Limitation**

Emissions units P011 and P012 combined shall be limited to 9.17 lb/hr of PM/PM<sub>10</sub> during normal operation from the thermal oxidizer:

**Applicable Compliance Method:**

Emissions Unit ID: P012

Compliance shall be demonstrated by testing as specified in Section A.V.3 based upon the procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 5 as set forth in "Appendix of Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996.

b. **Emission Limitation:**

Emissions units P011 and P012 combined shall be limited to 10.0 lb/hr of VOC during normal operation from the thermal oxidizer:

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following:

$$E = (VEF * GOB) * (1 - 0.98)$$

Where

E = VOC emission rate from emission units P011 and P012 combined, in pounds per hour.

VEF is the VOC emission factor per 1,000 gallons of oil burned, 200 lbs VOC/1,000 gal oil burned, submitted by the permittee and based upon their best engineering judgement and knowledge of the process.

GOB is the total gallons of oil burned per hour from emission units P011 and P012 combined.

(1 - 0.98) 98% is the required minimum destruction efficiency of the thermal incinerator for VOCs, which may be adjusted for emission records and reporting, if testing demonstrates a more accurate control efficiency.

If required, compliance shall be demonstrated based upon the procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 5 and Method 25 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996.

c. **Emission Limitation:**

Emissions units P011 and P012 combined shall be limited to 37.0 lb/hr of NO<sub>x</sub> during normal operation from the thermal oxidizer:

**Applicable Compliance Method:**

**Modification Issued: 5/27/2004**

Compliance shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E = NEF * PPPH$$

where

E = NO<sub>x</sub> emission rate from emission units P011 and P012 combined, in pounds per hour.

NEF is the NO<sub>x</sub> emission factor per 1,000 gallons of oil burned, 2.14 lbs NO<sub>x</sub>/1,000 lbs product, submitted by the permittee based upon their best engineering judgement and knowledge of the process.

PPPH is the pounds of product produced per hour from emission units P011 and P012 combined.

d. **Emission Limitation:**

Emissions units P011 and P012 combined shall be limited to 10.0 lb/hr of CO during normal operation from the thermal oxidizer:

**Applicable Compliance Method:**

Compliance shall be demonstrated by testing as specified in Section A.V.3 based upon the procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 5 and Method 10 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996.

e. **Emission Limitation:**

Emissions units P011 and P012 combined shall be limited to 337.3 lb/hr of SO<sub>2</sub> during normal operation from the thermal oxidizer:

**Applicable Compliance Method:**

Compliance shall be demonstrated by testing as specified in Section A.V.3 based upon the monitoring and recordkeeping requirements specified in sections A.III.3, A.III.4, A.III.5 and A.III.9; the emission calculation as specified in Section A.III.10; reporting requirement as specified in Section A.IV.5; and testing required in Section A.V.4 below.

f. **Emission Limitation:**

Visible particulate emissions shall not exceed 20% opacity as a 6-minute average, except as provided by rule.

**Applicable Compliance Method:**

If required, compliance shall be demonstrated in accordance with the requirements specified in 40 CFR Part 60, Appendix A, Method 9 and the methods and procedures specified in OAC rule 3745-17-03(B)(1).

g. **Emission Limitation:**

Emissions units P011 and P012 combined shall be limited to 1,477.4 tpy based upon a rolling, 365-day summation of SO<sub>2</sub> during normal operations.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the sum of the daily SO<sub>2</sub> emissions on the last day of each year, maintained and recorded as required in Section A.III.9.1, and divided by 2000 lbs/ton. Any exceedance shall be reported as required in Section A.IV.6.

h. **Emission Limitation:**

Emissions units P011 and P012 combined shall be limited to 43.8 tons of CO per year based upon a rolling, 12-month summation during normal operation from the thermal oxidizer:

**Applicable Compliance Method:**

Compliance with the annual limit shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E(\text{tpy}) = \text{AHEF} * \text{actual hours of normal operations} * 0.0005 \text{ ton/lb}$$

where

$E(\text{tpy})$  = the ton per year emissions of CO from emission units P011 and P012 combined.

AHEF is the hourly emission factor for emission units P011 and P012 combined, as determined in A.V.1.d, the value of E (lbs CO/hr); until testing is completed as required in Section A.V.4, an emission rate of "4.13 lbs CO/hr" shall be used.

i. **Emission Limitation:**

Emissions units P011 and P012 combined shall be limited to 162.1 tons/yr of NO<sub>x</sub> based upon a rolling, 12-month summation during normal operation from the thermal oxidizer:

**Applicable Compliance Method:**

Compliance with the annual limit shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E(\text{tpy}) = \text{AHEF} * \text{actual hours of normal operations} * 0.0005 \text{ ton/lb}$$

where

$E(\text{tpy})$  = the ton per year emissions of NO<sub>x</sub> from emission units P011 and P012 combined.

**Modification Issued: 5/27/2004**

AHEF is the hourly emission factor for emission units P011 and P012 combined, as determined in A.V.1.e, the value of E (lbs NO<sub>x</sub>/hr); until testing is completed as required in Section A.V.4, an emission rate of "0.5 lbs NO<sub>x</sub>/hr" shall be used.

j. **Emission Limitation:**

Emissions units P011 and P012 combined shall be limited to 36.3 tpy of particulate emissions based upon a rolling, 12-month summation during normal operations.

**Applicable Compliance Method:**

Compliance with the annual limit shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E(\text{tpy}) = \text{AHEF} * \text{actual hours of normal operations} * 0.0005 \text{ ton/lb}$$

where

E(tpy) = the ton per year emissions of PE from emission units P011 and P012 combined.

AHEF is the hourly emission factor for emission units P011 and P012 combined, as determined in A.V.1.e, the value of E (lbs PE<sub>10</sub>/hr); until testing is completed as required in Section A.V.4, an emission rate of "9.17 lbs PE/hr" shall be used.

k. **Emission Limitation:**

This emissions unit Emissions units P011 and P012 combined shall be limited to 43.8 tons of VOC per year based upon a rolling, 12-month summation during normal operation from the thermal oxidizer:

**Applicable Compliance Method:**

Compliance with the annual limit shall be demonstrated based upon the recordkeeping maintained in Section A.III.8 and performance of the following equation:

$$E(\text{tpy}) = \text{AHEF} * \text{actual hours of normal operations} * 0.0005 \text{ ton/lb}$$

where

**Modification Issued: 5/27/2004**

E(tpy) = the ton per year emissions of VOC from emission units P011 and P012 combined.

AHEF is the hourly emission factor for emission units P011 and P012 combined, as determined in A.V.1.b, the value of E (lbs VOC/hr).

2. Compliance with the operational restrictions in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

a. **Operational Restriction:**

Maximum annual production of carbon black for emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed 223,000,000 pounds on a rolling 12-month summation.

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in section A.III.8.

b. **Operational Restriction:**

3.0% sulfur content in the feedstock oil

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in sections A.III.3 and A.III.4.

c. **Operational Restriction:**

84 hrs/yr of start-up and shutdown operations

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the recordkeeping requirements specified in section A.III.2.

d. **Operational Restriction:**

Emissions Unit ID: P012

Annual emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following as a rolling 12-month average:

4547.0 tons of SO<sub>2</sub>

508.0 tons of NO<sub>x</sub>

84.9 tons of PE

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the monitoring, recordkeeping and testing requirements specified in Sections A.III, A.IV, and A.V.

e. **Operational Restriction:**

Annual emissions from emission units P001, P002, P005, P006, P011 and P012 combined shall not exceed the following as a rolling 365-day average:

151.0 tons of VOC

2556.0 tons of CO

**Applicable Compliance Method:**

Compliance shall be demonstrated based upon the monitoring, recordkeeping and testing requirements specified in Sections A.III, A.IV, and A.V.

3. The hourly limitations for start-up and shutdown operations in section A.I.2.a are the uncontrolled emission rates determined by the known chemical reaction of the process and represent the potentials to emit for this emissions unit; therefore, compliance with the hourly emission limitations is assumed. Compliance with the annual start-up and shutdown emission limitation(s) in Section A.I.2.a. of these terms and conditions shall be determined in accordance with the following method(s):

a. **Emission Limitation:**

0.1 tpy of SO<sub>2</sub> during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 2.0 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

b. **Emission Limitation:**

4.6 tpy of VOC during start-up/shutdown

129

Degus:

PTI A<sub>1</sub>

**Modification Issued: 5/27/2004**

Emissions Unit ID: P012

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 110 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

c. **Emission Limitation:**

172 tpy of CO during start-up/shutdown

**Modification Issued: 5/27/2004****Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 4,112 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

d. **Emission Limitation:**

0.1 tpy of NOX during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 2.4 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

e. **Emission Limitation:**

0.1 tpy of particulate emissions during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 2.3 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

f. **Emission Limitation:**1.9 tpy of H<sub>2</sub>S during start-up/shutdown**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 44.5 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

g. **Emission Limitation:**

0.4 tpy of COS during start-up/shutdown

**Modification Issued: 5/27/2004****Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 8.7 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

**h. Emission Limitation:**

0.9 tpy of CS<sub>2</sub> during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 20.1 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

**i. Emission Limitation:**

0.5 tpy of HCN during start-up/shutdown

**Applicable Compliance Method:**

Annual emissions shall be calculated using the following equation:

$$E(\text{tpy}) = 10.7 \text{ lbs/hr} * \text{actual hours of start-up/shutdown operation} * 0.0005 \text{ ton/lb}$$

4. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:
- a. The emission testing shall be conducted within 3 months after issuance of the original permit.
  - b. The emission testing shall be conducted to demonstrate compliance with the allowable mass emission rates for particulates, SO<sub>2</sub>, and CO.
  - c. The following test methods shall be employed to demonstrate compliance with the allowable mass emission rates:  
  
for particulates, Methods 1 through 5 of 40 CFR Part 60, Appendix A;  
for SO<sub>2</sub>, Methods 1 through 4 and Method 6 of 40 CFR Part 60, Appendix A; and

**Modif**

Emissions Unit ID: P012

for CO, Methods 1 through 4 and Method 10 of 40 CFR Part 60, Appendix A.

Alternative U.S. EPA approved test methods may be used with prior approval from the Ohio EPA.

- d. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency.

**Modification Issued: 5/27/2004**

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

**VI. Miscellaneous Requirements**

1. For purposes of this permit to install, normal operations is any time except during startup or shutdown of the emissions unit.

**Modification Issued: 5/27/2004**

**B. State Only Enforceable Section**

**I. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P012 - Carbon Black Unit Number 4	OAC rule 3745-31-05	None

**2. Additional Terms and Conditions**

- 2.a None

**II. Operational Restrictions**

None

**III. Monitoring and/or Recordkeeping Requirements**

None

**IV. Reporting Requirements**

None

**V. Testing Requirements**

None

**VI. Miscellaneous Requirements**

None