



State of Ohio Environmental Protection Agency

**RE: FINAL PERMIT TO INSTALL
CLARK COUNTY**

CERTIFIED MAIL

Street Address:

122 S. Front Street

Lazarus Gov. Center TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049

Application No: 08-04766

Fac ID: 0812100207

DATE: 9/26/2006

Cascade Corp
Larry Brunke
2501 Sheridan Ave
Springfield, OH 45505-2519

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action of the Director is final and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of \$70.00 which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, OH 43215

Sincerely,

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: USEPA

RAPCA



**Permit To Install
Terms and Conditions**

**Issue Date: 9/26/2006
Effective Date: 9/26/2006**

FINAL PERMIT TO INSTALL 08-04766

Application Number: 08-04766
Facility ID: 0812100207
Permit Fee: **\$400**
Name of Facility: Cascade Corp
Person to Contact: Larry Brunke
Address: 2501 Sheridan Ave
Springfield, OH 45505-2519

Location of proposed air contaminant source(s) [emissions unit(s)]:
**2501 Sheridan Ave
Springfield, Ohio**

Description of proposed emissions unit(s):
Chapter 31 modification replacing PTI 08-04397 issued 1/27/04 for K003 and K007 only to increase clean up material use rates.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Cascade Corp
PTI Application: 08-04766
Issued: 9/26/2006

Facility ID: 0812100207

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon

Cascade Corp
PTI Application: 08-04766
Issued: 9/26/2006

Facility ID: 0812100207

the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

Cascade Corp
PTI Application: 08-04766
Issued: 9/26/2006

Facility ID: 0812100207

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

Cascade Corp
 PTI Application: 08-04766
 Issued: 9/26/2006

Facility ID: 0812100207

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
 TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
Organic Compounds	46.9
Combine HAP	24.9
Individual HAP	9.9

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (K003) - Large Clamp Paint Booth, Manual Spray Booth with infrared drying oven

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	The volatile organic compound (VOC) emissions from this emissions unit shall not exceed 50.2 lbs/day excluding clean up. The organic compound (OC) emissions including clean up shall not exceed 11.2 tons per year (TPY)
OAC rule 3745-35-07(B) (Synthetic minor to avoid Title V and MACT)	The OC emissions from emissions units K002, K003, K005, K006, and K007 shall not exceed 46.9 TPY based upon a rolling, 12-month summation. The individual hazardous air pollutant (HAP) emissions from emissions units K002, K003, K005, K006, and K007 shall not exceed 9.9 TPY and combined HAP emissions shall not exceed 24.9 TPY based upon a rolling, 12-month summation.
OAC rule 3745-21-09(U)(1)(c)	The VOC content of the coatings applied in this emissions unit shall not exceed 3.5 lbs VOC/gallon excluding water and exempt solvents.

2. Additional Terms and Conditions

2.a None

B. Operational Restrictions

1. The maximum coating and clean up material use excluding liquid wastes recovered for off-site disposal, in emissions units K002, K003, K005, K006, and K007 combined shall not shall not exceed 46.9 TPY of OC, 9.9 TPY of any individual HAP and 24.9 TPY for any combination of HAPs, based on a 12-month rolling summation. The permittee has existing coating and clean up material usage records and therefore does not need to be

Issued: 9/26/2006

limited in the first year on a monthly basis.

2. Solvent based coatings usage in this emissions unit shall not exceed 15 gallons per day.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. The identification of each coating, as applied.
 - b. The volume, in gallons, of each coating material applied.
 - c. The VOC content of each coating excluding water and exempt solvents, as applied, in pounds of VOC per gallon.
 - d. The total VOC emissions from all coatings applied, in pounds per day for this emissions unit (the sum of b times c for each coating).
2. The permittee shall collect and record the following information each month for the purpose of determining annual OC emissions from this emissions unit.
 - a. The name and identification of coating and clean up material employed.
 - b. The volume, in gallons, of each coating and clean up material employed.
 - c. The OC content of each coating and clean up material employed, in pounds of OC per gallon.
 - d. The volume, in gallons, of clean up material recovered for disposal as liquid waste.
 - e. The total OC emissions from all coating and clean up materials, in pounds or tons per month, for this emission unit (the sum of (b x c) - (d x c)).
 - f. The sum of the monthly OC emissions rates calculated (in e) for each calendar year.
3. The permittee shall collect and record the following information each month for

Emissions Unit ID: **K003**

emissions units K002, K003, K005, K006, and K007:

- a. The name and identification of each coating and clean up material employed.
 - b. The volume, in gallons, of each coating and clean up material employed.
 - c. The OC content of each coating and clean up material employed, in pounds of OC per gallon.
 - d. The volume, in gallons, of clean up material recovered for disposal as liquid waste.
 - e. The total OC emissions from all coating, thinner, adhesive and clean up materials, in pounds or tons per month, for this emission unit (the sum of (b x c) - (d x c)).
 - f. The rolling, 12-month summation of the monthly OC emissions from emissions units K002, K003, K005, K006, and K007 (the sum of the monthly emissions rates calculated (in e) for the previous 12 months for each emissions unit).
4. The permittee shall collect and record the following information each month for emissions units K002, K003, K005, K006, and K007:
- a. The name and identification each coating clean up material employed in this emission unit.
 - b. The volume, in gallons, of each coating and cleanup material employed.
 - c. The individual HAP content of each coating and clean up material employed, in pounds of individual HAP per gallon.
 - d. The volume, in gallons, of clean up material that is disposed of as liquid waste.
 - e. The total individual HAP emissions from all coatings, thinners, and cleanup materials employed, in pounds per month, for this emission unit (the sum of (b x c) - (d x c)).
 - f. The rolling, 12-month summation of the monthly individual HAP emissions from emissions units K002, K003, K005, K006, and K007 (the sum of the monthly emissions rates calculated (in e) for the previous 12 months for each emissions unit).

Issued: 9/26/2006

- g. The combined HAP content of each coating and clean up material employed, in pounds of combined HAP per gallon.
 - h. The combined HAP emissions from all coatings, thinners, and cleanup materials employed, in pounds per month, for this emission unit (the sum of (b x g) - (d x g)).
 - i. The rolling, 12-month summation of the monthly combined HAP emissions from emissions units K002, K003, K005, K006, and K007 (the sum of the monthly emissions rates calculated (in h) for the previous 12 months for each emissions unit).
5. The permit to install for this emissions unit (K003) was evaluated based on the actual materials (typically coatings) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the ISCST3 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Acetone

TLV (mg/m³): 1,187

Maximum Hourly Emission Rate (lbs/hr): 33.0

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 4,148MAGLC (ug/m³): 28,265

Pollutant: N-butyl acetate

TLV (mg/m³): 713

Maximum Hourly Emission Rate (lbs/hr): 11.0

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 1378MAGLC (ug/m³): 16,968

Pollutant: Methyl Ethyl Ketone

TLV (mg/m³): 590

Maximum Hourly Emission Rate (lbs/hr): 1.63

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 205

Issued: 9/26/2006MAGLC (ug/m³): 14,042

Pollutant: Xylene

TLV (mg/m³): 434

Maximum Hourly Emission Rate (lbs/hr): 1.26

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 159MAGLC (ug/m³): 10,338

Pollutant: Methyl Amyl Ketone

TLV (mg/m³): 233

Maximum Hourly Emission Rate (lbs/hr): 1.0

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 126MAGLC (ug/m³): 5,560

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
 - b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
6. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant not previously emitted, and a modification of the existing permit to install will not be

Emissions Unit ID: **K003**

required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

7. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy":
 - a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. Where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that include an identification of:
 - a. All exceedances of the rolling 12-month 46.9 TPY of OC emissions limitation from emissions units K002, K003, K005, K006, and K007.
 - b. All exceedances of the rolling 12-month 9.9 TPY of individual HAP emissions limitation from emissions units K002, K003, K005, K006, and K007.
 - c. All exceedances of the rolling 12-month 24.9 TPY of combined HAP emissions limitation from emissions units K002, K003, K005, K006, and K007.

The quarterly deviation (excursion) reports shall be submitted as specified in section A.2.b of the General Terms and Conditions.

2. The permittee shall submit annual reports to the Director (the appropriate Ohio EPA District Office or local air agency) that specify:
 - a. The total OC emissions, in tons, from all coatings and clean up materials employed in this emissions unit.

Issued: 9/26/2006

- b. The rolling 12-month OC emissions for each month, in tons, from all coatings and clean up materials employed in emissions units K002, K003, K005, K006, K007.
- c. The rolling 12-month individual HAP emissions for each month, in tons, for emissions units K002, K003, K005, K006, and K007.
- d. The rolling 12-month combined HAP emissions for each month, in tons, for emissions units K002, K003, K005, K006, and K007.

These reports shall be submitted by April 15 of each year and shall cover the previous calendar year.

E. Testing Requirements

- 1. Compliance with the emissions limitations in section A.1 of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation -
The VOC emissions from this emissions unit shall not exceed 50.2 lbs/day excluding clean up.

Applicable Compliance Method -

Compliance shall be based upon the record keeping as specified in C.1 and shall be determined by multiplying the daily usage rate for each coating, in gallons, by its VOC content, in lbs VOC pounds per gallon, for each day.

Emissions Unit ID: **K003**

b. Emission Limitation -

The OC emissions from this emissions unit shall not exceed 11.2 TPY including clean up.

Applicable Compliance Method -

Compliance shall be based upon record keeping as specified in C.2 and shall be determined by summing the monthly emissions rates, for each calendar year.

c. Emission Limitation -

The OC emissions, from emissions units K002, K003, K005, K006, and K007 shall not exceed 46.9 TPY based upon a rolling 12-month summation.

Applicable Compliance Method -

Compliance shall be based upon record keeping as specified in C.3 and shall be determined by summing the monthly OC emissions rates, in tons, on a rolling 12-month basis.

d. Emission Limitation -

The individual HAP emissions from emissions units K002, K003, K005, K006, and K007 shall not exceed 9.9 TPY.

Applicable Compliance Method -

Compliance shall be based upon record keeping as specified in C.4 and shall be determined by summing the monthly individual HAP emissions rates, in tons, on a rolling 12-month basis.

e. Emission Limitation -

The combined HAP emissions from emissions units K002, K003, K005, K006, and K007 shall not exceed 24.9 TPY.

Applicable Compliance Method -

Compliance shall be based upon record keeping as specified in C.4 and shall be determined by summing the monthly combined HAP emissions rates, in tons, on a rolling 12-month basis.

F. Miscellaneous Requirements

1. This PTI is a modification of PTI 08-04397 to increase allowable OC emissions to reflect an increase in the use of acetone for clean up material in emissions units K003 and K007.

Issued: 9/26/2006

2. The terms and conditions of this PTI A.1 through E.1 are federally enforceable.

Issued: 9/26/2006

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - (K007) - Single Double/Carton Clamp Paint Booth, Manual Paint Spray Booth with Infrared Drying Oven

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	<p>The volatile organic compound (VOC) emissions from this emissions unit shall not exceed 50.2 lbs/day excluding clean up.</p> <p>The organic compound (OC) emissions including clean up shall not exceed 11.2 tons per year (TPY)</p>
OAC rule 3745-35-07(B) (Synthetic minor to avoid Title V and MACT)	<p>The OC Emissions from emissions units K002, K003, K005, K006, and K007 shall not exceed 46.9 TPY based upon a rolling, 12-month summation.</p> <p>The individual hazardous air pollutant (HAP) emissions from emissions units K002, K003, K005, K006, and K007 shall not exceed 9.9 TPY and combined HAP emissions shall not exceed 24.9 TPY based upon a rolling, 12-month summation.</p>
OAC rule 3745-21-09(U)(1)(c)	The VOC content of the coatings applied in this emissions unit shall not exceed 3.5 lbs VOC/gallon excluding water and exempt solvents.

2. Additional Terms and Conditions

2.a None

B. Operational Restrictions

1. The maximum coating and clean up material use excluding liquid wastes recovered for off-site disposal, in emissions units K002, K003, K005, K006, and K007 combined shall not shall not exceed 46.9 TPY of OC, 9.9 TPY of any individual HAP and 24.9 TPY for

Emissions Unit ID: **K007**

any combination of HAPs, based on a 12-month rolling summation. The permittee has existing coating, and clean up material usage records and therefore does not need to be limited in the first year on a monthly basis.

2. Solvent based coatings usage in this emissions unit shall not exceed 15 gallons per day.

C. Monitoring and/or Record Keeping Requirements

1. The permittee shall collect and record the following information each day for this emissions unit:
 - a. The identification of each coating, as applied.
 - b. The volume, in gallons, of each coating material applied.
 - c. The VOC content of each coating excluding water and exempt solvents, as applied, in pounds of VOC per gallon.
 - d. The total VOC emissions from all coatings applied, in pounds per day for this emissions unit (the sum of b times c for each coating).
2. The permittee shall collect and record the following information each month for the purpose of determining annual OC emissions from this emissions unit.
 - a. The name and identification of coating and clean up material employed.
 - b. The volume, in gallons, of each coating and clean up material employed.
 - c. The OC content of each coating and clean up material employed, in pounds of OC per gallon.
 - d. The volume, in gallons, of clean up material recovered for disposal as liquid waste.
 - e. The total OC emissions from all coating and clean up materials, in pounds or tons per month, for this emission unit (the sum of (b x c) - (d x c)).
 - f. The sum of the monthly OC emissions rates calculated (in e) for each calendar year.

Issued: 9/26/2006

3. The permittee shall collect and record the following information each month for emissions units K002, K003, K005, K006, and K007:
 - a. The name and identification of each coating and clean up material employed.
 - b. The volume, in gallons, of each coating and clean up material employed.
 - c. The OC content of each coating and clean up material employed, in pounds of OC per gallon.
 - d. The volume, in gallons, of clean up material recovered for disposal as liquid waste.
 - e. The total OC emissions from all coating, thinner, adhesive and clean up materials, in pounds or tons per month, for this emission unit (the sum of $(b \times c) - (d \times c)$).
 - f. The rolling, 12-month summation of the monthly OC emissions from emissions units K002, K003, K005, K006, and K007 (the sum of the monthly emissions rates calculated (in e) for the previous 12 months for each emissions unit).

4. The permittee shall collect and record the following information each month for emissions units K002, K003, K005, K006, and K007:
 - a. The name and identification each coating, clean up material employed in this emission unit.
 - b. The volume, in gallons, of each coating and cleanup material employed.
 - c. The individual HAP content of each coating and clean up material employed, in pounds of individual HAP per gallon.
 - d. The volume, in gallons, of clean up material that is disposed of as liquid waste.
 - e. The total individual HAP emissions from all coatings, thinners and cleanup materials employed, in pounds per month, for this emission unit (the sum of $(b \times c) - (d \times c)$).
 - f. The rolling, 12-month summation of the monthly individual HAP emissions from emissions units K002, K003, K005, K006, and K007 (the sum of the monthly

Issued: 9/26/2006

- emissions rates calculated (in e) for the previous 12 months for each emissions unit).
- g. The combined HAP content of each coating and clean up material employed, in pounds of combined HAP per gallon.
 - h. The combined HAP emissions from all coatings, thinners and cleanup materials employed, in pounds per month, for this emission unit (the sum of (b x g) - (d x g)).
 - i. The rolling, 12-month summation of the monthly combined HAP emissions from emissions units K002, K003, K005, K006, and K007 (the sum of the monthly emissions rates calculated (in h) for the previous 12 months for each emissions unit).
5. The permit to install for this emissions unit (K007) was evaluated based on the actual materials (typically coatings) and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the ISCST3 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Acetone

TLV (mg/m³): 1,187

Maximum Hourly Emission Rate (lbs/hr): 33.0

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 28,265MAGLC (ug/m³): 4,148

Pollutant: N-butyl acetate

TLV (mg/m³): 713

Maximum Hourly Emission Rate (lbs/hr): 11.0

Predicted 1-Hour Maximum Ground-Level Concentration (ug/m³): 1378MAGLC (ug/m³): 16,968

Pollutant: Methyl Ethyl Ketone

TLV (mg/m³): 590

Emissions Unit ID: **K007**

Maximum Hourly Emission Rate (lbs/hr): 1.63
Predicted 1-Hour Maximum Ground-Level Concentration ($\mu\text{g}/\text{m}^3$): 205
MAGLC ($\mu\text{g}/\text{m}^3$): 14,042

Pollutant: Xylene
TLV (mg/m^3): 434
Maximum Hourly Emission Rate (lbs/hr): 1.26
Predicted 1-Hour Maximum Ground-Level Concentration ($\mu\text{g}/\text{m}^3$): 159
MAGLC ($\mu\text{g}/\text{m}^3$): 10,338

Pollutant: Methyl Amyl Ketone
TLV (mg/m^3): 233
Maximum Hourly Emission Rate (lbs/hr): 1.0
Predicted 1-Hour Maximum Ground-Level Concentration ($\mu\text{g}/\text{m}^3$): 126
MAGLC ($\mu\text{g}/\text{m}^3$): 5,560

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. Changes in the composition of the materials used (typically for coatings or cleanup materials), or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;
 - b. Changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
 - c. Physical changes to the emissions unit or its exhaust parameters (e.g., increased/decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).
6. If the permittee determines that the "Air Toxic Policy" will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a "modification" under OAC rule 3745-31-01 solely due to the emissions of any type of toxic air contaminant

Issued: 9/26/2006

not previously emitted, and a modification of the existing permit to install will not be required, even if the toxic air contaminant emissions are greater than the de minimis level in OAC rule 3745-15-05. If the change(s) is (are) defined as a modification under other provisions of the modification definition, then the permittee shall obtain a final permit to install prior to the change.

7. The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the "Air Toxic Policy:"
 - a. A description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
 - b. Documentation of its evaluation and determination that the changed emissions unit still satisfies the "Air Toxic Policy"; and
 - c. Where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the "Air Toxic Policy" for the change.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation (excursion) reports that include an identification of:
 - a. All exceedances of the rolling 12-month 46.9 TPY of OC emissions limitation from emissions units K002, K003, K005, K006, and K007.
 - b. All exceedances of the rolling 12-month 9.9 TPY of individual HAP emissions limitation from emissions units K002, K003, K005, K006, and K007.
 - c. All exceedances of the rolling 12-month 24.9 TPY of combined HAP emissions limitation from emissions units K002, K003, K005, K006, and K007.

The quarterly deviation (excursion) reports shall be submitted as specified in section A.2.b of the General Terms and Conditions.

2. The permittee shall submit annual reports to the Director (the appropriate Ohio EPA District Office or local air agency) that specify:

Emissions Unit ID: **K007**

- a. The total OC emissions, in tons, from all coatings and clean up materials employed in this emissions unit.
- b. The rolling 12-month OC emissions for each month, in tons, from all coatings and clean up materials employed in emissions units K002, K003, K005, K006, and K007.
- c. The rolling 12-month individual HAP emissions for each month, in tons, for emissions units K002, K003, K005, K006, and K007.
- d. The rolling 12-month combined HAP emissions for each month, in tons, for emissions units K002, K003, K005, K006, and K007.

These reports shall be submitted by April 15 of each year and shall cover the previous calendar year.

E. Testing Requirements

1. Compliance with the emissions limitations in section A.1 of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitation -
The VOC emissions from this emissions unit shall not exceed 50.2 lbs/day excluding clean up.

Applicable Compliance Method -

Compliance shall be based upon the record keeping as specified in C.1 and shall be determined by multiplying the daily usage rate for each coating, in gallons, by its VOC content, in lbs VOC pounds per gallon, for each day.

Issued: 9/26/2006

- b. Emission Limitation -
The OC emissions from this emissions unit shall not exceed 11.2 TPY including clean up.

Applicable Compliance Method -
Compliance shall be based upon record keeping as specified in C.2 and shall be determined by summing the monthly emissions rates, for each calendar year.

- c. Emission Limitation -
The OC emissions, from emissions units K002, K003, K005, K006, and K007 shall not exceed 46.9 TPY based upon a rolling 12-month summation.

Applicable Compliance Method -
Compliance shall be based upon record keeping as specified in C.3 and shall be determined by summing the monthly OC emissions rates, in tons, on a rolling 12-month basis.

- d. Emission Limitation -
The individual HAP emissions from emissions units K002, K003, K005, K006, and K007 shall not exceed 9.9 TPY.

Applicable Compliance Method -
Compliance shall be based upon record keeping as specified in C.4 and shall be determined by summing the monthly individual HAP emissions rates, in tons, on a rolling 12-month basis.

- e. Emission Limitation -
The combined HAP emissions from emissions units K002, K003, K005, K006, and K007 shall not exceed 24.9 TPY.

Applicable Compliance Method -
Compliance shall be based upon record keeping as specified in C.4 and shall be determined by summing the monthly combined HAP emissions rates, in tons, on a rolling 12-month basis.

F. Miscellaneous Requirements

1. This PTI is a modification of PTI 08-04397 to increase allowable OC emissions to reflect an increase in the use of acetone for clean up material in emissions units K003 and K007.

2. The terms and conditions of this PTI A.1 through E.1 are federally enforceable.