

Facility ID: 0640010105 Issuance type: Final State Permit To Operate

This version of facility specific terms and conditions was converted from a database format to an HTML file during an upgrade of the Ohio EPA, Division of Air Pollution Control's permitting software. Every attempt has been made to convert the terms and conditions to look and substantively conform to the permit issued or being drafted in STARS. However, the format of the terms may vary slightly from the original. In addition, although it is not expected, there is a slight possibility that a term and condition may have been inadvertently "left out" of this reproduction during the conversion process. Therefore, if this version is to be used as a starting point in drafting a new version of a permit, it is imperative that the entire set of terms and conditions be reviewed to ensure they substantively mimic the issued permit. The official version of any permit issued final by Ohio EPA is kept in the Agency's Legal section. The Legal section may be contacted at (614) 644-3037.

In addition to the terms and conditions, hyperlinks have been inserted into the document so you may more readily access the section of the document you wish to review.

Finally, the term language under "Part II" and before "A. Applicable Emissions Limitations..." has been added to aid in document conversion, and was not part of the original issued permit.

\*\*\*THIS IS NOT AN OFFICIAL VERSION OF THE PERMIT. SEE PAGE 1 FOR ADDITIONAL INFORMATION\*\*\*

Facility ID: 0640010105 Emissions Unit ID: P906 Issuance type: Final State Permit To Operate

[Go to the top of this document](#)

**Part II - Special Terms and Conditions**

This permit document constitutes a permit-to-install issued in accordance with ORC 3704.03(F) and a permit-to-operate issued in accordance with ORC 3704.03(G).

1. For the purpose of a permit-to-install document, the emissions unit terms and conditions identified below are federally enforceable with the exception of those listed below which are enforceable under state law only.
  - (a) None.
2. For the purpose of a permit-to-operate document, the emissions unit terms and conditions identified below are enforceable under state law only with the exception of those listed below which are federally enforceable.
  - (a) None.

**A. Applicable Emissions Limitations and/or Control Requirements**

1. The specific operation(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be employed. Additional applicable emissions limitations and/or control measures (if any) may be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P906 - 90 lb/hr Induction furnace system - unit 3921.	OAC rule 3745-31-05(A)(3) (PTI 06-06686 issued on 11/27/01)	0.030 grain of particulate emissions per dry standard cubic foot of exhaust gases (gr/dscf) from the baghouse (equivalent to 2.57 lbs/hr at maximum process rate for P901 thru P906 combined) or no visible emissions, whichever is less stringent.
		Visible emissions of fugitive dust shall not exceed 20 percent opacity as a three-minute average.
		See A.2.a. below.
		11.26 tpy of particulate emissions for emission units P901 thru P906 combined.
		The requirements of this rule also include compliance with the requirements of OAC rule 3745-17-07(A)(1), OAC rule 3745-17-07(B)(1) and OAC rule 3745-17-08(B)(3).
	OAC rule 3745-17-07(A)(1)	The emissions limitation established by this rule is less stringent than those established by OAC 3745-31-05(A)(3).
	OAC rule 3745-17-07(B)(1)	The requirements established pursuant to this rule are equivalent to the requirements of OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-08(B)(3)	The requirements established pursuant to this rule are equivalent to the requirements of OAC rule 3745-31-05(A)(3).
	OAC rule 3745-17-11	The emissions limitation established by this rule is less stringent than those established by OAC 3745-31-05(A)(3).

2. **Additional Terms and Conditions**
  - (a) The permittee shall employ adequate enclosure(s), capture hoods and a baghouse to minimize or eliminate visible emissions of fugitive emissions.

**B. Operational Restrictions**

1. None

**C. Monitoring and/or Record Keeping Requirements**

1. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the stack serving this emissions unit. The presence or absence of any visible emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:

- a. the color of the emissions;
  - b. the total duration of any visible emission incident; and
  - c. any corrective actions taken to eliminate the visible emissions.
2. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible fugitive particulate emissions from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit. The presence or absence of any visible fugitive emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall also note the following in the operations log:
    - a. the location and color of the emissions;
    - b. whether the emissions are representative of normal operations;
    - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
    - d. the total duration of any visible emission incident; and
    - e. any corrective actions taken to minimize or eliminate the visible emissions.

If visible emissions are present, a visible emission incident has occurred. The observer does not have to document the exact start and end times for the visible emission incident under item (d) above or continue the daily check until the incident has ended. The observer may indicate that the visible emission incident was continuous during the observation period (or, if known, continuous during the operation of the emissions unit). With respect to the documentation of corrective actions, the observer may indicate that no corrective actions were taken if the visible emissions were representative of normal operations, or specify the minor corrective actions that were taken to ensure that the emissions unit continued to operate under normal conditions, or specify the corrective actions that were taken to eliminate abnormal visible emissions.

3. The permittee shall maintain a monthly record of the total hours of operation for emissions units P901 thru P906, combined.

#### D. Reporting Requirements

1. The permittee shall submit semiannual written reports that:
  - a. identify all days during which any visible particulate emissions were observed from the stack serving this emissions unit,
  - b. identify all days during which any visible emissions of fugitive dust were observed from the egress points (i.e., building windows, doors, roof monitors, etc.) serving this emissions unit, and
  - c. describe any corrective actions taken to minimize or eliminate the visible particulate emissions and/or visible fugitive dust emissions.

These reports shall be submitted to the Director (the appropriate Ohio EPA District Office or local air agency) by January 31 and July 31 of each year and shall cover the previous six-month periods.

#### E. Testing Requirements

1. Compliance with the emission limitations in section A.1 of these terms and conditions shall be determined in accordance with the following methods:  
 Emission Limitation: Particulate emissions from the baghouse exhaust shall not exceed 0.030 grain per dry standard cubic foot of exhaust gases (equivalent to 2.57 lbs/hr at maximum process rate for P901 thru P906 combined)  
  
 Applicable Compliance Method: If required, the permittee shall demonstrate compliance by emission testing in accordance with the procedures specified in 40 CFR Part 60, Appendix A, Methods 1 through 5 and the procedures specified in OAC rule 3745-17-03(B)(10).  
 Emission Limitation: There shall be no visible emissions from the baghouse exhaust stack.  
  
 Applicable Compliance Method: If required, compliance shall be demonstrated based upon Test Method 22-like visible emission observations. (Although Test Method 22 applies to fugitive emissions units, the visible/no visible emissions observation technique of 40 CFR Part 60, Appendix A, Method 22 can be applied to ducted emissions, i.e., Test Method 22-like visible emissions observations.)  
 Emission Limitation: Visible particulate emissions of fugitive dust shall not exceed 20% opacity as a 3-minute average.  
  
 Applicable Compliance Method: If required, compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 2002, and the applicable modifications listed in paragraphs (B)(3)(a) through (B)(3)(e) of OAC rule 3745-17-03.  
 Emission Limitation: 11.26 tpy of particulate emissions for emission units P901 thru P906 combined  
  
 Applicable Compliance Method: Compliance shall be demonstrated by multiplying the allowable hourly emission rate by the actual annual hours of operation of the emissions unit(s), and then dividing by 2000 lbs/ton.

#### F. Miscellaneous Requirements

1. None