

Synthetic Minor Determination and/or **Netting Determination**

Permit To Install PTI 01-8692

A. Source Description

Shelly Plant 63 located in Newark, has submitted a Permit to Install (PTI) application which includes proposed federally enforceable limits in order to effectively restrict Plant 63's Potential to Emit (PTE) below those levels which trigger Title V permitting requirements. The proposed Federally Enforceable limits are specific to emissions unit P901.

B. Facility Emissions and Attainment Status

Plant 63's current PTE based upon 8760 hours of operation, is above 100 tons/year for CO,SO2 and VOC. Plant 63's current PTE, based upon 8760 hours per year of operation, is described below.

<u>E.U.</u>	<u>NOx PTE(TPY)</u>	<u>CO PTE(TPY)</u>	<u>VOC PTE(TPY)</u>	<u>SO2 PTE(TPY)</u>	<u>PM PTE(TPY)</u>
P901	89.4	219	187.9	328.5	38.1
Total	89.4	219	187.9	328.5	38.1

Due to the proposed operational restriction of 400,000 tons of asphalt per 12 month rolling period, the PTE of P901, upon issuance of the PTI, will be as described below.

<u>E.U.</u>	<u>NOx PTE(TPY)</u>	<u>CO PTE(TPY)</u>	<u>VOC PTE(TPY)</u>	<u>SO2 PTE(TPY)</u>	<u>PM PTE(TPY)</u>
P901	17.4	42.7	36.7	62	9.51

Therefore, Plant 63's facility-wide PTE upon issuance of the PTI will be as described below:

<u>E.U.</u>	<u>NOx PTE(TPY)</u>	<u>CO PTE(TPY)</u>	<u>VOC PTE(TPY)</u>	<u>SO2 PTE(TPY)</u>	<u>PM PTE(TPY)</u>
P901	17.4	42.7	36.7	62	9.51
Total PTE	17.4	42.7	36.7	62	9.51

C. Source Emissions

The facility and the Ohio EPA have agreed to short term emission restrictions and operational restrictions which correspond to maximum annual emissions below those levels which trigger Title V permitting requirements. The facility has records to demonstrate that this plant has historically not exceeded 400,000 tons of production per rolling 12-month period for several years.

D. Conclusion

The operation of emissions units in accordance with the terms and conditions of the proposed PTI will result in maximum annual facility emissions below those levels which trigger Title V permitting requirements.

The proposed PTI includes federally enforceable limits, record keeping, reporting and production limitations to ensure continued compliance with the PTI's requirements.



State of Ohio Environmental Protection Agency

Street Address:

Lazarus Gov. Center
122 S. Front Street
Columbus, OH 43215

TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

**RE: DRAFT PERMIT TO INSTALL
LICKING COUNTY
Application No: 01-08692**

CERTIFIED MAIL

DATE: 9/18/2003

Y	TOXIC REVIEW
	PSD
Y	SYNTHETIC MINOR
	CEMS
	MACT
I	NSPS
	NESHAPS
	NETTING
	MAJOR NON-ATTAINMENT
	MODELING SUBMITTED
	GASOLINE DISPENSING FACILITY

Shelly Materials Plant 63
Larry Shively
Post Office Box 266 8775 Blackbird Ln
Thornville, OH 43076

You are hereby notified that the Ohio Environmental Protection Agency has made a draft action recommending that the Director issue a Permit to Install for the air contaminant source(s) [emissions unit(s)] shown on the enclosed draft permit. This draft action is not an authorization to begin construction or modification of your emissions unit(s). The purpose of this draft is to solicit public comments on the proposed installation. A public notice concerning the draft permit will appear in the Ohio EPA Weekly Review and the newspaper in the county where the facility will be located. Public comments will be accepted by the field office within 30 days of the date of publication in the newspaper. Any comments you have on the draft permit should be directed to the appropriate field office within the comment period. A copy of your comments should also be mailed to Robert Hodanbosi, Division of Air Pollution Control, Ohio EPA, P.O. Box 1049, Columbus, OH, 43266-0149.

A Permit to Install may be issued in proposed or final form based on the draft action, any written public comments received within 30 days of the public notice, or record of a public meeting if one is held. You will be notified in writing of a scheduled public meeting. Upon issuance of a final Permit to Install a fee of **\$1000** will be due. Please do not submit any payment now.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469. If you have any questions about this draft permit, please contact the field office where you submitted your application, or Mike Ahern, Field Operations & Permit Section at (614) 644-3631.

Very truly yours,

Michael W. Ahern, Supervisor
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA

CDO

LICKING COUNTY

PUBLIC NOTICE

**ISSUANCE OF DRAFT PERMIT TO INSTALL 01-08692 FOR AN AIR CONTAMINANT SOURCE FOR
SHELLY MATERIALS PLANT 63**

On 9/18/2003 the Director of the Ohio Environmental Protection Agency issued a draft action of a Permit To Install an air contaminant source for **Shelly Materials Plant 63**, located at **6824 Mt Vernon Rd, Newark, Ohio**.

Installation of the air contaminant source identified below may proceed upon final issuance of Permit To Install 01-08692:

Asphalt Plant Modification PTI 0108326.

Comments concerning this draft action, or a request for a public meeting, must be sent in writing to the address identified below no later than thirty (30) days from the date this notice is published. All inquiries concerning this draft action may be directed to the contact identified below.

Isaac Robinson, Ohio EPA, Central District Office, 3232 Alum Creek Drive, Columbus, OH 43207-3417
[(614)728-3778]



Permit To Install

Issue Date: To be entered upon final issuance

Terms and Conditions

Effective Date: To be entered upon final issuance

DRAFT PERMIT TO INSTALL 01-08692

Application Number: 01-08692

APS Premise Number: 0145020323

Permit Fee: **To be entered upon final issuance**

Name of Facility: Shelly Materials Plant 63

Person to Contact: Larry Shively

Address: Post Office Box 266 8775 Blackbird Ln
Thornville, OH 43076

Location of proposed air contaminant source(s) [emissions unit(s)]:

**6824 Mt Vernon Rd
Newark, Ohio**

Description of proposed emissions unit(s):

Asphalt Plant Modification PTI 0108326.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with

this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as

provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

a. If the permittee is required to apply for a Title V permit pursuant to OAC Chapter 3745-77, the permittee shall submit a complete Title V permit application or a complete Title V permit modification application within twelve (12) months after commencing operation of the emissions units covered by this permit. However, if the proposed new or modified source(s) would be prohibited by the terms and conditions of an existing Title V permit, a Title V permit modification must be obtained before the operation of such new or modified source(s) pursuant to OAC rule 3745-77-04(D) and OAC rule 3745-77-08(C)(3)(d).

b. If the permittee is required to apply for permit(s) pursuant to OAC Chapter 3745-35, the

source(s) identified in this Permit To Install is (are) permitted to operate for a period of up to one year from the date the source(s) commenced operation. Permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the source(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
NOx	17.4
CO	42.7
SO2	62
VOC	36.7
PM(stack)	7.43
PM-10(stack)	7.43
PM(fugitive)	2.08
PM-10(fugitive)	1.02

A. Applicable Emissions Limitations and/or Control Requirements

- The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P901 - 260 TPH batch type asphalt plant controlled by a baghouse	OAC rule 3745-31-05(A)(3)	<p>Carbon monoxide (CO) emissions from burning on-spec used oil shall not exceed 50.0 lbs/hr.</p> <p>CO emissions from burning natural gas shall not exceed 42.0 lbs/hr.</p> <p>CO emission from burning number 2 fuel oil shall not exceed 50.0 lbs/hr.</p> <p>Nitrogen Oxide (NO_x) emissions from burning on-spec used oil shall not exceed 20.4 lbs/hr.</p> <p>NO_x emissions from burning natural gas shall not exceed 17.0 lbs/hr.</p> <p>NO_x emissions from burning number 2 fuel oil shall not exceed 20.4 lbs/hr.</p> <p>Sulfur Dioxide (SO₂) emissions from burning on-spec used oil shall not exceed 75.0 lbs/hr.</p> <p>SO₂ emissions from burning natural gas shall not exceed 55.0 lbs/hr.</p> <p>SO₂ emissions from burning number 2 fuel oil shall not exceed 75.0 lbs/hr.</p> <p>Volatile Organic Compound (VOC) emissions from burning on-spec used oil shall not exceed 42.9 lbs/hr.</p> <p>VOC emissions from burning natural gas shall not exceed 35.0 lbs/hr.</p>

VOC emission from burning number 2 fuel oil shall not exceed 42.9 lbs/hr.

PM/PM-10 from the stack shall not exceed 0.04 gr/dscf when burning on-spec oil, number 2 fuel oil, or natural gas.

Emissions of fugitive PM-10 shall not exceed 1.02 pound per hour when burning on-spec oil, number 2 fuel oil, or natural gas.

Fugitive particulate emissions shall not exceed 2.08 pounds per hour when burning on-spec oil, number 2 fuel oil, or natural gas.

Arsenic, cadmium, chromium, and lead emissions are limited by the fuel specifications in A.2.b below.

Visible particulate emissions from the stack shall not exceed 10% opacity, as a 3-minute average.

Best available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see section A.2.a).

No visible emissions of fugitive dust from the enclosures for the hot aggregate elevator, vibrating screens, and weigh hopper.

Visible emissions of fugitive dust (from areas other than the enclosures for the hot aggregate elevator, vibrating screens, and weigh hopper) shall be less than or equal to 10% opacity, as a 3-minute average.

The drop height of the front end loader bucket shall be minimized to the extent possible in order to minimize or eliminate visible emissions of fugitive dust from the aggregate storage bins.

The aggregate loaded into the storage bins shall have a moisture content sufficient to

OAC rule 3745-31-05(D)

minimize the visible emissions of fugitive dust from conveyors and all transfer points to the dryer.

The requirements of this rule also include compliance with the requirements of OAC rule 3745-31-05(D) and 40CFR Part 60, Subpart I.

See A.2.c-e below

Particulate emissions (PE) from the stack shall not exceed 7.43 tons per rolling 12-month period.

PM-10 emissions from the stack shall not exceed 7.43 tons per rolling 12-month period.

Fugitive PE shall not exceed 2.08 tons per rolling 12-month period.

Fugitive PM-10 emissions shall not exceed 1.02 ton per rolling 12-month period.

CO emissions shall not exceed 42.7 tons per rolling 12-month period.

VOC emissions shall not exceed 36.7 tons per rolling 12-month period.

SO₂ emissions shall not exceed 62.0 tons per rolling 12-month period.

NO_x emissions shall not exceed 17.4 tons per rolling 12-month period.

OAC rule 3745-17-07(A)(1)
OAC rule 3745-17-11(B)(1)
OAC rule 3745-18-06(E)

The emissions limitations specified by these rules are less stringent than the emission limitations established pursuant to OAC rule 3745-31-05(A)(3).

40 CFR Part 60, Subpart I

PE from the stack shall not exceed 0.04 gr/dscf when burning on-spec used oil, number 2 fuel oil, or natural gas.

2. Additional Terms and Conditions

2.a The permittee shall ensure that the baghouse is operated with sufficient air volume to minimize or eliminate visible fugitive emissions from the rotary drum.

2.b All on-spec used oil burned in this emissions unit shall meet the following specifications:

<u>Contaminant/Property</u>	<u>Allowable Specifications</u>
arsenic	5 ppm, maximum
cadmium	2 ppm, maximum
chromium	10 ppm, maximum
lead	100 ppm, maximum
PCB's	50 ppm, maximum
total halogens	4000 ppm maximum
mercury	1 ppm, maximum
flash point	100°F, minimum
heat content	135,000 Btu/gallon, minimum

2.c On-spec used oil containing more than 1000 ppm total halogens is presumed to be a hazardous waste under the rebuttable presumption provided under 40 CFR Part 266.40(c) and OAC rule 3745-279. Therefore, the permittee may receive and burn on-spec used oil exceeding 1000 ppm of total halogens (but less than 4000 ppm, maximum) only if the supplier [“marketer” in 40 Part CFR 266.43(a)] has demonstrated to the Ohio EPA’s Division of Hazardous Waste Management that the on-spec used oil does not contain any hazardous waste.

2.d All number 2 and on-spec used oil burned in this emission unit shall have a sulfur content equal to or less than 0.5%.

2.e The permittee shall conduct burner performance tuning for purposes of minimizing emissions. Burner performance tuning shall contain at a minimum the evaluation of and adjustment to manufacturer’s specifications of the following:

- i. Fuel flow to the burner (for fuel oil and on spec used oil);
- ii. Differential pressure of the baghouse to ensure proper air flow through the plant;

- iii. Flue gas analysis (of gases present in the drum and or stack) for CO, O₂, CO₂, and NO_x;
- iv. Fuel pressure; and
- v. For burners that require compressed air for proper operation, correct pressure at the burner;

B. Operational Restrictions

1. The pressure drop across the fabric filter shall be maintained within the range of 2 to 8 inches of water while the emissions unit is in operation.
2. The permittee may not receive or burn any on-spec used oil which does not meet the specifications listed in A.2.b of this permit without first obtaining a permit to install that authorizes the burning of such off-specification used oil. The burning of off-specification used oil is subject to OAC rule 3745-279-60 through 67.
3. The maximum annual asphalt production rate for this emissions unit shall not exceed 400,000 tons per year, based upon a rolling, 12-month summation of the production rates. The company has existing records for the current operational location such that the applicant does not need to be restricted to first year monthly asphalt production.
4. The permittee shall conduct an initial burner tuning within 30 production days after commencement of the production season. The permittee shall conduct another burner tuning within the time period of 90 to 120 production days after the initial burner tuning. For purposes of this permit, the production season is defined as the time period between the date the first ton of asphalt is produced and the date that the last ton of asphalt is produced during the same calendar year.
5. In addition to the burner tuning required above, the permittee shall conduct additional burner tuning, within 30 production days, for each type of fuel burned during the production season that is different than the fuel(s) burned during the initial burner tuning or the burner tuning described above that occurs 90 to 120 production days after the initial burner tuning.
6. The permittee may substitute reclaimed asphalt pavement (RAP) in the raw material feed mix in amounts not to exceed 50 percent of all aggregate materials.
7. The exit of the stack serving this emissions unit shall be a minimum of 39 feet above ground.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall receive a chemical analysis with each shipment of on spec used oil from the supplier. The analysis shall identify the name and address of the supplier, the supplier's USEPA identification number, and the following information:

- a. date of shipment or delivery;
- b. quantity of on spec used oil received;
- c. the Btu value of the on spec used oil;
- d. the flash point of the on spec used oil;
- e. the arsenic content, in ppm;
- f. the cadmium content, in ppm;
- g. the chromium content, in ppm;;
- h. the lead content, in ppm;;
- i. the PCB content, in ppm;;
- j. the total halogen content, in ppm;; and
- k. the mercury content, in ppm;.

Each analysis shall be kept in a readily accessible location for at least 5 years and shall be made available to the Director (the appropriate Ohio EPA District Office or local air agency) upon verbal or written request. The Director or any authorized representative of the Director may require or may conduct periodic, detailed chemical analyses through an independent laboratory of any used oil shipment received by this facility, of any used oil stored at this facility, or of any used oil sampled at the dryer.

2. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the fabric filter while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the fabric filter on daily basis.
3. The permittee shall maintain monthly records of the following information:
 - a. The asphalt production for each month;
 - b. The rolling, 12-month summation of the asphalt production;
 - c. the maximum percentage RAP used for any mix.

4. For each shipment of number 2 fuel oil, and on-spec used oil received for burning in this emissions unit, the permittee shall maintain records of the total quantity of oil received and the permittees or oil supplier's analyses for sulfur content and heat content.
5. The permittee shall perform daily visible emission checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the enclosures for the hot aggregate elevator, vibrating screens and weigh hopper servicing this emissions unit. If visible particulate emissions are observed, the permittee shall note the following in the operation log:
 - a. the color of the visible particulate emissions;
 - b. the cause of the visible particulate emissions;
 - c. the total duration of the visible particulate emission incident; and
 - d. corrective actions taken to eliminate the visible particulate emissions.

The permittee may, upon receipt of written approval from the Ohio EPA, Central District Office, modify the above-mentioned visible particulate emissions check frequency if operating experience indicates that less frequent checks would be sufficient to ensure compliance with the visible particulate emissions requirements.

6. The permittee shall perform daily visible emission checks, when the emissions unit is in operation and when the weather conditions allow, for any abnormal visible particulate emissions from the stack, aggregate storage bins and cold aggregate elevator/conveyor serving this emissions unit. If abnormal visible emissions are observed, the permittee shall note the following in the operation log:
 - a. the color of the abnormal visible particulate emissions;
 - b. the cause of the abnormal visible particulate emissions;
 - d. the total duration of any abnormal visible particulate emissions incident; and
 - e. any corrective actions taken to eliminate the abnormal visible particulate emissions.

The permittee may, upon receipt of written approval from the Ohio EPA, Central District Office modify the above-mentioned visible particulate emissions check frequency if operating experience indicates that less frequent checks would be sufficient to ensure compliance with the visible particulate emissions requirements.

7. The permittee shall properly operate and maintain portable devices to monitor the concentration of NO_x, CO, O₂, and CO₂ present in the flue gases generated within the drum and/or stack during the burner performance tuning. The monitoring equipment shall be calibrated, operated and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The

- permittee shall maintain records of each portable monitoring device's calibration.
8. While performing the required burner tuning, the permittee shall record the following information:
 - a. date of the burner tuning;
 - b. results of the evaluation of the operating parameters listed above in A.2.e.;
 - c. detail list of adjustments and/or repairs made to bring the operating parameters into conformance with the manufacturer's specifications; and
 - d. type of fuel(s) employed during the burner tuning.
 9. The permit to install for this emissions unit (P901) was evaluated based on the actual materials and the design parameters of the emissions unit's exhaust system, as specified by the permittee in the permit to install application. The Ohio EPA's "Review of New Sources of Air Toxic Emissions" policy ("Air Toxic Policy") was applied for each pollutant emitted by this emissions unit using data from the permit to install application and the SCREEN 3.0 model (or other Ohio EPA approved model). The predicted 1-hour maximum ground-level concentration from the use of the SCREEN 3.0 model was compared to the Maximum Acceptable Ground-Level Concentration (MAGLC). The following summarizes the results of the modeling for the "worst case" pollutant(s):

Pollutant: Heptane

TLV (mg/m³): 1,640

Maximum Hourly Emission Rate (lbs/hr): 2.39

Predicted 1-Hour Maximum Ground-Level
Concentration (ug/m³): 3.53

MAGLC (ug/m³): 39,048

Physical changes to or changes in the method of operation of the emissions unit after its installation or modification could affect the parameters used to determine whether or not the "Air Toxic Policy" is satisfied. Consequently, prior to making a change that could impact such parameters, the permittee shall conduct an evaluation to determine that the "Air Toxic Policy" will still be still satisfied. If, upon evaluation, the permittee determines that the "Air Toxic Policy" will not be satisfied, the permittee will not make the change. Changes that can affect the parameters used in applying the "Air Toxic Policy" include the following:

- a. changes in the composition of the materials used or the use of new materials, that would result in the emission of a compound with a lower Threshold Limit Value (TLV), as indicated in the most recent version of the handbook entitled "American Conference of Governmental Industrial Hygienists (ACGIH)," than the lowest TLV value previously modeled;

- b. changes in the composition of the materials, or use of new materials, that would result in an increase in emissions of any pollutant with a listed TLV that was proposed in the application and modeled; and
- c. physical changes to the emissions unit or its exhaust parameters (e.g., increased/ decreased exhaust flow, changes in stack height, changes in stack diameter, etc.).

If the permittee determines that the “Air Toxic Policy” will be satisfied for the above changes, the Ohio EPA will not consider the change(s) to be a “modification” under OAC rule 3745-31-01(VV)(1)(a)(ii), and a modification of the existing permit to install will not be required. If the change(s) is (are) defined as a modification under other provisions of the modification definition (other than (VV)(1)(a)(ii)), then the permittee shall obtain a final permit to install prior to the change.

The permittee shall collect, record, and retain the following information when it conducts evaluations to determine that the changed emissions unit will still satisfy the “Air Toxic Policy:”

- a. a description of the parameters changed (composition of materials, new pollutants emitted, change in stack/exhaust parameters, etc.);
- b. documentation of its evaluation and determination that the changed emissions unit still satisfies the “Air Toxic Policy”; and
- c. where computer modeling is performed, a copy of the resulting computer model runs that show the results of the application of the “Air Toxic Policy” for the change.

D. Reporting Requirements

1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports are due by the date described in Part I- General Terms and Condition of this permit under section (A)(2).
2. The permittee shall submit quarterly deviation (excursion) reports which identify all exceedances of the rolling 12-month asphalt production limitation . These reports are due by the date described in Part I- General Terms and Conditions of this permit under section (A)(2).
3. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the RAP limitation specified above. These reports are due by the date described in Part I- General Terms and Condition of this permit under section (A)(2).
4. The permittee shall submit annual reports which specify the total PM, SO₂, NO_x, VOC and CO emissions from this emissions unit for the previous calendar year. These reports shall be submitted by April 15 of each year.

Shelly Materials Plant 63

PTI Application: 01-08692

Issued: To be entered upon final issuance

Facility ID: 0145020323

Emissions Unit ID: P901

5. The permittee shall notify the USEPA and the Ohio EPA if any of the on spec used oil exceeds the on spec used oil specifications found in OAC rule 3745-279-11. If the permittee is burning on spec used oil which exceeds the specifications found in OAC rule 3745-279-11, the permittee is subject to that rule and must comply with all provisions of that rule. The required notification shall be submitted within 30 days of the date in which the exceedance occurred.
6. The permittee shall submit quarterly deviation (excursion) reports that identify all exceedances of the sulfur content limit specified above. These reports are due by the date described in Part I- General Terms and Condition of this permit under section (A)(2).
7. The permittee shall submit quarterly deviation (excursion) reports that identify any of the following occurrences:
 - a. identify all days during which any abnormal visible particulate emissions were observed from the stack, aggregate storage bins and cold aggregate elevator/conveyors serving this emissions unit;
 - b. identify all days during which any visible fugitive particulate emissions were observed from the enclosures for the hot aggregate elevator, vibrating screens, weigh hopper;
 - c. describe any corrective actions taken to eliminate the abnormal visible particulate emissions.

These reports are due by the date described in Part I - General Terms and Conditions of this permit under section (A)(2).
8. The permittee shall submit burner performance tuning reports to the Ohio EPA Central District Office that summarize the results of each burner performance tuning. These reports are due within 30 days of the date that the burner performance tuning was performed.

E. Testing Requirements

1. Compliance with the emission limitations specified in Section A.1 of these terms and conditions shall be determined in accordance with the following methods:
 - a. Emission Limitations: PE shall not exceed 0.04 gr/dscf.

Applicable Compliance Method: If required, the permittee shall demonstrate compliance with this emission limitation in accordance with 40 CFR Part 60, Appendix A, Methods 1-5.
 - b. Emissions Limitation: PE emissions shall not exceed 7.43 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be determined by multiplying the observed emission rate from the most recent emissions testing,

in pounds of PE per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period, (as derived from the records required by term and condition C.3 above) and dividing by 2000.

- c. Emissions Limitation: VOC emissions shall not exceed 42.9 lbs/hr when burning number 2 fuel or on-spec used oil;

Applicable Compliance Method: If required, the permittee shall demonstrate compliance with this emission limitation in accordance with 40 CFR Part 60, Appendix A, Methods 1-4, 25 and/or 18.

- d. Emission Limitation: VOC emissions from burning natural gas shall not exceed 35.0 lbs/hr.

Applicable Compliance Method: If required, the permittee shall demonstrate compliance with this emission limitation in accordance with 40 CFR Part 60, Appendix A, Methods 1-4, 25 or 18.

- e. Emission Limitation: VOC emissions shall not exceed 36.7 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of VOC per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period, (as derived from the records required by term and condition C.3 above) and dividing by 2000.

- f. Emission Limitation: CO emissions from burning number 2 fuel or on-spec used oil shall not exceed 50.0 lbs/hr;

Applicable Compliance Method: If required, the permittee shall demonstrate compliance with this emission limitation in accordance with 40 CFR Part 60, Appendix A, Methods 1-4 and 10.

- g. Emission Limitation: CO emissions from burning natural gas shall not exceed 42.0 lbs/hr.

Applicable Compliance Method: If required, the permittee shall demonstrate compliance with this emission limitation in accordance with 40 CFR Part 60, Appendix A, Methods 1-4 and 10.

- h. Emission Limitation: CO emissions shall not exceed 42.7 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of CO per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period, (as derived from the records required by term and condition C.3 above) and dividing by 2000.

- i. Emission Limitation: SO₂ emissions from burning number 2 fuel or on-spec used oil shall not exceed 75.0 lbs/hr;

Applicable Compliance Method: If required, the permittee shall demonstrate compliance with this emission limitation in accordance with 40 CFR Part 60, Appendix A, Methods 1-4 and 6 or 6C.

- j. Emission Limitation: SO₂ emissions from burning natural gas shall not exceed 55.0 lbs/hr.

Applicable Compliance Method: If required, the permittee shall demonstrate compliance with this emission limitation in accordance with 40 CFR Part 60, Appendix A, Methods 1-4 and 6 or 6C.

- k. Emission Limitation: SO₂ emissions shall not exceed 62.0 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of SO₂ per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period, (as derived from the records required by term and condition C.3 above) and dividing by 2000.

- l. Emission Limitation: NO_x emissions from burning natural gas shall not exceed 17.0 lbs/hr.

Applicable Compliance Method: If required, the permittee shall demonstrate compliance with this emission limitation in accordance with 40 CFR Part 60, Appendix A, Methods 1-4 and 7E.

- m. Emission Limitation: NO_x emissions from burning number 2 fuel or on-spec used oil shall not exceed 20.4 lbs/hr;

Applicable Compliance Method: If required, the permittee shall demonstrate compliance with this emission limitation in accordance with 40 CFR Part 60, Appendix A, Methods 1-4 and 7E.

- n. Emission Limitation: NO_x emissions shall not exceed 17.4 tons per rolling 12-month period.

Applicable Compliance Method: Method: Compliance with the annual emissions limitation shall be determined by multiplying the observed emission rate from the most recent emissions testing, in pounds of NO_x per ton of asphalt produced, by the actual rolling 12 month summation of asphalt produced, in tons per rolling 12-month period, (as derived from the records required by term and condition C.3 above) and dividing by 2000.

- o. Emission Limitations: Arsenic, cadmium, chromium and lead emissions are limited by the fuel specifications in A.2.b.

Applicable Compliance Method: Compliance with the emissions limitation for arsenic, cadmium and lead shall be demonstrated by the monitoring and recordkeeping in Section C.3 of this permit.

- p. Emission Limitation: Visible particulate emissions from the stack shall not exceed 20% opacity as a 3-minute average.

Applicable Compliance Method: Compliance shall be determined using Method 9 as set forth in 40 CFR Part 60 Appendix A, as such appendix existed on July 1, 1996 and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

- q. Emission Limitation: No visible emissions of fugitive dust from the enclosures for the hot aggregate elevator, vibrating screens and weigh hopper.

Applicable Compliance Method: Compliance with the limitations on visible emissions of fugitive dust found in Section A.1 of this permit shall be demonstrated by the monitoring and record keeping in Section C.5.

- r. Emission Limitation: Visible emissions of fugitive dust (from areas other than the enclosures for the hot aggregate elevator, vibrating screens, and weigh hopper) shall be less than or equal to 10% opacity, as a 3-minute average.

Applicable Compliance Method: Compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

- s. Emissions Limitation: PM/PM-10 emissions from the stack shall not exceed 7.43 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be assumed as long as compliance is maintained with the rolling 12-month emissions limitation for particulate emissions.

- t. Emissions Limitation: Fugitive PM-10 emissions shall not exceed 1.02 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be assumed based upon the following worst case calculations:

Total fugitive emissions equal the summation of the fugitives from the cold end and the hot end of the plant operations.

Fugitives emissions from the cold end are calculated as follows

$((400,000 \text{ tons of material/year} \times 0.0024 \text{ lb PM-10/ton of material}) + (240,000 \text{ tons of aggregate/year} \times 0.0033 \text{ lb PM-10/ton of aggregate}) + (160,000 \text{ tons of sand/year} \times 0.00099 \text{ lb PM-10/ton of sand})) \times (1 \text{ ton}/2000 \text{ pounds}) = 0.96 \text{ tons of PM-10}$

Fugitives emissions from the hot end are calculated as follows

$(400,000 \text{ tons of asphalt produced} \times 0.0003 \text{ lb of PM-10/ton of asphalt produced}) \times (1 \text{ ton}/2000 \text{ pounds}) = 0.06 \text{ tons of PM-10.}$

Total fugitive emissions are therefore 1.02 tons.

The emission factors in the above equations are derived from AP-42, Fifth edition, Table 11.12-2(10/01) and from AP-42, Fifth edition, 11.1.2.5(12/00)

- u. Emissions Limitation: Fugitive PM emissions shall not exceed 2.08 tons per rolling 12-month period.

Applicable Compliance Method: Compliance with the annual emissions limitation shall be assumed based upon the following worst case calculations:

Total fugitive emissions equal the summation of the fugitives from the cold end and the hot end of the plant operations.

Fugitives emissions from the cold end are calculated as follows

$((400,000 \text{ tons of material/year} \times 0.0051 \text{ lb PM/ton of material}) + (240,000 \text{ tons of aggregate/year} \times 0.0069 \text{ lb PM/ton of aggregate}) + (160,000 \text{ tons of sand/year} \times 0.0021 \text{ lb PM/ton of sand})) \times (1 \text{ ton}/2000 \text{ pounds}) = 2.02 \text{ tons of PM}$

Fugitives emissions from the hot end are calculated as follows

$(400,000 \text{ tons of asphalt produced} \times 0.0003 \text{ lb of PM/ton of asphalt produced}) \times (1 \text{ ton}/2000 \text{ pounds}) = 0.06 \text{ tons of PM.}$

Total fugitive emissions are therefore 2.08 tons.

The emission factors in the above equations are derived from AP-42, Fifth edition, Table 11.12-2(10/01) and from AP-42, Fifth edition, 11.1.2.5(12/00)

- v. Emission Limitations: Emissions of fugitive PM-10 shall not exceed 1.02 pounds per hour when burning on-spec used oil or number 2 fuel oil.

Applicable Compliance Method: Compliance with this emissions limitation shall be assumed as long as compliance is maintained with the rolling 12-month operational restriction.

Shelly Materials Plant 63
PTI Application: 01-08692
Issued: To be entered upon final issuance

Facility ID: 0145020323
Emissions Unit ID: P901

- w. Emission Limitations: Emissions of fugitive PM shall not exceed 2.08 pounds per hour when burning on-spec used oil or number 2 fuel oil.

Applicable Compliance Method: Compliance with this emissions limitation shall be assumed as long as compliance is maintained with the rolling 12-month operational restriction.

F. Miscellaneous Requirements

- 1. The following source is subject to the applicable provision of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR part 60.

<u>Source Number</u>	<u>Source Description</u>	<u>NSPS Regulation (Subpart)</u>
P901	260 tph asphalt batch plant	Subpart I

The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

Pursuant to NSPS, the source owner/operator is hereby advised of the requirement to report the following at the appropriate times:

- 1. Construction date (no later than 30 days after such date);
- 2. Actual start-up date (within 15 days after such date); and
- 3. Date of performance testing (If required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency
DAPC- Air Quality Modeling and Planning
P.O. Box 1049
Columbus, OH 43216-1049

and

Central District Office
Division of Air Pollution Control
3232 Alum Creek Drive
Columbus, OH 43207

- 2. The terms and conditions of this PTI are federally enforceable.
- 3. This PTI replaces PTI number 01-8326, as issued on August 23, 2001.