



State of Ohio Environmental Protection Agency

Street Address:

Lazarus Gov. Center
122 S. Front Street
Columbus, OH 43215

TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

**RE: FINAL PERMIT TO INSTALL
COLUMBIANA COUNTY
Application No: 02-14795**

CERTIFIED MAIL

	TOXIC REVIEW
	PSD
	SYNTHETIC MINOR
	CEMS
	MACT
	NSPS
	NESHAPS
	NETTING
	MAJOR NON-ATTAINMENT
	MODELING SUBMITTED
	GASOLINE DISPENSING FACILITY

DATE: 7/24/2001

Polar Minerals Inc
Joseph Keating
2005 Newpoint Place Pkwy
Lawrenceville, GA 30043

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo, Manager
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA

NEDO



**Permit To Install
Terms and Conditions**

**Issue Date: 7/24/2001
Effective Date: 7/24/2001**

FINAL PERMIT TO INSTALL 02-14795

Application Number: 02-14795
APS Premise Number: 0215130332
Permit Fee: **\$3000**
Name of Facility: Polar Minerals Inc
Person to Contact: Joseph Keating
Address: 2005 Newpoint Place Pkwy
Lawrenceville, GA 30043

Location of proposed air contaminant source(s) [emissions unit(s)]:
**2400 Clark Ave
Wellsville, Ohio**

Description of proposed emissions unit(s):
3 grinders and 7 silos.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may

be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit to Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and

conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

<u>Pollutant</u>	<u>Tons Per Year</u>
PE	5.3 TPY

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
4 Product storage silos equipped with fabric filters	OAC rule 3745-31-05(A)(3)	PE: 0.01 grain per dry standard cubic foot of exhaust gases, 0.34 pound/hour and 1.5 tons per year. See A.I.2.a. Visible particulate emissions shall not exceed seven percent opacity
	OAC rule 3745-17-07	The emissions limit based on OAC rule 3745-17-07 is less stringent than the limit established pursuant to OAC rule 3745-31-05.
	OAC rule 3745-17-08	The emissions limit based on OAC rule 3745-17-08 is less stringent than the limit established pursuant to OAC rule 3745-31-05.
	40 CFR Part 60, Subpart OOO	The emissions limit based on 40 CFR 60, Subpart OOO is less stringent than the limit established pursuant to OAC rule 3745-31-05.

2. Additional Terms and Conditions

- 2.a** The permittee shall employ the following best available control measures for the purpose of ensuring compliance with the above-mentioned applicable requirements:
- i. The material shall be pneumatically transferred to the storage silos and to the hoppers. The pneumatic system shall be adequately enclosed so as to eliminate at all times visible emissions of fugitive dust.
 - ii. The storage silos shall be vented to fabric filters. The enclosure shall be sufficient so as to minimize at all times visible emissions of fugitive dust.

B. Operational Restrictions

1. The pressure drop across the baghouse shall be maintained within the range of 2 to 6 inches of water while the emissions unit is in operation.
2. The permittee shall regularly maintain the fabric filter control equipment associated with this emissions unit in accordance with the manufacturer's recommendations, instructions, and operating manual(s). Maintenance shall include but not be limited to regular repair and/or replacement of filters so as to maximize the particulate collection efficiency of this filter control system.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain equipment to monitor the pressure drop across the fabric filter while this emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a daily basis.
2. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible emissions from the stack(s) and/or any fugitive egress points serving this emissions unit. The presence or absence of any visible particulate emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall note the following in the operations log:
 - a. the color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. the total duration of any visible emission incident; and
 - e. any corrective action(s) taken to eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the fabric filter did not comply with the allowable range specified above.
2. The permittee shall submit semiannual written reports which (a) identify all days during which any visible emissions were observed from the stack(s) and/or any fugitive egress points serving this emissions unit, and (b) describe any corrective action(s) taken to eliminate the visible emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office) by January 31 and July 31 of each year and shall cover the previous 6-month period.

E. Testing Requirements

1. Emissions Limitation:
PE: 0.34 pounds per hour and 0.01 grain per dry standard cubic foot of exhaust gases

Applicable Compliance Method:

Compliance shall be demonstrated by the following equation:

$$E = [\text{bfr (cf/min)}] [0.01 \text{ gr/dscf}] [60 \text{ minutes/hour}] [1 \text{ pound/7000gr}]$$

where;

E = emission rate

bfr = baghouse flow rate

If required by the Ohio EPA, compliance with the particulate emission rate shall be determined in accordance 40 CFR Part 60, Appendix A, Methods 1 through 5, and the procedures outlined in OAC rule 3745-17-03.

2. Emissions Limitation:
PE: 1.5 tons per year

Applicable Compliance Method:

The annual particulate emission shall be determined by multiplying the annual number of hours the emissions unit operated by 0.34 pounds per hour of particulate emissions and then dividing by 2000 pounds per ton.

3. Emissions Limitation:
Seven percent opacity for visible particulate emissions

Polar Minerals Inc

PTI Application: 02-14795

Issued: 7/24/2001

Facility ID: 0215130332

Emissions Unit ID: F005

Applicable Compliance Method:

Compliance with the allowable visible emissions limitations shall be determined in accordance with 40 CFR Part 60, Appendix A, Method 9, the procedures outlined in OAC rule 3745-17-03, and the procedures outlined in 40 CFR Part 60.11.

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Jet mill grinding system equipped with a fabric filter	OAC rule 3745-31-05(A)(3)	PE: 0.01 grain per dry standard cubic foot of exhaust gases, 0.23 pound/hour and 1.0 ton per year.
		Visible particulate emissions shall not exceed seven percent opacity
	OAC rule 3745-17-11	The emissions limit based on OAC rule 3745-17-11 is less stringent than the limit established pursuant to OAC rule 3745-31-05.
	OAC rule 3745-17-07	The emissions limit based on OAC rule 3745-17-07 is less stringent than the limit established pursuant to OAC rule 3745-31-05.
	OAC rule 3745-17-08	The emissions limit based on OAC rule 3745-17-08 is less stringent than the limit established pursuant to OAC rule 3745-31-05.
	40 CFR Part 60, Subpart OOO	The emissions limit based on 40 CFR 60, Subpart OOO is less stringent than the limit established pursuant to OAC rule 3745-31-05.

2. Additional Terms and Conditions

2.a None

B. Operational Restrictions

1. The pressure drop across the baghouse shall be maintained within the range of 2 to 6 inches of water while the emissions unit is in operation.
2. The permittee shall regularly maintain the fabric filter control equipment associated with this emissions unit in accordance with the manufacturer's recommendations, instructions, and operating manual(s). Maintenance shall include but not be limited to regular repair and/or replacement of filters so as to maximize the particulate collection efficiency of this filter control system.
3. The collection efficiency of the associated capture hooding for this emissions unit shall be sufficient to minimize or eliminate visible particulate emissions of fugitive dust at all points of capture. The permittee shall maintain all capture hooding in good operating conditions. The collection efficiency shall be considered adequate, if visible particulate emissions of fugitive dust do not exceed ten percent opacity.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain equipment to monitor the pressure drop across the fabric filter while this emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a daily basis.
2. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible emissions from the stack(s) and/or any fugitive egress points serving this emissions unit. The presence or absence of any visible particulate emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall note the following in the operations log:
 - a. the color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. the total duration of any visible emission incident; and
 - e. any corrective action(s) taken to eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the fabric filter did not comply with the allowable range specified above.
2. The permittee shall submit semiannual written reports which (a) identify all days during which any visible emissions were observed from the stack(s) and/or any fugitive egress points serving this emissions unit, and (b) describe any corrective action(s) taken to eliminate the visible emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office) by January 31 and July 31 of each year and shall cover the previous 6-month period.

E. Testing Requirements

1. Emissions Limitation:
PE: 0.23 pounds per hour and 0.01 grain per dry standard cubic foot of exhaust gases

Applicable Compliance Method:

Compliance shall be demonstrated by the following equation:

$$E = [\text{bfr (cf/min)}] [0.01 \text{ gr/dscf}] [60 \text{ minutes/hour}] [1 \text{ pound/7000gr}]$$

where;

E = emission rate

bfr = baghouse flow rate

If required by the Ohio EPA, compliance with the particulate emission rate shall be determined in accordance 40 CFR Part 60, Appendix A, Methods 1 through 5, and the procedures outlined in OAC rule 3745-17-03.

2. Emissions Limitation:
PE: 1.0 ton per year

Applicable Compliance Method:

The annual particulate emission shall be determined by multiplying the annual number of hours the emissions unit operated by 0.23 pounds per hour of particulate emissions and then dividing by 2000 pounds per ton.

3. Emissions Limitation:
Seven percent opacity for visible particulate emissions

Polar Minerals Inc

PTI Application: 02-14795

Issued: 7/24/2001

Facility ID: 0215130332

Emissions Unit ID: P012

Applicable Compliance Method:

Compliance with the allowable visible emissions limitations shall be determined in accordance with 40 CFR Part 60, Appendix A, Method 9, the procedures outlined in OAC rule 3745-17-03, and the procedures outlined in 40 CFR Part 60.11.

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Jet Mill grinding system equipped with a fabric filter	OAC rule 3745-31-05(A)(3)	PE: 0.01 grain per dry standard cubic foot of exhaust gases, 0.23 pound/hour and 1.0 ton per year.
		Visible particulate emissions shall not exceed seven percent opacity
	OAC rule 3745-17-11	The emissions limit based on OAC rule 3745-17-11 is less stringent than the limit established pursuant to OAC rule 3745-31-05.
	OAC rule 3745-17-07	The emissions limit based on OAC rule 3745-17-07 is less stringent than the limit established pursuant to OAC rule 3745-31-05.
	OAC rule 3745-17-08	The emissions limit based on OAC rule 3745-17-08 is less stringent than the limit established pursuant to OAC rule 3745-31-05.
	40 CFR Part 60, Subpart OOO	The emissions limit based on 40 CFR 60, Subpart OOO is less stringent than the limit established pursuant to OAC rule 3745-31-05.

2. Additional Terms and Conditions

2.a None

B. Operational Restrictions

1. The pressure drop across the baghouse shall be maintained within the range of 2 to 6 inches of water while the emissions unit is in operation.
2. The permittee shall regularly maintain the fabric filter control equipment associated with this emissions unit in accordance with the manufacturer's recommendations, instructions, and operating manual(s). Maintenance shall include but not be limited to regular repair and/or replacement of filters so as to maximize the particulate collection efficiency of this filter control system.
3. The collection efficiency of the associated capture hooding for this emissions unit shall be sufficient to minimize or eliminate visible particulate emissions of fugitive dust at all points of capture. The permittee shall maintain all capture hooding in good operating conditions. The collection efficiency shall be considered adequate, if visible particulate emissions of fugitive dust do not exceed ten percent opacity.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain equipment to monitor the pressure drop across the fabric filter while this emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a daily basis.
2. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible emissions from the stack(s) and/or any fugitive egress points serving this emissions unit. The presence or absence of any visible particulate emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall note the following in the operations log:
 - a. the color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. the total duration of any visible emission incident; and
 - e. any corrective action(s) taken to eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the fabric filter did not comply with the allowable range specified above.
2. The permittee shall submit semiannual written reports which (a) identify all days during which any visible emissions were observed from the stack(s) and/or any fugitive egress points serving this emissions unit, and (b) describe any corrective action(s) taken to eliminate the visible emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office) by January 31 and July 31 of each year and shall cover the previous 6-month period.

E. Testing Requirements

1. Emissions Limitation:
PE: 0.23 pounds per hour and 0.01 grain per dry standard cubic foot of exhaust gases

Applicable Compliance Method:

Compliance shall be demonstrated by the following equation:

$$E = [\text{bfr (cf/min)}] [0.01 \text{ gr/dscf}] [60 \text{ minutes/hour}] [1 \text{ pound/7000gr}]$$

where;

E = emission rate

bfr = baghouse flow rate

If required by the Ohio EPA, compliance with the particulate emission rate shall be determined in accordance 40 CFR Part 60, Appendix A, Methods 1 through 5, and the procedures outlined in OAC rule 3745-17-03.

2. Emissions Limitation:
PE: 1.0 ton per year

Applicable Compliance Method:

The annual particulate emission shall be determined by multiplying the annual number of hours the emissions unit operated by 0.23 pounds per hour of particulate emissions and then dividing by 2000 pounds per ton.

3. Emissions Limitation:
Seven percent opacity for visible particulate emissions

Polar Minerals Inc

PTI Application: 02-14795

Issued: 7/24/2001

Facility ID: 0215130332

Emissions Unit ID: P013

Applicable Compliance Method:

Compliance with the allowable visible emissions limitations shall be determined in accordance with 40 CFR Part 60, Appendix A, Method 9, the procedures outlined in OAC rule 3745-17-03, and the procedures outlined in 40 CFR Part 60.11.

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Jet mill grinding system equipped with a fabric filter	OAC rule 3745-31-05(A)(3)	PE: 0.01 grain per dry standard cubic foot of exhaust gases, 0.23 pound/hour and 1.0 ton per year.
		Visible particulate emissions shall not exceed seven percent opacity
	OAC rule 3745-17-11	The emissions limit based on OAC rule 3745-17-11 is less stringent than the limit established pursuant to OAC rule 3745-31-05.
	OAC rule 3745-17-07	The emissions limit based on OAC rule 3745-17-07 is less stringent than the limit established pursuant to OAC rule 3745-31-05.
	OAC rule 3745-17-08	The emissions limit based on OAC rule 3745-17-08 is less stringent than the limit established pursuant to OAC rule 3745-31-05.
	40 CFR Part 60, Subpart OOO	The emissions limit based on 40 CFR 60, Subpart OOO is less stringent than the limit established pursuant to OAC rule 3745-31-05.

2. Additional Terms and Conditions

2.a None

B. Operational Restrictions

1. The pressure drop across the baghouse shall be maintained within the range of 2 to 6 inches of water while the emissions unit is in operation.
2. The permittee shall regularly maintain the fabric filter control equipment associated with this emissions unit in accordance with the manufacturer's recommendations, instructions, and operating manual(s). Maintenance shall include but not be limited to regular repair and/or replacement of filters so as to maximize the particulate collection efficiency of this filter control system.
3. The collection efficiency of the associated capture hooding for this emissions unit shall be sufficient to minimize or eliminate visible particulate emissions of fugitive dust at all points of capture. The permittee shall maintain all capture hooding in good operating conditions. The collection efficiency shall be considered adequate, if visible particulate emissions of fugitive dust do not exceed ten percent opacity.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain equipment to monitor the pressure drop across the fabric filter while this emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a daily basis.
2. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible emissions from the stack(s) and/or any fugitive egress points serving this emissions unit. The presence or absence of any visible particulate emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall note the following in the operations log:
 - a. the color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. the total duration of any visible emission incident; and
 - e. any corrective action(s) taken to eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the fabric filter did not comply with the allowable range specified above.
2. The permittee shall submit semiannual written reports which (a) identify all days during which any visible emissions were observed from the stack(s) and/or any fugitive egress points serving this emissions unit, and (b) describe any corrective action(s) taken to eliminate the visible emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office) by January 31 and July 31 of each year and shall cover the previous 6-month period.

E. Testing Requirements

1. Emissions Limitation:
PE: 0.23 pounds per hour and 0.01 grain per dry standard cubic foot of exhaust gases

Applicable Compliance Method:

Compliance shall be demonstrated by the following equation:

$$E = [\text{bfr (cf/min)}] [0.01 \text{ gr/dscf}] [60 \text{ minutes/hour}] [1 \text{ pound/7000gr}]$$

where;

E = emission rate

bfr = baghouse flow rate

If required by the Ohio EPA, compliance with the particulate emission rate shall be determined in accordance 40 CFR Part 60, Appendix A, Methods 1 through 5, and the procedures outlined in OAC rule 3745-17-03.

2. Emissions Limitation:
PE: 1.0 ton per year

Applicable Compliance Method:

The annual particulate emission shall be determined by multiplying the annual number of hours the emissions unit operated by 0.23 pounds per hour of particulate emissions and then dividing by 2000 pounds per ton.

3. Emissions Limitation:
Seven percent opacity for visible particulate emissions

Polar Minerals Inc

PTI Application: 02-14795

Issued: 7/24/2001

Facility ID: 0215130332

Emissions Unit ID: P014

Applicable Compliance Method:

Compliance with the allowable visible emissions limitations shall be determined in accordance with 40 CFR Part 60, Appendix A, Method 9, the procedures outlined in OAC rule 3745-17-03, and the procedures outlined in 40 CFR Part 60.11.

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Feed silo equipped with fabric filter	OAC rule 3745-31-05(A)(3)	PE: 0.01 grain per dry standard cubic foot of exhaust gases, 0.09 pound/hour and 0.4 ton per year. See A.I.2.a. Visible particulate emissions shall not exceed seven percent opacity
	OAC rule 3745-17-07	The emissions limit based on OAC rule 3745-17-07 is less stringent than the limit established pursuant to OAC rule 3745-31-05.
	OAC rule 3745-17-08	The emissions limit based on OAC rule 3745-17-08 is less stringent than the limit established pursuant to OAC rule 3745-31-05.
	40 CFR Part 60, Subpart OOO	The emissions limit based on 40 CFR 60, Subpart OOO is less stringent than the limit established pursuant to OAC rule 3745-31-05.

2. Additional Terms and Conditions

- 2.a** The permittee shall employ the following best available control measures for the purpose of ensuring compliance with the above-mentioned applicable requirements:
- i. The material shall be pneumatically transferred to the feed silo and to the hoppers. The pneumatic system shall be adequately enclosed so as to eliminate at all times visible emissions of fugitive dust.
 - ii. The feed silo shall be vented to fabric filter. The enclosure shall be sufficient so as to minimize at all times visible emissions of fugitive dust.

B. Operational Restrictions

1. The pressure drop across the baghouse shall be maintained within the range of 2 to 6 inches of water while the emissions unit is in operation.
2. The permittee shall regularly maintain the fabric filter control equipment associated with this emissions unit in accordance with the manufacturer's recommendations, instructions, and operating manual(s). Maintenance shall include but not be limited to regular repair and/or replacement of filters so as to maximize the particulate collection efficiency of this filter control system.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain equipment to monitor the pressure drop across the fabric filter while this emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a daily basis.
2. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible emissions from the stack(s) and/or any fugitive egress points serving this emissions unit. The presence or absence of any visible particulate emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall note the following in the operations log:
 - a. the color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. the total duration of any visible emission incident; and
 - e. any corrective action(s) taken to eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the fabric filter did not comply with the allowable range specified above.
2. The permittee shall submit semiannual written reports which (a) identify all days during which any visible emissions were observed from the stack(s) and/or any fugitive egress points serving this emissions unit, and (b) describe any corrective action(s) taken to eliminate the visible emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office) by January 31 and July 31 of each year and shall cover the previous 6-month period.

E. Testing Requirements

1. Emissions Limitation:
PE: 0.09 pounds per hour and 0.01 grain per dry standard cubic foot of exhaust gases

Applicable Compliance Method:

Compliance shall be demonstrated by the following equation:

$$E = [\text{bfr (cf/min)}] [0.01 \text{ gr/dscf}] [60 \text{ minutes/hour}] [1 \text{ pound/7000gr}]$$

where;

E = emission rate

bfr = baghouse flow rate

If required by the Ohio EPA, compliance with the particulate emission rate shall be determined in accordance 40 CFR Part 60, Appendix A, Methods 1 through 5, and the procedures outlined in OAC rule 3745-17-03.

2. Emissions Limitation:
PE: 0.4 ton per year

Applicable Compliance Method:

The annual particulate emission shall be determined by multiplying the annual number of hours the emissions unit operated by 0.09 pounds per hour of particulate emissions and then dividing by 2000 pounds per ton.

3. Emissions Limitation:
Seven percent opacity for visible particulate emissions

Polar Minerals Inc

PTI Application: 02-14795

Issued: 7/24/2001

Facility ID: 0215130332

Emissions Unit ID: P015

Applicable Compliance Method:

Compliance with the allowable visible emissions limitations shall be determined in accordance with 40 CFR Part 60, Appendix A, Method 9, the procedures outlined in OAC rule 3745-17-03, and the procedures outlined in 40 CFR Part 60.11.

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
Feed silo equipped with fabric filter	OAC rule 3745-31-05(A)(3)	PE: 0.01 grain per dry standard cubic foot of exhaust gases, 0.09 pound/hour and 0.4 ton per year. See A.I.2.a. Visible particulate emissions shall not exceed seven percent opacity
	OAC rule 3745-17-07	The emissions limit based on OAC rule 3745-17-07 is less stringent than the limit established pursuant to OAC rule 3745-31-05.
	OAC rule 3745-17-08	The emissions limit based on OAC rule 3745-17-08 is less stringent than the limit established pursuant to OAC rule 3745-31-05.
	40 CFR Part 60, Subpart OOO	The emissions limit based on 40 CFR 60, Subpart OOO is less stringent than the limit established pursuant to OAC rule 3745-31-05.

2. Additional Terms and Conditions

- 2.a** The permittee shall employ the following best available control measures for the purpose of ensuring compliance with the above-mentioned applicable requirements:
- i. The material shall be pneumatically transferred to the feed silo and to the hoppers. The pneumatic system shall be adequately enclosed so as to eliminate at all times visible emissions of fugitive dust.
 - ii. The feed silo shall be vented to fabric filter. The enclosure shall be sufficient so as to minimize at all times visible emissions of fugitive dust.

B. Operational Restrictions

1. The pressure drop across the baghouse shall be maintained within the range of 2 to 6 inches of water while the emissions unit is in operation.
2. The permittee shall regularly maintain the fabric filter control equipment associated with this emissions unit in accordance with the manufacturer's recommendations, instructions, and operating manual(s). Maintenance shall include but not be limited to regular repair and/or replacement of filters so as to maximize the particulate collection efficiency of this filter control system.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall operate and maintain equipment to monitor the pressure drop across the fabric filter while this emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a daily basis.
2. The permittee shall perform weekly checks, when the emissions unit is in operation and when the weather conditions allow, for any visible emissions from the stack(s) and/or any fugitive egress points serving this emissions unit. The presence or absence of any visible particulate emissions shall be noted in an operations log. If visible emissions are observed, the permittee shall note the following in the operations log:
 - a. the color of the emissions;
 - b. whether the emissions are representative of normal operations;
 - c. if the emissions are not representative of normal operations, the cause of the abnormal emissions;
 - d. the total duration of any visible emission incident; and
 - e. any corrective action(s) taken to eliminate the visible emissions.

D. Reporting Requirements

1. The permittee shall submit pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the fabric filter did not comply with the allowable range specified above.
2. The permittee shall submit semiannual written reports which (a) identify all days during which any visible emissions were observed from the stack(s) and/or any fugitive egress points serving this emissions unit, and (b) describe any corrective action(s) taken to eliminate the visible emissions. These reports shall be submitted to the Director (the appropriate Ohio EPA District Office) by January 31 and July 31 of each year and shall cover the previous 6-month period.

E. Testing Requirements

1. Emissions Limitation:
PE: 0.09 pounds per hour and 0.01 grain per dry standard cubic foot of exhaust gases

Applicable Compliance Method:

Compliance shall be demonstrated by the following equation:

$$E = [\text{bfr (cf/min)}] [0.01 \text{ gr/dscf}] [60 \text{ minutes/hour}] [1 \text{ pound/7000gr}]$$

where;

E = emission rate

bfr = baghouse flow rate

If required by the Ohio EPA, compliance with the particulate emission rate shall be determined in accordance 40 CFR Part 60, Appendix A, Methods 1 through 5, and the procedures outlined in OAC rule 3745-17-03.

2. Emissions Limitation:
PE: 0.4 ton per year

Applicable Compliance Method:

The annual particulate emission shall be determined by multiplying the annual number of hours the emissions unit operated by 0.09 pounds per hour of particulate emissions and then dividing by 2000 pounds per ton.

3. Emissions Limitation:
Seven percent opacity for visible particulate emissions

Applicable Compliance Method:

Compliance with the allowable visible emissions limitations shall be determined in accordance with 40 CFR Part 60, Appendix A, Method 9, the procedures outlined in OAC rule 3745-17-03, and the procedures outlined in 40 CFR Part 60.11.

F. Miscellaneous Requirements

None

NEW SOURCE REVIEW FORM B

PTI Number: 02-14795

Facility ID: 0215130332

FACILITY NAME Polar Minerals Inc

FACILITY DESCRIPTION Non-Metallic Mineral Processing Facility CITY/TWP Wellsville

SIC CODE 5050 SCC CODE 3-05-089-11 EMISSIONS UNIT ID F005

EMISSIONS UNIT DESCRIPTION 4 product storage silos equipped with fabric filters

DATE INSTALLED 05/01

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment	0.34 lb/hr	0.75 tpy	0.34 lb/hr	1.5 tpy
PM ₁₀					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? OOO NESHAP? _____ PSD? _____ OFFSET POLICY? _____

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination: Use of a fabric filter baghouse

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N/A

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ N/A

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES _____ X NO

IDENTIFY THE AIR CONTAMINANTS: _____

NEW SOURCE REVIEW FORM B

PTI Number: 02-14795

Facility ID: 0215130332

FACILITY NAME Polar Minerals Inc

FACILITY DESCRIPTION Non-Metallic Mineral Processing Facility CITY/TWP Wellsville

SIC CODE 5050 SCC CODE 3-05-089-11 EMISSIONS UNIT ID P012

EMISSIONS UNIT DESCRIPTION Jet mill grinding system equipped with a fabric filter

DATE INSTALLED 05/01

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment	0.23 lb/hr	0.5 tpy	0.23 lb/hr	1.0 tpy
PM ₁₀					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? OOO

NESHAP?

PSD?

OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination: Use of a fabric filter baghouse

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

N/A

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

\$ N/A

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*?

YES

X NO

IDENTIFY THE AIR CONTAMINANTS:

NEW SOURCE REVIEW FORM B

PTI Number: 02-14795

Facility ID: 0215130332

FACILITY NAME Polar Minerals Inc

FACILITY DESCRIPTION Non-Metallic Mineral Processing Facility CITY/TWP Wellsville

SIC CODE 5050 SCC CODE 3-05-089-11 EMISSIONS UNIT ID P013

EMISSIONS UNIT DESCRIPTION Jet Mill grinding system equipped with a fabric filter

DATE INSTALLED 05/01

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment	0.23 lb/hr	0.5 tpy	0.23 lb/hr	1.0 tpy
PM ₁₀					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? 000

NESHAP?

PSD?

OFFSET POLICY?

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination: Use of a fabric filter baghouse

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY?

N/A

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT?

\$ N/A

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*?

YES

X

NO

IDENTIFY THE AIR CONTAMINANTS:

NEW SOURCE REVIEW FORM B

PTI Number: 02-14795

Facility ID: 0215130332

FACILITY NAME Polar Minerals Inc

FACILITY DESCRIPTION Non-Metallic Mineral Processing Facility CITY/TWP Wellsville

SIC CODE 5050 SCC CODE 3-05-089-11 EMISSIONS UNIT ID P014

EMISSIONS UNIT DESCRIPTION Jet mill grinding system equipped with a fabric filter

DATE INSTALLED 05/01

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment	0.23 lb/hr	0.5 tpy	0.23 lb/hr	1.0 tpy
PM ₁₀					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? OOO NESHAP? _____ PSD? _____ OFFSET POLICY? _____

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination: Use of a fabric filter baghouse

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N/A

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ N/A

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES X NO

IDENTIFY THE AIR CONTAMINANTS: _____

NEW SOURCE REVIEW FORM B

PTI Number: 02-14795

Facility ID: 0215130332

FACILITY NAME Polar Minerals Inc

FACILITY DESCRIPTION Non-Metallic Mineral Processing Facility CITY/TWP Wellsville

SIC CODE 5050 SCC CODE 3-05-089-11 EMISSIONS UNIT ID P015

EMISSIONS UNIT DESCRIPTION Feed silo equipped with fabric filter

DATE INSTALLED 05/01

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment	0.09 lb/hr	0.2 tpy	0.09 lb/hr	0.4 tpy
PM ₁₀					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? OOO NESHAP? _____ PSD? _____ OFFSET POLICY? _____

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination: Use of a fabric filter baghouse

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N/A

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ N/A

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES _____ X NO

IDENTIFY THE AIR CONTAMINANTS: _____

NEW SOURCE REVIEW FORM B

PTI Number: 02-14795

Facility ID: 0215130332

FACILITY NAME Polar Minerals Inc

FACILITY DESCRIPTION Non-Metallic Mineral Processing Facility CITY/TWP Wellsville

SIC CODE 5050 SCC CODE 3-05-089-11 EMISSIONS UNIT ID P016

EMISSIONS UNIT DESCRIPTION Feed silo equipped with fabric filter

DATE INSTALLED 05/01

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment	0.09 lb/hr	0.2 tpy	0.09 lb/hr	0.4 tpy
PM ₁₀					
Sulfur Dioxide					
Organic Compounds					
Nitrogen Oxides					
Carbon Monoxide					
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? 000 NESHAP? _____ PSD? _____ OFFSET POLICY? _____

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?

Enter Determination: Use of a fabric filter baghouse

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? N/A

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? \$ N/A

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES _____ X NO

IDENTIFY THE AIR CONTAMINANTS: _____