



State of Ohio Environmental Protection Agency

Street Address:

Lazarus Gov. Center
122 S. Front Street
Columbus, OH 43215

TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

**RE: FINAL PERMIT TO INSTALL
SANDUSKY COUNTY
Application No: 03-16167**

CERTIFIED MAIL

	TOXIC REVIEW
	PSD
	SYNTHETIC MINOR
	CEMS
	MACT
KK	NSPS
	NESHAPS
	NETTING
	MAJOR NON-ATTAINMENT
	MODELING SUBMITTED
	GASOLINE DISPENSING FACILITY

DATE: 8/12/2004

Crown Battery Manufacturing Company
Robert Michael
990 1445 Majestic Drive
Fremont, OH 43420-0990

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern, Supervisor
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA

NWDO



Permit To Install
Terms and Conditions

Issue Date: 8/12/2004
Effective Date: 8/12/2004

FINAL PERMIT TO INSTALL 03-16167

Application Number: 03-16167
APS Premise Number: 0372030089
Permit Fee: **\$3700**
Name of Facility: Crown Battery Manufacturing Company
Person to Contact: Robert Michael
Address: 990 1445 Majestic Drive
Fremont, OH 43420-0990

Location of proposed air contaminant source(s) [emissions unit(s)]:
**1445 Majestic Drive
Fremont, Ohio**

Description of proposed emissions unit(s):
Modification to increase PE limit for P016 - P028 and installation of 4 new grid casting machines.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may

be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions

and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
PE	1.31
Pb	0.22

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P016 - Grid casting machine #1 serviced by lead melting pot #1 (modification to PTI 03-13450 issued 7/10/01 to increase PE limit)	OAC rule 3745-31-05 (A)(3)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart KK. Use of baghouse (See A.2.a) 0.30 lbs particulate emissions (PE)/hr, 1.31 tons PE/yr (See A.2.b & A.2.c) 0.05 lb lead (Pb)/hr, 0.22 tons Pb/yr (See A.2.c)
	40 CFR Part 60 Subpart KK	See A.2.d & A.2.e
	OAC rule 3745-17-07 (A)	See A.2.f
	OAC rule 3745-17-11(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) for this emissions unit has been determined to be the use of a baghouse with a 99% control efficiency.
- 2.b The particulate emission limitation is inclusive of lead emissions.
- 2.c The emission limitation established represents a combined allowable for emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036 and P037.

- 2.d The permittee shall not cause to be discharged into the atmosphere any gases that contain lead in excess of 0.51 milligram/dry standard cubic meter (0.0002229 grains per dry standard cubic foot) as determined in accordance with 40 CFR Part 60.372 (b).
- 2.e The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.
- 2.f The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The pressure drop across the baghouse shall be maintained within the range of 1 to 2.5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted in accordance with the general terms and conditions of this permit.

E. Testing Requirements

- 1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation: 0.30 lb PE/hr, 1.31 ton PE/yr

Applicable Compliance Method: The 0.30 lb/hr limitation represents the combined potential particulate emissions from emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036, and P037 based on a December 9, 2003 stack test. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 5 of 40 CFR Part 60, Appendix A

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.05 lb Pb/hr, 0.22 ton Pb/yr

Applicable Compliance Method: The hourly emission limitation was developed by multiplying the outlet grain loading of 0.0002229 gr/dscf by the maximum volumetric air flow rate of 25,000 acfm, then multiplying by 60 min/hour and dividing by 7000 gr/lb. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.0002229 gr Pb/dscf

Applicable Compliance Method: If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

Emission Limitation: The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. The emissions unit is subject to the applicable provisions of Subpart KK of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P017 - Grid casting machines # 2&3 serviced by lead melting pot #2 (modification to PTI 03-13450 issued on 7/10/01 to increase the PE limit)	OAC rule 3745-31-05 (A)(3)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart KK. Use of baghouse (See A.2.a) 0.30 lbs particulate emissions (PE)/hr, 1.31 tons PE/yr (See A.2.b & A.2.c) 0.05 lb lead (Pb)/hr, 0.22 tons Pb/yr (See A.2.c)
	40 CFR Part 60 Subpart KK	See A.2.d & A.2.e
	OAC rule 3745-17-07 (A)	See A.2.f
	OAC rule 3745-17-11(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) for this emissions unit has been determined to be the use of a baghouse with a 99% control efficiency.
- 2.b The particulate emission limitation is inclusive of lead emissions.
- 2.c The emission limitation established represents a combined allowable for emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036 and P037.

- 2.d The permittee shall not cause to be discharged into the atmosphere any gases that contain lead in excess of 0.51 milligram/dry standard cubic meter (0.0002229 grains per dry standard cubic foot) as determined in accordance with 40 CFR Part 60.372 (b).
- 2.e The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.
- 2.f The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The pressure drop across the baghouse shall be maintained within the range of 1 to 2.5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted in accordance with the general terms and conditions of this permit.

E. Testing Requirements

- 1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation: 0.30 lb PE/hr, 1.31 ton PE/yr

Applicable Compliance Method: The 0.30 lb/hr limitation represents the combined potential particulate emissions from emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036, and P037 based on a December 9, 2003 stack test. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 5 of 40 CFR Part 60, Appendix A

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.05 lb Pb/hr, 0.22 ton Pb/yr

Applicable Compliance Method: The hourly emission limitation was developed by multiplying the outlet grain loading of 0.0002229 gr/dscf by the maximum volumetric air flow rate of 25,000 acfm, then multiplying by 60 min/hour and dividing by 7000 gr/lb. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.0002229 gr Pb/dscf

Applicable Compliance Method: If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

Emission Limitation: The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. The emissions unit is subject to the applicable provisions of Subpart KK of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P018 - Grid casting machine #4&5 serviced by lead melting pot #3 (modification to PTI 03-13450 issued on 7/10/01 to increase PE limit)	OAC rule 3745-31-05 (A)(3)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart KK. Use of baghouse (See A.2.a) 0.30 lbs particulate emissions (PE)/hr, 1.31 tons PE/yr (See A.2.b & A.2.c) 0.05 lb lead (Pb)/hr, 0.22 tons Pb/yr (See A.2.c)
	40 CFR Part 60 Subpart KK	See A.2.d & A.2.e
	OAC rule 3745-17-07 (A)	See A.2.f
	OAC rule 3745-17-11(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) for this emissions unit has been determined to be the use of a baghouse with a 99% control efficiency.
- 2.b The particulate emission limitation is inclusive of lead emissions.
- 2.c The emission limitation established represents a combined allowable for emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036 and P037.

- 2.d The permittee shall not cause to be discharged into the atmosphere any gases that contain lead in excess of 0.51 milligram/dry standard cubic meter (0.0002229 grains per dry standard cubic foot) as determined in accordance with 40 CFR Part 60.372 (b).
- 2.e The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.
- 2.f The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The pressure drop across the baghouse shall be maintained within the range of 1 to 2.5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted in accordance with the general terms and conditions of this permit.

E. Testing Requirements

- 1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation: 0.30 lb PE/hr, 1.31 ton PE/yr

Applicable Compliance Method: The 0.30 lb/hr limitation represents the combined potential particulate emissions from emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036, and P037 based on a December 9, 2003 stack test. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 5 of 40 CFR Part 60, Appendix A

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.05 lb Pb/hr, 0.22 ton Pb/yr

Applicable Compliance Method: The hourly emission limitation was developed by multiplying the outlet grain loading of 0.0002229 gr/dscf by the maximum volumetric air flow rate of 25,000 acfm, then multiplying by 60 min/hour and dividing by 7000 gr/lb. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.0002229 gr Pb/dscf

Applicable Compliance Method: If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

Emission Limitation: The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. The emissions unit is subject to the applicable provisions of Subpart KK of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P019 - Grid casting machines #6&7 serviced by lead melting pot #4 (modification to PTI 03-13450 issued 7/10/01 to increase PE limit)	OAC rule 3745-31-05 (A)(3)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart KK. Use of baghouse (See A.2.a) 0.30 lbs particulate emissions (PE)/hr, 1.31 tons PE/yr (See A.2.b & A.2.c) 0.05 lb lead (Pb)/hr, 0.22 tons Pb/yr (See A.2.c)
	40 CFR Part 60 Subpart KK	See A.2.d & A.2.e
	OAC rule 3745-17-07 (A)	See A.2.f
	OAC rule 3745-17-11(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) for this emissions unit has been determined to be the use of a baghouse with a 99% control efficiency.
- 2.b The particulate emission limitation is inclusive of lead emissions.
- 2.c The emission limitation established represents a combined allowable for emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036 and P037.

- 2.d The permittee shall not cause to be discharged into the atmosphere any gases that contain lead in excess of 0.51 milligram/dry standard cubic meter (0.0002229 grains per dry standard cubic foot) as determined in accordance with 40 CFR Part 60.372 (b).
- 2.e The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.
- 2.f The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The pressure drop across the baghouse shall be maintained within the range of 1 to 2.5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted in accordance with the general terms and conditions of this permit.

E. Testing Requirements

- 1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation: 0.30 lb PE/hr, 1.31 ton PE/yr

Applicable Compliance Method: The 0.30 lb/hr limitation represents the combined potential particulate emissions from emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036, and P037 based on a December 9, 2003 stack test. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 5 of 40 CFR Part 60, Appendix A

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.05 lb Pb/hr, 0.22 ton Pb/yr

Applicable Compliance Method: The hourly emission limitation was developed by multiplying the outlet grain loading of 0.0002229 gr/dscf by the maximum volumetric air flow rate of 25,000 acfm, then multiplying by 60 min/hour and dividing by 7000 gr/lb. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.0002229 gr Pb/dscf

Applicable Compliance Method: If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

Emission Limitation: The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. The emissions unit is subject to the applicable provisions of Subpart KK of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P020 - Grid casting machines # 8&9 serviced by lead melting pot #5 (modification to PTI 03-13450 issued on 7/10/01 to increase PE limit)	OAC rule 3745-31-05 (A)(3)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart KK. Use of baghouse (See A.2.a) 0.30 lbs particulate emissions (PE)/hr, 1.31 tons PE/yr (See A.2.b & A.2.c) 0.05 lb lead (Pb)/hr, 0.22 tons Pb/yr (See A.2.c)
	40 CFR Part 60 Subpart KK	See A.2.d & A.2.e
	OAC rule 3745-17-07 (A)	See A.2.f
	OAC rule 3745-17-11(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) for this emissions unit has been determined to be the use of a baghouse with a 99% control efficiency.
- 2.b The particulate emission limitation is inclusive of lead emissions.
- 2.c The emission limitation established represents a combined allowable for emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036 and P037.

- 2.d The permittee shall not cause to be discharged into the atmosphere any gases that contain lead in excess of 0.51 milligram/dry standard cubic meter (0.0002229 grains per dry standard cubic foot) as determined in accordance with 40 CFR Part 60.372 (b).
- 2.e The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.
- 2.f The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The pressure drop across the baghouse shall be maintained within the range of 1 to 2.5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted in accordance with the general terms and conditions of this permit.

E. Testing Requirements

- 1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation: 0.30 lb PE/hr, 1.31 ton PE/yr

Applicable Compliance Method: The 0.30 lb/hr limitation represents the combined potential particulate emissions from emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036, and P037 based on a December 9, 2003 stack test. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 5 of 40 CFR Part 60, Appendix A

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.05 lb Pb/hr, 0.22 ton Pb/yr

Applicable Compliance Method: The hourly emission limitation was developed by multiplying the outlet grain loading of 0.0002229 gr/dscf by the maximum volumetric air flow rate of 25,000 acfm, then multiplying by 60 min/hour and dividing by 7000 gr/lb. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.0002229 gr Pb/dscf

Applicable Compliance Method: If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

Emission Limitation: The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. The emissions unit is subject to the applicable provisions of Subpart KK of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P021 - Grid casting machine #10 serviced by lead melting pot #6 (modification to PTI 03-13450 issued on 7/10/01 to increase PE limit)	OAC rule 3745-31-05 (A)(3)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart KK. Use of baghouse (See A.2.a) 0.30 lbs particulate emissions (PE)/hr, 1.31 tons PE/yr (See A.2.b & A.2.c) 0.05 lb lead (Pb)/hr, 0.22 tons Pb/yr (See A.2.c)
	40 CFR Part 60 Subpart KK	See A.2.d & A.2.e
	OAC rule 3745-17-07 (A)	See A.2.f
	OAC rule 3745-17-11(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) for this emissions unit has been determined to be the use of a baghouse with a 99% control efficiency.
- 2.b The particulate emission limitation is inclusive of lead emissions.
- 2.c The emission limitation established represents a combined allowable for emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036 and P037.

- 2.d The permittee shall not cause to be discharged into the atmosphere any gases that contain lead in excess of 0.51 milligram/dry standard cubic meter (0.0002229 grains per dry standard cubic foot) as determined in accordance with 40 CFR Part 60.372 (b).
- 2.e The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.
- 2.f The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The pressure drop across the baghouse shall be maintained within the range of 1 to 2.5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted in accordance with the general terms and conditions of this permit.

E. Testing Requirements

- 1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation: 0.30 lb PE/hr, 1.31 ton PE/yr

Applicable Compliance Method: The 0.30 lb/hr limitation represents the combined potential particulate emissions from emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036, and P037 based on a December 9, 2003 stack test. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 5 of 40 CFR Part 60, Appendix A

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.05 lb Pb/hr, 0.22 ton Pb/yr

Applicable Compliance Method: The hourly emission limitation was developed by multiplying the outlet grain loading of 0.0002229 gr/dscf by the maximum volumetric air flow rate of 25,000 acfm, then multiplying by 60 min/hour and dividing by 7000 gr/lb. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.0002229 gr Pb/dscf

Applicable Compliance Method: If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

Emission Limitation: The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. The emissions unit is subject to the applicable provisions of Subpart KK of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P022 - Grid casting machines #11,12&13 serviced by lead melting pot #7 (modification to PTI 03-13450 issued on 7/10/01 to increase PE limit)	OAC rule 3745-31-05 (A)(3)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart KK. Use of baghouse (See A.2.a) 0.30 lbs particulate emissions (PE)/hr, 1.31 tons PE/yr (See A.2.b & A.2.c) 0.05 lb lead (Pb)/hr, 0.22 tons Pb/yr (See A.2.c)
	40 CFR Part 60 Subpart KK	See A.2.d & A.2.e
	OAC rule 3745-17-07 (A)	See A.2.f
	OAC rule 3745-17-11(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) for this emissions unit has been determined to be the use of a baghouse with a 99% control efficiency.
- 2.b The particulate emission limitation is inclusive of lead emissions.
- 2.c The emission limitation established represents a combined allowable for emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036 and P037.

- 2.d The permittee shall not cause to be discharged into the atmosphere any gases that contain lead in excess of 0.51 milligram/dry standard cubic meter (0.0002229 grains per dry standard cubic foot) as determined in accordance with 40 CFR Part 60.372 (b).
- 2.e The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.
- 2.f The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The pressure drop across the baghouse shall be maintained within the range of 1 to 2.5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted in accordance with the general terms and conditions of this permit.

E. Testing Requirements

- 1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation: 0.30 lb PE/hr, 1.31 ton PE/yr

Applicable Compliance Method: The 0.30 lb/hr limitation represents the combined potential particulate emissions from emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036, and P037 based on a December 9, 2003 stack test. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 5 of 40 CFR Part 60, Appendix A

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.05 lb Pb/hr, 0.22 ton Pb/yr

Applicable Compliance Method: The hourly emission limitation was developed by multiplying the outlet grain loading of 0.0002229 gr/dscf by the maximum volumetric air flow rate of 25,000 acfm, then multiplying by 60 min/hour and dividing by 7000 gr/lb. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.0002229 gr Pb/dscf

Applicable Compliance Method: If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

Emission Limitation: The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. The emissions unit is subject to the applicable provisions of Subpart KK of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P023 - Industrial grid casting machines #1&2 serviced by lead melting pot #21 (modification to PTI 03-13450 issued on 7/10/01 to increase PE limit)	OAC rule 3745-31-05 (A)(3)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart KK. Use of baghouse (See A.2.a) 0.30 lbs particulate emissions (PE)/hr, 1.31 tons PE/yr (See A.2.b & A.2.c) 0.05 lb lead (Pb)/hr, 0.22 tons Pb/yr (See A.2.c)
	40 CFR Part 60 Subpart KK	See A.2.d & A.2.e
	OAC rule 3745-17-07 (A)	See A.2.f
	OAC rule 3745-17-11(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) for this emissions unit has been determined to be the use of a baghouse with a 99% control efficiency.
- 2.b The particulate emission limitation is inclusive of lead emissions.
- 2.c The emission limitation established represents a combined allowable for emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036 and P037.

- 2.d The permittee shall not cause to be discharged into the atmosphere any gases that contain lead in excess of 0.51 milligram/dry standard cubic meter (0.0002229 grains per dry standard cubic foot) as determined in accordance with 40 CFR Part 60.372 (b).
- 2.e The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.
- 2.f The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The pressure drop across the baghouse shall be maintained within the range of 1 to 2.5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted in accordance with the general terms and conditions of this permit.

E. Testing Requirements

- 1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation: 0.30 lb PE/hr, 1.31 ton PE/yr

Applicable Compliance Method: The 0.30 lb/hr limitation represents the combined potential particulate emissions from emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036, and P037 based on a December 9, 2003 stack test. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 5 of 40 CFR Part 60, Appendix A

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.05 lb Pb/hr, 0.22 ton Pb/yr

Applicable Compliance Method: The hourly emission limitation was developed by multiplying the outlet grain loading of 0.0002229 gr/dscf by the maximum volumetric air flow rate of 25,000 acfm, then multiplying by 60 min/hour and dividing by 7000 gr/lb. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.0002229 gr Pb/dscf

Applicable Compliance Method: If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

Emission Limitation: The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. The emissions unit is subject to the applicable provisions of Subpart KK of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P024 - Industrial grid casting machine #3 serviced by lead melting pot #22 (modification to PTI 03-13450 issued on 7/10/01 to increase PE limit)	OAC rule 3745-31-05 (A)(3)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart KK. Use of baghouse (See A.2.a) 0.30 lbs particulate emissions (PE)/hr, 1.31 tons PE/yr (See A.2.b & A.2.c) 0.05 lb lead (Pb)/hr, 0.22 tons Pb/yr (See A.2.c)
	40 CFR Part 60 Subpart KK	See A.2.d & A.2.e
	OAC rule 3745-17-07 (A)	See A.2.f
	OAC rule 3745-17-11(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) for this emissions unit has been determined to be the use of a baghouse with a 99% control efficiency.
- 2.b The particulate emission limitation is inclusive of lead emissions.
- 2.c The emission limitation established represents a combined allowable for emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036 and P037.

- 2.d The permittee shall not cause to be discharged into the atmosphere any gases that contain lead in excess of 0.51 milligram/dry standard cubic meter (0.0002229 grains per dry standard cubic foot) as determined in accordance with 40 CFR Part 60.372 (b).
- 2.e The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.
- 2.f The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The pressure drop across the baghouse shall be maintained within the range of 1 to 2.5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted in accordance with the general terms and conditions of this permit.

E. Testing Requirements

- 1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation: 0.30 lb PE/hr, 1.31 ton PE/yr

Applicable Compliance Method: The 0.30 lb/hr limitation represents the combined potential particulate emissions from emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036, and P037 based on a December 9, 2003 stack test. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 5 of 40 CFR Part 60, Appendix A

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.05 lb Pb/hr, 0.22 ton Pb/yr

Applicable Compliance Method: The hourly emission limitation was developed by multiplying the outlet grain loading of 0.0002229 gr/dscf by the maximum volumetric air flow rate of 25,000 acfm, then multiplying by 60 min/hour and dividing by 7000 gr/lb. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.0002229 gr Pb/dscf

Applicable Compliance Method: If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

Emission Limitation: The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. The emissions unit is subject to the applicable provisions of Subpart KK of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P025 - Industrial grid casting machine #4 serviced by lead melting pot #23 (modification to PTI 03-13450 issued on 7/10/01 to increase PE limit)	OAC rule 3745-31-05 (A)(3)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart KK. Use of baghouse (See A.2.a) 0.30 lbs particulate emissions (PE)/hr, 1.31 tons PE/yr (See A.2.b & A.2.c) 0.05 lb lead (Pb)/hr, 0.22 tons Pb/yr (See A.2.c)
	40 CFR Part 60 Subpart KK	See A.2.d & A.2.e
	OAC rule 3745-17-07 (A)	See A.2.f
	OAC rule 3745-17-11(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) for this emissions unit has been determined to be the use of a baghouse with a 99% control efficiency.
- 2.b The particulate emission limitation is inclusive of lead emissions.
- 2.c The emission limitation established represents a combined allowable for emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036 and P037.

- 2.d The permittee shall not cause to be discharged into the atmosphere any gases that contain lead in excess of 0.51 milligram/dry standard cubic meter (0.0002229 grains per dry standard cubic foot) as determined in accordance with 40 CFR Part 60.372 (b).
- 2.e The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.
- 2.f The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The pressure drop across the baghouse shall be maintained within the range of 1 to 2.5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted in accordance with the general terms and conditions of this permit.

E. Testing Requirements

- 1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation: 0.30 lb PE/hr, 1.31 ton PE/yr

Applicable Compliance Method: The 0.30 lb/hr limitation represents the combined potential particulate emissions from emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036, and P037 based on a December 9, 2003 stack test. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 5 of 40 CFR Part 60, Appendix A

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.05 lb Pb/hr, 0.22 ton Pb/yr

Applicable Compliance Method: The hourly emission limitation was developed by multiplying the outlet grain loading of 0.0002229 gr/dscf by the maximum volumetric air flow rate of 25,000 acfm, then multiplying by 60 min/hour and dividing by 7000 gr/lb. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.0002229 gr Pb/dscf

Applicable Compliance Method: If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

Emission Limitation: The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. The emissions unit is subject to the applicable provisions of Subpart KK of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P026 - Small parts hand pour casting machines serviced by lead melting pot #11 (modification to PTI 03-13450 issued on 7/10/01 to increase PE limit)	OAC rule 3745-31-05 (A)(3)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart KK. Use of baghouse (See A.2.a) 0.30 lbs particulate emissions (PE)/hr, 1.31 tons PE/yr (See A.2.b & A.2.c) 0.05 lb lead (Pb)/hr, 0.22 tons Pb/yr (See A.2.c)
	40 CFR Part 60 Subpart KK	See A.2.d & A.2.e
	OAC rule 3745-17-07 (A)	See A.2.f
	OAC rule 3745-17-11(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) for this emissions unit has been determined to be the use of a baghouse with a 99% control efficiency.
- 2.b The particulate emission limitation is inclusive of lead emissions.
- 2.c The emission limitation established represents a combined allowable for emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036 and P037.

- 2.d The permittee shall not cause to be discharged into the atmosphere any gases that contain lead in excess of 0.51 milligram/dry standard cubic meter (0.0002229 grains per dry standard cubic foot) as determined in accordance with 40 CFR Part 60.372 (b).
- 2.e The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.
- 2.f The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The pressure drop across the baghouse shall be maintained within the range of 1 to 2.5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted in accordance with the general terms and conditions of this permit.

E. Testing Requirements

- 1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation: 0.30 lb PE/hr, 1.31 ton PE/yr

Applicable Compliance Method: The 0.30 lb/hr limitation represents the combined potential particulate emissions from emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036, and P037 based on a December 9, 2003 stack test. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 5 of 40 CFR Part 60, Appendix A

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.05 lb Pb/hr, 0.22 ton Pb/yr

Applicable Compliance Method: The hourly emission limitation was developed by multiplying the outlet grain loading of 0.0002229 gr/dscf by the maximum volumetric air flow rate of 25,000 acfm, then multiplying by 60 min/hour and dividing by 7000 gr/lb. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.0002229 gr Pb/dscf

Applicable Compliance Method: If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

Emission Limitation: The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. The emissions unit is subject to the applicable provisions of Subpart KK of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P027 - Small parts automatic casting machines serviced by lead melting pot #12 (modification to PTI 03-13450 issued on 7/10/01 to increase PE limit)	OAC rule 3745-31-05 (A)(3)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart KK. Use of baghouse (See A.2.a) 0.30 lbs particulate emissions (PE)/hr, 1.31 tons PE/yr (See A.2.b & A.2.c) 0.05 lb lead (Pb)/hr, 0.22 tons Pb/yr (See A.2.c)
	40 CFR Part 60 Subpart KK	See A.2.d & A.2.e
	OAC rule 3745-17-07 (A)	See A.2.f
	OAC rule 3745-17-11(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) for this emissions unit has been determined to be the use of a baghouse with a 99% control efficiency.
- 2.b The particulate emission limitation is inclusive of lead emissions.
- 2.c The emission limitation established represents a combined allowable for emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036 and P037.

- 2.d The permittee shall not cause to be discharged into the atmosphere any gases that contain lead in excess of 0.51 milligram/dry standard cubic meter (0.0002229 grains per dry standard cubic foot) as determined in accordance with 40 CFR Part 60.372 (b).
- 2.e The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.
- 2.f The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The pressure drop across the baghouse shall be maintained within the range of 1 to 2.5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted in accordance with the general terms and conditions of this permit.

E. Testing Requirements

- 1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation: 0.30 lb PE/hr, 1.31 ton PE/yr

Applicable Compliance Method: The 0.30 lb/hr limitation represents the combined potential particulate emissions from emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036, and P037 based on a December 9, 2003 stack test. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 5 of 40 CFR Part 60, Appendix A

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.05 lb Pb/hr, 0.22 ton Pb/yr

Applicable Compliance Method: The hourly emission limitation was developed by multiplying the outlet grain loading of 0.0002229 gr/dscf by the maximum volumetric air flow rate of 25,000 acfm, then multiplying by 60 min/hour and dividing by 7000 gr/lb. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.0002229 gr Pb/dscf

Applicable Compliance Method: If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

Emission Limitation: The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. The emissions unit is subject to the applicable provisions of Subpart KK of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P028 - Lead stick casting machine serviced by lead melting pot #13 (modification to PTI 03-13450 issued on 7/10/01 to increase PE limit)	OAC rule 3745-31-05 (A)(3)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart KK. Use of baghouse (See A.2.a) 0.30 lbs particulate emissions (PE)/hr, 1.31 tons PE/yr (See A.2.b & A.2.c) 0.05 lb lead (Pb)/hr, 0.22 tons Pb/yr (See A.2.c)
	40 CFR Part 60 Subpart KK	See A.2.d & A.2.e
	OAC rule 3745-17-07 (A)	See A.2.f
	OAC rule 3745-17-11(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) for this emissions unit has been determined to be the use of a baghouse with a 99% control efficiency.
- 2.b The particulate emission limitation is inclusive of lead emissions.
- 2.c The emission limitation established represents a combined allowable for emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036 and P037.

- 2.d The permittee shall not cause to be discharged into the atmosphere any gases that contain lead in excess of 0.51 milligram/dry standard cubic meter (0.0002229 grains per dry standard cubic foot) as determined in accordance with 40 CFR Part 60.372 (b).
- 2.e The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.
- 2.f The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The pressure drop across the baghouse shall be maintained within the range of 1 to 2.5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted in accordance with the general terms and conditions of this permit.

E. Testing Requirements

- 1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation: 0.30 lb PE/hr, 1.31 ton PE/yr

Applicable Compliance Method: The 0.30 lb/hr limitation represents the combined potential particulate emissions from emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036, and P037 based on a December 9, 2003 stack test. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 5 of 40 CFR Part 60, Appendix A

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.05 lb Pb/hr, 0.22 ton Pb/yr

Applicable Compliance Method: The hourly emission limitation was developed by multiplying the outlet grain loading of 0.0002229 gr/dscf by the maximum volumetric air flow rate of 25,000 acfm, then multiplying by 60 min/hour and dividing by 7000 gr/lb. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.0002229 gr Pb/dscf

Applicable Compliance Method: If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

Emission Limitation: The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. The emissions unit is subject to the applicable provisions of Subpart KK of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P034 - SLI grid casting machine #14	OAC rule 3745-31-05 (A)(3)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart KK. Use of baghouse (See A.2.a) 0.30 lbs particulate emissions (PE)/hr, 1.31 tons PE/yr (See A.2.b & A.2.c) 0.05 lb lead (Pb)/hr, 0.22 tons Pb/yr (See A.2.c)
	40 CFR Part 60 Subpart KK	See A.2.d & A.2.e
	OAC rule 3745-17-07 (A)	See A.2.f
	OAC rule 3745-17-11(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) for this emissions unit has been determined to be the use of a baghouse with a 99% control efficiency.
- 2.b The particulate emission limitation is inclusive of lead emissions.
- 2.c The emission limitation established represents a combined allowable for emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036 and P037.

- 2.d The permittee shall not cause to be discharged into the atmosphere any gases that contain lead in excess of 0.51 milligram/dry standard cubic meter (0.0002229 grains per dry standard cubic foot) as determined in accordance with 40 CFR Part 60.372 (b).
- 2.e The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.
- 2.f The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The pressure drop across the baghouse shall be maintained within the range of 1 to 2.5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted in accordance with the general terms and conditions of this permit.

E. Testing Requirements

- 1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation: 0.30 lb PE/hr, 1.31 ton PE/yr

Applicable Compliance Method: The 0.30 lb/hr limitation represents the combined potential particulate emissions from emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036, and P037 based on a December 9, 2003 stack test. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 5 of 40 CFR Part 60, Appendix A

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.05 lb Pb/hr, 0.22 ton Pb/yr

Applicable Compliance Method: The hourly emission limitation was developed by multiplying the outlet grain loading of 0.0002229 gr/dscf by the maximum volumetric air flow rate of 25,000 acfm, then multiplying by 60 min/hour and dividing by 7000 gr/lb. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.0002229 gr Pb/dscf

Applicable Compliance Method: If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

Emission Limitation: The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. The emissions unit is subject to the applicable provisions of Subpart KK of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

Pursuant of 40 CFR Part 60.7, the permittee is hereby advised of the requirement to report the following at the appropriate times:

Crown Battery Manufacturing Company

PTI Application: 03-16167

Issued: 8/12/2004

Facility ID: 0372030089

Emissions Unit ID: P034

- a. construction date (no later than 30 days after such date);
- b. actual start-up date (within 15 days after such date); and,
- c. date of performance testing (if required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency
DAPC - Permit Management Unit
Lazarus Government Center
P.O. Box 1049
Columbus, OH 43216-1049

and

Ohio Environmental Protection Agency
Northwest District Office
Division of Air Pollution Control
347 North Dunbridge Road
Bowling Green, Ohio 43402

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P035 - SLI grid casting machine #15	OAC rule 3745-31-05 (A)(3)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart KK. Use of baghouse (See A.2.a) 0.30 lbs particulate emissions (PE)/hr, 1.31 tons PE/yr (See A.2.b & A.2.c) 0.05 lb lead (Pb)/hr, 0.22 tons Pb/yr (See A.2.c)
	40 CFR Part 60 Subpart KK	See A.2.d & A.2.e
	OAC rule 3745-17-07 (A)	See A.2.f
	OAC rule 3745-17-11(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) for this emissions unit has been determined to be the use of a baghouse with a 99% control efficiency.
- 2.b The particulate emission limitation is inclusive of lead emissions.
- 2.c The emission limitation established represents a combined allowable for emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036 and P037.

- 2.d The permittee shall not cause to be discharged into the atmosphere any gases that contain lead in excess of 0.51 milligram/dry standard cubic meter (0.0002229 grains per dry standard cubic foot) as determined in accordance with 40 CFR Part 60.372 (b).
- 2.e The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.
- 2.f The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The pressure drop across the baghouse shall be maintained within the range of 1 to 2.5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted in accordance with the general terms and conditions of this permit.

E. Testing Requirements

- 1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation: 0.30 lb PE/hr, 1.31 ton PE/yr

Applicable Compliance Method: The 0.30 lb/hr limitation represents the combined potential particulate emissions from emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036, and P037 based on a December 9, 2003 stack test. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 5 of 40 CFR Part 60, Appendix A

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.05 lb Pb/hr, 0.22 ton Pb/yr

Applicable Compliance Method: The hourly emission limitation was developed by multiplying the outlet grain loading of 0.0002229 gr/dscf by the maximum volumetric air flow rate of 25,000 acfm, then multiplying by 60 min/hour and dividing by 7000 gr/lb. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.0002229 gr Pb/dscf

Applicable Compliance Method: If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

Emission Limitation: The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. The emissions unit is subject to the applicable provisions of Subpart KK of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

Pursuant of 40 CFR Part 60.7, the permittee is hereby advised of the requirement to report the following at the appropriate times:

Crown Battery Manufacturing Company

PTI Application: 03-16167

Issued: 8/12/2004

Facility ID: 0372030089

Emissions Unit ID: P035

- a. construction date (no later than 30 days after such date);
- b. actual start-up date (within 15 days after such date); and,
- c. date of performance testing (if required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency
DAPC - Permit Management Unit
Lazarus Government Center
P.O. Box 1049
Columbus, OH 43216-1049

and

Ohio Environmental Protection Agency
Northwest District Office
Division of Air Pollution Control
347 North Dunbridge Road
Bowling Green, Ohio 43402

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P036 - SLI grid casting machine #5	OAC rule 3745-31-05 (A)(3)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart KK. Use of baghouse (See A.2.a) 0.30 lbs particulate emissions (PE)/hr, 1.31 tons PE/yr (See A.2.b & A.2.c) 0.05 lb lead (Pb)/hr, 0.22 tons Pb/yr (See A.2.c)
	40 CFR Part 60 Subpart KK	See A.2.d & A.2.e
	OAC rule 3745-17-07 (A)	See A.2.f
	OAC rule 3745-17-11(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) for this emissions unit has been determined to be the use of a baghouse with a 99% control efficiency.
- 2.b The particulate emission limitation is inclusive of lead emissions.
- 2.c The emission limitation established represents a combined allowable for emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036 and P037.

- 2.d The permittee shall not cause to be discharged into the atmosphere any gases that contain lead in excess of 0.51 milligram/dry standard cubic meter (0.0002229 grains per dry standard cubic foot) as determined in accordance with 40 CFR Part 60.372 (b).
- 2.e The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.
- 2.f The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The pressure drop across the baghouse shall be maintained within the range of 1 to 2.5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted in accordance with the general terms and conditions of this permit.

E. Testing Requirements

- 1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation: 0.30 lb PE/hr, 1.31 ton PE/yr

Applicable Compliance Method: The 0.30 lb/hr limitation represents the combined potential particulate emissions from emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036, and P037 based on a December 9, 2003 stack test. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 5 of 40 CFR Part 60, Appendix A

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.05 lb Pb/hr, 0.22 ton Pb/yr

Applicable Compliance Method: The hourly emission limitation was developed by multiplying the outlet grain loading of 0.0002229 gr/dscf by the maximum volumetric air flow rate of 25,000 acfm, then multiplying by 60 min/hour and dividing by 7000 gr/lb. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.0002229 gr Pb/dscf

Applicable Compliance Method: If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

Emission Limitation: The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. The emissions unit is subject to the applicable provisions of Subpart KK of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

Pursuant of 40 CFR Part 60.7, the permittee is hereby advised of the requirement to report the following at the appropriate times:

Crown Battery Manufacturing Company

PTI Application: 03-16167

Issued: 8/12/2004

Facility ID: 0372030089

Emissions Unit ID: P036

- a. construction date (no later than 30 days after such date);
- b. actual start-up date (within 15 days after such date); and,
- c. date of performance testing (if required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency
DAPC - Permit Management Unit
Lazarus Government Center
P.O. Box 1049
Columbus, OH 43216-1049

and

Ohio Environmental Protection Agency
Northwest District Office
Division of Air Pollution Control
347 North Dunbridge Road
Bowling Green, Ohio 43402

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
P037 - SLI grid casting machine #6	OAC rule 3745-31-05 (A)(3)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart KK. Use of baghouse (See A.2.a) 0.30 lbs particulate emissions (PE)/hr, 1.31 tons PE/yr (See A.2.b & A.2.c) 0.05 lb lead (Pb)/hr, 0.22 tons Pb/yr (See A.2.c)
	40 CFR Part 60 Subpart KK	See A.2.d & A.2.e
	OAC rule 3745-17-07 (A)	See A.2.f
	OAC rule 3745-17-11(B)	See A.2.f

2. Additional Terms and Conditions

- 2.a Best available technology (BAT) for this emissions unit has been determined to be the use of a baghouse with a 99% control efficiency.
- 2.b The particulate emission limitation is inclusive of lead emissions.
- 2.c The emission limitation established represents a combined allowable for emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036 and P037.

- 2.d The permittee shall not cause to be discharged into the atmosphere any gases that contain lead in excess of 0.51 milligram/dry standard cubic meter (0.0002229 grains per dry standard cubic foot) as determined in accordance with 40 CFR Part 60.372 (b).
- 2.e The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.
- 2.f The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3).

B. Operational Restrictions

- 1. The pressure drop across the baghouse shall be maintained within the range of 1 to 2.5 inches of water while the emissions unit is in operation.

C. Monitoring and/or Recordkeeping Requirements

- 1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a weekly basis.

D. Reporting Requirements

- 1. The permittee shall submit quarterly pressure drop deviation (excursion) reports that identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified above. These reports shall be submitted in accordance with the general terms and conditions of this permit.

E. Testing Requirements

- 1. Compliance with the emission limitation(s) in Section A.1 of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitation: 0.30 lb PE/hr, 1.31 ton PE/yr

Applicable Compliance Method: The 0.30 lb/hr limitation represents the combined potential particulate emissions from emissions units P016, P017, P018, P019, P020, P021, P022, P023, P024, P025, P026, P027, P028, P034, P035, P036, and P037 based on a December 9, 2003 stack test. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 5 of 40 CFR Part 60, Appendix A

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided

compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.05 lb Pb/hr, 0.22 ton Pb/yr

Applicable Compliance Method: The hourly emission limitation was developed by multiplying the outlet grain loading of 0.0002229 gr/dscf by the maximum volumetric air flow rate of 25,000 acfm, then multiplying by 60 min/hour and dividing by 7000 gr/lb. If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

The ton/yr limitation was developed by multiplying the lb/hr limitation by the maximum operating schedule of 8760 hrs/yr, and dividing by 2000 lbs/ton. Therefore, provided compliance is shown with the hourly limitation, compliance will also be shown with the annual limitation.

Emission Limitation: 0.0002229 gr Pb/dscf

Applicable Compliance Method: If required, compliance shall be demonstrated in accordance with the test method and procedures in Method 12, of 40 CFR Part 60, Appendix A.

Emission Limitation: The permittee shall not cause to be discharged into the atmosphere any gases with greater than 0% opacity.

Applicable Compliance Method: If required, compliance with the visible emission limitation shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

F. Miscellaneous Requirements

1. The emissions unit is subject to the applicable provisions of Subpart KK of the New Source Performance Standards (NSPS) as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60. The application and enforcement of these standards are delegated to the Ohio EPA. The requirements of 40 CFR Part 60 are also federally enforceable.

Pursuant of 40 CFR Part 60.7, the permittee is hereby advised of the requirement to report the following at the appropriate times:

Crown Battery Manufacturing Company

PTI Application: 03-16167

Issued: 8/12/2004

Facility ID: 0372030089

Emissions Unit ID: P037

- a. construction date (no later than 30 days after such date);
- b. actual start-up date (within 15 days after such date); and,
- c. date of performance testing (if required, at least 30 days prior to testing).

Reports are to be sent to:

Ohio Environmental Protection Agency
DAPC - Permit Management Unit
Lazarus Government Center
P.O. Box 1049
Columbus, OH 43216-1049

and

Ohio Environmental Protection Agency
Northwest District Office
Division of Air Pollution Control
347 North Dunbridge Road
Bowling Green, Ohio 43402