



State of Ohio Environmental Protection Agency

Street Address:

Lazarus Gov. Center
122 S. Front Street
Columbus, OH 43215

TELE: (614) 644-3020 FAX: (614) 644-2329

Mailing Address:

Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

**RE: FINAL PERMIT TO INSTALL
LUCAS COUNTY
Application No: 04-01332**

CERTIFIED MAIL

	TOXIC REVIEW
	PSD
	SYNTHETIC MINOR
	CEMS
	MACT
Kb	NSPS
	NESHAPS
	NETTING
	MAJOR NON-ATTAINMENT
	MODELING SUBMITTED
	GASOLINE DISPENSING FACILITY

DATE: 7/1/2003

Westway - Toledo 2
Anneliese Honsinger
2900 E. Allegheny Ave.
Philadelphia, PA 19134

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, Ohio 43215

Sincerely,

Michael W. Ahern, Supervisor
Field Operations and Permit Section
Division of Air Pollution Control

cc: USEPA

TDES



**Permit To Install
Terms and Conditions**

**Issue Date: 7/1/2003
Effective Date: 7/1/2003**

FINAL PERMIT TO INSTALL 04-01332

Application Number: 04-01332
APS Premise Number: 0448011724
Permit Fee: **\$1650**
Name of Facility: Westway - Toledo 2
Person to Contact: Anneliese Honsinger
Address: 2900 E. Allegheny Ave.
Philadelphia, PA 19134

Location of proposed air contaminant source(s) [emissions unit(s)]:
**235 Sinclair St.
Toledo, Ohio**

Description of proposed emissions unit(s):
Three internal floating roof amines storage tanks and loading/unloading rack.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

- a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.
- b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may

be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

**SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS**

<u>Pollutant</u>	<u>Tons Per Year</u>
VOC	3.763

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
J001 - Railcar and tank truck loading and unloading area for monobutylamine	OAC rule 3745-31-05(A)(3)	122.07 pounds of VOC per day 0.520 tons of VOC per year

2. **Additional Terms and Conditions**

- 2.a All product loading lines shall be equipped with fittings which are vapor tight.
- 2.b Means shall be provided to prevent drainage of the product from the loading device when it is not in use or accomplish complete drainage before the loading device is disconnected.

B. Operational Restrictions

1. The permittee shall not permit product to be spilled, discarded in sewers, stored in open containers or handled in any other manner that would result in evaporation.
2. When loading products the permittee shall make sure that the vessel being loaded has all hatches and/or openings sealed vapor tight so that the only vapor emissions are from approved vents.
3. All loading shall be accomplished by submerged or bottom filling.
4. The rolling 12-month summation of product throughput shall not exceed 810,000 gallons.
5. The permittee shall repair any leak found in the transfer equipment within 15 days.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall record any times loading was performed and the vessel being loaded was not properly secured in accordance with B.2 above.

2. The permittee shall record any times the submerged or bottom filling was not used during product loading.
3. The permittee shall record the following on a monthly basis:
 - a. the monthly throughput of product in gallons and ;
 - b. the rolling 12-month summation of product throughput in gallons.
4. The permittee shall visually inspect all transfer equipment and piping on a monthly basis for leaks.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. any time that a vessel was loaded and was not properly secured in accordance with B.2. above and;
 - b. any time that a vessel was loaded and submerged or bottom filling was not used during product loading and;
 - c. any accedence of the rolling 12-month summation restriction in B.4.and;
 - d. any visual inspections that were not performed in accordance with C.4. and;
 - e. any leaks that were not repaired in 15 days.
2. The deviation reports shall be submitted in writing to the Toledo Division of Environmental Services in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitations:
122.07 lbs/day VOC emissions

Compliance Method:
A one-time calculation of the daily potential to emit, based upon the maximum daily throughput in gallons, shall be used to demonstrate compliance with this limitation.

- b. Emission Limitations:
0.520 tons per year VOC emissions

Compliance Method:

A one-time calculation, based upon the maximum annual throughput, shall be used to demonstrate compliance with this limitation.

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
J002 - Railcar and tank truck loading and unloading area for triethylamine	OAC rule 3745-31-05(A)(3)	97.44 pounds of VOC per day 0.472 tons of VOC per year

2. **Additional Terms and Conditions**

- 2.a All product loading lines shall be equipped with fittings which are vapor tight.
- 2.b Means shall be provided to prevent drainage of the product from the loading device when it is not in use or accomplish complete drainage before the loading device is disconnected.

B. Operational Restrictions

1. The permittee shall not permit product to be spilled, discarded in sewers, stored in open containers or handled in any other manner that would result in evaporation.
2. When loading products the permittee shall make sure that the vessel being loaded has all hatches and/or openings sealed vapor tight so that the only vapor emissions are from approved vents.
3. All loading shall be accomplished by submerged or bottom filling.
4. The rolling 12-month summation of product throughput shall not exceed 810,000 gallons.
5. The permittee shall repair any leak found in the transfer equipment within 15 days.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall record any times loading was performed and the vessel being loaded was not properly secured in accordance with B.2 above.

2. The permittee shall record any times the submerged or bottom filling was not used during product loading.
3. The permittee shall record the following on a monthly basis:
 - a. the monthly throughput of product in gallons and ;
 - b. the rolling 12-month summation of product throughput in gallons.
4. The permittee shall visually inspect all transfer equipment and piping on a monthly basis for leaks.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. any time that a vessel was loaded and was not properly secured in accordance with B.2. above and;
 - b. any time that a vessel was loaded and submerged or bottom filling was not used during product loading and;
 - c. any accedence of the rolling 12-month summation restriction in B.4.and;
 - d. any visual inspections that were not performed in accordance with C.4. and;
 - e. any leaks that were not repaired in 15 days.
2. The deviation reports shall be submitted in writing to the Toledo Division of Environmental Services in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitations:
97.44 lbs/day VOC emissions

Compliance Method:
A one-time calculation of the daily potential to emit, based upon the maximum daily throughput in gallons, shall be used to demonstrate compliance with this limitation.
 - b. Emission Limitations:
0.472 tons per year VOC emissions

Compliance Method:

A one-time calculation, based upon the maximum annual throughput, shall be used to demonstrate compliance with this limitation.

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
J003 - Railcar and tank truck loading and unloading area for diethylamine	OAC rule 3745-31-05	300.06 pounds of VOC per day 2.051 tons of VOC per year

2. **Additional Terms and Conditions**

- 2.a All product loading lines shall be equipped with fittings which are vapor tight.
- 2.b Means shall be provided to prevent drainage of the product from the loading device when it is not in use or accomplish complete drainage before the loading device is disconnected.

B. Operational Restrictions

1. The permittee shall not permit product to be spilled, discarded in sewers, stored in open containers or handled in any other manner that would result in evaporation.
2. When loading products the permittee shall make sure that the vessel being loaded has all hatches and/or openings sealed vapor tight so that the only vapor emissions are from approved vents.
3. All loading shall be accomplished by submerged or bottom filling.
4. The rolling 12-month summation of product throughput shall not exceed 1,299,000 gallons.
5. The permittee shall repair any leak found in the transfer equipment within 15 days.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall record any times loading was performed and the vessel being loaded was not properly secured in accordance with B.2 above.

2. The permittee shall record any times the submerged or bottom filling was not used during product loading.
3. The permittee shall record the following on a monthly basis:
 - a. the monthly throughput of product in gallons and ;
 - b. the rolling 12-month summation of product throughput in gallons.
4. The permittee shall visually inspect all transfer equipment and piping on a monthly basis for leaks.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:
 - a. any time that a vessel was loaded and was not properly secured in accordance with B.2. above and;
 - b. any time that a vessel was loaded and submerged or bottom filling was not used during product loading and;
 - c. any accedence of the rolling 12-month summation restriction in B.4.and;
 - d. any visual inspections that were not performed in accordance with C.4. and;
 - e. any leaks that were not repaired in 15 days.
2. The deviation reports shall be submitted in writing to the Toledo Division of Environmental Services in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emission Limitations:
300.06 lbs/day VOC emissions

Compliance Method:
A one-time calculation of the daily potential to emit, based upon the maximum daily throughput in gallons, shall be used to demonstrate compliance with this limitation.
 - b. Emission Limitations:
2.051 tons per year VOC emissions

Compliance Method:

A one-time calculation, based upon the maximum annual throughput, shall be used to demonstrate compliance with this limitation.

F. Miscellaneous Requirements

None

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
T001 - 405,000 gallon internal floating roof storage tank storing monobutylamine.	OAC rule 3745-31-05(A)(3) 40 CFR 60, subpart Kb	0.176 tons volatile organic compounds (VOC) per year See II A.2.a See II A.2.b

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of 40 CFR 60, subpart Kb.
- 2.b The permittee of each storage vessel shall equip each storage vessel with one of the following:
A fixed roof in combination with an internal floating roof meeting the following specifications:
 - i. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal floating roof shall be floating on the liquid surface at all times, except during initial fill and during those intervals when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible.
 - ii. Each internal floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof:
 - (a) A foam-or liquid-filled seal mounted in contact with the liquid (liquid-mounted seal). A liquid-mounted seal means a foam-or

- liquid-filled seal mounted in contact with the liquid between the wall of the storage vessel and the floating roof continuously around the circumference of the tank.
- (b) Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage vessel and the edge of the internal floating roof. The lower seal may be vapor-mounted, but both must be continuous.
 - (c) A mechanical shoe seal. A mechanical shoe seal is a metal sheet held vertically against the wall of the storage vessel by springs or weighted levers and is connected by braces to the floating roof. A flexible coated fabric (envelope) spans the annular space between the metal sheet and the floating roof.
- iii. Each opening in a noncontact internal floating roof except for automatic bleeder vents (vacuum breaker vents) and the rim space vents is to provide a projection below the liquid surface.
 - iv. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use.
 - v. Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports.
 - vi. Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting
 - vii. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening.
 - viii. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover.
 - ix. Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover.

B. Operational Restrictions

1. The permittee shall have no more than two turnovers(810,000 gallons) in any rolling, 12-month period.

C. Monitoring and/or Recordkeeping Requirements.

1. The permittee shall:
 - a. Visually inspect the internal floating roof, the primary seal, and the secondary seal (if one is in service), prior to filling the storage vessel with volatile organic liquid (VOL). If there are holes, tears, or other openings in the primary seal, the secondary seal, or the seal fabric or defects in the internal floating roof, or both, the permittee shall repair the items before filling the storage vessel.
 - b. For Vessels equipped with a liquid-mounted or mechanical shoe primary seal, visually inspect the internal floating roof and the primary seal or the secondary seal (if one is in service) through manholes and roof hatches on the fixed roof at least once every 12 months after initial fill. If the internal floating roof is not resting on the surface of the VOL inside the storage vessel, or there is liquid accumulated on the roof, or the seal is detached, or there are holes or tears in the seal fabric, the permittee shall repair the items or empty and remove the storage vessel from service within 45 days. If a failure that is detected during inspections required in this paragraph cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from the Toledo Division of Environmental Services in the inspection report required in 40 CFR 60.115b(a)(3). Such a request for an extension must document that alternate storage capacity is unavailable and specify a schedule of actions the company will take that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible.
 - c. Visually inspect the internal floating roof, the primary seal, the secondary seal (if one is in service), gaskets, slotted membranes and sleeve seals (if any) each time the storage vessel is emptied and degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other openings in the seal or the seal fabric, or the secondary seal has holes, tears, or other openings in the seal or the seal fabric, or the gaskets no longer close off the liquid surfaces from the atmosphere, or the slotted membrane has more than 10 percent open area, the permittee shall repair the items as necessary so that none of the conditions specified in this paragraph exist before refilling the storage vessel with VOL. In no event shall inspections conducted in accordance with this provision occur at intervals greater than 10 years in the case of vessels conducting the annual visual inspection as specified in paragraph 1.b.

2. The permittee shall:
 - a. Keep a record of each inspection performed as required by C.1.a, 1.b and 1.c above. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment (seals, internal floating roof, and fittings).
3. The permittee shall keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. This record shall be kept for the life of the source.
4. The permittee shall maintain a record of the VOL stored, the period of storage, and the maximum true vapor pressure of that VOL during the respective storage period.
5. The permittee shall maintain monthly records of the following information:
 - a. The throughput for each month.
 - b. Beginning after the first 12 calendar months of operation following the issuance of this permit, the rolling, 12-month summation of the throughputs.

Also, during the first 12 calendar months of operation following the issuance of this permit, the permittee shall record the cumulative throughput for each calendar month.

D. Reporting Requirements

1. The permittee shall meet the following requirements:
 - a. Furnish the Toledo Division of Environmental Services with a report that describes the control equipment and certifies that the control equipment meets the specifications of 40 CFR 60.112b(a)(1) and 40 CFR 60.113b(a)(1). This report shall be an attachment to the notification required by 40 CFR 60.7(a)(3).
 - b. If any of the conditions described in 40 CFR 60.113b(a)(2) are detected during the annual visual inspection required by 40 CFR 60.113b(a)(2), a report shall be furnished to the Toledo Division of Environmental Services within 30 days of the inspection. Each report shall identify the storage vessel, the nature of the defects, and the date the storage vessel was emptied or the nature of and date the repair was made.
 - c. After each inspection required by 40 CFR 60.113b(a)(3) that finds holes or tears in the seal or seal fabric, or defects in the internal floating roof, or other control equipment defects listed in 40 CFR 60.113b(a)(3)(ii), a report shall be furnished to the Toledo Division of Environmental

Services within 30 days of the inspection. The report shall identify the storage vessel and the reason it did not meet the specifications of 40 CFR 61.112b(a)(1) or 40 CFR 60.113b(a)(3) and list each repair made.

2. Notify the Toledo Division of Environmental Services in writing at least 30 days prior to the filling or refilling of each storage vessel for which an inspection is required by paragraphs C.1.a and C.1.c to afford the Toledo Division of Environmental Services the opportunity to have an observer present. If the inspection required by paragraph C.1.c is not planned and the permittee could not have known about the inspection 30 days in advance or refilling the tank, the permittee shall notify the Toledo Division of Environmental Services at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Toledo Division of Environmental Services at least 7 days prior to the refilling.
3. The permittee shall submit semi-annual deviation (excursion) reports to the Toledo Division of Environmental Services that identify all exceedances of the rolling, 12-month throughput limitation and, for the first 12 calendar months of operation following the issuance of this permit, all exceedances of the maximum allowable cumulative production levels. These reports are due by January 30 and June 30 of each year and shall cover the previous six calendar months.

E. Testing Requirements

1. Compliance with the emission limitation of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emissions Limitations:
Volatile organic compound (VOC) emissions shall not exceed 0.176 tons per year.

Applicable Compliance Method:
Compliance shall be determined by estimating emissions using the most recent version of EPA's Tanks computer software or the most recent emission factors contained in AP-42 Chapter 7., using the actual annual throughput and annual average vapor pressure.

F. Miscellaneous Requirements

1. Available data on the storage temperature may be used to determine the maximum true vapor pressure as determined below.
 - 1.a For vessels operated above or below ambient temperatures, the maximum true vapor pressure is calculated based upon the highest expected calendar-month average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service.

- 1.b The vapor pressure may be obtained by the following:
 - 1.b.i Available data on the Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product may be used to determine the maximum true vapor pressure from nomographs contained in API Bulletin 2517 (incorporated by reference—see 40 CFR 60.17), unless the Administrator specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s).
 - 1.b.ii The true vapor pressure of each type of crude oil with a Reid vapor pressure less than 13.8 kPa or with physical properties that preclude determination by the recommended method is to be determined from available data and recorded if the estimated maximum true vapor pressure is greater than 3.5 kPa.
- 1.c For other liquids, the vapor pressure:
 - 1.c.i May be obtained from standard reference texts; or
 - 1.c.ii Determined by ASTM D2879-83, 96, or 97 (incorporated by reference—see 40 CFR 60.17); or
 - 1.c.iii Measured by an appropriate method approved by the Administrator; or
 - 1.c.iv Calculated by an appropriate method approved by the Administrator.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
T002 - 405,000 gallon internal floating roof storage tank storing triethylamine.	OAC rule 3745-31-05(A)(3) 40 CFR 60, subpart Kb	0.129 tons volatile organic compounds (VOC) per year See II A.2.a See II A.2.b

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of 40 CFR 60, subpart Kb.
- 2.b The permittee of each storage vessel shall equip each storage vessel with one of the following:

A fixed roof in combination with an internal floating roof meeting the following specifications:

- i. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal floating roof shall be floating on the liquid surface at all times, except during initial fill and during those intervals when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible.
- ii. Each internal floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof:

- (a) A foam-or liquid-filled seal mounted in contact with the liquid (liquid-mounted seal). A liquid-mounted seal means a foam-or liquid-filled seal mounted in contact with the liquid between the wall of the storage vessel and the floating roof continuously around the circumference of the tank.
 - (b) Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage vessel and the edge of the internal floating roof. The lower seal may be vapor-mounted, but both must be continuous.
 - (c) A mechanical shoe seal. A mechanical shoe seal is a metal sheet held vertically against the wall of the storage vessel by springs or weighted levers and is connected by braces to the floating roof. A flexible coated fabric (envelope) spans the annular space between the metal sheet and the floating roof.
- iii. Each opening in a noncontact internal floating roof except for automatic bleeder vents (vacuum breaker vents) and the rim space vents is to provide a projection below the liquid surface.
- iv. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use.
- v. Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports.
- vi. Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting
- vii. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening.
- viii. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover.
- ix. Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover.

B. Operational Restrictions

1. The permittee shall have no more than two turnovers(810,000 gallons) in any rolling, 12-month period.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall:
 - a Visually inspect the internal floating roof, the primary seal, and the secondary seal (if one is in service), prior to filling the storage vessel with volatile organic liquid (VOL). If there are holes, tears, or other openings in the primary seal, the secondary seal, or the seal fabric or defects in the internal floating roof, or both, the permittee shall repair the items before filling the storage vessel.
 - b For Vessels equipped with a liquid-mounted or mechanical shoe primary seal, visually inspect the internal floating roof and the primary seal or the secondary seal (if one is in service) through manholes and roof hatches on the fixed roof at least once every 12 months after initial fill. If the internal floating roof is not resting on the surface of the VOL inside the storage vessel, or there is liquid accumulated on the roof, or the seal is detached, or there are holes or tears in the seal fabric, the permittee shall repair the items or empty and remove the storage vessel from service within 45 days. If a failure that is detected during inspections required in this paragraph cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from the Toledo Division of Environmental Services in the inspection report required in 40 CFR 60.115b(a)(3). Such a request for an extension must document that alternate storage capacity is unavailable and specify a schedule of actions the company will take that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible.
 - c Visually inspect the internal floating roof, the primary seal, the secondary seal (if one is in service), gaskets, slotted membranes and sleeve seals (if any) each time the storage vessel is emptied and degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other openings in the seal or the seal fabric, or the secondary seal has holes, tears, or other openings in the seal or the seal fabric, or the gaskets no longer close off the liquid surfaces from the atmosphere, or the slotted membrane has more than 10 percent open area, the permittee shall repair the items as necessary so that none of the conditions specified in this paragraph exist before refilling the storage vessel with VOL. In no event shall inspections conducted in accordance with this provision occur at intervals greater than 10 years in the case of vessels conducting the annual visual inspection as specified in paragraph 1.b.

2. The permittee shall:
 - a. Keep a record of each inspection performed as required by C.1.a, 1.b and 1.c above. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment (seals, internal floating roof, and fittings).
3. The permittee shall keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. This record shall be kept for the life of the source.
4. The permittee shall maintain a record of the VOL stored, the period of storage, and the maximum true vapor pressure of that VOL during the respective storage period.
5. The permittee shall maintain monthly records of the following information:
 - a. The throughput for each month.
 - b. Beginning after the first 12 calendar months of operation following the issuance of this permit, the rolling, 12-month summation of the throughputs.

Also, during the first 12 calendar months of operation following the issuance of this permit, the permittee shall record the cumulative throughput for each calendar month.

D. Reporting Requirements

1. The permittee shall meet the following requirements:
 - a. Furnish the Toledo Division of Environmental Services with a report that describes the control equipment and certifies that the control equipment meets the specifications of 40 CFR 60.112b(a)(1) and 40 CFR 60.113b(a)(1). This report shall be an attachment to the notification required by 40 CFR 60.7(a)(3).
 - b. If any of the conditions described in 40 CFR 60.113b(a)(2) are detected during the annual visual inspection required by 40 CFR 60.113b(a)(2), a report shall be furnished to the Toledo Division of Environmental Services within 30 days of the inspection. Each report shall identify the storage vessel, the nature of the defects, and the date the storage vessel was emptied or the nature of and date the repair was made.
 - c. After each inspection required by 40 CFR 60.113b(a)(3) that finds holes or tears in the seal or seal fabric, or defects in the internal floating roof, or other control equipment defects listed in 40 CFR 60.113b(a)(3)(ii), a report shall be furnished to the Toledo Division of Environmental

Services within 30 days of the inspection. The report shall identify the storage vessel and the reason it did not meet the specifications of 40 CFR 61.112b(a)(1) or 40 CFR 60.113b(a)(3) and list each repair made.

2. Notify the Toledo Division of Environmental Services in writing at least 30 days prior to the filling or refilling of each storage vessel for which an inspection is required by paragraphs C.1.a and C.1.c to afford the Toledo Division of Environmental Services the opportunity to have an observer present. If the inspection required by paragraph C.1.c is not planned and the permittee could not have known about the inspection 30 days in advance or refilling the tank, the permittee shall notify the Toledo Division of Environmental Services at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Toledo Division of Environmental Services at least 7 days prior to the refilling.
3. The permittee shall submit semi-annual deviation (excursion) reports to the Toledo Division of Environmental Services that identify all exceedances of the rolling, 12-month throughput limitation and, for the first 12 calendar months of operation following the issuance of this permit, all exceedances of the maximum allowable cumulative production levels. These reports are due by January 30 and June 30 of each year and shall cover the previous six calendar months.

E. Testing Requirements

1. Compliance with the emission limitation of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emissions Limitations:
Volatile organic compound (VOC) emissions shall not exceed 0.129 tons per year.

Applicable Compliance Method:
Compliance shall be determined by estimating emissions using the most recent version of EPA's Tanks computer software or the most recent emission factors contained in AP-42 Chapter 7., using the actual annual throughput and annual average vapor pressure.

F. Miscellaneous Requirements

1. Available data on the storage temperature may be used to determine the maximum true vapor pressure as determined below.
 - 1.a For vessels operated above or below ambient temperatures, the maximum true vapor pressure is calculated based upon the highest expected calendar-month average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service.

- 1.b The vapor pressure may be obtained by the following:
 - 1.b.i Available data on the Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product may be used to determine the maximum true vapor pressure from nomographs contained in API Bulletin 2517 (incorporated by reference—see 40 CFR 60.17), unless the Administrator specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s).
 - 1.b.ii The true vapor pressure of each type of crude oil with a Reid vapor pressure less than 13.8 kPa or with physical properties that preclude determination by the recommended method is to be determined from available data and recorded if the estimated maximum true vapor pressure is greater than 3.5 kPa.
- 1.c For other liquids, the vapor pressure:
 - 1.c.i May be obtained from standard reference texts; or
 - 1.c.ii Determined by ASTM D2879-83, 96, or 97 (incorporated by reference—see 40 CFR 60.17); or
 - 1.c.iii Measured by an appropriate method approved by the Administrator; or
 - 1.c.iv Calculated by an appropriate method approved by the Administrator.

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

<u>Operations, Property, and/or Equipment</u>	<u>Applicable Rules/Requirements</u>	<u>Applicable Emissions Limitations/Control Measures</u>
T003 - 433,000 gallon internal floating roof storage tank storing diethylamine.	OAC rule 3745-31-05(A)(3) 40 CFR 60, subpart Kb	0.415 tons volatile organic compounds (VOC) per year See II A.2.a See II A.2.b

2. Additional Terms and Conditions

- 2.a The requirements of this rule also include compliance with the requirements of 40 CFR 60, subpart Kb.
- 2.b The permittee of each storage vessel shall equip each storage vessel with one of the following:

A fixed roof in combination with an internal floating roof meeting the following specifications:

- i. The internal floating roof shall rest or float on the liquid surface (but not necessarily in complete contact with it) inside a storage vessel that has a fixed roof. The internal floating roof shall be floating on the liquid surface at all times, except during initial fill and during those intervals when the storage vessel is completely emptied or subsequently emptied and refilled. When the roof is resting on the leg supports, the process of filling, emptying, or refilling shall be continuous and shall be accomplished as rapidly as possible.
- ii. Each internal floating roof shall be equipped with one of the following closure devices between the wall of the storage vessel and the edge of the internal floating roof:

- (a) A foam-or liquid-filled seal mounted in contact with the liquid (liquid-mounted seal). A liquid-mounted seal means a foam-or liquid-filled seal mounted in contact with the liquid between the wall of the storage vessel and the floating roof continuously around the circumference of the tank.
 - (b) Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage vessel and the edge of the internal floating roof. The lower seal may be vapor-mounted, but both must be continuous.
 - (c) A mechanical shoe seal. A mechanical shoe seal is a metal sheet held vertically against the wall of the storage vessel by springs or weighted levers and is connected by braces to the floating roof. A flexible coated fabric (envelope) spans the annular space between the metal sheet and the floating roof.
- iii. Each opening in a noncontact internal floating roof except for automatic bleeder vents (vacuum breaker vents) and the rim space vents is to provide a projection below the liquid surface.
- iv. Each opening in the internal floating roof except for leg sleeves, automatic bleeder vents, rim space vents, column wells, ladder wells, sample wells, and stub drains is to be equipped with a cover or lid which is to be maintained in a closed position at all times (i.e., no visible gap) except when the device is in actual use. The cover or lid shall be equipped with a gasket. Covers on each access hatch and automatic gauge float well shall be bolted except when they are in use.
- v. Automatic bleeder vents shall be equipped with a gasket and are to be closed at all times when the roof is floating except when the roof is being floated off or is being landed on the roof leg supports.
- vi. Rim space vents shall be equipped with a gasket and are to be set to open only when the internal floating roof is not floating or at the manufacturer's recommended setting
- vii. Each penetration of the internal floating roof for the purpose of sampling shall be a sample well. The sample well shall have a slit fabric cover that covers at least 90 percent of the opening.
- viii. Each penetration of the internal floating roof that allows for passage of a column supporting the fixed roof shall have a flexible fabric sleeve seal or a gasketed sliding cover.
- ix. Each penetration of the internal floating roof that allows for passage of a ladder shall have a gasketed sliding cover.

B. Operational Restrictions

1. The permittee shall have no more than two turnovers(1,233,000 gallons) in any rolling, 12-month period.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall:
 - a Visually inspect the internal floating roof, the primary seal, and the secondary seal (if one is in service), prior to filling the storage vessel with volatile organic liquid (VOL). If there are holes, tears, or other openings in the primary seal, the secondary seal, or the seal fabric or defects in the internal floating roof, or both, the permittee shall repair the items before filling the storage vessel.
 - b For Vessels equipped with a liquid-mounted or mechanical shoe primary seal, visually inspect the internal floating roof and the primary seal or the secondary seal (if one is in service) through manholes and roof hatches on the fixed roof at least once every 12 months after initial fill. If the internal floating roof is not resting on the surface of the VOL inside the storage vessel, or there is liquid accumulated on the roof, or the seal is detached, or there are holes or tears in the seal fabric, the permittee shall repair the items or empty and remove the storage vessel from service within 45 days. If a failure that is detected during inspections required in this paragraph cannot be repaired within 45 days and if the vessel cannot be emptied within 45 days, a 30-day extension may be requested from the Toledo Division of Environmental Services in the inspection report required in 40 CFR 60.115b(a)(3). Such a request for an extension must document that alternate storage capacity is unavailable and specify a schedule of actions the company will take that will assure that the control equipment will be repaired or the vessel will be emptied as soon as possible.
 - c Visually inspect the internal floating roof, the primary seal, the secondary seal (if one is in service), gaskets, slotted membranes and sleeve seals (if any) each time the storage vessel is emptied and degassed. If the internal floating roof has defects, the primary seal has holes, tears, or other openings in the seal or the seal fabric, or the secondary seal has holes, tears, or other openings in the seal or the seal fabric, or the gaskets no longer close off the liquid surfaces from the atmosphere, or the slotted membrane has more than 10 percent open area, the permittee shall repair the items as necessary so that none of the conditions specified in this paragraph exist before refilling the storage vessel with VOL. In no event shall inspections conducted in accordance with this provision occur at intervals greater than 10 years in the case of vessels conducting the annual visual inspection as specified in paragraph 1.b.

2. The permittee shall:
 - a. Keep a record of each inspection performed as required by C.1.a, 1.b and 1.c above. Each record shall identify the storage vessel on which the inspection was performed and shall contain the date the vessel was inspected and the observed condition of each component of the control equipment (seals, internal floating roof, and fittings).
3. The permittee shall keep readily accessible records showing the dimension of the storage vessel and an analysis showing the capacity of the storage vessel. This record shall be kept for the life of the source.
4. The permittee shall maintain a record of the VOL stored, the period of storage, and the maximum true vapor pressure of that VOL during the respective storage period.
5. The permittee shall maintain monthly records of the following information:
 - a. The throughput for each month.
 - b. Beginning after the first 12 calendar months of operation following the issuance of this permit, the rolling, 12-month summation of the throughputs.

Also, during the first 12 calendar months of operation following the issuance of this permit, the permittee shall record the cumulative throughput for each calendar month.

D. Reporting Requirements

1. The permittee shall meet the following requirements:
 - a. Furnish the Toledo Division of Environmental Services with a report that describes the control equipment and certifies that the control equipment meets the specifications of 40 CFR 60.112b(a)(1) and 40 CFR 60.113b(a)(1). This report shall be an attachment to the notification required by 40 CFR 60.7(a)(3).
 - b. If any of the conditions described in 40 CFR 60.113b(a)(2) are detected during the annual visual inspection required by 40 CFR 60.113b(a)(2), a report shall be furnished to the Toledo Division of Environmental Services within 30 days of the inspection. Each report shall identify the storage vessel, the nature of the defects, and the date the storage vessel was emptied or the nature of and date the repair was made.
 - c. After each inspection required by 40 CFR 60.113b(a)(3) that finds holes or tears in the seal or seal fabric, or defects in the internal floating roof, or other control equipment defects listed in 40 CFR 60.113b(a)(3)(ii), a report shall be furnished to the Toledo Division of Environmental

Services within 30 days of the inspection. The report shall identify the storage vessel and the reason it did not meet the specifications of 40 CFR 61.112b(a)(1) or 40 CFR 60.113b(a)(3) and list each repair made.

2. Notify the Toledo Division of Environmental Services in writing at least 30 days prior to the filling or refilling of each storage vessel for which an inspection is required by paragraphs C.1.a and C.1.c to afford the Toledo Division of Environmental Services the opportunity to have an observer present. If the inspection required by paragraph C.1.c is not planned and the permittee could not have known about the inspection 30 days in advance or refilling the tank, the permittee shall notify the Toledo Division of Environmental Services at least 7 days prior to the refilling of the storage vessel. Notification shall be made by telephone immediately followed by written documentation demonstrating why the inspection was unplanned. Alternatively, this notification including the written documentation may be made in writing and sent by express mail so that it is received by the Toledo Division of Environmental Services at least 7 days prior to the refilling.
3. The permittee shall submit semi-annual deviation (excursion) reports to the Toledo Division of Environmental Services that identify all exceedances of the rolling, 12-month throughput limitation and, for the first 12 calendar months of operation following the issuance of this permit, all exceedances of the maximum allowable cumulative production levels. These reports are due by January 30 and June 30 of each year and shall cover the previous six calendar months.

E. Testing Requirements

1. Compliance with the emission limitation of these terms and conditions shall be determined in accordance with the following method(s):
 - a. Emissions Limitations:
Volatile organic compound (VOC) emissions shall not exceed 0.416 tons per year.

Applicable Compliance Method:
Compliance shall be determined by estimating emissions using the most recent version of EPA's Tanks computer software or the most recent emission factors contained in AP-42 Chapter 7., using the actual annual throughput and annual average vapor pressure.

F. Miscellaneous Requirements

1. Available data on the storage temperature may be used to determine the maximum true vapor pressure as determined below.
 - 1.a For vessels operated above or below ambient temperatures, the maximum true vapor pressure is calculated based upon the highest expected calendar-month average of the storage temperature. For vessels operated at ambient temperatures, the maximum true vapor pressure is calculated based upon the maximum local monthly average ambient temperature as reported by the National Weather Service.

- 1.b The vapor pressure may be obtained by the following:
 - 1.b.i Available data on the Reid vapor pressure and the maximum expected storage temperature based on the highest expected calendar-month average temperature of the stored product may be used to determine the maximum true vapor pressure from nomographs contained in API Bulletin 2517 (incorporated by reference—see 40 CFR 60.17), unless the Administrator specifically requests that the liquid be sampled, the actual storage temperature determined, and the Reid vapor pressure determined from the sample(s).
 - 1.b.ii The true vapor pressure of each type of crude oil with a Reid vapor pressure less than 13.8 kPa or with physical properties that preclude determination by the recommended method is to be determined from available data and recorded if the estimated maximum true vapor pressure is greater than 3.5 kPa.
- 1.c For other liquids, the vapor pressure:
 - 1.c.i May be obtained from standard reference texts; or
 - 1.c.ii Determined by ASTM D2879-83, 96, or 97 (incorporated by reference—see 40 CFR 60.17); or
 - 1.c.iii Measured by an appropriate method approved by the Administrator; or
 - 1.c.iv Calculated by an appropriate method approved by the Administrator.