OhioEPA

State of Ohio Environmental Protection Agency

Street Address:
Lazarus Gov. Center
50 West Town Street, Suite 700
Columbus, OH 43215

TELE: (614) 644-3020 **FAX:** (614) 644-2329

Mailing Address:
Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

CERTIFIED MAIL

RE: FINAL PERMIT TO INSTALL MODIFICATION
BELMONT COUNTY
Application No: 06-08327
Fac ID: 0607100268

	TOXIC REVIEW
	PSD
	SYNTHETIC MINOR
	CEMS
	MACT
OOO	**NSPS**
	NESHAPS
	NETTING
	MAJOR NON-ATTAINMENT
	MODELING SUBMITTED
	GASOLINE DISPENSING FACILITY

DATE: 9/25/2007

Egypt Valley Stone LLC
Tillio Petrozzi
PO Box 188
Morristown, OH 43759

Enclosed Please find a modification to the Ohio EPA Permit To Install referenced above which will modify the terms and conditions.

You are hereby notified that this action of the Director is final and may be appealed to the Environmental Review Appeals Commission pursuant to Section 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. The appeal must be filed with the Commission within thirty (30) days after notice of the Director's action. The appeal must be accompanied by a filing fee of $70.00 which the Commission, in its discretion, may reduce if by affidavit you demonstrate that payment of the full amount of the fee would cause extreme hardship. Notice of the filing of the appeal shall be filed with the Director within three (3) days of filing with the Commission. Ohio EPA requests that a copy of the appeal be served upon the Ohio Attorney General's Office, Environmental Enforcement Section. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
309 South Fourth Street, Room 222
Columbus, OH 43215

Sincerely,

Michael W. Ahern

Michael W. Ahern, Manager
Permit Issuance and Data Management Section
Division of Air Pollution Control

CC: **USEPA** **SEDO**

STATE OF OHIO ENVIRONMENTAL PROTECTION AGENCY

Permit To Install **Issue Date: 9/25/2007**

Terms and Conditions **Effective Date: 9/25/2007**

FINAL ADMINISTRATIVE MODIFICATION OF PERMIT TO INSTALL 06-08327

Application Number: 06-08327

Facility ID: 0607100268

Permit Fee: **$450**

Name of Facility: Egypt Valley Stone LLC

Person to Contact: Tillio Petrozzi

Address: PO Box 188
Morristown, OH 43759

Location of proposed air contaminant source(s) [emissions unit(s)]:
66901 Egypt North Rd.
Morristown, **Ohio**

Description of proposed emissions unit(s):
Administrative modification to add one conveyor to aggregate processing plant (EU F004).

The above named entity is hereby granted a modification to the permit to install described above pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this modification does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described source(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans included in the application, the above described source(s) of pollutants will be granted the necessary operating permits.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Chris Korleski
Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements

The permittee shall submit required reports in the following manner:

a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.

b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted (i.e., postmarked) quarterly by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and

regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions

may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit To Install is applicable only to the emissions unit(s) identified in the Permit To Install. Separate Permit To Install for the installation or modification of any other emissions unit(s) are required for any emissions unit for which a Permit To Install is required.

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this

permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within ninety (90) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

Pollutant	Tons Per Year
PE	26.2
NOx	23.9
CO	5.2
SO_2	1.6
OC	2.0

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment - F001 - Plant unpaved roadways and parking areas (16,315 vehicle miles traveled per year)

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
ORC 3704.03(T)(4)	See Section A.2.a.
OAC rule 3745-17-07(B)(5)	No visible PE from unpaved roadways and parking areas except for a period of time not to exceed thirteen minutes during any 60-minute observation period.
OAC rule 3745-17-08(B)	Reasonably available control measures that are sufficient to minimize or eliminate visible PE of fugitive dust (See Sections A.2.b through A.2.e.).

2. Additional Terms and Conditions

2.a The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions from this air contaminant source since the calculated annual emission rate for particulate is less than ten tons per year taking into account the federally enforceable rule requirements under OAC rule 3745-17-08(B).

2.b The needed frequencies of implementation of the control measures shall be determined by the permittee's inspections pursuant to the monitoring section of this permit. Implementation of the control measures shall not be necessary for paved and unpaved roadways and parking areas that are covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Implementation of any control measure may be suspended if unsafe or hazardous driving conditions would be created by its use.

2.c Any unpaved roadway or parking area, which during the term of this permit is paved or takes the characteristics of a paved surface due to the application of certain types of dust suppressants, may be controlled using any combination of flushing, sweeping, and/or watering. Any unpaved roadway or parking area that takes the characteristics of a paved roadway or parking area due to the application of certain

C:\temp\permits3\8461.wpd

types of dust suppressants shall remain subject to the visible emission limitation for unpaved roadways and parking areas. Any unpaved area that is paved shall be subject to the visible emission limitation of no visible particulate emissions except for a period of time not to exceed one minute during any sixty minute observation period.

2.d The permittee shall promptly remove, in such a manner as to minimize or prevent resuspension, earth and/or other material from paved streets onto which such material has been deposited by trucking or earth moving equipment or erosion by water or other means.

2.e Open-bodied vehicles transporting materials likely to become airborne shall have such materials covered at all times if the control measure is necessary for the materials being transported.

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of each of the roadway segments and parking areas in accordance with the following frequencies:

unpaved roadways and parking areas	minimum inspection frequency
all roads and parking areas	daily

2. The purpose of the inspections is to determine the need for implementing the above-mentioned control measures. The inspections shall be performed during representative, normal traffic conditions. No inspection shall be necessary for a roadway or parking area that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above-identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.

3. The permittee shall maintain records of the following information:

   a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;

   b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;

C:\temp\permits3\8461.wpd

c. the dates the control measures were implemented; and

d. on a calendar quarter basis, the total number of days the control measures were implemented and the total number of days where snow and/or ice cover or precipitation were sufficient to not require the control measures.

The information required in 3.d. shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify any of the following occurrences:

   a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and

   b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

E. Testing Requirements

1. Compliance with the emission limitations specified in Section A.1 of the terms and conditions of this permit shall be determined in accordance with the following methods:

   a. Emissions Limitation:
   No visible PE from unpaved roadways and parking areas except for a period of time not to exceed thirteen minutes during any 60-minute observation period.

   Applicable Compliance Method:
   If required, visible particulate emissions shall be determined according to test Method 22 as set forth in the "Appendix on Test Methods" in 40 CFR, Part 60 "Standards of Performance for New Stationary Sources" as such appendix existed on July 1, 2002, with the modifications found in OAC 3745-17-03(B)(4).

F. Miscellaneous Requirements

None

C:\temp\permits3\8461.wpd

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment -F002 - Mineral extraction (maximum throughput of 2,025,000 TPY topsoil and overburden removed; 750,000 TPY minerals removed; 2,000,000 TPY overburden loaded; 750,000 TPY minerals loaded; 2,025,000 TPY topsoil and overburden replaced; 750,000 TPY material drilled; and 120 blasts per year)

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
ORC 3704.03(T)(4)	See Section A.2.a.
OAC rule 3745-17-07(B)	Visible PE shall not exceed 20% opacity, as a three-minute average.
OAC rule 3745-17-08(B)	Use of reasonably available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see A.2.b through A.2.d)

2. Additional Terms and Conditions

2.a The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions from this air contaminant source since the calculated annual emission rate for particulate is less than ten tons per year taking into account the federally enforceable rule requirements under OAC rule 3745-17-08(B).

2.b The following mineral extraction operations are covered by this permit and subject to the above mentioned requirements:

i. topsoil, overburden and mineral removal;
ii. loading of overburden and minerals;
iii. topsoil and overburden replacement;
iv. drilling; and
v. blasting.

2.c The permittee shall employ best available control measures for the above-identified mineral extraction operations for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's

C:\temp\permits3\8461.wpd

permit application, the permittee has committed to perform the following control measures to ensure compliance:

Mineral Extraction Operation	Control Measure(s)
topsoil, overburden and mineral removal	inherent moisture*; minimize disturbed land surface
overburden and mineral loading	inherent moisture*; prevent haul vehicle overloading
topsoil and overburden replacement	inherent moisture*; reclamation practices as soon as minerals extracted
Drilling	water injection; dust to filter
Blasting	Restrict area; prevent overshooting

*In accordance with the permit application, the permittee maintains that the inherent moisture content of the aggregate is more than sufficient to comply with all applicable requirements. If at any time the moisture content is not sufficient to meet the above applicable requirements, the permittee shall employ additional control measures to ensure compliance.

Nothing in the above table shall prohibit the permittee from employing other control measures to ensure compliance.

2.d For each mineral extraction operation, the above-identified control measure(s) shall be implemented if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measures(s) is (are) necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measures(s) shall continue during the mineral extraction operation(s) until further observation confirms that use of the control measure(s) is unnecessary.

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of such operations in accordance with the following minimum frequencies:

C:\temp\permits3\8461.wpd

Mineral Extraction Operation	Minimum Inspection Frequency
topsoil, overburden and mineral removal	once per day of operation
overburden and mineral loading	once per day of operation
topsoil and overburden replacement	once per day of operation
Drilling	once per day of operation
Blasting	once per day of operation

2. The purpose of the inspections is to determine the need for implementing the control measures specified above. The inspections shall be performed during representative, normal operating conditions.

3. The permittee shall maintain records of the following information:

   a. the date and reason any required inspection was not performed;

   b. the dates the control measure(s) was (were) not implemented; and

   c. on a calendar quarter basis, the total number of days the control measure(s) was (were) implemented.

   The information in 3.c shall be kept separately for each mineral extraction operation identified above, and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation reports that identify any of the following occurrences:

   a. each day during which an inspection was not performed by the required frequency; and

   b. each instance when a control measure, that was to be performed as a result of an inspection, was not implemented.

2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

C:\temp\permits3\8461.wpd

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):

   a. Emissions Limitation:
   Visible PE shall not exceed 20% opacity, as a three-minute average.

   Applicable Compliance Method:
   If required, visible particulate emissions shall be determined according to test Method 9 as set forth in the "Appendix on Test Methods" in 40 CFR, Part 60 "Standards of Performance for New Stationary Sources" as such appendix existed on July 1, 2002, with the modifications found in OAC 3745-17-03(B)(3)(a) and (b).

F. Miscellaneous Requirements

None

C:\temp\permits3\8461.wpd

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment -F003 - Aggregate storage piles (maximum throughput of 750,000 TPY and surface area less than or equal to 0.8 acres)

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
ORC 3704.03(T)(4)	See Section A.2.a.
OAC rule 3745-17-07(B)	No visible PE from storage pile activities except for a period of time not to exceed thirteen minutes during any 60-minute observation period.
OAC rule 3745-17-08(B)	Use of reasonably available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see A.2.b through A.2.e)

2. Additional Terms and Conditions

2.a The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions from this air contaminant source since the calculated annual emission rate for particulate is less than ten tons per year taking into account the federally enforceable rule requirements under OAC rule 3745-17-08(B).

2.b The permittee shall employ reasonably available control measures on all load-in and load-out operations associated with the storage piles for the purpose of ensuring compliance with the above-mentioned applicable requirements. The permittee shall maintain minimal drop heights for stackers and front-loaders, and use chemical stabilization/dust suppressants and/or watering/sprinkling systems at sufficient treatment frequencies to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

2.c The above-mentioned control measure(s) shall be employed for each load-in and load-out operation of each storage pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measure(s)

C:\temp\permits3\8461.wpd

shall continue during any such operation until further observation confirms that use of the measure(s) is unnecessary.

2.d The permittee shall employ reasonably available control measures for wind erosion from the surfaces of all storage piles for the purpose of ensuring compliance with the above mentioned applicable requirements. The permittee shall perform one or more of the following: chemical stabilization, watering/sprinkling systems/hoses, or covering the storage piles to ensure compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

2.e The above-mentioned control measure(s) shall be employed for wind erosion from each pile if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measure(s) are necessary to ensure compliance with the above-mentioned applicable requirements. Implementation of the control measure(s) shall not be necessary for a storage pile that is covered with snow and/or ice or if precipitation has occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements.

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. Except as otherwise provided in this section, the permittee shall perform inspections of each load-in operation at each storage pile in accordance with the following frequencies:

storage pile identification	minimum load-in inspection frequency
all	daily

2. Except as otherwise provided in this section, the permittee shall perform inspections of each load-out operation at each storage pile in accordance with the following frequencies:

storage pile identification	minimum load-out inspection frequency
all	daily

3. Except as otherwise provided in this section, the permittee shall perform inspections of the wind erosion from pile surfaces associated with each storage pile in accordance with the following frequencies:

storage pile identification	minimum wind erosion inspection frequency
all	daily

4. No inspection shall be necessary for wind erosion from the surface of a storage pile when the pile is covered with snow and/or ice and for any storage pile activity if precipitation has

C:\temp\permits3\8461.wpd

occurred that is sufficient for that day to ensure compliance with the above-mentioned applicable requirements. Any required inspection that is not performed due to any of the above identified events shall be performed as soon as such event(s) has (have) ended, except if the next required inspection is within one week.

5. The purpose of the inspections is to determine the need for implementing the control measures specified in this permit for load-in and load-out of a storage pile, and wind erosion from the surface of a storage pile. The inspections shall be performed during representative, normal storage pile operating conditions.

6. The permittee shall maintain records of the following information:

   a. the date and reason any required inspection was not performed, including those inspections that were not performed due to snow and/or ice cover or precipitation;

   b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measures;

   c. the dates the control measures were implemented; and

   d. on a calendar quarter basis, the total number of days the control measures were implemented and, for wind erosion from pile surfaces, the total number of days where
   snow and/or ice cover or precipitation were sufficient to not require the control measure(s).

   The information required in 6.d. shall be kept separately for (i) the load-in operations, (ii) the load-out operations, and (iii) the pile surfaces (wind erosion), and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation reports that identify any of the following occurrences:

   a. each day during which an inspection was not performed by the required frequency, excluding an inspection which was not performed due to an exemption for snow and/or ice cover or precipitation; and

   b. each instance when a control measure, that was to be implemented as a result of an inspection, was not implemented.

2. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

C:\temp\permits3\8461.wpd

E. Testing Requirements

1. Compliance with the emission limitations in Section A.1. of the terms and conditions of this permit shall be determined in accordance with the following methods:

   a. Emission Limitation:
   No visible PE from storage pile activities except for a period of time not to exceed thirteen minutes during any 60-minute observation period.

   Applicable Compliance Method:
   If required, visible particulate emissions shall be determined according to test Method 22 as set forth in the "Appendix on Test Methods" in 40 CFR, Part 60 "Standards of Performance for New Stationary Sources" as such appendix existed on July 1, 2002, with the modifications found in OAC 3745-17-03(B)(4).

F. Miscellaneous Requirements

None

C:\temp\permits3\8461.wpd

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment -F004 - Aggregate processing plant (300 TPH and a maximum throughput of 750,000 TPY)

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
ORC 3704.03(T)(4)	See Section A.2.a.
OAC rule 3745-17-07(B)	The emission limitation specified by this rule is less stringent than the emission limitation established pursuant to NSPS Subpart OOO.
OAC rule 3745-17-08(B)	Reasonably available control measures that are sufficient to minimize or eliminate visible emissions of fugitive dust (see Sections A.2.b through A.2.d).
NSPS Subpart OOO	Visible emissions of fugitive dust discharging from the crusher shall not exceed 15% opacity. Visible emissions of fugitive dust discharging from the screening operations, transfer points, or conveyors, shall not exceed 10% opacity.

2. Additional Terms and Conditions

2.a The Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3) do not apply to the particulate emissions from this air contaminant source since the calculated annual emission rate for particulate is less than ten tons per year taking into account the federally enforceable rule requirements under OAC rule 3745-17-08(B).

2.b The material handling operations that are covered by this permit and subject to the above-mentioned requirements are listed below:

Load in
Crushing (300 TPH Eagle 1400 Crusher)
Screening (300 TPH Cedar Rapids Screen)
Fines screening (300 TPH)

C:\temp\permits3\8461.wpd

Conveyor transfer points (~~9~~10)

2.c The permittee shall employ reasonably available control measures for the material handling operations listed above, for the purpose of ensuring compliance with the above-mentioned applicable requirements. In accordance with the permittee's permit application, the permittee has committed to maintain sufficient moisture content of the material, using water sprays as necessary, to maintain compliance. Nothing in this paragraph shall prohibit the permittee from employing other control measures to ensure compliance.

2.d For each material handling operation that is not adequately enclosed, the above-identified control measures shall be implemented if the permittee determines, as a result of the inspection conducted pursuant to the monitoring section of this permit, that the control measures are necessary to ensure compliance with the above-mentioned applicable requirements. Any required implementation of the control measures shall continue during the operation of the material handling operations until further observation confirms that use of the control measures is unnecessary.

B. Operational Restrictions

None

C. Monitoring and/or Recordkeeping Requirements

1. For material handling operations that are not adequately enclosed, the permittee shall perform inspections of such operations in accordance with the following minimum frequencies:

material handling operations	minimum inspection frequency
all	daily

2. The above-mentioned inspections shall be performed during representative, normal operating conditions.

3. The permittee shall maintain records of the following information:

   a. the date and reason any required inspection was not performed;

   b. the date of each inspection where it was determined by the permittee that it was necessary to implement the control measure(s):

   c. the dates the control measure(s) was (were) implemented; and

   d. on a calendar quarter basis, the total number of days the control measure(s) was (were) implemented.

C:\temp\permits3\8461.wpd

The information in 3.d. shall be kept separately for the crusher, the screens, and the transfer points identified above, and shall be updated on a calendar quarter basis within 30 days after the end of each calendar quarter.

D. Reporting Requirements

1. The permittee shall submit quarterly deviation reports that identify any of the following occurrences:

   a. each day during which an inspection was not performed by the required frequency; and

   b. each instance when a control measure, that was to be performed as a result of an inspection, was not implemented.

   These reports shall be submitted in accordance with Section A.2 of the General Terms and Conditions of this permit.

2. Pursuant to the NSPS, the source owner/operator is hereby advised of the requirement to report the following at the appropriate times:

   a. construction date (no later than 30 days after such date);

   b. actual start-up date (within 15 days after such date); and

   c. date of performance testing (if required, at least 30 days prior to testing).

   Reports are to be sent to:

   Ohio Environmental Protection Agency
   DAPC - Permit Management Unit
   50 West Town Street, Suite 700
   P. O. Box 1049
   Columbus, Ohio 43216-1049

   and

   Ohio EPA Southeast District Office
   Division of Air Pollution Control
   2195 Front Street
   Logan, Ohio 43138.

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.1. of these terms and conditions shall be determined in accordance with the following method(s):

C:\temp\permits3\8461.wpd

a. Emissions Limitation:
Visible emissions of fugitive dust discharging from the crusher shall not exceed 15% opacity.

Applicable Compliance Method:
Visible particulate emissions shall be determined according to test Method 9 as set forth in the "Appendix on Test Methods" in 40 CFR, Part 60 "Standards of Performance for New Stationary Sources".

b. Emissions Limitation:
Visible emissions of fugitive dust discharging from the screening operation, transfer points, or conveyors, shall not exceed 10% opacity.

Applicable Compliance Method:
Visible particulate emissions shall be determined according to test Method 9 as set forth in the "Appendix on Test Methods" in 40 CFR, Part 60 "Standards of Performance for New Stationary Sources".

2. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:

The emission testing shall be conducted within 180 days of start-up of the emissions unit.

The emission testing shall be conducted to demonstrate compliance with the visible emission limitations for fugitive emissions for each crusher, screening operation, transfer point and conveyor specified in Section A.2.b of this permit, and in accordance with the requirements of 40 CFR Part 60.675.

The following test method(s) shall be employed to demonstrate compliance with the allowable emission rate(s): for visible emissions, Method 9 of 40 CFR 60, Appendix A.

The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity, unless otherwise specified or approved by the Ohio EPA, Southeast District Office.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the Ohio EPA, Southeast District Office. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA, Southeast District Office's refusal to accept the results of the emission test(s).

Personnel from the Ohio EPA, Southeast District Office shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to

C:\temp\permits3\8461.wpd

ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the Ohio EPA, Southeast District Office within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the Ohio EPA, Southeast District Office.

F. Miscellaneous Requirements

None

C:\temp\permits3\8461.wpd

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment -P001 - Cummins KTA19P600 600 HP diesel engine

Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
OAC rule 3745-31-05(A)(3)	Emissions of nitrogen oxides (NO_x) shall not exceed 19.1 pounds per hour.
OAC rule 3745-31-05(C) (synthetic minor to avoid state modeling requirements)	Emissions of NO_x shall not exceed 23.9 tons per year. See Section B.1 below.
OAC rule 3745-31-05(C)	Emissions of carbon monoxide (CO) shall not exceed 5.1 tons per year. See Section A.2.b. below.
ORC rule 3704.03(T)(4)	See Section A.2.a. below.
OAC rule 3745-17-07(A)(1)	Visible emissions shall not exceed 20% opacity as a six-minute average, except as provided by rule.
OAC rule 3745-17-11(B)(5)(a)	PE shall not exceed 0.310 lb/million Btu actual heat input.
OAC rule 3745-18-06(G)	Exempt. See Section A.2.c below.
OAC rule 3745-21-08(B)	See Section A.2.d below.

2. Additional Terms and Conditions

2.a The Best Available Technology (BAT) requirements under 3745-31-05(A)(3) do not apply to the Volatile Organic Compound (VOC), sulfur dioxide, or particulate emissions from this air contaminant source since the uncontrolled potential to emit for VOC, sulfur dioxide, and particulate emissions is each less than ten tons per year.

C:\temp\permits3\8461.wpd

2.b Permit to Install 06-08327 for this air contaminant source takes into account the following voluntary restrictions (including the use of any applicable air pollution control equipment) as proposed by the permittee for the purposes of avoiding Best Available Technology (BAT) requirements under OAC rule 3745-31-05(A)(3).

i. operational restriction of 2500 hours per year.

2.c This emissions unit is exempt from the requirements of OAC rule 3745-18-06(G) pursuant to OAC rule 3745-18-06(B).

2.d The permittee has satisfied the "best available control techniques and operating practices" required pursuant to OAC rule 3745-21-08(B).

On November 5, 2002, OAC rule 3745-21-08 was revised to delete paragraph (B); therefore, paragraph (B) is no longer part of the State regulations. However, that rule revision has not yet been submitted to the U.S. EPA as a revision to Ohio's State Implementation Plan (SIP). Therefore, until the SIP revision occurs and the U.S. EPA approves the revisions to OAC rule 3745-21-08, the requirement to satisfy the "best available control techniques and operating practices" still exists as part of the federally-approved SIP for Ohio.

B. Operational Restrictions

1. The maximum operating hours for emissions unit P001 shall not exceed 2500 hours per year.

2. The permittee shall only burn low sulfur No. 2 or diesel fuel, containing less than or equal to 0.5% sulfur by weight, in this emissions unit.

C. Monitoring and/or Recordkeeping Requirements

1. The permittee shall maintain monthly records of the operating hours for each month.

2. For each day during which the permittee burns a fuel other than low sulfur No. 2 or diesel fuel, the permittee shall maintain a record of the type and quantity of fuel burned in this emissions unit.

D. Reporting Requirements

1. The permittee shall submit deviation reports that identify each year when the operation limitation was exceeded. Each report shall be submitted within 30 days after the deviation occurs.

2. The permittee shall submit deviation reports that identify each day when a fuel other than low sulfur No. 2 or diesel fuel was burned in this emission unit. Each report shall be submitted within 30 days after the deviation occurs.

C:\temp\permits3\8461.wpd

E. Testing Requirements

1. Compliance with the emission limitations specified in section A.1. of these terms and conditions shall be determined in accordance with the following methods:

   a. Emissions Limitations:

      Emissions of nitrogen oxides (NO_x) shall not exceed 19.1 pounds per hour. Emissions of NO_x shall not exceed 23.9 tons per year.

      Applicable Compliance Method:

      Compliance with the lb/hr NOx emission limitation may be demonstrated by multiplying the NOx emissions factor from AP-42, Table 3.3-1, 10/96 by the maximum rated capacity of the emissions unit as shown in the following equation.

      (4.41 lbs/mmBtu)(4.33 mmBtu/hr) = 19.1 lb/hr

      If required, compliance with the lb/hr NOx emission limitation shall be demonstrated by performing an emission test in accordance with the procedures specified in Methods 1 through 4 and Method 7 of 40 CFR Part 60, Appendix A. Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, Southeast District Office.

      The annual emission limitation was developed by multiplying the short-term allowable NOx emission limitation (19.1 lb/hr) by the maximum annual hours of operation (2500 hours), and then dividing by 2,000 lbs per ton. Therefore, if compliance is shown with the short-term allowable emission limitation and the annual hours of operation limitation, compliance shall also be shown with the annual emission limitation.

   b. Emissions Limitation:

      Emissions of carbon monoxide (CO) shall not exceed 5.1 tons per year.

      Applicable Compliance Method:

      Compliance with the lb/hr CO emission limitation may be demonstrated by multiplying the CO emissions factor from AP-42, Table 3.3-1, 10/96 by the maximum rated capacity of the emissions unit and by the maximum annual hours of operation (2500 hours), and then dividing by 2,000 lbs per ton as shown in the following equation:

      (0.95 lbs/mmBtu)(4.33 mmBtu/hr)(2500 hr/yr)/(2000 lb/ton) = 5.14 ton/yr

C:\temp\permits3\8461.wpd

If required, compliance with the lb/hr CO emission limitation shall be demonstrated by performing an emission test in accordance with the procedures specified in Methods 1 through 4 and Method 10 of 40 CFR Part 60, Appendix A. Alternative U.S. EPA-approved test methods may be used with prior approval from the Ohio EPA, Southeast District Office.

c. Emissions Limitation:
PE shall not exceed 0.310 lb/mmBtu of actual heat input.

Applicable Compliance Method:

Compliance shall be determined based on the emission factor of 0.31 lb/million Btu specified in AP-42, Table 3.3-1 (10/96).

If required, the permittee shall demonstrate compliance with this emission limitation in accordance with the methods and procedures specified in Methods 1-5 of 40 CFR Part 60, Appendix A.

d. Emissions Limitation:
Visible particulate emissions shall not exceed 20% opacity as a 6-minute average.

Applicable Compliance Method:
If required, compliance with the visible emission limitation shall be determined in accordance with Method 9 of 40 CFR Part 60, Appendix A.

F. Miscellaneous Requirements

None

C:\temp\permits3\8461.wpd