OhioEPA

State of Ohio Environmental Protection Agency

Street Address:
Lazarus Gov. Center
122 S. Front Street
Columbus, OH 43215

TELE: (614) 644-3020 **FAX:** (614) 644-2329

Mailing Address:
Lazarus Gov. Center
P.O. Box 1049
Columbus, OH 43216-1049

RE: FINAL PERMIT TO INSTALL
HOCKING COUNTY
Application No: 06-06481

CERTIFIED MAIL

	TOXIC REVIEW
	PSD
Y	**SYNTHETIC MINOR**
	CEMS
	MACT
Subpart I	**NSPS**
	NESHAPS
	NETTING
	MAJOR NON-ATTAINMENT
	MODELING SUBMITTED
	GASOLINE DISPENSING FACILITY

DATE: 10/9/2001

Mar Zane Plant No 4
Ronald Morrison
PO Box 1585
Zanesville, OH 43701

Enclosed please find an Ohio EPA Permit to Install which will allow you to install the described source(s) in a manner indicated in the permit. Because this permit contains several conditions and restrictions, I urge you to read it carefully.

The Ohio EPA is urging companies to investigate pollution prevention and energy conservation. Not only will this reduce pollution and energy consumption, but it can also save you money. If you would like to learn ways you can save money while protecting the environment, please contact our Office of Pollution Prevention at (614) 644-3469.

You are hereby notified that this action by the Director is final and may be appealed to the Ohio Environmental Review Appeals Commission pursuant to Chapter 3745.04 of the Ohio Revised Code. The appeal must be in writing and set forth the action complained of and the grounds upon which the appeal is based. It must be filed within thirty (30) days after the notice of the Directors action. A copy of the appeal must be served on the Director of the Ohio Environmental Protection Agency within three (3) days of filing with the Commission. An appeal may be filed with the Environmental Review Appeals Commission at the following address:

Environmental Review Appeals Commission
236 East Town Street, Room 300
Columbus, Ohio 43215

Very truly yours,

Thomas G. Rigo

Thomas G. Rigo, Manager
Field Operations and Permit Section
Division of Air Pollution Control

CC: USEPA SEDO

STATE OF OHIO ENVIRONMENTAL PROTECTION AGENCY

Permit To Install	**Issue Date: 10/9/2001**
Terms and Conditions	**Effective Date: 10/9/2001**

FINAL PERMIT TO INSTALL 06-06481

Application Number:	06-06481
APS Premise Number:	0637000000
Permit Fee:	**$1000**
Name of Facility:	Mar Zane Plant No 4
Person to Contact:	Ronald Morrison
Address:	PO Box 1585 Zanesville, OH 43701

Location of proposed air contaminant source(s) [emissions unit(s)]:
37561 Wandling Rd
Haydenville, **Ohio**

Description of proposed emissions unit(s):
200 Ton Per Hour Asphalt Batch Plant Chapter 32 Modification.

The above named entity is hereby granted a Permit to Install for the above described emissions unit(s) pursuant to Chapter 3745-31 of the Ohio Administrative Code. Issuance of this permit does not constitute expressed or implied approval or agreement that, if constructed or modified in accordance with the plans included in the application, the above described emissions unit(s) of environmental pollutants will operate in compliance with applicable State and Federal laws and regulations, and does not constitute expressed or implied assurance that if constructed or modified in accordance with those plans and specifications, the above described emissions unit(s) of pollutants will be granted the necessary permits to operate (air) or NPDES permits as applicable.

This permit is granted subject to the conditions attached hereto.

Ohio Environmental Protection Agency

Director

Part I - GENERAL TERMS AND CONDITIONS

A. Permit to Install General Terms and Conditions

1. Compliance Requirements

The emissions unit(s) identified in this Permit to Install shall remain in full compliance with all applicable State laws and regulations and the terms and conditions of this permit.

2. Reporting Requirements Related to Monitoring and Recordkeeping Requirements

The permittee shall submit required reports in the following manner:

a. Reports of any required monitoring and/or recordkeeping information shall be submitted to the appropriate Ohio EPA District Office or local air agency.

b. Except as otherwise may be provided in the terms and conditions for a specific emissions unit, quarterly written reports of (a) any deviations (excursions) from emission limitations, operational restrictions, and control device operating parameter limitations that have been detected by the testing, monitoring, and recordkeeping requirements specified in this permit, (b) the probable cause of such deviations, and (c) any corrective actions or preventive measures which have been or will be taken, shall be submitted to the appropriate Ohio EPA District Office or local air agency. If no deviations occurred during a calendar quarter, the permittee shall submit a quarterly report, which states that no deviations occurred during that quarter. The reports shall be submitted quarterly, i.e., by January 31, April 30, July 31, and October 31 of each year and shall cover the previous calendar quarters. (These quarterly reports shall exclude deviations resulting from malfunctions reported in accordance with OAC rule 3745-15-06.)

3. Records Retention Requirements

Each record of any monitoring data, testing data, and support information required pursuant to this permit shall be retained for a period of five years from the date the record was created. Support information shall include, but not be limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. Such records may be maintained in computerized form.

4. Inspections and Information Requests

The Director of the Ohio EPA, or an authorized representative of the Director, may, subject to the safety requirements of the permittee and without undue delay, enter upon the premises of this source at any reasonable time for purposes of making inspections, conducting tests, examining records or reports pertaining to any emission of air contaminants, and determining compliance with any applicable State air pollution laws and regulations and the terms and conditions of this permit. The permittee shall furnish to the Director of the Ohio EPA, or an authorized representative of the Director, upon receipt of a written request and within a reasonable time, any information that may

be requested to determine whether cause exists for modifying, reopening or revoking this permit or to determine compliance with this permit. Upon verbal or written request, the permittee shall also furnish to the Director of the Ohio EPA, or an authorized representative of the Director, copies of records required to be kept by this permit.

5. Scheduled Maintenance/Malfunction Reporting

Any scheduled maintenance of air pollution control equipment shall be performed in accordance with paragraph (A) of OAC rule 3745-15-06. The malfunction of any emissions units or any associated air pollution control system(s) shall be reported to the appropriate Ohio EPA District Office or local air agency in accordance with paragraph (B) of OAC rule 3745-15-06. Except as provided in that rule, any scheduled maintenance or malfunction necessitating the shutdown or bypassing of any air pollution control system(s) shall be accompanied by the shutdown of the emissions unit(s) that is (are) served by such control system(s).

6. Permit Transfers

Any transferee of this permit shall assume the responsibilities of the prior permit holder. The appropriate Ohio EPA District Office or local air agency must be notified in writing of any transfer of this permit.

7. Air Pollution Nuisance

The air contaminants emitted by the emissions units covered by this permit shall not cause a public nuisance, in violation of OAC rule 3745-15-07.

8. Termination of Permit to Install

This Permit to Install shall terminate within eighteen months of the effective date of the Permit to Install if the owner or operator has not undertaken a continuing program of installation or modification or has not entered into a binding contractual obligation to undertake and complete within a reasonable time a continuing program of installation or modification. This deadline may be extended by up to 12 months if application is made to the Director within a reasonable time before the termination date and the party shows good cause for any such extension.

9. Construction of New Sources(s)

The proposed emissions unit(s) shall be constructed in strict accordance with the plans and application submitted for this permit to the Director of the Ohio Environmental Protection Agency. There may be no deviation from the approved plans without the express, written approval of the Agency. Any deviations from the approved plans or the above conditions may lead to such sanctions and penalties as provided under Ohio law. Approval of these plans does not constitute an assurance that the proposed facilities will operate in compliance with all Ohio laws and regulations. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed sources cannot meet the requirements of this permit or cannot meet applicable standards.

If the construction of the proposed emissions unit(s) has already begun or has been completed prior to the date the Director of the Environmental Protection Agency approves the permit application and plans, the approval does not constitute expressed or implied assurance that the proposed facility has been constructed in accordance with the approved plans. The action of beginning and/or completing construction prior to obtaining the Director's approval constitutes a violation of OAC rule 3745-31-02. Furthermore, issuance of the Permit to Install does not constitute an assurance that the proposed source will operate in compliance with all Ohio laws and regulations. Approval of the plans in any case is not to be construed as an approval of the facility as constructed and/or completed. Moreover, issuance of the Permit to Install is not to be construed as a waiver of any rights that the Ohio Environmental Protection Agency (or other persons) may have against the applicant for starting construction prior to the effective date of the permit. Additional facilities shall be installed upon orders of the Ohio Environmental Protection Agency if the proposed facilities cannot meet the requirements of this permit or cannot meet applicable standards.

10. Public Disclosure

The facility is hereby notified that this permit, and all agency records concerning the operation of this permitted source, are subject to public disclosure in accordance with OAC rule 3745-49-03.

11. Applicability

This Permit to Install is applicable only to the emissions unit(s) identified in the Permit to Install. Separate application must be made to the Director for the installation or modification of any other emissions unit(s).

12. Best Available Technology

As specified in OAC Rule 3745-31-05, all new sources must employ Best Available Technology (BAT). Compliance with the terms and conditions of this permit will fulfill this requirement.

13. Source Operation and Operating Permit Requirements After Completion of Construction

This facility is permitted to operate each source described by this Permit to Install for a period of up to one year from the date the source commenced operation. This permission to operate is granted only if the facility complies with all requirements contained in this permit and all applicable air pollution laws, regulations, and policies. Pursuant to OAC Chapter 3745-35, the permittee shall submit a complete operating permit application within thirty (30) days after commencing operation of the emissions unit(s) covered by this permit.

14. Construction Compliance Certification

The applicant shall provide Ohio EPA with a written certification (see enclosed form) that the facility has been constructed in accordance with the Permit to Install application and the terms and

conditions of the Permit to Install. The certification shall be provided to Ohio EPA upon completion of construction but prior to startup of the source.

15. Fees

The permittee shall pay fees to the Director of the Ohio EPA in accordance with ORC section 3745.11 and OAC Chapter 3745-78. The permittee shall pay all applicable Permit to Install fees within 30 days after the issuance of this Permit to Install.

B. Permit to Install Summary of Allowable Emissions

The following information summarizes the total allowable emissions, by pollutant, based on the individual allowable emissions of each air contaminant source identified in this permit.

SUMMARY (for informational purposes only)
TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

Pollutant	Tons Per Year
PM	6.45
VOC	6.83
NOx	18
SO2	13.2
CO	60

C:\temp\permits3\8670.wpd

PART II - SPECIAL TERMS AND CONDITIONS FOR SPECIFIC EMISSIONS UNIT(S)

A. Applicable Emissions Limitations and/or Control Requirements

1. The specific operations(s), property, and/or equipment which constitute this emissions unit are listed in the following table along with the applicable rules and/or requirements and with the applicable emissions limitations and/or control measures. Emissions from this unit shall not exceed the listed limitations, and the listed control measures shall be specified in narrative form following the table.

Operations, Property, and/or Equipment	Applicable Rules/Requirements	Applicable Emissions Limitations/Control Measures
P901 - 200 Ton Per Hour Asphalt Batch Plant Chapter 31 Modification of PTI 06-722 issued April 21, 1981 to allow the use of #2, #4, #6 and waste oil.	OAC rule 3745-31-05(A)(3)	Hourly emissions of CO, NOx, VOC and SO2 shall not exceed 80, 24, 9.1 and 17.6 pounds respectively. No visible emissions of fugitive dust from the enclosures for the hot aggregate elevator, vibrating screens, and weigh hopper.
	OAC rule 3745-31-05(D) 40 CFR Part 60, Subpart I OAC rule 3745-17-07(A)(1) OAC rule 3745-17-11 OAC rule 3745-18-06(E)	The requirements of this rule also include compliance with the requirements of 40 CFR Part 60 Subpart I, OAC rule 3745-17-07, OAC rule 3745-17-11, OAC rule 3745-18-06(E), and OAC rule 3745-31-05(D). (See Section A.2.a) Annual emissions shall not exceed the following based on a rolling 12-month average 6.42 TPY PM 60 TPY CO 13.2 TPY SO_2 18 TPY NOx 6.83 TPY VOC

C:\temp\permits3\8670.wpd

aggregate storage bins, cold aggregate elevator	OAC rule 3745-31-05(A)(3)	Particulate emissions shall not exceed 0.04 grain/dscf The emissions unit shall not discharge into the atmosphere any stack gases which exhibit 20 percent opacity or greater. The emissions limitation specified by this rule is less stringent than the emission limitation established pursuant to OAC rule 3745-31-05(A)(3). Visible emissions of fugitive dust shall be less than or equal to 20 percent opacity, as a 3-minute average. The drop height of the front end loader bucket shall be minimized to the extent possible in order to minimize or eliminate visible emissions of fugitive dust from the elevator loading area. The aggregate loaded into the storage bins shall have a moisture content sufficient to eliminate the visible emissions of fugitive dust from the elevator and the transfer point to the dryer.

2. Additional Terms and Conditions

2.a The fabric filter shall be used at all times when the emissions unit is in operation.

2.b The application and enforcement of the provisions of the New Source Performance Standards (NSPS), as promulgated by the United States Environmental Protection Agency, 40 CFR Part 60, are delegated to the Ohio Environmental Protection Agency. The requirements of 40 CFR Part 60 are also federally enforceable.

B. Operational Restrictions

C:\temp\permits3\8670.wpd

1. To ensure the baghouse is operated according to the manufacturer's specifications and to maintain compliance with the allowable particulate emission rate, the pressure drop across the baghouse shall be maintained within the range of 3.0 to 5.0 inches of water while the emissions unit is in operation.

2. The maximum annual asphalt production rate for emissions unit P901 shall not exceed 300,000 tons per year based upon a rolling, 12-month summation of the production rates. To ensure enforceability during the first 12 calendar months of operation following the startup of the modified emissions unit P901, the permittee shall not exceed the production levels specified in the following table:

Month(s)	Maximum Allowable Cumulative Production (Tons)
1	100,000
1-2	150,000
1-3	200,000
1-4	250,000
1-5	300,000
1-6	300,000
1-7	300,000
1-8	300,000
1-9	300,000
1-10	300,000
1-11	300,000
1-12	300,000

After the first 12 calendar months of operation following the startup of the modified emissions unit P901, compliance with the annual production rate limitation shall be based upon a rolling, 12-month summation of the production rates.

3. All recycled, used oil burned in emissions unit P901 shall meet the following specifications:

Contaminant/Property	Allowable Specifications
arsenic	5 ppm, maximum
cadmium	2 ppm, maximum
chromium	10 ppm, maximum
lead	100 ppm, maximum
PCB's	50 ppm, maximum*
total halogens	4000 ppm maximum**

C:\temp\permits3\8670.wpd

mercury	1 ppm, maximum
flash point	100ºF, minimum
heat content	135,000 Btu/gallon, minimum

* If the permittee is burning used oil with any quantifiable level ≥2 ppm < 50 ppm of PCB's, then the permittee is subject to any applicable requirements found under 40 CFR part 279, subparts G and H and 40 CFR 761.20 (e).

** Used oil containing more than 1000 ppm total halogens is presumed to be a hazardous waste under the rebuttable presumption provided under 40 CFR 279.10 (b)(1)*(ii)* and OAC rule 3745-279-10 (B)(1)(b). Therefore, the permittee may receive and burn used oil exceeding 1000 ppm of total halogens (but less than 4000 ppm, maximum) only if the used oil burner can demonstrate the used oil does not contain any hazardous waste pursuant to OAC rule 3745-279-63**.**

4. The burning of hazardous waste is prohibited without first complying with all applicable state and federal hazardous waste and air regulations and permits.

C. Monitoring and/or Record keeping Requirements

1. The permittee shall properly install, operate, and maintain equipment to monitor the pressure drop across the baghouse while the emissions unit is in operation. The monitoring equipment shall be installed, calibrated, operated, and maintained in accordance with the manufacturer's recommendations, instructions, and operating manual(s). The permittee shall record the pressure drop across the baghouse on a once per shift basis.

2. The permittee shall receive a chemical analysis with each shipment of used oil from the supplier. The analysis shall identify the name and address of the supplier, the supplier's USEPA identification number, and the following information:

   a. The date of shipment or delivery.
   b. The quantity of used oil received.
   c. The Btu value of the used oil, in BTU/gallon.
   d. The flash point of the used oil in degrees F.
   e. The arsenic content, in ppm.
   f. The cadmium content, in ppm.
   g. The chromium content, in ppm.
   h. The lead content, in ppm.
   i. The PCB content, in ppm.
   j. The total halogen content, in ppm.
   k. The mercury content, in ppm.

   Each analysis shall be kept in a readily accessible location for at least 5 years and shall be made available to the Director (the appropriate Ohio EPA District Office or local air agency) upon verbal or written request. The Director or any authorized representative of the Director may require or may conduct periodic, detailed chemical analyses through an independent laboratory

C:\temp\permits3\8670.wpd

of any used oil shipment received by this facility, of any used oil stored at this facility, or of any used oil sampled at the dryer.

3. The permittee shall maintain monthly records of the following information for emissions unit P901:

   a. The monthly asphalt production, in tons.

   b. For the first 12 calendar months following the startup of the modified emissions unit P901, the cumulative asphalt production calculated by adding the current month's asphalt production to the asphalt production for each calendar month since the startup of the modified emissions unit P901.

   c. Beginning after the first 12 calendar months following the startup of the modified emissions unit P901, the rolling, 12-month summation of asphalt production calculated by adding the current month's asphalt production to the asphalt production for the preceding eleven calendar months.

4. The permittee shall perform daily checks, when the emissions unit is in operation and when the weather conditions allow, for any visible particulate emissions from the enclosures for the hot aggregate elevator, vibrating screens, and weigh hopper associated with this emissions unit. The presence or absence of any visible particulate emissions shall be noted in an operation log. If visible particulate emissions are observed, the permittee shall also note the following in the operation log:

   a. the color of the emissions;

   b. whether the emissions are representative of normal operations;

   c. if the emission are not representative of normal operations, the cause of the abnormal emissions;

   d. the total duration of any abnormal visible emission incident; and

   e. any corrective actions taken to eliminate the abnormal visible emissions.

   The permittee may, upon receipt of written approval from the Ohio EPA, Southeast District Office, modify the above-mentioned visible particulate emissions check frequency if operating experience indicates that less frequent checks would be sufficient to ensure compliance with the visible particulate emissions requirements.

C:\temp\permits3\8670.wpd

D. Reporting Requirements

1. The permittee shall submit deviation (excursion) reports which identify all periods of time during which the pressure drop across the baghouse did not comply with the allowable range specified in Term B.1.

2. The permittee shall submit deviation (excursion) reports that identify all exceedances of the rolling, 12-month production rate limitation and, for the first 12 calendar months of operation following the issuance of this permit, all exceedances of the maximum allowable cumulative production levels.

3. The permittee shall submit deviation reports to the Southeast District Office that identify any of the following occurrences:

   a. identify all days during which any visible fugitive particulate emissions were observed from the enclosures for the hot aggregate elevator, vibrating screens, and weigh hopper associated with this emissions unit; and

   b. describe any corrective actions taken to eliminate the abnormal visible particulate emissions.

4. The deviation reports shall be submitted in accordance with the reporting requirements of the General Terms and Conditions of this permit.

5. The permittee shall notify the USEPA and the Ohio EPA if any of the used oil exceeds the used oil specifications found in OAC rule 3745-279-11 and the applicable portions of 40 CFR part 761 and shall also notify Ohio EPA if any used oil exceed the mercury limitation and falls below the heat content limitation listed in term B.3 within thirty days after the exceedance occurs. If the permittee is burning used oil which exceeds the specifications found in OAC rule 3745-279-11 and the applicable portions 40 CFR part 761, the permittee is subject to that rule and must comply with all applicable provisions of that rule(s).

6. Pursuant to the NSPS, the source owner/operator is hereby advised of the requirement to report the following at the appropriate times:

   a. Construction date (no later than 30 days after such date);

   b. Anticipated start-up date (not more than 60 days or less than 30 days prior to such date);

   c. Actual start-up date (within 15 days after such date); and

   d. Date of performance testing (if required, at least 30 days prior to testing).

   Reports are to be sent to:

C:\temp\permits3\8670.wpd

Ohio Environmental Protection Agency
DAPC - Permit Management Unit
P. O. Box 163669
Columbus, Ohio 43216-3669

and

Southeast District Office of the Ohio EPA
Division of Air Pollution Control
2195 Front Street
Logan, Ohio 43138

E. Testing Requirements

1. Compliance with the emission limitation(s) in Section A.I. of these terms and conditions shall be determined in accordance with the following method(s):

   a. Emission Limitation:

      0.04 gr/dscf of particulates

      Applicable Emission Limitation

      Compliance shall be determined in accordance with Test Methods 1-5 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

   b. Emission Limitation:

      No visible emissions of fugitive dust from the enclosures for the hot aggregate elevator, vibrating screens and weigh hopper.

      Applicable Compliance Method:

      Compliance with the limitations on visible emissions of fugitive dust found in Section A.1. of this permit shall be demonstrated by the monitoring and record keeping in Section C.4.

   c. Emission Limitation

      6.42 TPY of particulates

C:\temp\permits3\8670.wpd

Applicable Emission Limitation

Compliance shall be determined based upon the following equation:

E = EF * AAPR * 0.0005 ton/lb = TPY of particulates

Where

EF is the emission factor from AP-42 chapter 11 table 1-1 (12/00) in lb/ton, and

AAPR is the actual annual production rate during the previous 12 month period

d. Emission Limitation

80 lb/hr of carbon monoxide (CO)

Applicable Compliance Method

Compliance shall be determined based upon the following equation:

E = EF * 200 ton/hr = lb/hr of CO

Where

EF is the emission factor from AP-42 chapter 11 table 1-5 (12/00) in lb/ton.

e. Emission Limitation

60 TPY of CO

Applicable Compliance Method

Compliance shall be determined based upon the following equation:

E = EF * AAPR = TPY of CO

Where

EF is the emission factor from AP-42 chapter 11 table 1-5 (12/00) in lb/ton, and

AAPR is the actual annual production rate in tons per year.

f. Emission Limitation

17.6 lb/hr of SO2

C:\temp\permits3\8670.wpd

Applicable Compliance Method

Compliance shall be determined based upon the following equation:

E = EF * 200 ton/hr = lb/hr of SO2

Where

EF is the emission factor from AP-42 chapter 11 table 1-5 (12/00) in lb/ton.

g. Emission Limitation

13.2 TPY of SO2

Applicable Compliance Method

Compliance shall be determined based upon the following equation:

E = EF * AAPR = TPY of SO2

Where

EF is the emission factor from AP-42 chapter 11 table 1-5 (12/00) in lb/ton, and

AAPR is the actual annual production rate in tons per year.

h Emission Limitation

Used Oil Specifications

Applicable Compliance Method

Compliance will be demonstrated by the record keeping in Term C.2.

i. Emission Limitation

300,000 Tons of asphalt per rolling 12 month period

Applicable Compliance Method

Compliance shall be demonstrated by the record keeping in Term C.3.

C:\temp\permits3\8670.wpd

j. Emission Limitation

Visible particulate emissions from the stack shall not exceed 20% opacity, as a 6-minute average.

Applicable Compliance Method

Compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources," as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(4)(a) through (B)(4)(d) of OAC rule 3745-17-03.

k. Emission Limitation

24 lb/hr of nitrogen oxides (NOx)

Applicable Compliance Method

Compliance shall be determined based upon the following equation:

E = EF * 200 ton/hr = lb/hr of NOx

Where

EF is the emission factor from AP-42 chapter 11 table 1-5 (12/00) in lb/ton

l. Emission Limitation

18 TPY of NOx

Applicable Compliance Method

Compliance shall be determined based upon the following equation:

E = EF * AAPR = TPY of NOx

Where

EF is the emission factor from AP-42 chapter 11 table 1-5 (12/00) in lb/ton, and

AAPR is the actual annual production rate in tons per year.

m. Emission Limitation

9.1 lb/hr of volatile organic compounds (VOC)

C:\temp\permits3\8670.wpd

Applicable Compliance Method

Compliance shall be determined in accordance with Test Method 25 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996.

n. Emission Limitation

6.83 TPY of VOC's

Applicable Emission Limitation

Compliance shall be determined based upon the following equation:

E = EF * AAPR * 0.0005 ton/lb = TPY of VOC's

Where

EF is the emission factor from AP-42 chapter 11 table 1-10 (12/00) in lb/ton, and

AAPR is the actual annual production rate during the previous 12 month period

o. Emission Limitation:

Visible particulate emissions of fugitive dust shall not exceed 20% opacity, as a 3-minute average.

Applicable Compliance Method:

Compliance shall be determined in accordance with Test Method 9 as set forth in "Appendix on Test Methods" in 40 CFR, Part 60 ("Standards of Performance for New Stationary Sources"), as such Appendix existed on July 1, 1996, and the modifications listed in paragraphs (B)(3)(a) and (B)(3)(b) of OAC rule 3745-17-03.

2. The permittee shall conduct, or have conducted, emission testing for this emissions unit in accordance with the following requirements:

a. The emission testing shall be conducted within 60 days after startup of the modified emissions unit.

b. The emission testing shall be conducted to demonstrate compliance with the allowable mass emission rate(s) for particulates and VOC's

C:\temp\permits3\8670.wpd

c. The following test method(s) shall be employed to demonstrate compliance with the allowable mass emission rate(s): Methods 1 -5 for particulates, and Method 25 for VOC's.

d. The test(s) shall be conducted while the emissions unit is operating at or near its maximum capacity using worst case fuel, unless otherwise specified or approved by the appropriate Ohio EPA District Office or local air agency.

Not later than 30 days prior to the proposed test date(s), the permittee shall submit an "Intent to Test" notification to the appropriate Ohio EPA District Office or local air agency. The "Intent to Test" notification shall describe in detail the proposed test methods and procedures, the emissions unit operating parameters, the time(s) and date(s) of the test(s), and the person(s) who will be conducting the test(s). Failure to submit such notification for review and approval prior to the test(s) may result in the Ohio EPA District Office's or local air agency's refusal to accept the results of the emission test(s).

Personnel from the appropriate Ohio EPA District Office or local air agency shall be permitted to witness the test(s), examine the testing equipment, and acquire data and information necessary to ensure that the operation of the emissions unit and the testing procedures provide a valid characterization of the emissions from the emissions unit and/or the performance of the control equipment.

A comprehensive written report on the results of the emissions test(s) shall be signed by the person or persons responsible for the tests and submitted to the appropriate Ohio EPA District Office or local air agency within 30 days following completion of the test(s). The permittee may request additional time for the submittal of the written report, where warranted, with prior approval from the appropriate Ohio EPA District Office or local air agency.

F. Miscellaneous Requirements

1. Modeling to demonstrate compliance with the Ohio EPA's "Air Toxic Policy" was not necessary because the emissions unit's maximum annual emissions for each toxic compound will be less than 1.0 ton. OAC Chapter 3745-31 requires permittees to apply for and obtain a new or modified permit to install prior to making a "modification" as defined by OAC rule 3745-31-01. The permittee is hereby advised that changes in the composition of the materials, or use of new materials, that would cause the emissions of any pollutant that has a listed TLV to increase to above 1.0 ton per year may require the permittee to apply for and obtain a new permit to install.

C:\temp\permits3\8670.wpd

NEW SOURCE REVIEW FORM B

PTI Number: 06-06481 Facility ID: 0637000000

FACILITY NAME Mar Zane Plant No 4

FACILITY DESCRIPTION 200 Ton Per Hour Asphalt Batch Plant Chapter 32 Modification CITY/TWP Haydenville

SIC CODE 2951 SCC CODE 30500298 EMISSIONS UNIT ID P901

EMISSIONS UNIT DESCRIPTION 200 Ton Per Hour Asphalt Batch Plant Chapter 31 Modification of PTI 06-722 issued April 21, 1981 to allow the use of alternative fuels.

DATE INSTALLED 6/1984

EMISSIONS: (Click on bubble help for Air Quality Descriptions)

Pollutants	Air Quality Description	Actual Emissions Rate		PTI Allowable	
		Short Term Rate	Tons Per Year	Short Term Rate	Tons Per Year
Particulate Matter	Attainment	0.040 gr/dscf	5.04	0.040 gr/dscf	6.45
PM_{10}					
Sulfur Dioxide	Attainment	17.6 lb/hr	10.56	17.6 lb/hr	13.2
Organic Compounds	Attainment	9.1 lb/hr	5.46	9.1 lb/hr	6.83
Nitrogen Oxides	Attainment	24 lb/hr	14.4	24 lb/hr	18
Carbon Monoxide	Attainment	80 lb/hr	48	80 lb/hr	60
Lead					
Other: Air Toxics					

APPLICABLE FEDERAL RULES:

NSPS? Subpart I NESHAP? NO PSD? NO OFFSET POLICY? NO

WHAT IS THE BAT DETERMINATION, AND WHAT IS THE BASIS FOR THE DETERMINATION?
Vent particulate emission to a baghouse.

IS THIS SOURCE SUBJECT TO THE AIR TOXICS POLICY? NO

OPTIONAL: WHAT IS THE CAPITAL COST OF CONTROL EQUIPMENT? $75,000

TOXIC AIR CONTAMINANTS

Ohio EPA's air toxics policy applies to contaiminants for which the American Conference of Governmental Industrial Hygienists (ACGIH) has a listed threshold limit value.

AIR TOXICS MODELING PERFORMED*? _____ YES _____ NO

IDENTIFY THE AIR CONTAMINANTS: _____

Ohio EPA Permit to Install Information Form Please describe below any documentation which is being submitted with this recommendation (must be sent the same day). Electronic items should be submitted with the e-mail transmitting the PTI terms, and in software that CO can utilize. If mailing any hard copy, this section must be printed as a cover page. All items must be clearly labeled indicating the PTI name and number. Submit hard copy items to **Pam McGraner**, AQM&P, DAPC, Central Office, and electronic files to **airpti@epa.state.oh.us**

NEW SOURCE REVIEW FORM B

PTI Number: 06-06481 Facility ID: 0637000000

FACILITY NAME Mar Zane Plant No 4

FACILITY DESCRIPTION 200 Ton Per Hour Asphalt Batch Plant Chapter 32 Modification CITY/TWP Haydenville

Please fill out the following. If the checkbox does not work, replace it with an 'X'	Electronic	**Additional information** File Name Convention (your PTI # plus this letter)	Hard Copy	None
Calculations (required)	☒	0000000**c**.wpd	☐	
Modeling form/results	☐	0000000**s**.wpd	☐	☒
PTI Application (complete or partial)*	☐	0000000**a**.wpd	☐	☒
BAT Study	☐	0000000**b**.wpd	☐	☒
Other/misc.	☒	0000000**t**.wpd	☐	☐

* Mandatory for netting, PSD, nonattainment NSR, 112(g), 21-07(G)(9)(g) and 21-09(U)(2)(f) - 2 complete copies.

Please complete (see comment bubble to the left for additional instructions):

NSR Discussion

The purpose of this PTI is to allow the facility to use alternative fuels for combustion in the asphalt plant

Please complete for these type permits (For PSD/NSR Permit, place mouse over this text):

☒ **Synthetic Minor Determination and/or** ☐ **Netting Determination**

Permit To Install **ENTER PTI NUMBER HERE**

A. Source Description

This source, Mar- Zane Plant #4, is proposing to use #2, #4, #6 and waste 'on-spec' oil as alternative fuels for the 200 TPH asphaltic plant at 37561 Wandling Road in Haydenville.

B. Facility Emissions and Attainment Status

The asphaltic concrete plant is located in Hocking County. Hocking County is attainment for particulate, sulfur dioxide, carbon monoxide, ozone, lead and oxides of nitrogen. The maximum potential to emit at 8760 hours per year for this emissions unit (P901) is 350.4 tons per year for carbon monoxide (CO). This would make the facility a 'major source' requiring a Title V permit and the application to undergo Prevention of Significant Deterioration (PSD) review.

C. Source Emissions

Mar-Zane Plant #4 will limit the plant's annual production to 300,000 tons per rolling 12-month period. With the proposed production restriction, the total annual CO emissions will be limited to 60 tons per year. The PTI requires record keeping to ensure compliance with the production restriction.

D. Conclusion

The production restriction required in this permit is sufficient to provide federally enforceable limitations for ensuring that the applicable Title V and PSD thresholds will not be exceeded.

PLEASE PROVIDE ADDITIONAL NOTES OR COMMENTS AS NECESSARY:

NONE

Please complete:

SUMMARY (for informational purposes only)

TOTAL PERMIT TO INSTALL ALLOWABLE EMISSIONS

NEW SOURCE REVIEW FORM B

PTI Number: 06-06481 Facility ID: 0637000000

FACILITY NAME Mar Zane Plant No 4

FACILITY DESCRIPTION 200 Ton Per Hour Asphalt Batch Plant Chapter 32 Modification

CITY/TWP Haydenville

Pollutant	Tons Per Year
PM	6.45
VOC	6.83
NOx	18
SO2	13.2
CO	60

NEW SOURCE REVIEW FORM B

PTI Number: 06-06481 Facility ID: 0637000000

FACILITY NAME Mar Zane Plant No 4

FACILITY DESCRIPTION	200 Ton Per Hour Asphalt Batch Plant Chapter 32 Modification	CITY/TWP	Haydenville

C:\temp\permits3\8670.wpd